

40-2038
File Copy

KERR-McGEE OIL INDUSTRIES, INC.

Kerr-McGee Building • Oklahoma City 2, Oklahoma

April 12, 1961



Mr. Robert Lowenstein, Acting Director
Division of Licensing and Regulation
U. S. Atomic Energy Commission
Washington 25, D. C.

Dear Mr. Lowenstein:

Your Reference
DLR:CGW 40-2038

(see rpts follow)

The attached letter and report from our Mr. John A. Maxwell covers the information requested in your letter of March 16, 1961 addressed to Dean A. McGee regarding the August 22, 1960 tailings pond dam failure at the Shiprock, New Mexico uranium mill. We trust that the attached information adequately covers this situation.

We appreciate your assistance in the renewal of our license.

Very truly yours,

George H. Cobb
Vice President, Minerals

GHC/az
attachments


Air Mail - Registered
Return Receipt Requested

9810130261 610412
PDR ADOCK 04002038
C PDR

598

B/66

DOCKET NO. *40-2038*
File Copy
Trans. w/ltm 4/12-61



Report to U. S. Atomic Energy Commission
Division of Licensing & Regulations
Attn: Robert Lowenstein, Acting Director

Relative to your Report of March 16, 1961
KERR-McGEE OIL INDUSTRIES, INC.
(Shiprock)

*See incoming letter
dated April 12, 1961*

A. Heavy mechanical excavation equipment was used to build the earthen dikes. The material was placed in even lifts approximately 6 inches deep. The fill section was maintained as level as practical. Effective compaction of the dikes was realized by directing equipment travel over the dikes on each pass made. The layers of fill material were carried across the entire width of the embankments and the embankments were built to the required slope of 1-1/2 : 1, and were not widened with loose material from the top. The height was built as designated. The crown of the embankment was finished to be suitable for a roadway. The material used for the embankment construction was adobe, which was moistened by means of truck sprinklers to maintain consistent moisture content to insure maximum compaction. The material was distributed so that the compacted material was homogeneous and was free from streaks, pockets or other imperfections. The placing operations were directed so that the materials, when compacted, were blended sufficiently to secure the best applicable degree of compaction, impermeability, and stability. The embankments as completed are impervious. There are no leaks or seepage through any of these fills. See attached sheet for cross sections of dikes which are presently in use. These cross sections are also noted on the attached Mill and Storage map.

B. On hand here at the Shiprock mill is the following company equipment that can be used for emergency or for routine maintenance to retain dams of either tailings or raffinate ponds.

- 1 - D-7 Caterpillar Dozer
- 2 - 1-1/2 yd. Michigan front end loaders
- 1 - 2 yd. Michigan front end loader
- 4 - 3-ton dump trucks
- 1 - road maintainer

C. VX raffinate was discharged to Pond No. 7 from 1/1/61 through 3/22/61. From 3/23/61 to 4/3/61 (11 days), the pond depth has dropped 2.5 feet. The area of this pond is approximately 109,166 square feet. See below for distribution of gallons loss through seepage and evaporation.

a. Total gallons lost (11 days)	2,046,863	
b. Total gallons evaporated (.3 inches per day)	225,148	
c. Total gallons lost to seepage	1,821,715	
(Seepage flow rate--115 GPM)		

$\frac{18 \times 1,75}{109,166} = 16.7 \text{ gal/ft}^2 \text{ in 11 days}$

Based upon the above figures, the following calculations are submitted to show that the barren tailings ponds are adequate to handle the mill liquid tailings.

Plant Output per Month to Ponds (155 GPM) 6,696,000 gallons

Seepage Output per Month (115 GPM) 4,968,000 "

$$a. \frac{4,968,000}{109,160} = 45.5 \text{ gal/ft}^2 \text{ /month}$$

Evaporation Output per Month (.3 inches per day) 614,040 "

$$b. \frac{614,040}{109,160} = 5.6 \text{ gal/ft}^2 \text{ /month}$$

Item C continued

$$\begin{array}{rcl} a \text{ plus } b & = & 45.5 \\ & & 5.6 \\ \hline & & 51.1 \end{array} \text{ gal/ft}^2/\text{month total output of seepage and} \\ \text{evaporation based on Pond No. 7}$$

$$\frac{6,696,000}{51.1} = 131,037 \text{ ft}^2 \text{ of surface required to handle mill output}$$

$$\frac{655,000}{131,037} = 499.8\% \text{ safety factor}$$

- D. Since the initiation of the November 28, 1960, report, it has been deemed more advantageous, for spillage control purposes, to install an auxiliary dam north of the barren liquor ponds within the plant site fence. This dam was put in place early in January of 1961, in lieu of the earlier proposed flood gate at the road culvert.
- E. At present, the lead operator makes an inspection of the dikes and the ponds every two hours. This is done on an around-the-clock basis.
- F. The barren raffinate carrying line, at the time the rupture occurred in September, 1960, was not suitable for this duty due to the decomposition of the line caused by organic solvent entrained in the raffinate. At present, this carrying line is made up of 4 inch diameter PVC Schedule 40 pipe. The carrying line is laid in a 6-inch V-shaped wooden trough which offers maximum support and minimum movement of the pipe, thereby lessening the chances of a pipe break. This line shall also be inspected on an around-the-clock basis by lead operators.

At the time of the rupture, no liquid effluent was discharged to an unrestricted area. The rupture was in the pipe on the side parallel to the tailings pond and the effluent was discharged into the pond.

V. Liquid Effluent Survey Program

Liquid effluents are discharged from the mill process and retained in appropriate ponds. These effluents are designated as follows:

I. VX Raffinate

- a. Description--this effluent is discharged from the solvent extraction circuit. It is pumped to and retained in ponds as described in Item 4 of our November 25, 1960, report.

Continue Item V

- b. Sampling procedure--this effluent is continuously sampled over a 24-hour period, utilizing an automatic sampler. These daily samples shall be combined to make a monthly composite.
- c. Analysis--the monthly composite shall be analyzed for uranium, Radium-226 and Thorium-230. The monthly composites shall be analyzed until such time representative concentrations of radionuclides are realized.
- d. Volume--the volume of this effluent is constantly metered (GPM) before discharging into the ponds. A daily record of this volume is maintained.

II. Sand-Slime Tails Pulp

- a. Description--this is the waste material discharged from the acid leach circuit. It consists of solids and liquid, and is pumped in pulp form to and retained in the pond as described in Item 4 of our November 25, 1960, report.
- b. Sampling Procedure--this effluent is continuously sampled over a 24-hour period, utilizing an automatic sampler. These daily samples shall be combined to make a monthly composite. Only the liquid effluent portion shall be composited and analyzed.
- c. Analysis--the monthly composite of this liquid effluent shall be analyzed for uranium, Radium-226 and Thorium-230. The monthly composites shall be analyzed until such time representative concentrations of radionuclides are realized.
- d. Volume--the volume of this liquid effluent may be calculated from daily records maintained on the solids-liquid weight ratios.

The volume of all seepage and mill effluent streams shall be determined and records maintained of same. The seepage samples shall be determined on a weekly basis.

To determine the sub-surface movement of seepage liquids, a series of test holes have been drilled and pits dug in the vicinity of our tailings areas. These test holes have been drilled to the Mancos shale. The location and depth of these test holes and pits are spotted on the attached Mill and Storage map. Samples of these test holes have been taken and shall be continued to be taken for analysis of Radium-226. Further work of this type shall be continued in the area north of our present sand tailings pond. Detailed evaluation of these test holes shall be submitted at a later date.

The cooling water stream which was discharging to an unrestricted area was being contaminated with liquid effluent discharging from the barometric leg of our vacuum system. At present, both of these effluents are being fed

back into the mill process. In addition to the above precautionary measure, an earthen dam has been constructed across the gully, inside the plant-site to retain any effluent that may escape from the mill process. Any effluent discharging into this gully would not be excessive to the point of breaking the dam. This would allow sufficient time to stop any effluent escapes and pump the effluent retained by the dam to our present tailings pond. This measure would prevent escape of any effluent, down this gully, to an unrestricted area.

7. Dust Collection and Ventilation Equipment

Ore Crushing and Sampling Plant. The ore crushing and sampling plant is ventilated by two exhaust vents situated in the roof of the building. These vents are 2 feet in diameter and are covered with louvered spherical cowls. The dust generated in this building is vented to the atmosphere by movement of convection currents through these vents.

Sample Bucking Room. The pulverizer in this room is enclosed on three sides with plywood and hooded to a 10-inch diameter exhaust pipe. Air is drawn from the hooded and enclosed pulverizer area utilizing a Buffalo Forge "Breezflo" fan. The rated output of this fan is 500 CFM. The fan and motor assembly is enclosed in a metal housing, with one louvered side open for exhaust discharge. This metal housing is situated directly above the pulverizer area, flush on the roof of the building.

Improvements to Control Dust Concentrations in the Product Packaging Area. At the time that the air samples were taken (your reference to August, 1959, and June, 1960, samples) the efficiency of the dust collector in this area was very low. In lieu of this problem, the dust collector was completely replaced with a new one to insure maximum dust collecting efficiency. Periodic operational and mechanical inspections of this dust collector and its ducts are made to insure maximum operating efficiency.

11. Respiratory Protective Equipment

Respirators are worn by operators while working in areas having airborne radioactive particulates in excess of MPC. These areas are posted as respirator areas and are worded, "Safety First, Wear Your Respirator."

Breathing zone samples indicate that these areas are in excess of MPC based on the fact that an operator works in said areas forty hours per week. However, in most instances, the operator remains in these areas for a short period of time each day. Time and motion studies are being surveyed and weighted exposure averages shall relate whether or not these operators are respiring airborne radioactive particulates in excess of MPC during their total forty hour working week. If this survey indicates that some operators are respiring airborne radioactive particulates in excess of MPC, then one of three actions shall be taken. These actions are as follows:

Item 11 continued

- a. The operator shall be transferred to other duties in lower level areas. This immediate action will relieve the operator or operators of exposure to airborne radioactivity in excess of MPC until ventilation modifications can be utilized to lower the concentrations of radioactive particulates.
- b. The ventilation problem shall be studied and proper measures shall be taken to lower dust levels.
- c. If the above measures are inapplicable, then application shall be made to the Commission proper to compliance with Section 20.103 of 10 CFR 20.

12. Description of Mill Discharge Stacks.

No. 1 National Hydro Filter. The exhaust port of this dust collector is 8 inches in diameter and extends 6.5 feet above the roof of the building. It exhausts vertically to the atmosphere. See attached sheets for results of concentrations of radioactive particulates released to the atmosphere.

No. 2 National Hydro Filter. The exhaust port of this dust collector is 9 inches in diameter and extends 7 feet above the roof of the building. It exhausts vertically to the atmosphere. See attached sheets for results of concentrations of radioactive particulates released to the atmosphere.

Exhaust Port at Sample Bucking Room. The exhaust of the ventilating fan discharges to the atmosphere through a louvered port. This exhaust port extends 18 inches above the roof of the building. Samples of this exhaust port have not been taken at this time.

Exhaust Ports at the Ore Crushing and Sampling Plant. The ore crushing and sampling plant is vented to the atmosphere through two 24-inch diameter vents, covered with louvered spherical cowls. The spherical cowls are flush with the roof of the building. Samples of these vents have not been taken at this time.

See attached sheets for results of concentrations of radioactive particulates released to the atmosphere through stacks described in Item 12 of our November 25, 1960, report.

APPENDIX

1. Attach. sheet of cross sections of dikes (1)
2. Attach. Mill and Storage Map (1)
3. Attach. sheet of results of concentrations of radioactive particulate^a released to the atmosphere and through stacks described in Item 12 of our November 25, 1960, report (1)

STACK EFFLUENT SURVEY SAMPLES

<u>Location Sampled</u>	<u>Date</u>	<u>Sampling Time</u>	<u>Ml of air ($\times 10^2$)</u>	<u>Total uc ($\times 10^{-6}$)</u>	<u>uc/ml ($\times 10^{-11}$)</u>
Yellow Cake Dust Collector Stack	11/29/60	180 min.	12.60	3.22	3.22
Leaching Tank Stacks (8) <i>← averaged?</i>	12/19/60	240 min.	16.80	34.48	2.05
	1/31/61	360 min.	14.40	7.33	0.51
	3/1/61	480 min.	37.84	212.15	2.42
Uranium Precipitation Tank Stack	3/2/61	240 min.	31.20	33.21	1.00

All of the above samples were taken utilizing the following equipment:

- a. Air Sampler - Gelman Air Sampling Kit
- b. Filtering Media - Distilled water in a 500 ml impinger

SEE APERTURE CARD FILES

NUMBER OF OVERSIZE PAGES FILMED ON APERTURE CARD(S) 10


ACCESSION NUMBERS OF OVERSIZE PAGES:

9810130261-01-10

DOCUMENT NO. 40-2038

HPA

EXHIBIT I




M DIVISION
N. M.

PLANT FLOWSHEET

APERTURE CARD

Also Available on
Aperture Card



9810-130261-11

EXHIBIT I

DRAWN BY: JLM
DATE: 11/13/62


1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1

APERTURE CARD/PAPER COPY AVAILABLE THROUGH NRC FILE CENTER

ACCESSION NUMBERS OF OVERSIZE PAGES:

9810130261-12-18

SAMPLING AND CRUSHING



LAB File Copy

M. M. DIVISION
N. M.

PLANT FLOWSHEET

APERTURE
CARDAlso A
Apertable on
Card

DRYING PAN

COFFEE MILL

SAMPLE SPLITTER

ORE SAMPLE

REJECT

CUBICAL BLENDER

ORE STOCKPILE

SAMPLE SPLITTER

ORE SAMPLE

REJECT

8100 PULVERIZER


50# LOT SAMPLE

100 MESH SCREEN

CUBICAL BLENDER

SAMPLE ENVELOPE

LABORATORY



9810180261-19

EXHIBIT I

DRAWN BY: FLH
DATE: 11/13/62

OVERSIZE DOCUMENT PAGE(S) PULLED

=====

SEE APERTURE CARD FILES

APERTURE CARD/PAPER COPY AVAILABLE THROUGH NRC FILE CENTER

.....

NUMBER OF OVERSIZE PAGES FILMED ON APERTURE CARD(S) 5

.....

ACCESSION NUMBERS OF OVERSIZE PAGES:

9810130261-20

-21

-22

-23

9810130265