

This slide intentionally left blank.

Westinghouse Nuclear Safety Culture



Cobalt-60 Production in Westinghouse PWRs

NRC-Westinghouse Technical Exchange Meeting
July 15, 2020

Agenda



- Background & Objective
- Licensing approach
- Co-60 Production Process
- []^{a,c}
- Safety Analyses, Dose Rates, & SFP Criticality
- Harvesting
- Schedule
- Summary & Closing Statements

Background: Cobalt-60 Global Production



FEBRUARY 26, 2020

Westinghouse and Nordion (Canada) Inc. announce that they have signed a Letter of Intent to develop innovative isotope production technology that will allow Cobalt-60 to be produced in Pressurized Water Reactors (PWRs).



Objective

- Initial dialogue with NRC Staff to provide clarity
 - Licensing approach
 - Production process
 - Component structure & design
 - Applicability of NRC-approved codes and methods
 - Production schedule

Licensing Approach

- Plant-specific Operating License will need to be amended for the inclusion of a 10 CFR Part 30 license, “Rules of General Applicability to Domestic Licensing of Byproduct Material”
- Westinghouse will prepare a technical report to supplement the License Amendment Request (LAR)
- Changes to the Technical Specifications will be made if required
- UFSAR updates will be required

Licensing Approach (contd.)

- Current NRC-approved codes and methods remain applicable for core design and reload safety evaluations

a,c



Cobalt-60 Production

a,c



[

]a,c

a,c



Key Design Considerations

- Preclude cobalt, reactor coolant interaction
 - []^{a,c}
- Reducing foreign material in harvesting area as low as reasonably practical
 - Design to allow easier harvesting
- Crediting existing licensed designs
 - Use pre-licensed containers / casks without modifications that would require relicensing

[]^{a,c}

Nuclear Design & Safety Analyses


- Areas of focused analysis
 - Nuclear Design impacts
 - Doses
 - SFP criticality

- Anticipate no impact to the Analysis Of Record
 - Loss of Coolant Accident
 - Fuel Rod Design
 - Thermal-Hydraulic Design
 - Transient Analysis
 - Reload safety analyses

Current NRC-approved codes and methods remain applicable for modeling []^{a,c}

Modeling of []^{a,c}

- Fairly simple Cobalt depletion chain to model :



- Depletion chain added to existing NEXUS / PARAGON / ANC code system

- No changes to basic neutronic solution methods already reviewed / approved by U.S. NRC

a,c

Modeling of []^{a,c} (contd.)

a,c

Modeling of []^{a,c} (contd.)

a,c

Typical 18-Month Loading Patterns

No []^{a,c}

^{a,c}



Example 18-Month Loading Patterns

With []^{a,c}

^{a,c}

[]^{a,c} Impacts on Core Design

a,c

[]^{a,c} Impacts on Safety Analyses

a,c



Spent Fuel Pool Building Dose Rate

- Typical NPP Fuel Building Radiation Zoning above spent fuel pool (SFP) < 2.5 mRem/hr (i.e., Zone III)
- Dose Rate Contributed from
 - SFP Water Source Terms
 - Elevated Irradiated Fuel Assembly in Movement (at least 10 feet underneath the SFP water surface)
- Co-60 is a major gamma source (5.271 years half-life)
 - Emits 1.173 MeV and 1.332 MeV gamma rays
 - Cascade decay with almost 100% branching ratio
 - About []^{a,c} Co-60 produced each unit per campaign


Spent Fuel Pool Building Dose Rate (contd.)

- SFP Water Source Terms (Typical)



Spent Fuel Pool Building Dose Rate (contd.)

- Elevated Irradiated Fuel Assembly in Movement (10 feet underneath the SFP water surface)



Spent Fuel Pool Building Dose Rate (contd.)

a,c



Spent Fuel Pool Dose Rate Summary

- Co-60 bearing assemblies are expected to yield higher dose rates than a standard assembly during movement
- Westinghouse will be performing detailed evaluations to assess dose rate above the water surface while moving irradiated []^{a,c}
- Site-specific radiation zone mapping will be updated if necessary

Spent Fuel Pool Criticality

- SFP criticality will be performed on a plant specific basis.

a,c

Harvesting

a,c

Harvesting (contd.)

a,c

Harvesting (contd.)

a,c

Harvesting (contd.)

a,c

Harvesting (contd.)

a,c



Co-60 Activity Measurements

- Platinum Self Powered Detector (SPD) has established Co-60 gamma sensitivity⁽¹⁾
 - Generates current from both Compton and photoelectric effects

a,c

Transportation of Co-60 [

]a,c

a,c

Transportation of Co-60 [[REDACTED]]^{a,c} (contd.)

^{a,c}

^{a,c}

Schedule

a,c

Summary

- Changes anticipated to the operating license, but not to the Technical Specifications
- Previously licensed process in the U.S. (Hope Creek, Clinton)
- Leveraging the existing processes/procedures for Westinghouse PWRs that can be extended to Co-60 production

Utility Interest

a,c