



**1-HS/4524 FL LOCATED ON 1-HV-036**

CONTACT BLOCKS	SELECTOR SWITCH OPERATOR 01226	POSITION SPRING RETAIN RIGHT TO CENTER	STANDARD HANDLE
1ST BLOCK (FRONT)	L11 0 0 0 R11 0	L12 5 0 0 R12 0	R10 0
2ND BLOCK	L21 0 0 0 R21 0	L22 0 0 0 R22 0	R20 0

**NOTE:** CONTACT ARRANGEMENT SHOWN AS VIEWED FROM FRONT.

**1-HS/4524 FL LOCATED ON 1-HV-01**

CONTACT BLOCKS	SELECTOR SWITCH OPERATOR 01251	POSITION SPRING MAINTAINS STANDARD HANDLE
1ST BLOCK (FRONT)	L11 0 0 0 R11 0	L12 0 0 0 R12 0

**NOTE:** CONTACT ARRANGEMENT SHOWN AS VIEWED FROM FRONT.

**CLASS T**

NO.	DATE	BY	CHKD.	APP'D.	REVISION	DESCRIPTION
1	11-15-50	...	...	...	1	...
2	11-15-50	...	...	...	2	...
3	11-15-50	...	...	...	3	...
4	11-15-50	...	...	...	4	...
5	11-15-50	...	...	...	5	...

**THIS DOCUMENT AFFECTED BY DESIGN CHANGES**

**TEXAS UTILITIES SERVICES, INC.**  
 AGENT FOR:  
 DALLAS POWER & LIGHT COMPANY  
 TEXAS ELECTRIC SERVICE COMPANY  
 TEXAS POWER & LIGHT COMPANY

COMANCHE PEAK S.E.S.  
 1980-82 - 2300 MW INST. ALLIATION

**MOTOR OPERATED VALVE**  
 1-HV-4524  
 NON-SAFETY LOOP RETURN TO  
 CCW HDR. ISOL. VLV.

**GP-2** \*14101/REV 3  
 \*8015/REV 0  
 \*14101/REV 3

**2323-EI-0050**  
 SHEET NO. 10

8410050432

PDR RIDS

8410050432

