

9699-FC-40G



NOTES:
1. ALL CONCRETE SHALL BE 3000 PSI STRENGTH.
2. ALL REINFORCING SHALL BE 1/2" DIA. OR LARGER.
3. ALL REINFORCING SHALL BE WELDED TOGETHER OR LAP WELDED.
4. ALL REINFORCING SHALL BE PLACED IN THE CENTER OF THE CONCRETE.
5. ALL REINFORCING SHALL BE PLACED IN THE CENTER OF THE CONCRETE.
6. ALL REINFORCING SHALL BE PLACED IN THE CENTER OF THE CONCRETE.
7. ALL REINFORCING SHALL BE PLACED IN THE CENTER OF THE CONCRETE.
8. ALL REINFORCING SHALL BE PLACED IN THE CENTER OF THE CONCRETE.
9. ALL REINFORCING SHALL BE PLACED IN THE CENTER OF THE CONCRETE.
10. ALL REINFORCING SHALL BE PLACED IN THE CENTER OF THE CONCRETE.

FOR INFORMATION ONLY
THIS CHANGE FOR
EDCR #79-22 ONLY
REFERENCE ONLY

PLAN & DETAILS SHEET
PRIMARY AUXILIARY BUILDING
POWER STATION
YANKEE ATOMIC ELECTRIC COMPANY
ROWE, MASS.
STONE & WEBSTER ENGINEERING CORPORATION
DRAWING NUMBER: 9699-FC-40G

7911200 450

79112 00450

