



- NOTES
1. WELDS AND CRANES ADDED BY CONSTRUCTION.
 2. SOFT SEATED VALVE.
 3. SEE P.V. SUPPORT DRAWING MC-1000-1.
 4. PLUGS DRAWN BY LOW POINT IN SYSTEM.
 5. PROVIDE PLUG CONNECTION FOR CONTAINER REACTOR COOLANT DRAIN FROM HEAT EXCHANGER.
 6. LOCATE AS CLOSE TO CONTAINMENT ISOLATION VALVE AS POSSIBLE.

FOR
INFORMATION
ONLY

SI
APERTURE
CARD

NO.	REVISIONS	CHG	APP'D	DATE	SCALE	DWG. NO.
1	REV. FOR C.O. 01573-D-1-01	GLE	GLE	11/18/50	SCALE	MC-1573-D-1
2	REV. FOR C.O. 01573-D-1-02	GLE	GLE	11/18/50	SCALE	MC-1573-D-1

Q.A. CONDITION 1
 BUREAU OF POWER COMPANY
 NUCLEAR POWER DIVISION UNIT 1
 PLANT DIVISION OF
 COAST GUARD COAST GUARD SYSTEM
 (MCS)

0.7.14

8903220171

PDR RIDS

