



- NOTES:**
1. LOCATE IN LOWER CONTAINMENT.
 2. A BULK FLOWER WITH A PRESSURE TAP CONNECTION WILL BE INSTALLED TO THE EXISTING PIPING FOR PRESSURE TESTING AND REQUIRED FOR LOCAL OPERATION.
 3. LOCATE IN UPPER CONTAINMENT.
 4. CHECKER TYPE CHECKVALVE FILTER.
 5. VALVES SHOWN IN CONTAINMENT PRESSURE REDUCTION MODE.
 6. VALVE OPERATOR AND SOLENOID VALVE TO BE DESIGNED FOR A MAXIMUM CLOSING TIME OF 4 SECONDS.
 7. A FLOW INDICATOR AND A FLOW TOTALIZER WILL BE LOCATED IN THE CONTROL ROOM.
 8. VENTS AND DRAINIS POCED BY CONSTRUCTION FOR FLOW AND HEARD.

DESIGN PARAMETERS

NO.	PIPE	TEMPERATURE	CLASS	WATERMARK
01	50	PSIG	304	304
02	10	PSIG	304	304
03	10	PSIG	304	304

REVISIONS

NO.	REVISIONS	CHG	DATE	APP	DATE	CHKD	DATE	APP	DATE
1	REV. FOR CORRECTION OF DRAWING								
2	REV. FOR CORRECTION OF DRAWING								

AS BUILT
DATE 5-22-78

QA CONDITION 2
QA CONDITION 1

DUKE POWER COMPANY
MOBILE FLUIDS STRIKE UNIT 1

PLANT DIVISION OF
CONTAINMENT AIR RELEASE PIPING
REVISIONS SHEET 1/2

DWG. NO. UC-1545-1.0

FOR
INFORMATION
ONLY

APERTURE
CARD

8903220179

PDR RIDS

