



- NOTES:
1. PRIMARY SYSTEM AND STEAM GENERATOR SAMPLE SINKS, WITH ISOLATION VALVE AND/OR CHECK VALVE, SUPPLIED AS PROVIDED BY VENDOR (SAMPLE PAK 1, EQUIPMENT NO. 11).
  2. ISOLATION VALVE SUPPLY.
  3. VALVE IS NOT TO EXCEED 50.
  4. INDICATOR TO BE VIEWED FROM SAMPLE SINK.
  5. VALVE IS NOT TO EXCEED 57 AND TO REGULATE AUTOMATICALLY DOWN TO 4 CY OF AIR.
  6. PRIMARY SAMPLE TAPS WITH TYPICAL CONNECTORS AT THE END (INDICATED FOR REMOVAL).
  7. CONNECTION OF PRIMARY SYSTEM SAMPLE SINK FROM SAMPLE LINE TO SINK.
  8. USE REDUCING FITTINGS.

DETAILED PROVISIONS

NO.	PRESSURE	TEMPERATURE	CLASS	ARTICULAR
11	150 PSIG	200°F	SI	SI
12	150 PSIG	200°F	SI	SI
13	150 PSIG	200°F	SI	SI
14	150 PSIG	200°F	SI	SI
15	150 PSIG	200°F	SI	SI
16	150 PSIG	200°F	SI	SI
17	150 PSIG	200°F	SI	SI
18	150 PSIG	200°F	SI	SI
19	150 PSIG	200°F	SI	SI
20	150 PSIG	200°F	SI	SI

REVISIONS

NO.	DATE	BY	REVISION
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			

G.A. CONDITION 2  
G.A. CONDITION 1

DURE POWER COMPANY  
LOCKING HOLLOW STATION UNIT 2

FLUX DENSITY OF  
MAGNET SAMPLES 676-74  
(100)

ITEM NUMBERS  
C07021030 System

FOR INFORMATION ONLY  
SI APERTURE CARD

3-73  
CL 2 448 R0

PDR RIDS

8904050010

