



POOR ORIGINAL

30X

- NOTES:
- OP-9V-0755 SHOULD BE LOCATED WITHIN THREE FEET OF TANK NOZZLES.
 - VACUUM RELIEF VALVE INLET LINE TO BE PROVIDED WITH LOOPS TO PREVENT DUST ACCUMULATION.
 - SERVICE AIR TO PIPED TO THE NEAREST NEIGHBOR CONNECTIONS.
 - THE PRESSURE POINTS FOR PUMPS OP-C9V ARE ONLY BE USED FOR VENTING AND FLUSHING DURING POWER MAINTENANCE.
 - RADIATION MONITORING SAMPLE HEAT EXCHANGER SHOULD BE SUPPORTED BY AT LEAST 2 DIAMETERS OF THE LINE BEING SAMPLED.

NO.	DATE	BY	REVISION
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			

TERA APERTURE CARD

BECHTEL
4800 ARCADE, BERKELEY, CALIF. 94702

MIDLAND PLANT UNITS 1 & 2
CONSUMERS POWER COMPANY

PIPING AND INSTRUMENT DIAGRAM
LIQUID WASTE UNIT 1 & 2

JOB NO.	DATE	REV.
7220	M-407 SH36	2

RIDS

8112230112

