


GENERAL NOTE :
THIS DWG. REPRESENTS FUNCTIONAL
REQUIREMENTS ONLY.



1. THIS LOGIC IS APPLICABLE TO THE FOLLOWING:

2. EQUIPMENT WITHIN DASHES LINES REPRESENTS VENDOR-FURNISHED VALVE & ELECTRO-HYDRAULIC ACTUATOR SYSTEM.
3. MOTOR STARTER FOR 460V 3Ø 60HZ HYDRAULIC PUMP MOTOR.
4. WHEN TRANSFER OCCURS, THE NEWLY-ACTUATED AIM STATION COMES UP IN A PREDETERMINED STATE & THE SETPOINT REMAINS THE SAME.
5. PY-7411 IS VENDOR FURNISHED SERVO-AMPLIFIER ASSY.
6. OPEN LIMIT SWITCH FURNISHED ON VALVE, BUT NOT USED.
7. SOLENOIDS PY-7411A & B OPERATE ON 120VDC PROVIDED BY RECTIFIER IN PY-7411.
8. SOLENOID PY-7411C OPERATES DIRECTLY FROM 125 VDC SOURCE BY BUYER. DC POWER TO BE INTERRUPTED UPON

HOUSTON OFFICE ISSUED
INFORMATION ONLY
STP 14926

22 X 34 "D" SIZE

PDR RIDS

8506030411

