

11-10-1941



HOUSTON OFFICE ISSUED
INFORMATION ONLY
STP 14926

1. SUPPLIED BY VENDOR.
2. FIELD TO SET TIME FOR 5 SEC LONGER THAN DELAY REQUIRED TO ESTABLISH NORMAL FLOW.
3. COMMON WINDOW FOR LWPS PUMP SEAL FLOWS.
4. FIELD TO SET FOR 1 SEC LONGER THAN DELAY REQUIRED FOR SYSTEM FLOW TO DROP FROM HIGH FLOW TO LOW ON CLOSURE OF SEAL WATER VALVE.

THIS DWG REPRESENTS FUNCTIONAL REQUIREMENTS ONLY.

PRID: 3-F-30017 * 3-F-05026
LOGIC SYMBOLS: 3-Z-40418 THEN 3-Z-40421
ELECT. DWGS: W.E. RECR. PR TR320INPA13A; 3-E-WL03-01
W.E. CONC. TRANS. PR TR320INPA13A; 3-E-WL02-01
W.E. AUX. FEED PR TR320INPA13A; 3-E-WL01-01
W.E. CONC. TRANS. P.P. SEAL WTR. WLV. FV-5007
W.E. RECR. P.P. SEAL WTR. WLV. FV-5006
W.E. AUX. FEED P.P. SEAL WTR. WLV. FV-5008
3-E-WL46-01

22 N 88 "D" 817

