



- NOTES**
1. THE 6x4x6x4 MAY BE CUT TO ALLOW FOR OBSTRUCTION'S SUCH AS PIPE OR CONDUIT AS LONG AS THE DISTANCE BETWEEN ENDS OF ANGLES IS LIMITED TO 12". CONNECTIONS SHALL BE PLACED AT A DISTANCE NOT GREATER THAN 4" FROM THE ENDS OF ANGLES.
  2. WALLS WHICH HAVE SO MANY OBSTRUCTIONS SO AS TO MAKE THE ABOVE MODIFICATIONS IMPRACTICAL SHOULD BE REPORTED TO THE EDISON FIELD ENGINEER.
  3. ALL STEEL SHALL BE ASTM A36 & FURNISHED BY FIELD WELDING ELECTRODES TO BE E7018.
  4. Q. A. LEVEL - NONE.
  5. ALL WEDGE ANCHORS ARE 3/8" UNLESS NOTED @ 12" O.C. ORDERED BY FIELD.
  6. ALL ANGLES AND PLATES WILL BE BOLTED TO CONCRETE W/ WEDGE ANCHORS AND BOLTED TO MASONRY W/ 1/4" FORWARD EXPANSION SHIELDS (U.S. EXPANSION BOLT CO. OR EQUAL) @ 12" O.C. THE TOLERANCE ALLOWED FOR TIGHTENING ANCHORS ON BASE IR'S TO MISS REBAR IS 2" BUT NOT CLOSER TO EDGE THAN MIN. PER AISC.

NO.	DATE	DESCRIPTION	BY	CHECKED	APP'D
1		ORIGINAL DRAWING	JOHNS		
2		REVISED & REDRAWN	JOHNS		
3		ADDED 4 BLOCK TO WALL #209. ADDED SECT. 3 & STRAP ANCH. DETAIL.	JOHNS		
4			JOHNS		
5			JOHNS		
6			JOHNS		
7			JOHNS		

TERA APERTURE CARD  
81 05950 17

RIDS-PDR

8105050717

