



POOR ORIGINAL

PRC  
APERTURE  
CARD  
8108250814  
AS BUILT  
DATE 7-2-81

- NOTES:
1. REMOVE PLUG PLATES FOR SYSTEM FLUID.
  2. LOCATE VENT CLOSE TO CEILING AND VENTILATION EXHAUST LOCATED AS NEAR AS POSSIBLE.
  3. LOCATE VENT CLOSE TO CEILING AND VENTILATION EXHAUST LOCATED AS NEAR AS POSSIBLE.
  4. LOCATE VENT CLOSE TO CEILING AND VENTILATION EXHAUST LOCATED AS NEAR AS POSSIBLE.
  5. LOCATE VENT CLOSE TO CEILING AND VENTILATION EXHAUST LOCATED AS NEAR AS POSSIBLE.
  6. LOCATE VENT CLOSE TO CEILING AND VENTILATION EXHAUST LOCATED AS NEAR AS POSSIBLE.
  7. LOCATE VENT CLOSE TO CEILING AND VENTILATION EXHAUST LOCATED AS NEAR AS POSSIBLE.
  8. LOCATE VENT CLOSE TO CEILING AND VENTILATION EXHAUST LOCATED AS NEAR AS POSSIBLE.
  9. LOCATE VENT CLOSE TO CEILING AND VENTILATION EXHAUST LOCATED AS NEAR AS POSSIBLE.
  10. VENTS AND DRAINAGE SHOULD BE CONSTRUCTED FOR PLUMB AND WELD.

DESIGN PARAMETERS				DESIGN PARAMETERS					
NO.	PRESSURE	TEMPERATURE	CLASS	MATERIAL	NO.	PRESSURE	TEMPERATURE	CLASS	MATERIAL
11	2775 PSIG	100°F	D	SS	33	600 PSIG	300°F	A	SS
12	2775 PSIG	650°F	D	SS	41	2400 PSIG	650°F	A	SS
13	2400 PSIG	650°F	D	SS	46	2400 PSIG	650°F	A	SS
14	2400 PSIG	650°F	D	SS	48	2400 PSIG	650°F	A	SS
15	2400 PSIG	650°F	D	SS	49	2400 PSIG	650°F	A	SS
16	2400 PSIG	650°F	D	SS	51	2400 PSIG	650°F	A	SS
17	2400 PSIG	650°F	D	SS	52	2400 PSIG	650°F	A	SS
18	2400 PSIG	650°F	D	SS	53	2400 PSIG	650°F	A	SS
19	2400 PSIG	650°F	D	SS	54	2400 PSIG	650°F	A	SS
20	2400 PSIG	650°F	D	SS	55	2400 PSIG	650°F	A	SS
21	2400 PSIG	650°F	D	SS	56	2400 PSIG	650°F	A	SS
22	2400 PSIG	650°F	D	SS	57	2400 PSIG	650°F	A	SS
23	2400 PSIG	650°F	D	SS	58	2400 PSIG	650°F	A	SS
24	2400 PSIG	650°F	D	SS	59	2400 PSIG	650°F	A	SS
25	2400 PSIG	650°F	D	SS	60	2400 PSIG	650°F	A	SS
26	2400 PSIG	650°F	D	SS	61	2400 PSIG	650°F	A	SS
27	2400 PSIG	650°F	D	SS	62	2400 PSIG	650°F	A	SS
28	2400 PSIG	650°F	D	SS	63	2400 PSIG	650°F	A	SS
29	2400 PSIG	650°F	D	SS	64	2400 PSIG	650°F	A	SS
30	2400 PSIG	650°F	D	SS	65	2400 PSIG	650°F	A	SS
31	2400 PSIG	650°F	D	SS	66	2400 PSIG	650°F	A	SS
32	2400 PSIG	650°F	D	SS	67	2400 PSIG	650°F	A	SS
33	2400 PSIG	650°F	D	SS	68	2400 PSIG	650°F	A	SS
34	2400 PSIG	650°F	D	SS	69	2400 PSIG	650°F	A	SS
35	2400 PSIG	650°F	D	SS	70	2400 PSIG	650°F	A	SS

AUTHORIZED PRESSURE BOUNDARY REVISION - REV 3 (COI-9-24-81)  
 AS BUILT FOR PRESSURE BOUNDARY TESTING - REV 2 (COI-1-2-79)

NO.	REVISION	DATE	BY	CHKD
1	AS BUILT	7-2-81		

SYSTEM CHANGE ORDER NUMBER MC-2554-1.2-COIT  
 REQUIRED FOR START-UP: YES  NO   
 REVISION INFORMATION  
 A. INTERPRETATION CHANGE TO REGULATORY STANDARDS  
 B. INTERPRETATION CHANGE TO REGULATORY STANDARDS  
 C. INTERPRETATION CHANGE TO REGULATORY STANDARDS

DESIGNER	CHECKER	DATE	INSPECTED	DATE	RESULT

DWG. NO. MC-2554-1.8

G.A. CONDITION 2	
G.A. CONDITION 1	
DURS POWER SUPPLY	
GROUPING FLOW SWITCH UNIT 8	
FLOW DIRECTION	
ORIENTATION & VALVE CONTROL	
SYSTEM (HW)	

RIDS

8108250814

