



NOTES:

1. SEE DWG. 7220-M-448 SH 1 (Q)
2. DEPTH BELOW GRADE TO 1.2 FT. MIN.
3. FILL CONNECTIONS TO BE PROVIDED WITH WELDABLE BRANDED API CAPSULES WITH WIRE TIGHT LOCKING O-RING GASKETS & PULL CAP FITTINGS AND HOVE PLANNED OR SPECIFIED CODE.
4. STRAINERS ELEMENTS TO BE REMOVED FOLLOWING START-UP, NOT REQUIRED DURING NORMAL OPERATION.
5. FOR ON DRAIN PIPING SEE VENDOR SCHEMATICS 7220-M-452 THRU 7220-M-520. FOR RELIEF CONTROL SCHEMATICS SEE 7220-M-250 THRU 7220-M-250 (Q).
6. FLAME ARRESTOR WITH WEATHERPROOF HOOD. WENT FITTINGS CONNECTIONS MAY BE PLANNED OR SPECIFIED.
7. MAY REQUIRE ACCESS CONNECTION TO BE PROVIDED WITH APT COVER, AND WIRE TIGHT LOCKING CAP FLETTED OR SEARCHED CORRECTORS OR FITTINGS.

REVISIONS

NO.	DATE	DESCRIPTION
1	11-15-68	ISSUED FOR INFORMATION
2	11-15-68	ISSUED FOR INFORMATION
3	11-15-68	ISSUED FOR INFORMATION
4	11-15-68	ISSUED FOR INFORMATION
5	11-15-68	ISSUED FOR INFORMATION
6	11-15-68	ISSUED FOR INFORMATION
7	11-15-68	ISSUED FOR INFORMATION
8	11-15-68	ISSUED FOR INFORMATION
9	11-15-68	ISSUED FOR INFORMATION
10	11-15-68	ISSUED FOR INFORMATION

BECHTEL
AN AMERICAN CORPORATION

MIDLAND PLANT UNITS 1 & 2
CONSUMERS POWER COMPANY

PIPING INSTRUMENT DIAGRAM
EMERGENCY DIESEL GENERATOR FUEL OIL STORAGE & TRANSFER UNITS 1 & 2

7220	M-452 SH 1A(Q)	5
------	----------------	---

30X

17"
11"
8.5"
8.5"
11"
8.5"
11"
17"

17"
11"
8.5"
8.5"
11"
8.5"
11"
17"

RIDS

8302100509

