



LOCATION OF RELIEF STACK AS LOCATED FROM 1/4 OF DISCHARGE PIPE

VALVE	AV. AZIMUTH	DISTANCE
2 P.V. 3203 A	270°	3/4
3203	270°	3/4
3204	270°	3/4
3205	270°	3/4
3206	270°	3/4
3207	270°	3/4
3208	270°	3/4
3209	270°	3/4
3210	270°	3/4

\* SEE DRIP PAN DETAIL "I" THIS DWG. (C-5)

SEE DETAIL AT (C-3)  
DWG NO. H-432 SH.3

APPROX. L.F. 955'-0" INCL STACKS

NOTES CONTINUED  
11. MANHOLES LOCATED ON THIS AND OTHER DECKERS, DIMENSIONS INDICATED BY DIMENSIONED-DIM LINE FOR APPROXIMATE, OR CHECK FOR CLIENT'S CONFORMANCE.

DESIGN MANAGER'S DATA	
NAME	
NO.	
DATE	
PROJECT	
DESCRIPTION	
LOCATION	
SCALE	
OTHER DATA	

  

DESIGN APPROVED DATA	
NAME	
NO.	
DATE	
PROJECT	
DESCRIPTION	
LOCATION	
SCALE	
OTHER DATA	

SYMBOLS	
○	CLOSE
○	OPEN
○	DRIP PAN
○	RELIEF STACK
○	VALVE
○	WELD
○	FLANGE
○	PIPE
○	PLATE
○	ROOF
○	STAIR
○	ELEVATOR
○	WIND
○	DRIP PAN
○	RELIEF STACK
○	VALVE
○	WELD
○	FLANGE
○	PIPE
○	PLATE
○	ROOF
○	STAIR
○	ELEVATOR
○	WIND

1. ALL PIPES TO BE FABRICATED AND INSTALLED IN ACCORDANCE WITH SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
2. THE MINIMUM WALL THICKNESS OF PIPE, VALVES AND FITTINGS, USE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
3. THE PIPES AND FITTINGS SHALL BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
4. THE PIPES AND FITTINGS SHALL BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
5. THE PIPES AND FITTINGS SHALL BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
6. ALL ALLOWABLE BESS (B.S.S.) SHALL BE USED IN ALL WELDS AND ALL PIPES TO BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
7. THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000 SHALL BE USED.
8. THE PIPES AND FITTINGS SHALL BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
9. THE PIPES AND FITTINGS SHALL BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
10. THE PIPES AND FITTINGS SHALL BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
11. FOR VENTS AND DRAINS USE MATERIALS 1218-0-20, 1218-0-200, 1218-0-2000.
12. ALL PIPES TO BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
13. ALL PIPES TO BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
14. ALL PIPES TO BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.
15. ALL PIPES TO BE WELDED TO THE PIPE SPECIFICATIONS 1218-0-20, 1218-0-200, 1218-0-2000.

POOR ORIGINAL

NO.	REVISION	DATE	BY	CHECKED
1	ISSUED FOR CONSTRUCTION	10/15/50	J.P.	J.P.
2	ISSUED FOR SUPPORT	11/15/50	J.P.	J.P.

DESIGNED BY	J.P.
CHECKED BY	J.P.
DATE	10/15/50
PROJECT	H-432 SH.3
SCALE	AS SHOWN
APP. 1	J.P.
APP. 2	J.P.
APP. 3	J.P.

7220	H-632 SH.2 (D)	10
------	----------------	----

RIDS

8302160044

