



APPROX. L.F. 204

- NOTES:
1. ALL PIPING TO BE FABRICATED AND ASSEMBLED IN ACCORDANCE WITH SPECIFICATION (S) 7700-0-04.
 2. FOR ALL PIPING TO BE WELDED, WELDING SHALL BE PERFORMED IN ACCORDANCE WITH THE WELDING PROCEDURE SPECIFICATION (WPS) AND QUALIFICATION RECORD (QTR) FOR THE WELDER.
 3. FOR PIPING AND EQUIPMENT TO BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS).
 4. FOR EQUIPMENT TO BE INSTALLED IN ACCORDANCE WITH THE EQUIPMENT SPECIFICATION (ES).
 5. FOR EQUIPMENT CONNECTIONS, SEE DRAWING M-41.
 6. NO ALLOWANCE HAS BEEN MADE FOR WELDED JOINTS OR GASKETS AND ALL PIPING IS TO BE INSTALLED IN THE CORRECT POSITION UNLESS OTHERWISE NOTED IN THE DRAWING.
 7. FOR PIPING SYSTEMS, COMPRESSIVE STRESS SHALL BE INDICATED BY THE FOLLOWING:
 - 10-00, 10-00, 10-01, 10-02, 10-03, 10-04.
 8. FOR TOLERANCES, SEE SPEC. M-41.
 9. PIPE BENDS UNLESS OTHERWISE NOTED SHALL BE MADE WITH CONTROLLING RADIUS OF PIPE (S) TIMES THE MINIMAL PIPE O.D. SIZE.
 10. FOR PIPING AND EQUIPMENT, UNLESS OTHERWISE NOTED, ALL PIPING SHALL BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS).
 11. FOR VENTS AND DRAINS, SEE DRAWING M-41. VENTS AND DRAINS ARE TO BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS).
 12. ALL PIPING TO BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS).
 13. ALL PIPING TO BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS).
 14. ALL PIPING TO BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS).
 15. ALL PIPING TO BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS).
 16. ALL PIPING TO BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS).
 17. BASED PIPING SPACER MATERIAL AS RECOMMENDED FOR PIPING (SEE DRAWING M-41) SHALL BE SMALLER THAN THE PIPING AND SHALL BE INSTALLED IN ACCORDANCE WITH THE INSTALLATION SPECIFICATION (IS). THE SPACER SHALL BE INSTALLED WITH 3/8" CONCENTRIC GROOVES 1/8" DEEP.

POOR ORIGINAL

PRC APERTURE CARD

SECTION VIEW OF SPACER

LINE NUMBER	CONNECTION	THICKNESS
1MBC-9B	8	0.13
1MBC-103	9	0.26
1MBC-110	15	0.10
1MBC-9D	9	0.10
1MBC-9D	16	1.03

REVISION	DATE	BY	CHKD
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			

30X

REACTOR BLDG. COOLING UNIT 1VM-56A
RETURN HEADER

REACTOR BLDG. COOLING UNIT 1VM-56B
RETURN HEADER

REACTOR BLDG. COOLING UNIT 1VM-56C
RETURN HEADER

REACTOR BLDG. COOLING UNIT 1VM-56D
RETURN HEADER

REACTOR BLDG. COOLING UNIT 1VM-56B
DRAIN SYSTEM

REACTOR BLDG. COOLING UNIT 1VM-56C
DRAIN SYSTEM

REACTOR BLDG. COOLING UNIT 1VM-56D
DRAIN SYSTEM

17"
8.5"
11"
8.5"
11"
8.5"
17"

17"
8.5"
11"
8.5"
11"
8.5"
17"

RIDS

8302160047

