



REFERENCE DRAWINGS

- LIST OF DRAWINGS 3240-B-1005
- PIPING LINE LIST 3240-A-1005
- VALVE LIST 3240-A-1007
- LIST OF SYMBOLS 3240-B-1006
- SAFETY INJ. SYS 3240-C-1013
- CHEM. VOL. CNTL. SYS 3240-G-1074
- MISC. GAS SYS 3240-G-1082
- GASEOUS WASTE MANAGEMENT SYS 3240-G-1085
- ESSENTIAL COOLING WTR SYS 3240-G-1067
- CONTAINMENT SPRAY PIPING 3240-C-1100
- REL. PIPING PENETRATIONS 3240-G-1300
- NOTES:
- 1. CONTAINMENT ISOLATION VALVES ZCS-V5005A, ZCS-V5005B, ZCS-V5005C, ZCS-V5005D TO BE LOCATED AS CLOSE AS POSSIBLE TO THE CONTAINMENT PENETRATIONS.
- 2. TOTAL NUMBER OF SPRAY NOZZLES AT CONTAINMENT HEADERS IS FOUR (4) FOR ORIENTATION SEE 3240-G-1082.
- 3. ALL MOTOR OPERATED VALVES ARE 4" x 1.5" (1" FN).
- 4. UNLESS OTHERWISE NOTED, ALL 2" REM. LEAK-OFF LINES IN P.A.B. ARE TO BE DESIGNATED AS CC54-1355A, UNLESS NOTED OTHERWISE.

WPPSS QUALITY CLASS II, G

PROJ. CARD

THIS PROJECT HAS BEEN REVIEWED AND APPROVED FOR CONSTRUCTION BY THE PROJECT ENGINEER.

DATE: 10/15/80

PROJECT ENGINEER: [Signature]

CONTRACT NO. [Blank]

ISSUE NO. [Blank]

REVISIONS:

1	ISSUED FOR PERMITTING
2	ISSUED FOR CONSTRUCTION

22"

11"

8.5"

11"

17"

22"

RIDS

8303010056

