



| CONTACT | POSITION FRONT VIEW | | | CWD |
|---------|---------------------|------|------|-----|
| | CLOSE | NORM | OPEN | |
| 1 | X | | | * |
| 2 | | | X | |
| 3 | X | | | |
| 4 | | | X | |

SPRING RETURN TO NORM WITH KEY LOCK, KEY REMOVABLE IN NORM POS ONLY
 * THIS SHEET

| LIMIT SW DEVELOPMENT | | | | |
|----------------------|-------|-----------------------------------|-----|-----|
| EBASCO SYMBOL | CONT. | VALVE OPNG. % | CWD | SH. |
| bo | 1-2 | C | 100 | |
| at | 3-4 | | | * |
| bo | 5-6 | | | * |
| ac | 7-8 | | | * |
| ac | 9-10 | | | * |
| bc | 11-12 | | | * |
| ao | 13-14 | | | * |
| bc | 15-16 | | | * |
| b % | 17-18 | | | |
| b % | 19-20 | | | |
| a % | 21-22 | | | |
| b % | 23-24 | | | |
| b % | 25-26 | | | |
| b % | 27-28 | | | |
| b % | 29-30 | | | |
| a % | 31-32 | | | |
| tc | 35-36 | OPENS ON OVERLOAD ON CLOSE STROKE | | * |
| to | 45-46 | OPENS ON OVERLOAD ON OPEN STROKE | | * |

CONT. CLOSED * THIS SHEET

PRO APERTURE CARD

| | | | | | |
|------------------------------|----------|----|----------|---------------------------------------|--|
| EBASCO SERVICES INCORPORATED | | | | WASHINGTON PUBLIC POWER SUPPLY SYSTEM | |
| DIV. CONTROL DR. R. GHATAK | | | | NUCLEAR PROJECTS NO 3 & 5 | |
| CH. E. OVALLE | | | | CONTROL WIRING DIAGRAM | |
| DATE SEP 30, 1977 | | | | TWST TO S1 & CS PUMES A | |
| APPROVED <i>U. Wellach</i> | | | | ISO VA 2CH-VW404SAP (CH-531) | |
| REV | DATE | BY | APPROVED | | |
| 3 | 10-15-81 | PM | VA | | |
| 1 | 7-29-80 | VA | VA | | |

NUCLEAR SAFETY RELATED WPPSS QUALITY CLASS I

WPPS-3240
 D-6001
 SHEET 1955

RIDS

8303040083

