



NOTES

- UNLESS OTHERWISE INDICATED ALL PIPING IS CATEGORY II QUALITY GROUP D AND PER PIPING DESIGN TABLE 002BB.
- INLET PIPING FOR STATION AIR COMPRESSORS SHALL BE TAKEN FROM OUTDOORS.
- 3" x 1/2" REDUCING FLANGE.
- THE SERVICE AIR PIPING SYSTEM AS SHOWN ON THIS PLOD IS TO BE FURNISHED & INSTALLED COMPLETE BY SPEC Y-2739 EXCEPT AS NOTED.
- SPEC Y-2739 IS TO PROVIDE AS NOTED A TEMPORARY HEADER CAP.
- FOR DETAILS OF STATION AIR COMPRESSOR INTERNAL PIPING SEE ATLAS C-2000 DRWG Y-2734.

UNIT - 1 CIRCULATING WATER PUMPHOUSE

UNIT - 2 CIRCULATING WATER PUMPHOUSE

SODIUM HYPOCHLORITE INJECTION PUMPHOUSE

DIAGRAM OF SERVICE AIR PIPING FOR TURBINE BUILDING STATION UNITS 1 & 2
 CONSTRUCTION DIVISION
 CHICAGO, ILLINOIS

REVISION RECORD

REV.	DATE	BY	REASON
1	5-6-82	J. M. ...	RECORD BYRON REV. X-6-81 INTER. T. L. CO. (BIT) NOT APPLICABLE TO M-H. ADD FORS M-521 & M-525. DELETE & REVISE UNIQUE FEATURES FOR FAB PER SPEC Y-2282 & CONSTR. PER SPEC Y-2739.
2	9-1-82	J. M. ...	ADD UNIQUE FEATURES - CRFB-8 - FOR FAB PER SPEC Y-2282 & CONSTR. PER SPEC Y-2739.
3	12-21-82	J. M. ...	DEL. M-H NO. 2 - ADD UNQ. FEAT. FOR SA SYS. REV. - SSS-735 - FOR FAB/CONSTR. PER SPEC Y-2739 FOR INFO Y-2702.

SCALE
 NONE

PROJECT NUMBER
 4803

DRAWING NO.
 M-54

SHEET
 1 OF 4

DIAGRAM OF SERVICE AIR PIPING FOR TURBINE BUILDING STATION UNITS 1 & 2
 PUBLIC SERVICE INDIANA
 PLAINFIELD, INDIANA

8305090299

RIDS

