



- NOTES:
1. C-DRIP LEG AT LEAST 36" LONG WITH 2" SIDE OUTLET
 2. F-DRIP LEG AT LEAST 24" LONG WITH 1" SIDE OUTLET
 3. B-DRIP LEG AT LEAST 24" LONG WITH 1" SIDE OUTLET
 4. F-DRIP LEG AT LEAST 24" LONG WITH 1" SIDE OUTLET
 5. C-DRIP LEG AT LEAST 36" LONG WITH 2" SIDE OUTLET
 6. F-DRIP LEG AT LEAST 24" LONG WITH 1" SIDE OUTLET
 7. B-DRIP LEG AT LEAST 24" LONG WITH 1" SIDE OUTLET
 8. F-DRIP LEG AT LEAST 24" LONG WITH 1" SIDE OUTLET
 9. C-DRIP LEG AT LEAST 36" LONG WITH 2" SIDE OUTLET

DESIGN PARAMETERS

LISTING	SIZE	CLASS	PRESSURE	TEMPERATURE	CLASS	INSTR.
SM 01	157A.5	1200	PSIA	600°F	B	CS
SM 02	157A.5	1200	PSIA	600°F	F	CS
SM 03	157A.5	1200	PSIA	600°F	G	CS
SM 04	157A.5	1200	PSIA	600°F	G	CS

REVISIONS

NO.	DATE	BY	CHKD.	REASON
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				

OR CONDITION 4
OR CONDITION 1
DUKE POWER COMPANY
CATARAUGUS NUCLEAR STATION UNIT 2
FLOW DIAGRAM OF
MAIN STEAM SYSTEM (SM)

ERN:CN001HW

PDR RIDS

9603180048

