



**PLANT AIR COMPRESSORS**

- NOTES:
1. ALL VALVES ON THIS SHEET HAVE "SW" SERVICE WATER SYSTEM PREFIX, UNLESS OTHERWISE NOTED.
  2. SC 98-153 PERMITS 3/4" OFFSET FOR EXPANSION JOINT.
  3. EXPANSION JOINT HAS 7" UNEXTENDED HEIGHT PER SC 98-153.
  4. MV-SW-278 THROTTLED PER SERVICE WATER FLOW VERIFICATION TEST 1-216.
  5. FOR DIESEL LUBE OIL AND JACKET WATER COOLING SEE P&ID M-214 SH. 1.
  6. PIPE CLASS 180-230 TO PERMIT USAGE OF AVAILABLE MATERIAL.
  7. FLANGED CONNECTIONS NOTED ARE FOR FC-955 TEMPORARY COOLING.

REV	DATE	DESCRIPTION	BY	CHK	APP
31	0-14-95	REVISED MV-SW 535 & 536 TO BALL VALVES PER SC 98-986 & DCR 95-789 (2.6.4)			
	0-18-95	CHANGED SW 136 TO CLUB VALVE PER FES 95-095 & DCR 95-614 (C.A.M.)			
<p><b>CONSUMERS POWER COMPANY</b>          PALISADES NUCLEAR PLANT          COVERT, MICHIGAN</p>					
<p><b>PIPING &amp; INSTRUMENT DIAGRAM</b>          SERVICE WATER SYSTEM</p>					
M208				1A	31

**ANSTEC APERTURE CARD**

0603280182

PDR-RIDS

