



- NOTES:**
1. LOCATE TV OR IC ON THE BOTTOM OF THE CONNECTING PIPE.
 2. DELETE.
 3. LOCATE VALVES AS CLOSE TO INSTRUMENTATION AS POSSIBLE.
 4. REMOVE FLOW METER FROM COOLING WATER LINE TO BE INSTALLED IN THE INSTRUMENTATION ROOM. INSTALL IN LINE ON A 4" OR 6" PIPE. USE VACUUM FOR INSTRUMENTATION. REMOVE FLOW METER FROM INSTRUMENTATION ROOM.
 5. FOR PIPING, VALVES, INSTRUMENTS, EQUIPMENT, ETC. REFER TO THE IDENTIFICATION NUMBER AT THE END.
 6. ALL INSTRUMENTS ON THIS P&ID ARE TO BE INSTALLED AS SHOWN UNLESS OTHERWISE NOTED.
 7. ALL INSTRUMENTS ON THIS P&ID ARE TO BE INSTALLED AS SHOWN UNLESS OTHERWISE NOTED.
 8. SWITCH LOCATED IN THE PUMP ROOM.
 9. TAG NUMBER OF VALVES (UNLESS BY GA) IS SHOWN ON TAG #.
 10. SYSTEM DESIGNATOR IS EXCEPT AS NOTED. WHEN THIS VALVE IS POWER LOCKED OUT AT THE S.C.C.

- REFERENCES:**
1. P&ID INSTRUMENT SYMBOLS
 2. GENERAL ATOMIC INC. NO. 200-1000-10011, SHEET 20-100-1000-10011-001

ANSTEC APERTURE CARD

NO.	DATE	REVISION	BY	CHK	RE	DV	HA	SE	PE	ISSUE DATE	REVISION	BY	CHK	RE	DV	HA	SE	PE	
17	10-7-93	INCORP. DCH. NO. 2914																	
16	9-25-93	INCORP. DCH. NO. 2917																	
15	6-4-93	INCORP. DCH. NO. 2882																	
14	8-8-92	INCORP. DCH. NO. 2527																	
13	4-25-93	ISSUED FOR CONSTRUCTION (PROGRAM)																	
8-12	4-25-93	ISSUED FOR CONSTRUCTION (PROGRAM)																	

HOUSTON LIGHTING & POWER COMPANY
 HOUSTON ELECTRIC GENERATING STATION

SCALE	DRG. NO.	REV.
NONE	5R289F050178	02

30:1

09/22/1997

5R209F050178?

18

PRIORITY

FJ4594 USR

9710030020

PDR RIDS

9710030020

