



- NOTES:**
1. ALL INSTRUMENTS PURCHASED VALVES (IP-1000) INSTALLED WITH FLOW UNDER SLAT EXCEPT AS NOTED.
 2. ALL CHECK VALVES SHOULD BE "T" TYPE LEFT HAND.
 3. FLOW COIL - SIZE 1/2" O.D. - THIN WALL 0.040" I.D. (DIPING SPECIFICATIONS DATA SHEET 3-0007).
 4. ALL THINGS CHECKED WHERE OPERATOR INDICATED IS FOR P.C. 7 168996.
 5. FOR SAMPLE COOLER PANEL SEE F-3010 OR 151-12-012-0.
 6. LOCATE SAMPLE VALVE AS CLOSE TO PROCESS LINE AS POSSIBLE.
 7. THE INTERVALS OF IP1017 ARE TO BE REVERSED.

REV	NO	DATE	DESCRIPTION	BY	CHKD
1	1	10/1/58	ISSUED FOR CONSTRUCTION	J. J.
2	2	10/1/58
3	3	10/1/58
4	4	10/1/58
5	5	10/1/58

ANSTEC APERTURE CARD
 DIAGRAM OF PROCESS SAMPLING (PRIMARY & SECONDARY)
 BYRON STATION UNIT I
 COMMERCIAL TRADING CO.
 CHICAGO, ILLINOIS

MC

PDR RIDS

9603290003

