



- NOTES:
1. OPERATING MODE REPRESENTED BY SOLID LINES ONE
 2. MANUALLY OPERATED LEITON FILTER IS IN SERVICE
 3. FROM SHUTDOWN MODES FOR FILTERS IN SERVICE
 4. 1/2" THRU 4" SCA - 1/2"
 5. 1/2" THRU 4" SCA - 1/2"
 6. 1/2" THRU 4" SCA - 1/2"
 7. 1/2" THRU 4" SCA - 1/2"
 8. THE ORIGINATOR OF THIS DRAWING IS BASED ON PD-181A-L, REV. 11/10/58, II, 11.1.
 9. VALVE 10P-22 WILL NOT OPERATE - AIR SUPPLY DISCONNECTED

7

LINE NO.	SYMBOL	DESIGNATION	DATE	BY	REVISION	DESCRIPTION
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						
21						
22						
23						
24						
25						
26						
27						
28						
29						
30						
31						
32						
33						
34						
35						
36						
37						
38						
39						
40						
41						
42						
43						
44						
45						
46						
47						
48						
49						
50						
51						
52						
53						
54						
55						
56						
57						
58						
59						
60						
61						
62						
63						
64						
65						
66						
67						
68						
69						
70						
71						
72						
73						
74						
75						
76						
77						
78						
79						
80						
81						
82						
83						
84						
85						
86						
87						
88						
89						
90						
91						
92						
93						
94						
95						
96						
97						
98						
99						
100						

NO.	REVISIONS	DATE	BY	DATE	APP'D	DATE	REVISIONS
1							
2							
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
14							

ANSTEC APERTURE CARD

QA CONDITION 2
QA CONDITION 1

DUKE POWER COMPANY
OCONEE NUCLEAR STATION UNIT 1

FULLY DIAGRAM OF
HIGH PRESSURE
INJECTION SYSTEM
(STORAGE SECTION)

DWG. NO. ODF-101A-1, 2

PDR RIDS

9607120124

