

# **Radioactive Material Transport Packaging System Safety Analysis Report**

**for Model AOS-025, AOS-050, and AOS-100 Transport Packages**

**Prepared by  
Alpha-Omega Services, Inc.  
Bellflower, CA**

## NOTICE AND DISCLAIMER

Alpha-Omega Services, Inc., solely for the use of the U.S. Nuclear Regulatory Commission (NRC) in licensing the AOS Radioactive Material Transport Packaging System ("AOS Transport Packaging System"), prepared this report. Alpha-Omega Services, Inc., and/or its Contractor assume no responsibility for liability nor damage, which may result from any other use of the information disclosed in this report.

The information contained in this report is believed to be an accurate and true representation of the facts known by or provided to Alpha-Omega Services, Inc., and/or its Contractor at the time this report was prepared. Alpha-Omega Services, Inc., and/or its contractor and the individual contributors to this report make no express nor implied warranty with respect to the accuracy, completeness, or usefulness of the information contained in this report, other than for the licensing of the AOS Transport Packaging System or that the use of any information disclosed in this report may not infringe privately owned rights, including patent rights.

The printed copy of this report, as submitted to the NRC, contains PDF files, one or more of which contains hyperlinks to other files (within the report) or to the Internet. These hyperlinks are either inoperable or are not essential to the use of the filing. Any material referenced by hyperlinks to the Internet that was essential for use of this filing has been submitted as part of the filing. Any material referenced by a hyperlink to another PDF that was essential for the use of this filing has either been included by reference or submitted as part of this filing.

## Revision History

Revision	Date	Description of Changes
A	January 11, 2008	Preliminary release.
B	June 20, 2009	Preliminary release.
C	September 11, 2009	Preliminary release.
D	September 28, 2010	Preliminary release.
E	October 11, 2011	Preliminary release.
F	February 1, 2012	Initial Release.
G	July 27, 2012	<ul style="list-style-type: none"> <li>Update to include cask lid elastomeric seal, and included text so the cask lid metallic seal is differentiated from the new elastomeric seal.</li> <li>Applied miscellaneous corrections (table of changes included with cover page of the submittal).</li> </ul>
H	December 30, 2012	<ul style="list-style-type: none"> <li>Updated in response to NRC RAIs.</li> <li>Applied miscellaneous corrections (table of changes included with cover page of the submittal).</li> </ul>
H-1	March 11, 2016	<ul style="list-style-type: none"> <li>Updated to add new isotope, Ir-194.</li> <li>General update to correct errors and incorporate changes communicated to NRC in letters dated April 4, May 14, and September 26, 2013, and May 6, June 5, and August 5, 2015.</li> <li>Applied miscellaneous updates and corrections (table of changes included with cover page of the submittal).</li> </ul>
H-2	June 27, 2016	Updated in response to NRC RAI.
H-3	May 3, 2017	Clarified <i>Special Form</i> material shipment requirements and applied miscellaneous corrections.
H-4	November 28, 2017	Updated Cask Thread Sealant-related information.
H-5	July 20, 2018	<ul style="list-style-type: none"> <li><b>Chapter 1</b> – Revised <a href="#">Subsection 1.2.2</a> (added discussion relating to isotope mixtures); revised <a href="#">Table 1-2</a> (deleted footnote e and renumbered remaining footnotes); added <a href="#">Table 1-2b</a>; updated <a href="#">Table 1-5</a> drawing revisions</li> <li><b>Chapter 2</b> – Replaced <a href="#">Paragraph 2.5.3.1.4</a>; added Appendix 2.12.16</li> <li><b>Chapter 5</b> – Added <a href="#">Appendix 5.5.5</a>, <a href="#">Appendix 5.5.6</a>, and <a href="#">Appendix 5.5.7</a></li> <li><b>Chapter 7</b> – Added <a href="#">Appendix 7.5.1</a></li> <li>Applied miscellaneous corrections (table of changes included with cover page of the submittal)</li> </ul>
H-6	December 10, 2018	<ul style="list-style-type: none"> <li>Update in response to NRC RAI (10-09-2018) addressing changes and clarifications in SAR Chapters 1, 5, 7, and 8</li> <li>Applied miscellaneous corrections (table of changes included with cover page of the submittal)</li> </ul>
H-7	January 25, 2019	<ul style="list-style-type: none"> <li>Updated in response to NRC questions (email dated 01-15-2019) addressing changes and clarifications in SAR Chapters 1, 2, 5, and 7</li> <li>Table of changes included with the cover page of the submittal</li> </ul>

Revision	Date	Description of Changes
J	January 31, 2021	<ul style="list-style-type: none"> <li>• Consolidation of Revisions H – H7 (Revision I intentionally skipped)</li> <li>• <a href="#">Subsection 1.2.2</a> and <a href="#">Section 7.1</a> – Clarified that the shoring materials are structural</li> <li>• Paragraphs <a href="#">2.5.3.1.2</a> through <a href="#">2.5.3.1.4</a> – Calculations revised to correct minor errors and typos</li> <li>• <a href="#">Subsection 2.6.7</a> – Removed stale note created in Revision H-5</li> <li>• <a href="#">Figures 3-18</a> through <a href="#">3-20</a> – Replaced thermal transient plots for AOS Model-025 fire condition</li> <li>• <a href="#">Figure 4-3</a> – Changed port cover torque requirement</li> <li>• <a href="#">Chapter 9</a> – Updated with current requirements, approval letter, and certificate</li> <li>• Updated <i>ANSI N14.5</i> references to 2014 edition</li> <li>• Applied miscellaneous corrections (table of changes included with cover page of the submittal)</li> </ul>

# CONTENTS

<b>1. General Information</b>	<b>1-1</b>
1.1. INTRODUCTION	1-1
1.2. PACKAGE DESCRIPTION	1-7
1.2.1. Packaging	1-8
1.2.2. Contents	1-12
1.2.3. Special Requirements for Plutonium	1-17
1.2.4. Operational Features	1-17
1.2.5. Fabrication Codes, Standards, and Acceptance Tests	1-17
1.3. APPENDIX	1-23
1.3.1. AOS Transport Packaging System, Certification Drawings	1-23
1.4. REFERENCES	1-45
<b>2. Structural Evaluation</b>	<b>2-1</b>
2.1. DESCRIPTION OF STRUCTURAL DESIGN	2-2
2.1.1. Discussion	2-2
2.1.2. Design Criteria	2-8
2.1.3. Weights and Centers of Gravity	2-23
2.1.4. Identification of Codes and Standards for Package Design	2-27
2.2. MATERIALS	2-29
2.2.1. Material Properties and Specifications	2-29
2.2.2. Chemical, Galvanic, and/or Other Reactions	2-36
2.2.3. Effects of Radiation on Materials	2-37
2.3. FABRICATION AND EXAMINATION	2-38
2.3.1. Fabrication	2-38
2.3.2. Examination	2-42
2.4. GENERAL REQUIREMENTS FOR ALL PACKAGES	2-43
2.4.1. Minimum Package Size	2-43
2.4.2. Tamper-Indicating Feature	2-43
2.4.3. Positive Closure	2-43
2.5. LIFTING AND TIE-DOWN STANDARDS FOR ALL PACKAGES	2-44
2.5.1. Lifting Devices	2-44
2.5.2. Tie-Down Devices	2-51
2.5.3. Other Devices	2-51
2.6. NORMAL CONDITIONS OF TRANSPORT	2-74
2.6.1. Heat	2-74
2.6.2. Cold	2-79
2.6.3. Reduced External Pressure	2-80
2.6.4. Increased External Pressure	2-80
2.6.5. Vibration	2-81
2.6.6. Water Spray	2-82
2.6.7. Free Drop	2-82
2.6.8. Corner Drop	2-83
2.6.9. Compression	2-83
2.6.10. Penetration	2-83
2.6.11. Structural Evaluation Results Summary and Minimum Margins of Safety under Normal Conditions of Transport	2-86
2.7. HYPOTHETICAL ACCIDENT CONDITIONS	2-92
2.7.1. Free Drop	2-93
2.7.2. Crush	2-145
2.7.3. Puncture	2-145
2.7.4. Thermal	2-147
2.7.5. Immersion – Fissile Material	2-152
2.7.6. Immersion – All Packages	2-152

2.7.7. Deep Water Immersion Test (for Type B Packages Containing More than $10^5 A_2$ )	2-152
2.7.8. Summary of Damages	2-153
2.8. ACCIDENT CONDITIONS FOR AIR TRANSPORT OF PLUTONIUM	2-158
2.9. ACCIDENT CONDITIONS FOR FISSILE MATERIAL PACKAGE FOR AIR TRANSPORT	2-158
2.10. <b>SPECIAL FORM</b>	2-158
2.11. FUEL RODS	2-158
2.12. APPENDIX	2-159
2.12.1. Data CDs	2-160
2.12.2. Structural Evaluation Results – Models AOS-025, AOS-050, and AOS-100	2-161
2.12.3. LIBRA Finite Element Analysis Program and Verification Problems	2-696
2.12.4. Description of LIBRA Files and Post-Processors: AOS Safety Analysis Report	2-727
2.12.5. Selected Material Properties References	2-753
2.12.6. Impact (Free-Drop) Test Report	2-805
2.12.7. Dimensional Inspection Report	2-881
2.12.8. Analysis of Content-Cask Lid Impact	2-891
2.12.9. Comparison of Libra Static and Dynamic Impact Analysis	2-895
2.12.10. Effect of Ribs on Stress at Foam-Cask Interface	2-913
2.12.11. Analysis of 30-Ft. Drops with Shipping Cages	2-917
2.12.12. Analysis of Tie-Down Devices	2-926
2.12.13. Certificate of Conformance, General Plastics FR-3700 Series Foam – AOS-165A Prototype	2-947
2.12.14. Analysis of Shipping Cage Lifting Bars – Models AOS-050A and AOS-100	2-949
2.12.15. Shielding/Spacer Component Evaluation – Models AOS-050A, AOS-100A, and AOS-100A-S	2-967
2.13. REFERENCES	2-985

**3. Thermal Evaluation . . . . . 3-1**

3.1. DESCRIPTION OF THERMAL DESIGN	3-1
3.1.1. Design Features	3-1
3.1.2. Contents' Decay Heat	3-2
3.1.3. Summary Tables of Temperatures	3-3
3.1.4. Summary Tables of Maximum Pressures	3-11
3.2. MATERIAL PROPERTIES AND COMPONENT SPECIFICATIONS	3-12
3.2.1. Material Properties	3-12
3.2.2. Component Specifications	3-19
3.3. THERMAL EVALUATION UNDER NORMAL CONDITIONS OF TRANSPORT	3-20
3.3.1. Heat and Cold	3-20
3.3.2. Maximum Normal Operating Pressure	3-21
3.3.3. Thermal Finite Element Model	3-21
3.3.4. Normal Conditions of Transport Thermal Results	3-45
3.4. THERMAL EVALUATION UNDER HYPOTHETICAL ACCIDENT CONDITIONS	3-46
3.4.1. Initial Conditions	3-48
3.4.2. Fire Test Conditions	3-48
3.4.3. Maximum Temperatures and Pressures	3-48
3.4.4. Maximum Thermal Stresses	3-48
3.4.5. Accident Conditions for Fissile Material Packages for Air Transport	3-48
3.4.6. Hypothetical Accident Conditions of Transport Thermal Results	3-49
3.5. APPENDIX	3-51
3.5.1. Data CDs	3-52
3.5.2. Thermal Evaluation Results – Models AOS-025, AOS-050, and AOS-100	3-53
3.5.3. LIBRA Finite Element Program Heat Transfer Module	3-262
3.5.4. Analysis Modeling Data	3-268
3.5.5. LIBRA File Input Showing Material Property Assignment	3-388
3.5.6. Justification for Use of Uniformly Distributed Decay Heat throughout Cask Cavity	3-411
3.5.7. Thermal Tests	3-425
3.5.8. Heat Test Report – AOS-165A Prototype	3-439

3.5.9. Copper Seal Locations with Analytical Model (with Cask Lid Metallic Seal) . . . . .	3-861
3.5.10. Garlock Helicoflex Report, Helicoflex Seal Temperature Limit – Cask Lid Metallic Seal . .	3-865
3.6. REFERENCES . . . . .	3-881

**4. Containment . . . . . 4-1**

4.1. DESCRIPTION OF THE CONTAINMENT SYSTEM . . . . .	4-1
4.1.1. Containment Boundary . . . . .	4-1
4.1.2. Containment Penetrations (Port Plugs) . . . . .	4-4
4.1.3. Cask Lid Seal . . . . .	4-6
4.1.4. Closure . . . . .	4-8
4.1.5. Keensert Device Evaluation . . . . .	4-18
4.2. CONTAINMENT UNDER NORMAL CONDITIONS OF TRANSPORT . . . . .	4-29
4.2.1. Containment of Radioactive Material . . . . .	4-29
4.2.2. Pressurization of Containment Boundary . . . . .	4-29
4.2.3. Containment Criterion . . . . .	4-30
4.3. CONTAINMENT UNDER HYPOTHETICAL ACCIDENT CONDITIONS . . . . .	4-31
4.3.1. Containment of Radioactive Material . . . . .	4-32
4.3.2. Containment Criterion . . . . .	4-32
4.3.3. Fission Gas Products . . . . .	4-32
4.4. LEAKAGE RATE TESTS FOR TYPE B PACKAGES . . . . .	4-32
4.5. APPENDIX . . . . .	4-33
4.5.1. Garlock Helicoflex Cask Lid Metallic Seal and AOS Cask Lid Elastomeric Seal Drawings . .	4-35
4.5.2. Fortran Program Used to Analyze Cask Lid Attachment Bolts (Reference [4.6]). . . . .	4-43
4.5.3. Cask Lid Attachment Bolt Fortran Program Input/Output Files . . . . .	4-55
4.6. REFERENCES . . . . .	4-216

**5. Shielding Evaluation . . . . . 5-1**

5.1. DESCRIPTION OF SHIELDING DESIGN . . . . .	5-1
5.1.1. Design Features . . . . .	5-1
5.1.2. Summary Table of Maximum Radiation Levels . . . . .	5-5
5.2. SOURCE SPECIFICATION . . . . .	5-6
5.2.1. Gamma Source . . . . .	5-7
5.2.2. Neutron Source . . . . .	5-8
5.3. SHIELDING MODEL . . . . .	5-9
5.3.1. Configuration of Source and Shielding . . . . .	5-9
5.3.2. Material Properties . . . . .	5-16
5.4. SHIELDING EVALUATION . . . . .	5-17
5.4.1. Methods . . . . .	5-17
5.4.2. Input and Output Data . . . . .	5-19
5.4.3. Flux-to-Dose-Rate Conversion . . . . .	5-19
5.4.4. External Radiation Levels . . . . .	5-20
5.5. APPENDIX . . . . .	5-29
5.5.1. AOS Cask Isotopic Heat Load Calculations . . . . .	5-29
5.5.2. Isotope Values for Calculations . . . . .	5-31
5.5.3. MCNP6 Input and Output Files for Dose Calculations . . . . .	5-42
5.5.4. Cobalt-60-C Volume Source Calculation Study . . . . .	5-42
5.5.5. Shipments of Multiple Isotopes under 10 CFR 71.47(a) . . . . .	5-45
5.5.6. Isotopes Insignificant to External Dose Rates . . . . .	5-49
5.5.7. 10 CFR 71.47(b) Exclusive Use Activity Limits for Models AOS-100A and AOS-100A-S . .	5-52
5.5.8. Evaluation of Dose Rate Tally Locations . . . . .	5-58
5.6. REFERENCES . . . . .	5-82

<b>6. Criticality Evaluation</b> .....	<b>6-1</b>
<b>7. Package Operations</b> .....	<b>7-1</b>
7.1. PACKAGE LOADING .....	7-6
7.1.1. Preparation for Loading .....	7-6
7.1.2. Loading of Contents .....	7-8
7.1.3. Preparation for Transport .....	7-10
7.2. PACKAGE UNLOADING .....	7-18
7.2.1. Receipt of Package from Carrier .....	7-19
7.2.2. Removal of Contents .....	7-20
7.2.3. Installing the Cask Lid .....	7-20
7.2.4. Removing the Cask from the Staging Area .....	7-21
7.2.5. Securing the Cask Lid .....	7-21
7.3. PREPARATION OF EMPTY PACKAGE FOR TRANSPORT .....	7-22
7.3.1. Inspecting the Cask Cavity .....	7-22
7.3.2. Installing and Securing the Cask Lid .....	7-22
7.3.3. Leak Testing to Verify the Assembly .....	7-23
7.3.4. Preparing the Empty Cask for Transport .....	7-23
7.4. OTHER OPERATIONS .....	7-24
7.4.1. Records and Reporting Requirements .....	7-24
7.5. APPENDIX .....	7-25
7.5.1. Dose Rate and Decay Heat Limit Compliance .....	7-25
7.6. REFERENCES .....	7-28
<b>8. Acceptance Tests and Maintenance Program</b> .....	<b>8-1</b>
8.1. ACCEPTANCE TESTS .....	8-1
8.1.1. Visual Inspections and Measurements .....	8-3
8.1.2. Weld Examinations .....	8-3
8.1.3. Structural and Pressure Tests .....	8-3
8.1.4. Leakage Tests .....	8-4
8.1.5. Component and Material Tests .....	8-4
8.1.6. Shielding Tests .....	8-14
8.1.7. Thermal Tests .....	8-15
8.1.8. Miscellaneous Tests .....	8-16
8.2. MAINTENANCE PROGRAM .....	8-17
8.2.1. Structural and Pressure Tests .....	8-17
8.2.2. Leakage Tests <a href="#">[8.4]</a> .....	8-17
8.2.3. Component and Material Tests .....	8-19
8.2.4. Thermal Tests .....	8-19
8.2.5. Miscellaneous Tests .....	8-19
8.3. APPENDIX (NONE) .....	8-20
8.4. REFERENCES .....	8-21
<b>9. Quality Assurance Program</b> .....	<b>9-1</b>
9.1. U.S. QUALITY ASSURANCE PROGRAM REQUIREMENTS .....	9-1
9.2. IAEA QUALITY ASSURANCE PROGRAM REQUIREMENTS .....	9-1
9.3. APPENDIX .....	9-2
9.3.1. U.S. Nuclear Regulatory Commission Quality Assurance Program Approval for Radioactive Material Packages No. 0086, Revision 9, Dated August 7, 2015 .....	9-2
9.4. REFERENCES .....	9-5



# FIGURES

## 1. General Information

Figure 1-1.	Isometric View – Model AOS-025A	1-3
Figure 1-2.	Isometric View – Model AOS-050A	1-4
Figure 1-3.	Isometric View – Models AOS-100A and AOS-100B	1-5
Figure 1-4.	Isometric View – Model AOS-100A-S	1-6

## 2. Structural Evaluation

Figure 2-1.	Assembled Transport Package Cutaway – Model AOS-025A	2-3
Figure 2-2.	Assembled Transport Package Cutaway – Model AOS-050A	2-4
Figure 2-3.	Assembled Transport Package Cutaway – Models AOS-100A and AOS-100B	2-5
Figure 2-4.	Isometric View – Typical Cask	2-6
Figure 2-5.	Isometric View – Typical Impact Limiter	2-7
Figure 2-6.	Axisymmetric (2D) Model – Models AOS-025, AOS-050, and AOS-100	2-15
Figure 2-7.	3D Model – Models AOS-025, AOS-050, and AOS-100	2-16
Figure 2-8.	3D Rendered Model – Models AOS-025, AOS-050, and AOS-100	2-16
Figure 2-9.	$P_m$ and $P_b$ Stress Monitoring Points – All Models	2-17
Figure 2-10.	Center of Gravity – Model AOS-025	2-24
Figure 2-11.	Center of Gravity – Model AOS-050	2-25
Figure 2-12.	Center of Gravity – Model AOS-100	2-26
Figure 2-13.	Trunnion Area Cross-Section and Force Diagram Associated with Lifting Loads	2-44
Figure 2-14.	Mesh Diagonal Tension	2-52
Figure 2-15.	Side Drop Impact Forces	2-59
Figure 2-16.	Cask and Impact Limiter FEA Model – Model AOS-100	2-61
Figure 2-17.	Cask and Impact Limiter Deformed FEA Model – Model AOS-100	2-61
Figure 2-18.	Critical Stress at Skin and J-Bolt Box Connection – Model AOS-025	2-66
Figure 2-19.	Critical Stress at Rib Connector Pin's Bearing – Models AOS-050 and AOS-100	2-67
Figure 2-20.	LIBRA Liner Model – Model AOS-025	2-70
Figure 2-21.	Equivalent Stress Due to Longitudinal Acceleration – Model AOS-025	2-71
Figure 2-22.	Equivalent Stress Due to Transverse Acceleration – Model AOS-025	2-72
Figure 2-23.	DELETED	2-73
Figure 2-24.	DELETED	2-73
Figure 2-25.	Typical Corner Cask Cavity Shell Weld Joint Configuration – All Models	2-78
Figure 2-26.	Fixed Points for Shock and Vibration Analyses	2-81
Figure 2-27.	Head-On, Side, and Slap-Down Free-Drop Orientations	2-83
Figure 2-28.	Rod Impact Analysis Load Distribution – Model AOS-100	2-84
Figure 2-29.	Rod Impact Time History Displacement at Impact Node – Model AOS-100	2-85
Figure 2-30.	Head-On, Side, and Slap-Down Free-Drop Orientations	2-94
Figure 2-31.	Test Setup (Head-On Orientation Shown) – AOS-165A Prototype	2-96
Figure 2-32.	Finite Element Model of Impact Limiter – Model AOS-100	2-98
Figure 2-33.	Head-On Drop Force and Energy – Model AOS-100	2-98
Figure 2-34.	Head-On Drop, Maximum Foam Displacement (Deformed Model) – Model AOS-100	2-99
Figure 2-35.	Head-On Drop, Maximum Equivalent Stress in Foam – Model AOS-100	2-99
Figure 2-36.	Head-On Drop Analysis Load Distribution – All Models	2-100
Figure 2-37.	Sectioned Impact Limiter Used in Head-On Drop – AOS-165A Prototype	2-103
Figure 2-38.	Impact Limiter after Head-On Drop – AOS-165A Prototype	2-104
Figure 2-39.	Rendered LIBRA Deformed Head-On Drop – AOS-165A Prototype	2-105
Figure 2-40.	Photograph Frames from High-Speed Video of Head-On Drop – AOS-165A Prototype	2-106
Figure 2-41.	Impact Response for Damping, = 0.06 – AOS-165A Prototype	2-107
Figure 2-42.	Head-On Drop Force and Energy – AOS-165A Prototype	2-108
Figure 2-43.	Side Drop Force and Energy – Model AOS-100	2-109
Figure 2-44.	Side Drop, Maximum Foam Displacement (Deformed Model) – Model AOS-100	2-110
Figure 2-45.	Side Drop, Maximum Equivalent Stress in Foam – Model AOS-100	2-110
Figure 2-46.	Side Drop, Maximum Principal Strain in Foam – Model AOS-100	2-111
Figure 2-47.	Side Drop Analysis Load Distribution – All Models	2-113

Figure 2-48.	Slap Finite Element Model – AOS-165A Prototype . . . . .	2-116
Figure 2-49.	Maximum Support Displacement versus Offset – AOS-165A Prototype. . . . .	2-117
Figure 2-50.	Slap-Down Analysis Support Displacements versus Time – AOS-165A Prototype . . . . .	2-117
Figure 2-51.	Cg/Corner Drop Analysis Load Distribution – All Models . . . . .	2-119
Figure 2-52.	Head-On Drop Cask Model . . . . .	2-122
Figure 2-53.	Side+Slap-Down and Cg/Corner Drop Cask Model . . . . .	2-123
Figure 2-54.	Force-Displacement for Head-On Drop at 75°F – Model AOS-025 . . . . .	2-124
Figure 2-55.	Force-Displacement for Side Drop at 75°F – Model AOS-025 . . . . .	2-125
Figure 2-56.	Force-Displacement for Cg/Corner Drop at 75°F – Model AOS-025 . . . . .	2-126
Figure 2-57.	Force-Displacement for Head-On Drop at 75°F – Model AOS-050 . . . . .	2-127
Figure 2-58.	Force-Displacement for Side Drop at 75°F – Model AOS-050 . . . . .	2-128
Figure 2-59.	Force-Displacement for Cg/Corner Drop at 75°F – Model AOS-050 . . . . .	2-129
Figure 2-60.	Force-Displacement for Head-On Drop at 75°F – Model AOS-100 . . . . .	2-130
Figure 2-61.	Force-Displacement for Head-On Drop at -40°F – Model AOS-100 . . . . .	2-131
Figure 2-62.	Force-Displacement for Side Drop at 75°F – Model AOS-100 . . . . .	2-132
Figure 2-63.	Force-Displacement for Cg/Corner Drop at 75°F – Model AOS-100 . . . . .	2-133
Figure 2-64.	Impact Load Distributions . . . . .	2-134
Figure 2-65.	Circumferential Impact Load Distribution for Side and Cg/Corner Drops . . . . .	2-134
Figure 2-66.	Side Impact Slap-Down Analysis . . . . .	2-138
Figure 2-67.	FEA Model of Puncture Drop . . . . .	2-146
Figure 2-68.	Generalized Model of Impact I . . . . .	2-891
Figure 2-69.	Dynamic Analysis FEA Model . . . . .	2-896
Figure 2-70.	Cask Displacement Time-History . . . . .	2-897
Figure 2-71.	Ground Impact Forces in Dynamic Model. . . . .	2-898
Figure 2-72.	Total Ground Impact Force in Dynamic Model . . . . .	2-899
Figure 2-73.	Deformed Dynamic Model at Maximum Displacement . . . . .	2-900
Figure 2-74.	Displacement Contours n Deformed Dynamic Model . . . . .	2-900
Figure 2-75.	Foam Static Analysis FEA Model . . . . .	2-901
Figure 2-76.	Deformed Foam Static Model at Maximum Displacement . . . . .	2-901
Figure 2-77.	Energy and Force Plots for Static Analysis . . . . .	2-902
Figure 2-78.	Energy and Force Plots for Static Analysis with Bi-Linear Stress-Strain. . . . .	2-903
Figure 2-79.	foam-cask.t5 LIBRA Model . . . . .	2-910
Figure 2-80.	FEA Model Used in Rib Study. . . . .	2-913
Figure 2-81.	FEA Model Section Showing Rib . . . . .	2-914
Figure 2-82.	Z-Cask Section Z-Displacements . . . . .	2-915
Figure 2-83.	Cask Section Z-Stress. . . . .	2-916
Figure 2-84.	Configuration of Cask and Pallet Impact. . . . .	2-917
Figure 2-85.	AGS Model and Typical Input File. . . . .	2-918
Figure 2-86.	Bilinear Representation of Head-On Force-Displacement – Model AOS-100. . . . .	2-920
Figure 2-87.	Trilinear Representation of Cg/Corner Force-Displacement – Model AOS-100 . . . . .	2-921
Figure 2-88.	Model AOS-100 Cg/Corner Pallet and Cask Displacements. . . . .	2-924
Figure 2-89.	Model AOS-100 Cg/Corner Pallet and Ground Impact Forces . . . . .	2-924
Figure 2-90.	Tie-Down Schematic . . . . .	2-926
Figure 2-91.	Bearing Traction Along Line $\theta = 0 - 180$ . . . . .	2-927
Figure 2-92.	Schematic of Lateral Bearing Forces . . . . .	2-929
Figure 2-93.	Tension Cables – Model AOS-100 . . . . .	2-931
Figure 2-94.	Bearing Pressure and Cable Forces . . . . .	2-933
Figure 2-95.	FEA Model of Tie-Down Ring . . . . .	2-935
Figure 2-96.	Lateral (Z) Displacement in Conical Shell – Model AOS-100 . . . . .	2-937
Figure 2-97.	Maximum Principal Membrane Stress – Model AOS-100 . . . . .	2-937
Figure 2-98.	Maximum Principal Membrane Stress – Model AOS-050 . . . . .	2-944
Figure 2-99.	Tie-Down Strap Load – Model AOS-025 . . . . .	2-945
Figure 2-100.	Lateral (Z) Displacement in Conical Shell – Model AOS-050 . . . . .	2-946
Figure 2-101.	Shipping Cage and Lifting Bar – Model AOS-050A. . . . .	2-950
Figure 2-102.	Lifting Bar – Model AOS-050A . . . . .	2-950
Figure 2-103.	Deformation of Frame and Lifting Bar under Inertia Loading – Model AOS-050A . . . . .	2-952
Figure 2-104.	Equivalent Stress within Shipping Cage Frame and Lifting Bar – Model AOS-050A . . . . .	2-953
Figure 2-105.	Lifting Bar First Buckling Mode – Model AOS-050A . . . . .	2-955
Figure 2-106.	Shipping Cage and Lifting Bar – Model AOS-100. . . . .	2-957

Figure 2-107. Lifting Bar – Model AOS-100. . . . .	2-957
Figure 2-108. Model of Lifting Bar Bolted Connection – Model AOS-100 . . . . .	2-957
Figure 2-109. Shipping Cage Vertical Displacements – Model AOS-100 . . . . .	2-960
Figure 2-110. Shipping Cage von Mises Equivalent Stress – Model AOS-100 . . . . .	2-960
Figure 2-111. Lifting Bar von Mises Equivalent Stress – Model AOS-100. . . . .	2-961
Figure 2-112. Deformation of Frame and Lifting Bar Under Inertia Loading – Model AOS-100 . . . . .	2-962
Figure 2-113. Lifting Bar First Buckling Mode – Model AOS-100 . . . . .	2-966
Figure 2-114. Lifting Bar Second Buckling Mode – Model AOS-100. . . . .	2-966
Figure 2-115. Model AOS-100A-S Co-60-C Configuration with Axial Shielding Plates and Cavity Spacer Plates . . . . .	2-968
Figure 2-116. Axial Shielding Plate ANSYS Model – Model AOS-050A . . . . .	2-971
Figure 2-117. Axial Shielding Plate End Drop ANSYS Stress Results – Model AOS-050A . . . . .	2-973
Figure 2-118. Axial Shielding Plate Side Drop ANSYS Stress Results – Model AOS-050A . . . . .	2-974
Figure 2-119. Axial Shielding Plate Corner Drop ANSYS Stress Results – Model AOS-050A . . . . .	2-974
Figure 2-120. Axial Shielding Plate – Models AOS-100A and AOS-100A-S . . . . .	2-975
Figure 2-121. ANSYS Model Contact Elements – Models AOS-100A and AOS-100A-S . . . . .	2-976
Figure 2-122. ANSYS Surface Effect Elements – Models AOS-100A and AOS-100A-S . . . . .	2-977
Figure 2-123. Axial Shielding Plate Hypothetical Accident Conditions of Transport End Drop Stress Intensity Results (psi) – Model AOS-100A and AOS-100A-S . . . . .	2-979
Figure 2-124. Axial Shielding Plate Hypothetical Accident Conditions of Transport Side Drop Stress Intensity Results (psi) – Model AOS-100A and AOS-100A-S . . . . .	2-980
Figure 2-125. Axial Shielding Plate Hypothetical Accident Conditions of Transport Corner Drop Stress Intensity Results (psi) – Model AOS-100A and AOS-100A-S . . . . .	2-980
Figure 2-126. Cavity Spacer Plate Stress ANSYS Model – Models AOS-100A and AOS-100A-S . . . . .	2-981
Figure 2-127. Cavity Spacer Plate End Drop ANSYS Stress Results – Models AOS-100A and AOS-100A-S . . . . .	2-983
Figure 2-128. Cavity Spacer Plate Side Drop ANSYS Stress Results – Models AOS-100A and AOS-100A-S . . . . .	2-984
Figure 2-129. Cavity Spacer Plate Corner Drop ANSYS Stress Results – Models AOS-100A and AOS-100A-S . . . . .	2-984

### 3. Thermal Evaluation

Figure 3-1. Analytical FEA Model – Normal Conditions of Transport . . . . .	3-22
Figure 3-2. Cask Assembly External Surface Identification, Normal Conditions of Transport – All Models (Typical; Surfaces 5, 6, 7, and 8 are not used on Model AOS-025) . . . . .	3-32
Figure 3-3. Cask Assembly External Surface Identification, Fire Condition – All Models (Typical; Surfaces 5, 6, 7, and 8 are not used on Model AOS-025) . . . . .	3-34
Figure 3-4. Expanded View of Thermal Model Defining Component Interfaces . . . . .	3-44
Figure 3-5. Thermal Finite Element Model – Fire Conditions . . . . .	3-47
Figure 3-6. Selected Nodal Locations for Normal Conditions of Transport – Model AOS-025A . . . . .	3-57
Figure 3-7. Load Case 101, 100°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-025A . . . . .	3-60
Figure 3-8. Load Case 101, 100°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-025A . . . . .	3-61
Figure 3-9. Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-025A . . . . .	3-64
Figure 3-10. Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-025A . . . . .	3-65
Figure 3-11. Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation, Entire Model – Model AOS-025A . . . . .	3-67
Figure 3-12. Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation, Entire Model – Model AOS-025A . . . . .	3-69
Figure 3-13. Load Case 105, -40°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-025A . . . . .	3-72
Figure 3-14. Load Case 105, -40°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-025A . . . . .	3-73
Figure 3-15. Load Case 106, -20°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-025A . . . . .	3-76
Figure 3-16. Load Case 106, -20°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-025A . . . . .	3-77
Figure 3-17. Selected Nodal Locations for Fire Condition – Model AOS-025A . . . . .	3-79
Figure 3-18. Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Cavity Shell, Cask Lid, Cask Lid Plug, Bottom Plate, and Tungsten Alloy – Model AOS-025A . . . . .	3-80

Figure 3-19.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Lid Seal Area, Cask Vent Port, Cask Drain Port, and Test Port – Model AOS-025A . . . . .	3-81
Figure 3-20.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Outer Shell and Impact Limiter – Model AOS-025A . . . . .	3-82
Figure 3-21.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-025A . . . . .	3-85
Figure 3-22.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-025A . . . . .	3-86
Figure 3-23.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-025A . . . . .	3-89
Figure 3-24.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-025A . . . . .	3-90
Figure 3-25.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-025A . . . . .	3-93
Figure 3-26.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-025A . . . . .	3-94
Figure 3-27.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-025A . . . . .	3-97
Figure 3-28.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-025A . . . . .	3-98
Figure 3-29.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-025A . . . . .	3-101
Figure 3-30.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-025A . . . . .	3-102
Figure 3-31.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-025A . . . . .	3-105
Figure 3-32.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-025A . . . . .	3-106
Figure 3-33.	Selected Nodal Locations for Normal Conditions of Transport – Model AOS-050A . . . . .	3-110
Figure 3-34.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-050A . . . . .	3-113
Figure 3-35.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-050A . . . . .	3-114
Figure 3-36.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-050A . . . . .	3-117
Figure 3-37.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-050A . . . . .	3-118
Figure 3-38.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation, Entire Model – Model AOS-050A . . . . .	3-120
Figure 3-39.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation, Entire Model – Model AOS-050A . . . . .	3-122
Figure 3-40.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-050A . . . . .	3-125
Figure 3-41.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-050A . . . . .	3-126
Figure 3-42.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-050A . . . . .	3-129
Figure 3-43.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-050A . . . . .	3-130
Figure 3-44.	Selected Nodal Locations for Fire Condition – Model AOS-050A . . . . .	3-132
Figure 3-45.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Cavity Shell, Cask Lid, Cask Lid Plug, Bottom Plate, and Tungsten Alloy – Model AOS-050A . . . . .	3-133
Figure 3-46.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Lid Seal Area, Cask Vent Port, Cask Drain Port, and Test Port – Model AOS-050A . . . . .	3-134
Figure 3-47.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Outer Shell and Impact Limiter – Model AOS-050A . . . . .	3-135
Figure 3-48.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-050A . . . . .	3-138
Figure 3-49.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-050A . . . . .	3-139
Figure 3-50.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-050A . . . . .	3-142

Figure 3-51.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-050A . . . . .	3-143
Figure 3-52.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-050A . . . . .	3-146
Figure 3-53.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-050A . . . . .	3-147
Figure 3-54.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-050A . . . . .	3-150
Figure 3-55.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-050A . . . . .	3-151
Figure 3-56.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-050A . . . . .	3-154
Figure 3-57.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-050A . . . . .	3-155
Figure 3-58.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-050A . . . . .	3-158
Figure 3-59.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-050A . . . . .	3-159
Figure 3-60.	Selected Nodal Locations for Normal Conditions of Transport – Model AOS-100 . . . . .	3-163
Figure 3-61.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-166
Figure 3-62.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-167
Figure 3-63.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-170
Figure 3-64.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-171
Figure 3-65.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-173
Figure 3-66.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-175
Figure 3-67.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-178
Figure 3-68.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-179
Figure 3-69.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-182
Figure 3-70.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-183
Figure 3-71.	Selected Nodal Locations for Fire Condition – Model AOS-100 . . . . .	3-185
Figure 3-72.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Cavity Shell, Cask Lid, Cask Lid Plug, Bottom Plate, and Tungsten Alloy – Models AOS-100A and AOS-100A-S . . . . .	3-186
Figure 3-73.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Lid Seal Area, Cask Vent Port, Cask Drain Port, and Test Port – Models AOS-100A and AOS-100A-S . . . . .	3-187
Figure 3-74.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Outer Shell and Impact Limiter – Models AOS-100A and AOS-100A-S . . . . .	3-188
Figure 3-75.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-191
Figure 3-76.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-192
Figure 3-77.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-195
Figure 3-78.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-196
Figure 3-79.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-199

Figure 3-80.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-200
Figure 3-81.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-203
Figure 3-82.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-204
Figure 3-83.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-207
Figure 3-84.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-208
Figure 3-85.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Models AOS-100A and AOS-100A-S . . . . .	3-211
Figure 3-86.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Models AOS-100A and AOS-100A-S . . . . .	3-212
Figure 3-87.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-100B . .	3-216
Figure 3-88.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-100B . .	3-217
Figure 3-89.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-100B . . . . .	3-220
Figure 3-90.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-100B . . . . .	3-221
Figure 3-91.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation, Entire Model – Model AOS-100B . . . . .	3-223
Figure 3-92.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation, Entire Model – Model AOS-100B . . . . .	3-225
Figure 3-93.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-100B . .	3-228
Figure 3-94.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-100B . .	3-229
Figure 3-95.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-100B . .	3-232
Figure 3-96.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-100B . .	3-233
Figure 3-97.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Cavity Shell, Cask Lid, Cask Lid Plug, Bottom Plate, and Carbon Steel – Model AOS-100B . . . . .	3-235
Figure 3-98.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Lid Seal Area, Cask Vent Port, Cask Drain Port, and Test Port – Model AOS-100B . . . . .	3-236
Figure 3-99.	Fire for 30 Minutes and Post Fire Cool Down for 7.5 Hours, Temperature versus Time, for Cask Outer Shell and Impact Limiter – Model AOS-100B . . .	3-237
Figure 3-100.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Entire Model – Model AOS-100B . . . . .	3-240
Figure 3-101.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Cask Model – Model AOS-100B . . . . .	3-241
Figure 3-102.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-100B . . . . .	3-244
Figure 3-103.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-100B . . . . .	3-245
Figure 3-104.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-100B . . . . .	3-248
Figure 3-105.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-100B . . . . .	3-249
Figure 3-106.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-100B . . . . .	3-252
Figure 3-107.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Cask Model – Model AOS-100B . . . . .	3-253
Figure 3-108.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-100B . . . . .	3-256
Figure 3-109.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Cask – Model AOS-100B . . . . .	3-257
Figure 3-110.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Model – Model AOS-100B . . . . .	3-260

Figure 3-111. Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Entire Cask – Model AOS-100B . . . . .	3-261
Figure 3-112. SS304 Stainless Steel Thermal Conductivity . . . . .	3-270
Figure 3-113. SS304 Stainless Steel Specific Heat . . . . .	3-271
Figure 3-114. Tungsten Alloy Conductivity . . . . .	3-272
Figure 3-115. Tungsten Alloy Specific Heat . . . . .	3-273
Figure 3-116. SA-105 Carbon Steel Conductivity . . . . .	3-275
Figure 3-117. SA-105 Carbon Steel Specific Heat . . . . .	3-276
Figure 3-118. Air Conductivity . . . . .	3-278
Figure 3-119. Air Specific Heat . . . . .	3-279
Figure 3-120. Air Density . . . . .	3-280
Figure 3-121. Normal Conditions of Transport Model Dimensions – Model AOS-025 . . . . .	3-281
Figure 3-122. Normal Conditions of Transport Model Dimensions – Model AOS-050 . . . . .	3-282
Figure 3-123. Normal Conditions of Transport Model Dimensions – Model AOS-100 . . . . .	3-283
Figure 3-124. Applied 30-ft. Drop Deformations – Model AOS-025 . . . . .	3-284
Figure 3-125. Applied 30-ft. Drop Deformations – Model AOS-050 . . . . .	3-285
Figure 3-126. Applied 30-ft. Drop Deformations – Model AOS-100 . . . . .	3-285
Figure 3-127. Hypothetical Accident Conditions of Transport Model Dimensions – Model AOS-025 . . . . .	3-286
Figure 3-128. Hypothetical Accident Conditions of Transport Model Dimensions – Model AOS-050 . . . . .	3-287
Figure 3-129. Hypothetical Accident Conditions of Transport Model Dimensions – Model AOS-100 . . . . .	3-288
Figure 3-130. Cask Assembly External Surface Identification, Normal Conditions of Transport – Model AOS-025 . . . . .	3-289
Figure 3-131. Cask Assembly External Surface Identification, Normal Conditions of Transport – Model AOS-050 . . . . .	3-290
Figure 3-132. Cask Assembly External Surface Identification, Normal Conditions of Transport – Model AOS-100 . . . . .	3-291
Figure 3-133. Cask Assembly External Surface Identification, Hypothetical Accident Conditions of Transport – Model AOS-025 . . . . .	3-292
Figure 3-134. Cask Assembly External Surface Identification, Hypothetical Accident Conditions of Transport – Model AOS-050 . . . . .	3-293
Figure 3-135. Cask Assembly External Surface Identification, Hypothetical Accident Conditions of Transport – Model AOS-100 . . . . .	3-294
Figure 3-136. Configuration 1, Impact Limiters with 30-Ft. Head-On Drop Deformation – Model AOS-100A FEA Model . . . . .	3-297
Figure 3-137. Configuration 2, Impact Limiters with No Deformations – Model AOS-100A FEA Model . . . . .	3-298
Figure 3-138. Configuration 3, Impact Limiters with Full Crush Deformations from Three (3) Directions of Drop Applied Simultaneously – Model AOS-100A FEA Model . . . . .	3-299
Figure 3-139. Analysis FEA Model, Normal Conditions of Transport – Model AOS-025 . . . . .	3-302
Figure 3-140. Analysis FEA Model, Normal Conditions of Transport – Model AOS-050 . . . . .	3-303
Figure 3-141. Analysis FEA Model, Normal Conditions of Transport – Model AOS-100A . . . . .	3-304
Figure 3-142. Analysis FEA Model, Hypothetical Accident Conditions of Transport – Model AOS-025 . . . . .	3-305
Figure 3-143. Analysis FEA Model, Hypothetical Accident Conditions of Transport – Model AOS-050 . . . . .	3-306
Figure 3-144. Analysis FEA Model, Hypothetical Accident Conditions of Transport – Model AOS-100A . . . . .	3-307
Figure 3-145. Equivalent Conductivity at Enclosed Gaps 0.0118, 0.0124, 0.0176, 0.0147, 0.0403, and 0.0108 in. – Model AOS-025A . . . . .	3-310
Figure 3-146. Equivalent Conductivity at Enclosed Gaps 0.0140, 0.0150, 0.0250, 0.0190, 0.0710, and 0.0120 in. – Model AOS-050A . . . . .	3-312
Figure 3-147. Equivalent Conductivity at Enclosed Gaps 0.0170, 0.0200, 0.0290, and 0.0130 in. – Model AOS-100A . . . . .	3-314
Figure 3-148. Equivalent Conductivity at Enclosed Gaps 0.0400 and 0.1310 in. – Model AOS-100A . . . . .	3-315
Figure 3-149. Equivalent Conductivity at Enclosed Gaps 0.0170, 0.0200, 0.0290, and 0.0130 in. – Model AOS-100B . . . . .	3-318
Figure 3-150. Equivalent Conductivity at Enclosed Gaps 0.0400 and 0.1310 in. – Model AOS-100B . . . . .	3-319
Figure 3-151. Air Kinematic Viscosity . . . . .	3-321
Figure 3-152. Cask Assembly External Surface Identification, Normal Conditions of Transport – Model AOS-025 . . . . .	3-326

Figure 3-153.	Surface Convective Coefficients at 100°F Ambient Temperature, Normal Conditions of Transport – Model AOS-025 . . . . .	3-328
Figure 3-154.	Surface Convective Coefficients at -20°F Ambient Temperature, Normal Conditions of Transport – Model AOS-025 . . . . .	3-330
Figure 3-155.	Surface Convective Coefficients at -40°F Ambient Temperature, Normal Conditions of Transport – Model AOS-025 . . . . .	3-332
Figure 3-156.	Cask Assembly External Surface Identification, Normal Conditions of Transport – Model AOS-050 . . . . .	3-334
Figure 3-157.	Surface Convective Coefficients at 100°F Ambient Temperature for Surfaces 1, 2, 3, and 11, Normal Conditions of Transport – Model AOS-050 . . . . .	3-336
Figure 3-158.	Surface Convective Coefficients at 100°F Ambient Temperature for Surfaces 4, 5, and 6, Normal Conditions of Transport – Model AOS-050 . . . . .	3-337
Figure 3-159.	Surface Convective Coefficients at -20°F Ambient Temperature for Surfaces 1, 2, 3, and 11, Normal Conditions of Transport – Model AOS-050 . . . . .	3-339
Figure 3-160.	Surface Convective Coefficients at -20°F Ambient Temperature for Surfaces 4, 5, and 6, Normal Conditions of Transport – Model AOS-050 . . . . .	3-340
Figure 3-161.	Surface Convective Coefficients at -40°F Ambient Temperature for Surfaces 1, 2, 3, and 11, Normal Conditions of Transport – Model AOS-050 . . . . .	3-342
Figure 3-162.	Surface Convective Coefficients at -40°F Ambient Temperature for Surfaces 4, 5, and 6, Normal Conditions of Transport – Model AOS-050 . . . . .	3-343
Figure 3-163.	Cask Assembly External Surface Identification, Normal Conditions of Transport – Models AOS-100A and AOS-100B . . . . .	3-345
Figure 3-164.	Surface Convective Coefficients at 100°F Ambient Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100B . . . . .	3-347
Figure 3-165.	Surface Convective Coefficients at -20°F Ambient Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100B . . . . .	3-349
Figure 3-166.	Surface Convective Coefficients at -40°F Ambient Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100B . . . . .	3-351
Figure 3-167.	Cask Assembly External Surface Identification, Hypothetical Accident Conditions of Transport – Model AOS-025 . . . . .	3-352
Figure 3-168.	Surface Convective Coefficients at 100°F Ambient Temperature, Fire Condition – Model AOS-025 . . . . .	3-354
Figure 3-169.	Cask Assembly External Surface Identification, Hypothetical Accident Conditions of Transport – Model AOS-050 . . . . .	3-356
Figure 3-170.	Surface Convective Coefficients at 100°F Ambient Temperature for Surfaces 3, 4, 5, 6, 8, and 11, Hypothetical Accident Conditions of Transport – Model AOS-050 . . . . .	3-358
Figure 3-171.	Cask Assembly External Surface Identification, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100B. . . . .	3-360
Figure 3-172.	Surface Convective Coefficients at 100°F Ambient Temperature, Fire Condition – Models AOS-100A and AOS-100B. . . . .	3-362
Figure 3-173.	Surface Convective Coefficients under Fire Condition at 1,475°F Environment – All Models . . . . .	3-364
Figure 3-174.	Maximum Decay Heat, 100°F Ambient, 24-Hour Transient with 12-Hour Solar Heat and 12-Hour Cool-Down Cycle, Maximum Temperature for Foam Inside Impact Limiter, Node 9952 – Model AOS-025A . . . . .	3-371
Figure 3-175.	Maximum Decay Heat, 100°F Ambient, 24-Hour Transient with 12-Hour Solar Heat and 12-Hour Cool-Down Cycle, Maximum Temperature for Foam Inside Impact Limiter, Node 9413 – Model AOS-050A . . . . .	3-372
Figure 3-176.	Maximum Decay Heat, 100°F Ambient, 24-Hour Transient with 12-Hour Solar Heat and 12-Hour Cool-Down Cycle, Maximum Temperature for Foam Inside Impact Limiter, Node 9079 – Model AOS-100A . . . . .	3-373
Figure 3-177.	Maximum Decay Heat, 100°F Ambient, 24-Hour Transient with 12-Hour Solar Heat and 12-Hour Cool-Down Cycle, Maximum Temperature for Foam Inside Impact Limiter, Node 9079 – Model AOS-100B . . . . .	3-374
Figure 3-178.	Case 1 – Temperature . . . . .	3-419
Figure 3-179.	Case 2 – Temperature . . . . .	3-420
Figure 3-180.	Case 3 – Temperature . . . . .	3-421



Figure 3-181.	Case 1 – Maximum Principal Stress at Cask Lid Corner. . . . .	3-422
Figure 3-182.	Case 2 – Maximum Principal Stress at Cask Lid Corner. . . . .	3-423
Figure 3-183.	Case 3 – Maximum Principal Stress at Cask Lid Corner. . . . .	3-424
Figure 3-184.	Typical Thermal Test Setup . . . . .	3-426
Figure 3-185.	Test Cask Modeling Features . . . . .	3-428
Figure 3-186.	Instrument Cask Inside Pit . . . . .	3-429
Figure 3-187.	Temperature versus Time – Heat Cycle for Thermocouples 3 through 12 . . . . .	3-431
Figure 3-188.	Temperature versus Time – Heat Cycle for Thermocouples 10 through 16 . . . . .	3-431
Figure 3-189.	Temperature versus Time – Cooling Cycle for Thermocouples 3 through 12. . . . .	3-432
Figure 3-190.	Temperature versus Time – Cooling Cycle for Thermocouples 10 through 16. . . . .	3-432
Figure 3-191.	Verification Analysis – Axisymmetric (2D) Model of Test Cask. . . . .	3-433
Figure 3-192.	Verification Analysis – Heat Cycle Boundary Conditions . . . . .	3-434
Figure 3-193.	Verification Analysis – Cooling Cycle Boundary Conditions . . . . .	3-434
Figure 3-194.	Comparison Test Data versus Analytical Results – Center, Cask Bottom . . . . .	3-435
Figure 3-195.	Comparison Test Data versus Analytical Results – Center, Inside Cask Lid Surface. . . . .	3-435
Figure 3-196.	Comparison Test Data versus Analytical Results – Center, Outside Cask Lid Surface . . . . .	3-436
Figure 3-197.	Comparison Test Data versus Analytical Results – Middle, Cask Cavity Wall . . . . .	3-436
Figure 3-198.	Comparison Test Data versus Analytical Results – Middle, Outside Wall. . . . .	3-437
Figure 3-199.	Comparison Test Data versus Analytical Results – Cask Drain Port Area . . . . .	3-437
Figure 3-200.	Comparison Test Data versus Analytical Results – Cask Vent Port Area. . . . .	3-438
Figure 3-201.	Comparison Test Data versus Analytical Results – Test Port Area . . . . .	3-438
Figure 3-202.	Boundary Nodes Excerpt, Copper Seal Locations – Model AOS-100. . . . .	3-861
Figure 3-203.	Cask Lid Metallic Seal, Test Port, Cask Vent Port, Cask Vent Port Seal, and Cask Vent Port Conical Seal Boundary Node Detail – Model AOS-100 . . . . .	3-862
Figure 3-204.	Cask Drain Port, Cask Drain Port Seal, and Cask Drain Port Conical Seal Boundary Node Detail – Model AOS-100 . . . . .	3-863

#### 4. Containment

Figure 4-1.	Containment Boundary (Cask Lid Metallic Seal Shown) . . . . .	4-2
Figure 4-2.	Typical Corner Cask Cavity Shell Weld Joint Configuration – All Models . . . . .	4-3
Figure 4-3.	Typical Port Plug Configuration . . . . .	4-5
Figure 4-4.	Cask Lid Elastomeric and Metallic Seals . . . . .	4-6
Figure 4-5.	Cask Lid Showing the Cask Lid Metallic Seal Installed – Attachment by way of Four (4) Screws, and Leak-Testing Hole . . . . .	4-7
Figure 4-6.	Cask Lid, Cask Lid Attachment Bolt, and Cask Temperature Evaluation Nodes . . . . .	4-8

#### 5. Shielding Evaluation

Figure 5-1.	Cross-Sectional View of Cask Components . . . . .	5-1
Figure 5-2.	Cask Component Half-Height – All Models . . . . .	5-3
Figure 5-3.	MCNP6 Geometry Model . . . . .	5-9
Figure 5-4.	MCNP6 Point Source Locations . . . . .	5-12
Figure 5-5.	Shielding Model Tallies for Top Source Location . . . . .	5-13
Figure 5-6.	Shielding Model Tallies for Side Source Location . . . . .	5-14
Figure 5-7.	Shielding Model Tallies for Corner Source Location . . . . .	5-14
Figure 5-8.	MCNP6 Volume Source Location/Geometries . . . . .	5-44
Figure 5-9.	Exclusive Use MCNP Tally Locations . . . . .	5-57
Figure 5-10.	Simplified 1D Dose Rate Calculations. . . . .	5-58
Figure 5-11.	Impact Limiter Gap Dose Rate Locations – Model AOS-050A . . . . .	5-61
Figure 5-12.	Impact Limiter Gap Dose Rate Locations – Models AOS-100A, AOS-100A-S, and AOS-100B . . . . .	5-61
Figure 5-13.	Impact Limiter Gap Dose Rate Locations – Ir-194 (Model AOS-050A) and Co-60-C (Models AOS-100A and AOS-100A-S) . . . . .	5-65
Figure 5-14.	Example Cross-Sectional View Showing Impact Limiter Recessed Regions – Models AOS-100A and AOS-100B Shown . . . . .	5-66
Figure 5-15.	Transport Package Surface Tallies – Model AOS-025A . . . . .	5-69
Figure 5-16.	Transport Package Surface Tallies – Model AOS-050A . . . . .	5-71
Figure 5-17.	Recessed Region Model – Model AOS-050A . . . . .	5-74

Figure 5-18.	1-m TI Tallies – Models AOS-100A and AOS-100A-S	5-76
Figure 5-19.	1-m TI Tallies – Model AOS-100B.	5-79

## 6. Criticality Evaluation

There are no figures in Chapter 6.

## 7. Package Operations

Figure 7-1.	Isometric View – Model AOS-025A	7-2
Figure 7-2.	Isometric View – Model AOS-050A	7-3
Figure 7-3.	Isometric View – Models AOS-100A and AOS-100B	7-4
Figure 7-3a.	Isometric View – Model AOS-100A-S	7-5
Figure 7-4.	Typical Vacuum Drying System Setup and Equipment	7-11
Figure 7-5.	Latch Pin Security Seal	7-15
Figure 7-6.	Turnbuckle Security Seal	7-16
Figure 7-7.	Shipping Cage Security Seal	7-17
Figure 7-8.	Example Dose Rate/Decay Heat Calculation Sheet (Model AOS-100A Non-Exclusive Shipment Version Shown)	7-27

## 8. Acceptance Tests and Maintenance Program

Figure 8-1.	Typical Thermal Test Setup	8-16
Figure 8-2.	Cask Lid Showing the Cask Lid Metallic Seal Installed – Attachment by way of Four (4) Screws, and Leak-Testing Hole	8-18

## 9. Quality Assurance Program

There are no figures in Chapter 9.

# TABLES

## 1. General Information

Table 1-1.	AOS Transport Packaging System Dimensions and Maximum Authorized Package Weight – All Models . . . . .	1-7
Table 1-2.	10 CFR 71.47(a) Activity Limits (All Isotopes Except Ir-192 and Ir-194) – All Models . . . . .	1-14
Table 1-2a.	10 CFR 71.47(a) Ir-192 and Ir-194 Activity Limits – All Models . . . . .	1-15
Table 1-2b.	10 CFR 71.47(b) Activity Limits – Model AOS-100A and AOS-100A-S . . . . .	1-16
Table 1-3.	Content Limitations – All Models . . . . .	1-16
Table 1-4.	AOS Transport Packaging System Analyses Summary – All Models . . . . .	1-18
Table 1-5.	AOS Transport Packaging System Certification Drawing List – All Models . . . . .	1-23

## 2. Structural Evaluation

Table 2-1.	Summary of Load Combinations for Normal and Hypothetical Accident Conditions of Transport . . . . .	2-10
Table 2-2.	Buckling Stress Values – All Models . . . . .	2-14
Table 2-3.	$P_m$ and $P_b$ Stress Monitoring Section Elements – All Models . . . . .	2-18
Table 2-4.	Load Cases . . . . .	2-19
Table 2-5.	Load Case Designation Summary . . . . .	2-20
Table 2-6.	Load Combinations . . . . .	2-21
Table 2-7.	AOS Transport Packaging System Maximum Authorized Package Weight and $C_g$ Locations – All Models . . . . .	2-23
Table 2-8.	Applicable Codes and Standards for Design, Fabrication, and Testing of the AOS Transport Packaging System . . . . .	2-27
Table 2-9.	Stainless Steel Mechanical Properties (Reference [2.5]) . . . . .	2-30
Table 2-10.	Cask Lid Attachment Bolt Mechanical Properties (Reference [2.5]) . . . . .	2-31
Table 2-11.	Tungsten Alloy Material Mechanical Properties . . . . .	2-32
Table 2-12.	Carbon Steel (SA-105) Material Mechanical Properties (Reference [2.5]) . . . . .	2-32
Table 2-13.	Trunnion Screw Mechanical Properties (Reference [2.5]) – All Models . . . . .	2-33
Table 2-14.	LAST-A-FOAM FR-3700 Series Foam Dynamic Strength, psi, Parallel to Direction of Rise – All Models . . . . .	2-34
Table 2-15.	LAST-A-FOAM FR-3700 Series Foam Dynamic Strength, psi, Perpendicular to Direction of Rise – All Models . . . . .	2-35
Table 2-16.	Permanent Dissimilar Metal Joints within Cask Component . . . . .	2-36
Table 2-17.	Temporary Dissimilar Metal Joints within Cask Component . . . . .	2-36
Table 2-18.	Material Selection of Major AOS Transport Packaging System Components (Typical) . . . . .	2-39
Table 2-19.	Examination Program Summary . . . . .	2-42
Table 2-20.	Lifting Load Analysis – All Models . . . . .	2-47
Table 2-21.	Average Bearing Stress – All Models . . . . .	2-49
Table 2-22.	Maximum Shear Stress, $S_V$ – All Models . . . . .	2-50
Table 2-23.	Calculation of Shipping Cage Margins of Safety – All Models . . . . .	2-53
Table 2-24.	Boundary Forces – Model AOS-025 . . . . .	2-62
Table 2-25.	Boundary Forces – Model AOS-050 . . . . .	2-63
Table 2-26.	Boundary Forces – Model AOS-100 . . . . .	2-64
Table 2-27.	Mechanical Connector Impact Load Summary – All Models . . . . .	2-65
Table 2-28.	Mechanical Connector Loads for 10g Inertia Force – All Models . . . . .	2-65
Table 2-29.	Transport Package Thermal Environment Conditions – All Models . . . . .	2-74
Table 2-30.	Temperature Summary of Normal Conditions of Transport – All Models . . . . .	2-76
Table 2-31.	Maximum Cask Cavity Pressure Due to Normal Conditions of Transport – All Models . . . . .	2-76
Table 2-32.	Stresses Resulting from Load Combinations Associated with Heat Environment under Normal Conditions of Transport – All Models . . . . .	2-79
Table 2-33.	Stresses Resulting from Load Combinations Associated with Cold Environment under Normal Conditions of Transport – All Models . . . . .	2-79
Table 2-34.	Free-Drop Distance – All Models . . . . .	2-82
Table 2-35.	Maximum Displacements in Free Drops, Normal Conditions of Transport – All Models . . . . .	2-82
Table 2-36.	Load Cases under Normal Conditions of Transport Structural Evaluation Results – All Models . . . . .	2-87

Table 2-37.	Load Combinations under Normal Conditions of Transport Structural Evaluation Results – All Models . . . . .	2-88
Table 2-38.	Min MS for Normal Conditions of Transport – Model AOS-025A . . . . .	2-90
Table 2-39.	Min MS for Normal Conditions of Transport – Model AOS-050A . . . . .	2-90
Table 2-40.	Min MS for Normal Conditions of Transport – Model AOS-100A and AOS-100A-S . . . . .	2-91
Table 2-41.	Min MS for Normal Conditions of Transport – Model AOS-100B . . . . .	2-91
Table 2-42.	Side-Drop Analysis and Test, Radial Displacement at Impact Limiters 1 and 2 – AOS-165A Prototype . . . . .	2-114
Table 2-43.	Support Displacements – AOS-165A Prototype . . . . .	2-115
Table 2-44.	Slap-Down Drop Analysis and Test, Radial Displacement at Impact Limiters 1 and 2 – AOS-165A Prototype . . . . .	2-118
Table 2-45.	9-m (30-ft.) Drop Analyses Conducted upon Each Cask Model . . . . .	2-121
Table 2-46.	Shipping Cage Weights Used in LIBRA-AGS Dynamic Response Analyses . . . . .	2-137
Table 2-47.	Loads and Accelerations Determined in Drop Analysis Impact – Model AOS-025 . . . . .	2-139
Table 2-48.	Loads and Accelerations Applied in Cask Stress Analyses – Model AOS-025 . . . . .	2-140
Table 2-49.	Loads Determined in Drop Impact Analyses – Model AOS-050 . . . . .	2-141
Table 2-50.	Loads and Accelerations Applied in Cask Stress Analyses – Model AOS-050 . . . . .	2-142
Table 2-51.	Loads Determined in Drop Analysis – Model AOS-100 . . . . .	2-143
Table 2-52.	Loads and Accelerations Applied in Cask Stress Analyses – Model AOS-100 . . . . .	2-144
Table 2-53.	Temperature Summary of Fire Condition – All Models . . . . .	2-148
Table 2-54.	Maximum Cask Cavity Pressure Due to Fire Condition – All Models . . . . .	2-148
Table 2-55.	Load Cases Associated with Thermal Stresses under Hypothetical Accident Conditions of Transport – All Models . . . . .	2-150
Table 2-56.	Load Combinations Associated with Thermal Stresses under Hypothetical Accident Conditions of Transport – All Models . . . . .	2-151
Table 2-57.	Stresses Resulting from Additional Increased External Pressure under Hypothetical Accident Conditions of Transport – All Models . . . . .	2-152
Table 2-58.	Load Cases Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – All Models . . . . .	2-154
Table 2-59.	Load Combinations Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – All Models . . . . .	2-155
Table 2-60.	Min MS for Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-156
Table 2-61.	Min MS for Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-156
Table 2-62.	Min MS for Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-157
Table 2-63.	Min MS for Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-157
Table 2-64.	Load Cases Associated with Allowable Stresses under Normal Conditions of Transport – Model AOS-025A . . . . .	2-162
Table 2-65.	Load Combinations Associated with Allowable Stresses under Normal Conditions of Transport – Model AOS-025A . . . . .	2-163
Table 2-66.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-025A . . . . .	2-164
Table 2-67.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Normal Conditions of Transport – Model AOS-025A . . . . .	2-166
Table 2-68.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation, Normal Conditions of Transport – Model AOS-025A . . . . .	2-168
Table 2-69.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation, Normal Conditions of Transport – Model AOS-025A . . . . .	2-170
Table 2-70.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-025A . . . . .	2-172
Table 2-71.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-025A . . . . .	2-174
Table 2-72.	Load Case 201, Internal Design Pressure, 207 kPa (30 psia), Normal Conditions of Transport – Model AOS-025A . . . . .	2-176
Table 2-73.	Load Case 202, Minimum External Pressure, 24 kPa (3.5 psia), Normal Conditions of Transport – Model AOS-025A . . . . .	2-178
Table 2-74.	Load Case 203, Maximum Increased External Pressure, 140 kPa (20 psia), Normal Conditions of Transport – Model AOS-025A . . . . .	2-180

Table 2-75.	Load Case 204, Additional Increased External Pressure, 2 MPa (290 psia), Normal Conditions of Transport – Model AOS-025A. . . . .	2-182
Table 2-76.	Load Case 211, Fabrication Stress, Normal Conditions of Transport – Model AOS-025A. . . . .	2-184
Table 2-77.	Load Case 215, Compression Load (5x weight), Normal Conditions of Transport – Model AOS-025A. . . . .	2-186
Table 2-78.	Load Case 216, Rod Drop onto Cask, Normal Conditions of Transport – Model AOS-025A. . . . .	2-188
Table 2-79.	Load Case 221, Forward 10g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-025A. . . . .	2-190
Table 2-80.	Load Case 222, Lateral 5g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-025A. . . . .	2-192
Table 2-81.	Load Case 223, Vertical 2g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-025A. . . . .	2-194
Table 2-82.	Load Case 231, 4-ft. Head-On Drop, Normal Conditions of Transport – Model AOS-025A. . . . .	2-196
Table 2-83.	Load Case 232, 30-ft. Head-On Drop Impact Test, Normal Conditions, Normal Conditions of Transport – Model AOS-025A. . . . .	2-198
Table 2-84.	Load Combination 101, Hot Environment, Normal Conditions of Transport – Model AOS-025A. . . . .	2-200
Table 2-85.	Load Combination 102, Cold Environment, Normal Conditions of Transport – Model AOS-025A. . . . .	2-202
Table 2-86.	Load Combination 103, Increased External Pressure, Normal Conditions of Transport – Model AOS-025A. . . . .	2-204
Table 2-87.	Load Combination 104, Minimum External Pressure, Normal Conditions of Transport – Model AOS-025A. . . . .	2-206
Table 2-88.	Load Combination 105, Cold Environment with Maximum Decay Heat, Normal Conditions of Transport – Model AOS-025A. . . . .	2-208
Table 2-89.	Load Combination 106, Maximum Pressure, Hot Environment, Normal Conditions of Transport – Model AOS-025A. . . . .	2-210
Table 2-90.	Load Combination 107, Maximum Pressure, Cold Environment, Normal Conditions of Transport – Model AOS-025A. . . . .	2-212
Table 2-91.	Load Combination 215, Compression Load, Normal Conditions of Transport – Model AOS-025A. . . . .	2-214
Table 2-92.	Load Combination 216, Rod Drop, Normal Conditions of Transport – Model AOS-025A. . . . .	2-216
Table 2-93.	Load Combination 217, Rod Drop, Cold Environment, Normal Conditions of Transport – Model AOS-025A. . . . .	2-218
Table 2-94.	Load Combination 221, Forward Vibration, Normal Conditions of Transport – Model AOS-025A. . . . .	2-220
Table 2-95.	Load Combination 222, Lateral Vibration, Normal Conditions of Transport – Model AOS-025A. . . . .	2-222
Table 2-96.	Load Combination 223, Vertical Vibration, Normal Conditions of Transport – Model AOS-025A. . . . .	2-224
Table 2-97.	Load Combination 224, Forward Vibration at Cold Temperature, Normal Conditions of Transport – Model AOS-025A. . . . .	2-226
Table 2-98.	Load Combination 225, Lateral Vibration at Cold Temperature, Normal Conditions of Transport – Model AOS-025A. . . . .	2-228
Table 2-99.	Load Combination 226, Vertical Vibration at Cold Temperature, Normal Conditions of Transport – Model AOS-025A. . . . .	2-230
Table 2-100.	Load Combination 231, 4-ft. Head-On Drop, Normal Conditions, Normal Conditions of Transport – Model AOS-025A. . . . .	2-232
Table 2-101.	Load Combination 232, 30-ft. Head-On Drop, Normal Conditions (Impact Test), Normal Conditions of Transport – Model AOS-025A. . . . .	2-234
Table 2-102.	Load Combination 233, 4-ft. Drop at Cold Temperature, Normal Conditions of Transport – Model AOS-025A. . . . .	2-236

Table 2-103.	Load Cases Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-238
Table 2-104.	Load Combinations Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-239
Table 2-105.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-240
Table 2-106.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-242
Table 2-107.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-244
Table 2-108.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-246
Table 2-109.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-248
Table 2-110.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-250
Table 2-111.	Load Case 301, 30-ft. Head-On Drop, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-252
Table 2-112.	Load Case 302, 30-ft. Side Drop + Slap-Down, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-254
Table 2-113.	Load Case 303, 30-ft. Cg/Corner Drop, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-256
Table 2-114.	Load Case 304, 30-ft. Head-On Drop at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-258
Table 2-115.	Load Case 305, 30-ft. Side Drop + Slap-Down at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-260
Table 2-116.	Load Case 306, 30-ft. Cg/Corner Drop at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-262
Table 2-117.	Load Case 311, 4-ft. Drop onto Rod, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-264
Table 2-118.	Load Combination 301, Head-On Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-266
Table 2-119.	Load Combination 302, Side Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-268
Table 2-120.	Load Combination 303, Cg/Corner Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-270
Table 2-121.	Load Combination 304, Head-On Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-272
Table 2-122.	Load Combination 305, Side Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-274
Table 2-123.	Load Combination 306, Cg/Corner Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-276
Table 2-124.	Load Combination 310, Additional Increased External Pressure (290 psi), Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-278
Table 2-125.	Load Combination 311, 4-ft. Drop onto Rod, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-280
Table 2-126.	Load Combination 312, 4-ft. Drop onto Rod at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-282
Table 2-127.	Load Combination 350, Fire at 30 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-284
Table 2-128.	Load Combination 351, Post Fire at 60 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-286
Table 2-129.	Load Combination 352, Post Fire at 90 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-288
Table 2-130.	Load Combination 353, Post Fire at 120 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-290
Table 2-131.	Load Combination 354, Post Fire at 150 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-292

Table 2-132.	Load Combination 355, Post Fire at 180 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-025A . . . . .	2-294
Table 2-133.	Load Cases Associated with Allowable Stresses under Normal Conditions of Transport – Model AOS-050A . . . . .	2-296
Table 2-134.	Load Combinations Associated with Allowable Stresses under Normal Conditions of Transport – Model AOS-050A . . . . .	2-297
Table 2-135.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-050A. . . . .	2-298
Table 2-136.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Normal Conditions of Transport – Model AOS-050A. . . . .	2-300
Table 2-137.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation, Normal Conditions of Transport – Model AOS-050A. . . . .	2-302
Table 2-138.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation, Normal Conditions of Transport – Model AOS-050A. . . . .	2-304
Table 2-139.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-050A. . . . .	2-306
Table 2-140.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-050A. . . . .	2-308
Table 2-141.	Load Case 201, Internal Design Pressure, 414 kPa (60 psia), Normal Conditions of Transport – Model AOS-050A. . . . .	2-310
Table 2-142.	Load Case 202, Minimum External Pressure, 24 kPa (3.5 psia), Normal Conditions of Transport – Model AOS-050A. . . . .	2-312
Table 2-143.	Load Case 203, Maximum Increased External Pressure, 140 kPa (20 psia), Normal Conditions of Transport – Model AOS-050A. . . . .	2-314
Table 2-144.	Load Case 204, Additional Increased External Pressure, 2 MPa (290 psia), Normal Conditions of Transport – Model AOS-050A. . . . .	2-316
Table 2-145.	Load Case 211, Fabrication Stress, Normal Conditions of Transport – Model AOS-050A. . . . .	2-318
Table 2-146.	Load Case 215, Compression Load (5x weight), Normal Conditions of Transport – Model AOS-050A. . . . .	2-320
Table 2-147.	Load Case 216, Rod Drop onto Cask, Normal Conditions of Transport – Model AOS-050A. . . . .	2-322
Table 2-148.	Load Case 221, Forward 10g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-050A. . . . .	2-324
Table 2-149.	Load Case 222, Lateral 5g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-050A. . . . .	2-326
Table 2-150.	Load Case 223, Vertical 2g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-050A. . . . .	2-328
Table 2-151.	Load Case 231, 4-ft. Head-On Drop, Normal Conditions of Transport – Model AOS-050A . .	2-330
Table 2-152.	Load Case 232, 30-ft. Head-On Drop Impact Test, Normal Conditions, Normal Conditions of Transport – Model AOS-050A. . . . .	2-332
Table 2-153.	Load Combination 101, Hot Environment, Normal Conditions of Transport – Model AOS-050A. . . . .	2-334
Table 2-154.	Load Combination 102, Cold Environment, Normal Conditions of Transport – Model AOS-050A. . . . .	2-336
Table 2-155.	Load Combination 103, Increased External Pressure, Normal Conditions of Transport – Model AOS-050A. . . . .	2-338
Table 2-156.	Load Combination 104, Minimum External Pressure, Normal Conditions of Transport – Model AOS-050A. . . . .	2-340
Table 2-157.	Load Combination 105, Cold Environment with Maximum Decay Heat, Normal Conditions of Transport – Model AOS-050A. . . . .	2-342
Table 2-158.	Load Combination 106, Maximum Pressure, Hot Environment, Normal Conditions of Transport – Model AOS-050A. . . . .	2-344
Table 2-159.	Load Combination 107, Maximum Pressure, Cold Environment, Normal Conditions of Transport – Model AOS-050A. . . . .	2-346
Table 2-160.	Load Combination 215, Compression Load, Normal Conditions of Transport – Model AOS-050A. . . . .	2-348
Table 2-161.	Load Combination 216, Rod Drop, Normal Conditions of Transport – Model AOS-050A. . . . .	2-350

Table 2-162.	Load Combination 217, Rod Drop, Cold Environment, Normal Conditions of Transport – Model AOS-050A. . . . .	2-352
Table 2-163.	Load Combination 221, Forward Vibration, Normal Conditions of Transport – Model AOS-050A. . . . .	2-354
Table 2-164.	Load Combination 222, Lateral Vibration, Normal Conditions of Transport – Model AOS-050A. . . . .	2-356
Table 2-165.	Load Combination 223, Vertical Vibration, Normal Conditions of Transport – Model AOS-050A. . . . .	2-358
Table 2-166.	Load Combination 224, Forward Vibration at Cold Temperature, Normal Conditions of Transport – Model AOS-050A. . . . .	2-360
Table 2-167.	Load Combination 225, Lateral Vibration at Cold Temperature, Normal Conditions of Transport – Model AOS-050A. . . . .	2-362
Table 2-168.	Load Combination 226, Vertical Vibration at Cold Temperature, Normal Conditions of Transport – Model AOS-050A. . . . .	2-364
Table 2-169.	Load Combination 231, 4-ft. Head-On Drop, Normal Conditions, Normal Conditions of Transport – Model AOS-050A. . . . .	2-366
Table 2-170.	Load Combination 232, 30-ft. Head-On Drop, Normal Conditions (Impact Test), Normal Conditions of Transport – Model AOS-050A. . . . .	2-368
Table 2-171.	Load Combination 233, 4-ft. Drop at Cold Temperature, Normal Conditions of Transport – Model AOS-050A. . . . .	2-370
Table 2-172.	Load Cases Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-372
Table 2-173.	Load Combinations Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-373
Table 2-174.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-374
Table 2-175.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-050A . . .	2-376
Table 2-176.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-050A . . .	2-378
Table 2-177.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-050A . . .	2-380
Table 2-178.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-050A . . .	2-382
Table 2-179.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-050A . . .	2-384
Table 2-180.	Load Case 301, 30-ft. Head-On Drop, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-386
Table 2-181.	Load Case 302, 30-ft. Side Drop + Slap-Down, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-388
Table 2-182.	Load Case 303, 30-ft. Cg/Corner Drop, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-390
Table 2-183.	Load Case 304, 30-ft. Head-On Drop at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-392
Table 2-184.	Load Case 305, 30-ft. Side Drop + Slap-Down at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-394
Table 2-185.	Load Case 306, 30-ft. Cg/Corner Drop at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-396
Table 2-186.	Load Case 311, 4-ft. Drop onto Rod, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-398
Table 2-187.	Load Combination 301, Head-On Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-400
Table 2-188.	Load Combination 302, Side Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-402
Table 2-189.	Load Combination 303, Cg/Corner Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-404
Table 2-190.	Load Combination 304, Head-On Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-406



Table 2-191.	Load Combination 305, Side Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-408
Table 2-192.	Load Combination 306, Cg/Corner Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-410
Table 2-193.	Load Combination 310, Additional Increased External Pressure (290 psi), Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-412
Table 2-194.	Load Combination 311, 4-ft. Drop onto Rod, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-414
Table 2-195.	Load Combination 312, 4-ft. Drop onto Rod at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-416
Table 2-196.	Load Combination 350, Fire at 30 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-418
Table 2-197.	Load Combination 351, Post Fire at 60 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-420
Table 2-198.	Load Combination 352, Post Fire at 90 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-422
Table 2-199.	Load Combination 353, Post Fire at 120 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-424
Table 2-200.	Load Combination 354, Post Fire at 150 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-426
Table 2-201.	Load Combination 355, Post Fire at 180 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-428
Table 2-202.	Load Cases Associated with Allowable Stresses under Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-431
Table 2-203.	Load Combinations Associated with Allowable Stresses under Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-432
Table 2-204.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-433
Table 2-205.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-435
Table 2-206.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-437
Table 2-207.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-439
Table 2-208.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-441
Table 2-209.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-443
Table 2-210.	Load Case 201, Internal Design Pressure, 1,930 kPa (280 psia), Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-445
Table 2-211.	Load Case 202, Minimum External Pressure, 24 kPa (3.5 psia), Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-447
Table 2-212.	Load Case 203, Maximum Increased External Pressure, 140 kPa (20 psia), Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-449
Table 2-213.	Load Case 204, Additional Increased External Pressure, 2 MPa (290 psia), Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-451
Table 2-214.	Load Case 211, Fabrication Stress, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-453
Table 2-215.	Load Case 215, Compression Load (5x weight), Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-455
Table 2-216.	Load Case 216, Rod Drop onto Cask, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-457
Table 2-217.	Load Case 221, Forward 10g Vibration Inertia Load, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-459
Table 2-218.	Load Case 222, Lateral 5g Vibration Inertia Load, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-461
Table 2-219.	Load Case 223, Vertical 2g Vibration Inertia Load, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-463

Table 2-220.	Load Case 231, 3-ft. Head-On Drop, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-465
Table 2-221.	Load Case 232, 30-ft. Head-On Drop Impact Test, Normal Conditions, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-467
Table 2-222.	Load Combination 101, Hot Environment, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-469
Table 2-223.	Load Combination 102, Cold Environment, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-471
Table 2-224.	Load Combination 103, Increased External Pressure, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-473
Table 2-225.	Load Combination 104, Minimum External Pressure, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-475
Table 2-226.	Load Combination 105, Cold Environment with Maximum Decay Heat, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-477
Table 2-227.	Load Combination 106, Maximum Pressure, Hot Environment, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-479
Table 2-228.	Load Combination 107, Maximum Pressure, Cold Environment, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-481
Table 2-229.	Load Combination 215, Compression Load, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-483
Table 2-230.	Load Combination 216, Rod Drop, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-485
Table 2-231.	Load Combination 217, Rod Drop, Cold Environment, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-487
Table 2-232.	Load Combination 221, Forward Vibration, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-489
Table 2-233.	Load Combination 222, Lateral Vibration, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-491
Table 2-234.	Load Combination 223, Vertical Vibration, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-493
Table 2-235.	Load Combination 224, Forward Vibration at Cold Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-495
Table 2-236.	Load Combination 225, Lateral Vibration at Cold Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-497
Table 2-237.	Load Combination 226, Vertical Vibration at Cold Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-499
Table 2-238.	Load Combination 231, 3-ft. Head-On Drop, Normal Conditions, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-501
Table 2-239.	Load Combination 233, 3-ft. Drop at Cold Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-503
Table 2-240.	Load Cases Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-505
Table 2-241.	Load Combinations Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-506
Table 2-242.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-507
Table 2-243.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-509
Table 2-244.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-511
Table 2-245.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-513
Table 2-246.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S .....	2-515

Table 2-247.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-517
Table 2-248.	Load Case 301, 30-ft. Head-On Drop, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-519
Table 2-249.	Load Case 302, 30-ft. Side Drop + Slap-Down, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-521
Table 2-250.	Load Case 303, 30-ft. Cg/Corner Drop, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-523
Table 2-251.	Load Case 304, 30-ft. Head-On Drop at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-525
Table 2-252.	Load Case 305, 30-ft. Side Drop + Slap-Down at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-527
Table 2-253.	Load Case 306, 30-ft. Cg/Corner Drop at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-529
Table 2-254.	Load Case 311, 4-ft. Drop onto Rod, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-531
Table 2-255.	Load Combination 301, Head-On Drop Orientation, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-533
Table 2-256.	Load Combination 302, Side Drop Orientation, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-535
Table 2-257.	Load Combination 303, Cg/Corner Drop Orientation, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-537
Table 2-258.	Load Combination 304, Head-On Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-539
Table 2-259.	Load Combination 305, Side Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-541
Table 2-260.	Load Combination 306, Cg/Corner Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-543
Table 2-261.	Load Combination 310, Additional Increased External Pressure (290 psi), Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-545
Table 2-262.	Load Combination 311, 4-ft. Drop onto Rod, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-547
Table 2-263.	Load Combination 312, 4-ft. Drop onto Rod at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-549
Table 2-264.	Load Combination 350, Fire at 30 Minutes, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-551
Table 2-265.	Load Combination 351, Post Fire at 60 Minutes, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-553
Table 2-266.	Load Combination 352, Post Fire at 90 Minutes, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-555
Table 2-267.	Load Combination 353, Post Fire at 120 Minutes, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-557
Table 2-268.	Load Combination 354, Post Fire at 150 Minutes, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-559
Table 2-269.	Load Combination 355, Post Fire at 180 Minutes, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-561
Table 2-270.	Load Cases Associated with Allowable Stresses under Normal Conditions of Transport – Model AOS-100B . . . . .	2-564
Table 2-271.	Load Combinations Associated with Allowable Stresses under Normal Conditions of Transport – Model AOS-100B . . . . .	2-565
Table 2-272.	Load Case 101, 100°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-100B . . . . .	2-566
Table 2-273.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Normal Conditions of Transport – Model AOS-100B . . . . .	2-568
Table 2-274.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation, Normal Conditions of Transport – Model AOS-100B . . . . .	2-570
Table 2-275.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation, Normal Conditions of Transport – Model AOS-100B . . . . .	2-572

Table 2-276.	Load Case 105, -40°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-100B. . . . .	2-574
Table 2-277.	Load Case 106, -20°F Ambient, Maximum Decay Heat, Normal Conditions of Transport – Model AOS-100B. . . . .	2-576
Table 2-278.	Load Case 201, Internal Design Pressure, 1,930 kPa (280 psia), Normal Conditions of Transport – Model AOS-100B. . . . .	2-578
Table 2-279.	Load Case 202, Minimum External Pressure, 24 kPa (3.5 psia), Normal Conditions of Transport – Model AOS-100B. . . . .	2-580
Table 2-280.	Load Case 203, Maximum Increased External Pressure, 140 kPa (20 psia), Normal Conditions of Transport – Model AOS-100B. . . . .	2-582
Table 2-281.	Load Case 204, Additional Increased External Pressure, 2 MPa (290 psia), Normal Conditions of Transport – Model AOS-100B. . . . .	2-584
Table 2-282.	Load Case 211, Fabrication Stress, Normal Conditions of Transport – Model AOS-100B. . . . .	2-586
Table 2-283.	Load Case 215, Compression Load (5x weight), Normal Conditions of Transport – Model AOS-100B. . . . .	2-588
Table 2-284.	Load Case 216, Rod Drop onto Cask, Normal Conditions of Transport – Model AOS-100B. . . . .	2-590
Table 2-285.	Load Case 221, Forward 10g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-100B. . . . .	2-592
Table 2-286.	Load Case 222, Lateral 5g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-100B. . . . .	2-594
Table 2-287.	Load Case 223, Vertical 2g Vibration Inertia Load, Normal Conditions of Transport – Model AOS-100B. . . . .	2-596
Table 2-288.	Load Case 231, 3-ft. Head-On Drop, Normal Conditions of Transport – Model AOS-100B. . . . .	2-598
Table 2-289.	Load Case 232, 30-ft. Head-On Drop Impact Test, Normal Conditions, Normal Conditions of Transport – Model AOS-100B. . . . .	2-600
Table 2-290.	Load Combination 101, Hot Environment, Normal Conditions of Transport – Model AOS-100B. . . . .	2-602
Table 2-291.	Load Combination 102, Cold Environment, Normal Conditions of Transport – Model AOS-100B. . . . .	2-604
Table 2-292.	Load Combination 103, Increased External Pressure, Normal Conditions of Transport – Model AOS-100B. . . . .	2-606
Table 2-293.	Load Combination 104, Minimum External Pressure, Normal Conditions of Transport – Model AOS-100B. . . . .	2-608
Table 2-294.	Load Combination 105, Cold Environment with Maximum Decay Heat, Normal Conditions of Transport – Model AOS-100B. . . . .	2-610
Table 2-295.	Load Combination 106, Maximum Pressure, Hot Environment, Normal Conditions of Transport – Model AOS-100B. . . . .	2-612
Table 2-296.	Load Combination 107, Maximum Pressure, Cold Environment, Normal Conditions of Transport – Model AOS-100B. . . . .	2-614
Table 2-297.	Load Combination 215, Compression Load, Normal Conditions of Transport – Model AOS-100B. . . . .	2-616
Table 2-298.	Load Combination 216, Rod Drop, Normal Conditions of Transport – Model AOS-100B. . . . .	2-618
Table 2-299.	Load Combination 217, Rod Drop, Cold Environment, Normal Conditions of Transport – Model AOS-100B. . . . .	2-620
Table 2-300.	Load Combination 221, Forward Vibration, Normal Conditions of Transport – Model AOS-100B. . . . .	2-622
Table 2-301.	Load Combination 222, Lateral Vibration, Normal Conditions of Transport – Model AOS-100B. . . . .	2-624
Table 2-302.	Load Combination 223, Vertical Vibration, Normal Conditions of Transport – Model AOS-100B. . . . .	2-626
Table 2-303.	Load Combination 224, Forward Vibration at Cold Temperature, Normal Conditions of Transport – Models AOS-100B. . . . .	2-628
Table 2-304.	Load Combination 225, Lateral Vibration at Cold Temperature, Normal Conditions of Transport – Models AOS-100B. . . . .	2-630

Table 2-305.	Load Combination 226, Vertical Vibration at Cold Temperature, Normal Conditions of Transport – Models AOS-100B. . . . .	2-632
Table 2-306.	Load Combination 231, 3-ft. Head-On Drop, Normal Conditions, Normal Conditions of Transport – Model AOS-100B. . . . .	2-634
Table 2-307.	Load Combination 233, 3-ft. Drop at Cold Temperature, Normal Conditions of Transport – Models AOS-100B. . . . .	2-636
Table 2-308.	Load Cases Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-638
Table 2-309.	Load Combinations Associated with Allowable Stresses under Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-639
Table 2-310.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-640
Table 2-311.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-100B . . .	2-642
Table 2-312.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-100B . . .	2-644
Table 2-313.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-100B . . .	2-646
Table 2-314.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-100B . . .	2-648
Table 2-315.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation, Hypothetical Accident Conditions of Transport – Model AOS-100B . . .	2-650
Table 2-316.	Load Case 301, 30-ft. Head-On Drop, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-652
Table 2-317.	Load Case 302, 30-ft. Side Drop + Slap-Down, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-654
Table 2-318.	Load Case 303, 30-ft. Cg/Corner Drop, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-656
Table 2-319.	Load Case 304, 30-ft. Head-On Drop at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-658
Table 2-320.	Load Case 305, 30-ft. Side Drop + Slap-Down at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-660
Table 2-321.	Load Case 306, 30-ft. Cg/Corner Drop at -40°F, Low Temperature, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-662
Table 2-322.	Load Case 311, 4-ft. Drop onto Rod, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-664
Table 2-323.	Load Combination 301, Head-On Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-666
Table 2-324.	Load Combination 302, Side Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-668
Table 2-325.	Load Combination 303, Cg/Corner Drop Orientation, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-670
Table 2-326.	Load Combination 304, Head-On Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-672
Table 2-327.	Load Combination 305, Side Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-674
Table 2-328.	Load Combination 306, Cg/Corner Drop Orientation at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-676
Table 2-329.	Load Combination 310, Additional Increased External Pressure (290 psi), Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-678
Table 2-330.	Load Combination 311, 4-ft. Drop onto Rod, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-680
Table 2-331.	Load Combination 312, 4-ft. Drop onto Rod at -40°F, Cold Environment, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-682
Table 2-332.	Load Combination 350, Fire at 30 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-684
Table 2-333.	Load Combination 351, Post Fire at 60 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-686

Table 2-334.	Load Combination 352, Post Fire at 90 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-688
Table 2-335.	Load Combination 353, Post Fire at 120 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-690
Table 2-336.	Load Combination 354, Post Fire at 150 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-692
Table 2-337.	Load Combination 355, Post Fire at 180 Minutes, Hypothetical Accident Conditions of Transport – Model AOS-100B . . . . .	2-694
Table 2-338.	STIF1 Element Property Record . . . . .	2-912
Table 2-339.	Generalized Stiffness Properties – All Models . . . . .	2-919
Table 2-340.	Generalized Pallet and Cask Mass Properties – All Models . . . . .	2-919
Table 2-341.	AGS Analysis – Model AOS-025 . . . . .	2-922
Table 2-342.	AGS Analysis – Model AOS-050 . . . . .	2-923
Table 2-343.	AGS Analysis – Model AOS-100 . . . . .	2-923
Table 2-344.	Increased Ground Impact Forces – All Models . . . . .	2-923
Table 2-345.	Model AOS-100 Cable Loads . . . . .	2-931
Table 2-346.	Maximum von Mises Stress in Shipping Cage Frame – Model AOS-050A . . . . .	2-951
Table 2-347.	Maximum von Mises Stress in Lifting Bar – Model AOS-050A . . . . .	2-952
Table 2-348.	Bolt Stresses – Model AOS-050A . . . . .	2-952
Table 2-349.	Contact Forces – Model AOS-050A . . . . .	2-952
Table 2-350.	Convergence of Elastic Stability Analysis, Mode 1 – Model AOS-050A . . . . .	2-954
Table 2-351.	Maximum von Mises Stress in Shipping Cage Frame – Model AOS-100 . . . . .	2-959
Table 2-352.	Maximum von Mises Stress in Lifting Bar – Model AOS-100 . . . . .	2-959
Table 2-353.	Displacements and Forces within Contact Elements – Model AOS-100 . . . . .	2-963
Table 2-354.	Displacements and Forces within Bolt Elements – Model AOS-100 . . . . .	2-963
Table 2-355.	Convergence of Elastic Stability Analysis, Mode 1 – Model AOS-100 . . . . .	2-964
Table 2-356.	Convergence of Elastic Stability Analysis, Mode 2 – Model AOS-100 . . . . .	2-965
Table 2-357.	Additional Required Shoring Components – Models AOS-050A, AOS-100A, and AOS-100A-S . . . . .	2-967
Table 2-358.	Stress Criteria – Models AOS-050A, AOS-100A, and AOS-100A-S . . . . .	2-970
Table 2-359.	Axial Shielding Plate ANSYS Model Loads – Model AOS-050A . . . . .	2-972
Table 2-360.	Axial Shielding Plate Stress Analysis Results during Hypothetical Accident Conditions of Transport – Model AOS-050A . . . . .	2-973
Table 2-361.	Axial Shielding Plate ANSYS Model Loads – Models AOS-100A and AOS-100A-S . . . . .	2-978
Table 2-362.	Axial Shielding Plate Stress Analysis Results during Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-979
Table 2-363.	Cavity Spacer Plate ANSYS Model Loads – Models AOS-100A and AOS-100A-S . . . . .	2-982
Table 2-364.	Cavity Spacer Plate Stress Analysis Results during Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100A-S . . . . .	2-983

### 3. Thermal Evaluation

Table 3-1.	Transport Package Thermal Environment Conditions – All Models . . . . .	3-2
Table 3-2.	Contents' Decay Heat – All Models . . . . .	3-2
Table 3-3.	Maximum Temperature Summary, Normal Conditions of Transport – All Models . . . . .	3-3
Table 3-4.	Maximum Temperature Summary, Hypothetical Accident Conditions of Transport (Condition 3) – All Models . . . . .	3-7
Table 3-5.	Type 304 Stainless Steel (SS304) Thermophysical Properties (Reference [3.16]) . . . . .	3-13
Table 3-6.	Tungsten Alloy Thermophysical Properties (Reference [3.3]) – Models AOS-025A, AOS-050A, AOS-100A, and AOS-100A-S . . . . .	3-14
Table 3-7.	Carbon Steel Properties – Model AOS-100B (Reference [3.16]) . . . . .	3-15
Table 3-8.	Air Thermophysical Properties (Reference [3.4]) . . . . .	3-17
Table 3-9.	LAST-A-FOAM FR-3700 Series Foam Thermophysical Properties – All Models (Reference [3.19]) . . . . .	3-18
Table 3-10.	Heat Flux Values – All Models . . . . .	3-24
Table 3-11.	Thermal Properties Used in Analysis as Function of Temperature, with Respect to the Air Gaps – All Models . . . . .	3-29

Table 3-12.	Cask Assembly External Surface Orientation and Size, Normal Conditions of Transport – All Models . . . . .	3-31
Table 3-13.	Cask Assembly External Surface Orientation and Size, Fire Condition – All Models . . . . .	3-33
Table 3-14.	Polynomial Coefficients Used in Equivalent Convective Property of Ambient Temperature and External Surface, Normal Conditions of Transport – All Models. . . . .	3-36
Table 3-15.	Polynomial Coefficients Used in Equivalent Convective Property of Ambient Temperature and External Surface, Steady-State Leading to the Fire and Cool-Down Conditions – All Models . . . . .	3-39
Table 3-16.	Solar Heat Application to Cask Outside Surfaces – All Models. . . . .	3-42
Table 3-17.	Temperature Monitoring Points by Condition – Model AOS-025A . . . . .	3-54
Table 3-18.	Normal Conditions of Transport Thermal Evaluation Results – Model AOS-025A . . . . .	3-56
Table 3-19.	Load Case 101, 100°F Ambient, Maximum Decay Heat – Model AOS-025A. . . . .	3-58
Table 3-20.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation – Model AOS-025A . . . . .	3-62
Table 3-21.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation – Model AOS-025A . . . . .	3-66
Table 3-22.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation – Model AOS-025A . . . . .	3-68
Table 3-23.	Load Case 105, -40°F Ambient, Maximum Decay Heat – Model AOS-025A . . . . .	3-70
Table 3-24.	Load Case 106, -20°F Ambient, Maximum Decay Heat – Model AOS-025A . . . . .	3-74
Table 3-25.	Fire Condition Thermal Evaluation Results – Model AOS-025A . . . . .	3-78
Table 3-26.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat – Model AOS-025A . . . . .	3-83
Table 3-27.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-025A. . . . .	3-87
Table 3-28.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-025A. . . . .	3-91
Table 3-29.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-025A. . . . .	3-95
Table 3-30.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-025A. . . . .	3-99
Table 3-31.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-025A. . . . .	3-103
Table 3-32.	Temperature Monitoring Points, by Condition – Model AOS-050A. . . . .	3-107
Table 3-33.	Normal Conditions of Transport Thermal Evaluation Results – Model AOS-050A . . . . .	3-109
Table 3-34.	Load Case 101, 100°F Ambient, Maximum Decay Heat – Model AOS-050A. . . . .	3-111
Table 3-35.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation – Model AOS-050A . . . . .	3-115
Table 3-36.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation – Model AOS-050A . . . . .	3-119
Table 3-37.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation – Model AOS-050A . . . . .	3-121
Table 3-38.	Load Case 105, -40°F Ambient, Maximum Decay Heat – Model AOS-050A . . . . .	3-123
Table 3-39.	Load Case 106, -20°F Ambient, Maximum Decay Heat – Model AOS-050A . . . . .	3-127
Table 3-40.	Fire Condition Thermal Evaluation Results – Model AOS-050A . . . . .	3-131
Table 3-41.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat – Model AOS-050A . . . . .	3-136
Table 3-42.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-050A. . . . .	3-140
Table 3-43.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-050A. . . . .	3-144
Table 3-44.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-050A. . . . .	3-148
Table 3-45.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-050A. . . . .	3-152
Table 3-46.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-050A. . . . .	3-156
Table 3-47.	Temperature Monitoring Points, by Condition – Model AOS-100 . . . . .	3-160
Table 3-48.	Normal Conditions of Transport Thermal Evaluation Results – Models AOS-100A and AOS-100A-S . . . . .	3-162
Table 3-49.	Load Case 101, 100°F Ambient, Maximum Decay Heat – Models AOS-100A and AOS-100A-S . . . . .	3-164

Table 3-50.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation – Models AOS-100A and AOS-100A-S . . . . .	3-168
Table 3-51.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation – Models AOS-100A and AOS-100A-S . . . . .	3-172
Table 3-52.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation – Models AOS-100A and AOS-100A-S . . . . .	3-174
Table 3-53.	Load Case 105, -40°F Ambient, Maximum Decay Heat – Models AOS-100A and AOS-100A-S . . . . .	3-176
Table 3-54.	Load Case 106, -20°F Ambient, Maximum Decay Heat – Models AOS-100A and AOS-100A-S . . . . .	3-180
Table 3-55.	Fire Condition Thermal Evaluation Results – Models AOS-100A and AOS-100A-S. . . . .	3-184
Table 3-56.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat – Models AOS-100A and AOS-100A-S . . . . .	3-189
Table 3-57.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Models AOS-100A and AOS-100A-S . . . . .	3-193
Table 3-58.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Models AOS-100A and AOS-100A-S . . . . .	3-197
Table 3-59.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Models AOS-100A and AOS-100A-S . . . . .	3-201
Table 3-60.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Models AOS-100A and AOS-100A-S . . . . .	3-205
Table 3-61.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Models AOS-100A and AOS-100A-S . . . . .	3-209
Table 3-62.	Normal Conditions of Transport Thermal Evaluation Results – Model AOS-100B . . . . .	3-213
Table 3-63.	Load Case 101, 100°F Ambient, Maximum Decay Heat – Model AOS-100B. . . . .	3-214
Table 3-64.	Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation – Model AOS-100B . . . . .	3-218
Table 3-65.	Load Case 103, -20°F Ambient, Zero Decay Heat, Zero Insolation – Model AOS-100B . . . . .	3-222
Table 3-66.	Load Case 104, -40°F Ambient, Zero Decay Heat, Zero Insolation – Model AOS-100B . . . . .	3-224
Table 3-67.	Load Case 105, -40°F Ambient, Maximum Decay Heat – Model AOS-100B . . . . .	3-226
Table 3-68.	Load Case 106, -20°F Ambient, Maximum Decay Heat – Model AOS-100B . . . . .	3-230
Table 3-69.	Fire Condition Thermal Evaluation Results – Model AOS-100B . . . . .	3-234
Table 3-70.	Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat – Model AOS-100B . . . . .	3-238
Table 3-71.	Load Case 112, Post Fire at 60 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-100B. . . . .	3-242
Table 3-72.	Load Case 112, Post Fire at 90 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-100B. . . . .	3-246
Table 3-73.	Load Case 112, Post Fire at 120 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-100B. . . . .	3-250
Table 3-74.	Load Case 112, Post Fire at 150 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-100B. . . . .	3-254
Table 3-75.	Load Case 112, Post Fire at 180 Minutes, 100°F, Maximum Decay Heat, Maximum Insolation – Model AOS-100B. . . . .	3-258
Table 3-76.	Summary of Heat Transfer Exact Solution Properties and their Results. . . . .	3-264
Table 3-77.	Comparison of Heat Test GE Model 2000 and LIBRA Results . . . . .	3-265
Table 3-78.	SS304 Stainless Steel Thermal Properties . . . . .	3-269
Table 3-79.	Tungsten Alloy Thermal Properties . . . . .	3-272
Table 3-80.	SA-105 Carbon Steel Thermal Properties . . . . .	3-274
Table 3-81.	Air Properties. . . . .	3-277
Table 3-82.	Fire Condition Impact Limiter Crushed Geometry 30-Ft. Head-On Drop Analysis Results – All Models . . . . .	3-284
Table 3-83.	30-Ft. Drop Deformations – Model AOS-100A . . . . .	3-296
Table 3-84.	Impact Limiter Foam Properties – Model AOS-100A . . . . .	3-296
Table 3-85.	Compare Results Provided in Configuration 1 Versus Configuration 2, after 30 Minutes of Fire at 1,475°F – Model AOS-100A . . . . .	3-300
Table 3-86.	Compare Results Provided in Configuration 1 Versus Configuration 2, 7.5-Hour Cool-Down Transient – Model AOS-100A . . . . .	3-300



Table 3-87.	Compare Results Provided in Configuration 1 Versus Configuration 3, after 30 Minutes of Fire at 1,475°F – Model AOS-100A . . . . .	3-301
Table 3-88.	Compare Results Provided in Configuration 1 Versus Configuration 3, 7.5-Hour Cool-Down Transient – Model AOS-100A . . . . .	3-301
Table 3-89.	Total Conductivity – Model AOS-025A . . . . .	3-309
Table 3-90.	Total Conductivity – Model AOS-050A . . . . .	3-311
Table 3-91.	Total Conductivity – Model AOS-100A . . . . .	3-313
Table 3-92.	Total Conductivity – Model AOS-100B . . . . .	3-317
Table 3-93.	Maximum Grashof Number – All Models. . . . .	3-320
Table 3-94.	Grashof Number Evaluation at All Air Gaps – Model AOS-025A . . . . .	3-322
Table 3-95.	Grashof Number Evaluation at All Air Gaps – Model AOS-050A . . . . .	3-323
Table 3-96.	Grashof Number Evaluation at All Air Gaps – Model AOS-100A . . . . .	3-324
Table 3-97.	Surface Measurements and Descriptions, Normal Conditions of Transport – Model AOS-025. . . . .	3-325
Table 3-98.	External Convection Coefficients at 100°F Ambient Temperature, Normal Conditions of Transport – Model AOS-025. . . . .	3-327
Table 3-99.	External Convection Coefficients at -20°F Ambient Temperature, Normal Conditions of Transport – Model AOS-025. . . . .	3-329
Table 3-100.	External Convection Coefficients at -40°F Ambient Temperature, Normal Conditions of Transport – Model AOS-025. . . . .	3-331
Table 3-101.	Surface Measurements and Descriptions, Normal Conditions of Transport – Model AOS-050. . . . .	3-333
Table 3-102.	External Convection Coefficients at 100°F Ambient Temperature, Normal Conditions of Transport – Model AOS-050. . . . .	3-335
Table 3-103.	External Convection Coefficients at -20°F Ambient Temperature, Normal Conditions of Transport – Model AOS-050. . . . .	3-338
Table 3-104.	External Convection Coefficients at -40°F Ambient Temperature, Normal Conditions of Transport – Model AOS-050. . . . .	3-341
Table 3-105.	Surface Measurements and Descriptions, Normal Conditions of Transport – Models AOS-100A and AOS-100B . . . . .	3-344
Table 3-106.	External Convection Coefficients at 100°F Ambient Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100B . . . . .	3-346
Table 3-107.	External Convection Coefficients at -20°F Ambient Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100B . . . . .	3-348
Table 3-108.	External Convection Coefficients at -40°F Ambient Temperature, Normal Conditions of Transport – Models AOS-100A and AOS-100B . . . . .	3-350
Table 3-109.	Surface Measurements and Descriptions, Hypothetical Accident Conditions of Transport – Model AOS-025 . . . . .	3-352
Table 3-110.	External Convection Coefficients at 100°F Ambient Temperature, Hypothetical Accident Conditions of Transport – Model AOS-025 . . . . .	3-353
Table 3-111.	Surface Measurements and Descriptions, Hypothetical Accident Conditions of Transport – Model AOS-050 . . . . .	3-355
Table 3-112.	External Convection Coefficients at 100°F Ambient Temperature, Hypothetical Accident Conditions of Transport – Model AOS-050 . . . . .	3-357
Table 3-113.	Surface Measurements and Descriptions, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100B. . . . .	3-359
Table 3-114.	External Convection Coefficients at 100°F Ambient Temperature, Hypothetical Accident Conditions of Transport – Models AOS-100A and AOS-100B. . . . .	3-361
Table 3-115.	External Convection Coefficients at 1,475°F Environment, Fire Condition – All Models. . . . .	3-363
Table 3-116.	Plate Temperature and Length Values . . . . .	3-365
Table 3-117.	Air Property Values at 172°F. . . . .	3-365
Table 3-118.	Curved Vertical Plates Used as Flat Vertical Plate Evaluation for Thermal Condition 1 at 100°F Ambient, Maximum Decay Heat, Maximum Insolation (Load Case 102) – All Models. . . . .	3-369
Table 3-119.	Maximum Foam Temperature, 24-Hour Solar Heat Transient . . . . .	3-370
Table 3-120.	Configuration 1 and Configuration 2 Inside Plate and Cylindrical/Conical Ring Thicknesses – All Models. . . . .	3-375

Table 3-121.	Maximum Component Temperatures, Normal Conditions of Transport – Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Model AOS-025A . . . . .	3-376
Table 3-122.	Maximum Component Temperatures, Hypothetical Accident Conditions of Transport – Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Model AOS-025A . . . . .	3-377
Table 3-123.	Maximum Component Temperatures, Hypothetical Accident Conditions of Transport – Load Case 112, 7.5-Hour Cool-Down Transient, Model AOS-025A . . . . .	3-377
Table 3-124.	Maximum Component Temperatures, Normal Conditions of Transport – Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Model AOS-050A . . . . .	3-378
Table 3-125.	Maximum Component Temperatures, Hypothetical Accident Conditions of Transport – Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Model AOS-050A . . . . .	3-379
Table 3-126.	Maximum Component Temperatures, Hypothetical Accident Conditions of Transport – Load Case 112, 7.5-Hour Cool-Down Transient, Model AOS-050A . . . . .	3-379
Table 3-127.	Maximum Component Temperatures, Normal Conditions of Transport – Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Model AOS-100A . . . . .	3-380
Table 3-128.	Maximum Component Temperatures, Hypothetical Accident Conditions of Transport – Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Model AOS-100A . . . . .	3-381
Table 3-129.	Maximum Component Temperatures, Hypothetical Accident Conditions of Transport – Load Case 112, 7.5-Hour Cool-Down Transient, Model AOS-100A . . . . .	3-381
Table 3-130.	Maximum Component Temperatures, Normal Conditions of Transport – Load Case 102, 100°F Ambient, Maximum Decay Heat, Maximum Insolation, Model AOS-100B . . . . .	3-382
Table 3-131.	Maximum Component Temperatures, Hypothetical Accident Conditions of Transport – Load Case 111, Fire at 30 Minutes, 1,475°F Ambient, Maximum Decay Heat, Model AOS-100B . . . . .	3-383
Table 3-132.	Maximum Component Temperatures, Hypothetical Accident Conditions of Transport – Load Case 112, 7.5-Hour Cool-Down Transient, Model AOS-100B . . . . .	3-383
Table 3-133.	Foam Density Properties – Nominal, 115% Nominal, and 85% Nominal, Model AOS-100A . . . . .	3-384
Table 3-134.	Comparison of Maximum Component Temperatures with Varying Foam Densities – Model AOS-100A . . . . .	3-385
Table 3-135.	Nominal, 115% Nominal, and 80% Nominal Foam Specific Heat Properties – Model AOS-100A . . . . .	3-386
Table 3-136.	Comparison of Maximum Component Temperatures with Varying Specific Heat Values – Model AOS-100A . . . . .	3-387
Table 3-137.	Case 1, Maximum Component Temperatures . . . . .	3-412
Table 3-138.	Case 2, Maximum Component Temperatures . . . . .	3-412
Table 3-139.	Case 3, Maximum Component Temperatures . . . . .	3-412
Table 3-140.	Case 1, Stress (psi/MPa) . . . . .	3-413
Table 3-141.	Case 2, Stress (psi/MPa) . . . . .	3-415
Table 3-142.	Case 3, Stress (psi/MPa) . . . . .	3-417

#### 4. Containment

Table 4-1.	Cask Lid Attachment Bolt Features and Properties Used for Fortran Program Input – All Models . . . . .	4-12
Table 4-2.	Cask Lid Attachment Bolt Fortran Program Results Summary – All Models . . . . .	4-17
Table 4-3.	Keensert Evaluation – Model AOS-025 . . . . .	4-20
Table 4-4.	Keensert Evaluation – Model AOS-050 . . . . .	4-23
Table 4-5.	Keensert Evaluation – Model AOS-100 . . . . .	4-26
Table 4-6.	Maximum Cask Cavity Pressure Due to Normal Conditions of Transport – All Models . . . . .	4-30
Table 4-7.	Maximum Cask Cavity Pressure Due to Fire Condition – All Models . . . . .	4-30

## 5. Shielding Evaluation

Table 5-1.	Cask Component Dimensions, Outside Radius and Half-Height – All Models . . . . .	5-2
Table 5-2.	Cask Component Dimensions, Cavity Height and Axial Shield Thickness – All Models . . . . .	5-3
Table 5-3.	Cask Component Materials Important to Shielding – All Models . . . . .	5-4
Table 5-4.	Maximum Radiation Level Summary for Normal Conditions of Transport – All Models . . . . .	5-5
Table 5-5.	Maximum Radiation Level Summary for Hypothetical Accident Conditions of Transport – All Models . . . . .	5-5
Table 5-6.	Isotopes Analyzed for AOS Transport Packages – All Models . . . . .	5-6
Table 5-7.	AOS Cask Components – All Models . . . . .	5-11
Table 5-8.	Point Source Locations . . . . .	5-12
Table 5-9.	External Surface Deformation Used for Dose Calculation in Axial Direction – End Drop . . . . .	5-15
Table 5-10.	External Surface Deformation Used for Dose Calculation in Radial Direction – Side Drop . . . . .	5-15
Table 5-11.	Distances from Center of Cask Used for Dose Calculations – Axial Location. . . . .	5-16
Table 5-12.	Distances from Center of Cask Used for Dose Calculations – Radial Location . . . . .	5-16
Table 5-13.	Maximum Radiation Levels (All Isotopes Except Ir-192 and Ir-194) – Model AOS-025A . . . . .	5-22
Table 5-14.	Maximum Radiation Levels (All Isotopes Except Ir-192 and Ir-194) – Model AOS-050A . . . . .	5-23
Table 5-15.	Maximum Radiation Levels (All Isotopes Except Ir-192 and Ir-194) – Models AOS-100A and AOS-100A-S . . . . .	5-24
Table 5-16.	Maximum Radiation Levels (All Isotopes Except Ir-192 and Ir-194) – Model AOS-100B . . . . .	5-25
Table 5-17.	Maximum Ir-192/Ir-194 Radiation Levels – Model AOS-025A. . . . .	5-26
Table 5-18.	Maximum Ir-192/Ir-194 Radiation Levels – Model AOS-050A. . . . .	5-27
Table 5-19.	Maximum Ir-192/Ir-194 Radiation Levels – Models AOS-100A and AOS-100A-S . . . . .	5-28
Table 5-20.	Maximum Ir-192/Ir-194 Radiation Levels – Model AOS-100B. . . . .	5-28
Table 5-21.	AOS Cask Isotopic Heat Loads (Reference <a href="#">[5.2]</a> ). . . . .	5-30
Table 5-22.	AOS Cask Isotopic Heat Load Results . . . . .	5-30
Table 5-23.	Isotope Photon per Decay – All Models . . . . .	5-31
Table 5-24.	Co-60 Gamma Spectra Used in Shielding Models – All Models . . . . .	5-31
Table 5-25.	Cs-137 Gamma Spectra Used in Shielding Models – All Models . . . . .	5-32
Table 5-26.	Hf-181 Gamma Spectra Used in Shielding Models – All Models . . . . .	5-32
Table 5-27.	Ir-192 Gamma Spectra Used in Shielding Models – All Models . . . . .	5-33
Table 5-28.	Ir-194 Gamma Spectra Used in Shielding Models – All Models . . . . .	5-35
Table 5-29.	Zr/Nb-95 Gamma Spectra Used in Shielding Models – All Models. . . . .	5-38
Table 5-30.	THIS TABLE INTENTIONALLY LEFT BLANK . . . . .	5-38
Table 5-31.	Yb-169 Gamma Spectra Used in Shielding Models – All Models . . . . .	5-39
Table 5-32.	Volume Source Analysis – Source Geometry Dimensions . . . . .	5-43
Table 5-33.	Volume Source Analysis – Results . . . . .	5-43
Table 5-34.	<i>10 CFR 71.47(a)</i> Dose Rate Acceptance Criteria for Multiple Isotopes . . . . .	5-45
Table 5-35.	Multiple Isotope Calculation Reference Value Summary – Models AOS-100A and AOS-100A-S . . . . .	5-46
Table 5-35a.	Multiple Isotope Calculation Reference Value Summary – Model AOS-025A . . . . .	5-47
Table 5-35b.	Multiple Isotope Calculation Reference Value Summary – Model AOS-050A . . . . .	5-47
Table 5-35c.	Multiple Isotope Calculation Reference Value Summary – Model AOS-100B . . . . .	5-48
Table 5-36.	Low-Energy Gamma External Dose Rates – Models AOS-100A and AOS-100A-S. . . . .	5-49
Table 5-37.	Example Low-Energy Gamma and Beta Emitter Decay Heat Values. . . . .	5-51
Table 5-38.	Additional Exclusive Use Dose Rate Locations and Activity Limits – Models AOS-100A and AOS-100A-S . . . . .	5-52
Table 5-39.	Exclusive Use Activity Limit Maximum Dose Rates and Decay Heat – Models AOS-100A and AOS-100A-S . . . . .	5-54
Table 5-40.	Exclusive Use Maximum Activity Dose Rates and Decay Heat – Models AOS-100A and AOS-100A-S . . . . .	5-55
Table 5-40a.	<i>10 CFR 71.47(b)</i> Dose Rate Acceptance Criteria for Multiple Isotopes . . . . .	5-56
Table 5-41.	Multiple Isotope Exclusive Use Calculation Reference Values – Models AOS-100A and AOS-100A-S . . . . .	5-57
Table 5-42.	Approximate Change in Side Dose Rates – Models AOS-050 and AOS-100. . . . .	5-59
Table 5-43.	Side Dose Rates – Model AOS-050A . . . . .	5-62
Table 5-44.	Side Dose Rates – Models AOS-100A and AOS-100A-S. . . . .	5-63
Table 5-45.	Side Dose Rates – Model AOS-100B . . . . .	5-64
Table 5-46.	New Isotopic Dose Rates and Limits – Models AOS-050A, AOS-100A, and AOS-100A-S . . . . .	5-64

Table 5-47.	Impact Limiter Offset Distance Differences – All Models. . . . .	5-67
Table 5-48.	Projected Dose Rate Increase within Recessed Regions of Upper and Lower Impact Limiters – All Models. . . . .	5-68
Table 5-49.	Full Transport Package Surface Dose Rates/Ci – Model AOS-025A . . . . .	5-70
Table 5-50.	Maximum Transport Package Surface Dose Rate within Recessed Region of Upper and Lower Impact Limiters – Model AOS-025A . . . . .	5-70
Table 5-51.	Full Transport Package Surface Dose Rates/Ci – Model AOS-050A . . . . .	5-72
Table 5-52.	Maximum Transport Package Surface Dose Rate within Recessed Region of Upper and Lower Impact Limiters – Model AOS-050A . . . . .	5-73
Table 5-53.	Dose Rates within Recessed Region of Upper and Lower Impact Limiters – Model AOS-050A . . . . .	5-75
Table 5-54.	1-m TI Dose Rates/Ci – Models AOS-100A and AOS-100A-S . . . . .	5-77
Table 5-55.	Maximum 1-m TI Dose Rate within Recessed Region of Upper and Lower Impact Limiters – Models AOS-100A and AOS-100A-S. . . . .	5-78
Table 5-56.	Maximum Dose Rates within Recessed Region of Upper and Lower Impact Limiters – Models AOS-100A and AOS-100A-S. . . . .	5-78
Table 5-57.	1-m TI Dose Rate/Ci – Model AOS-100B . . . . .	5-80
Table 5-58.	Maximum 1-m TI Dose Rate within Recessed Region of Upper and Lower Impact Limiters – Model AOS-100B . . . . .	5-81
Table 5-59.	Maximum Dose Rates within Recessed Region of Upper and Lower Impact Limiters – Model AOS-100B . . . . .	5-81

## 6. Criticality Evaluation

There are no tables in Chapter 6.

## 7. Package Operations

Table 7-1.	Additional Required Shielding – Models AOS-025A, AOS-050A, AOS-100A, and AOS-100A-S. . . . .	7-9
Table 7-2.	Cask Lid Attachment Bolt Size and Preload Torque – All Models. . . . .	7-11
Table 7-3.	Maximum Distance from Loaded Cask Surface to Take Transport Package Surface Dose Rate Measurements – All Models . . . . .	7-14

## 8. Acceptance Tests and Maintenance Program

Table 8-1.	Acceptance Test Matrix. . . . .	8-2
Table 8-2.	Type 304 and 316 Material Requirements . . . . .	8-5
Table 8-3.	Bolting/Screw Material Requirements . . . . .	8-7
Table 8-4.	Casting Pipe/Casting Material Requirements (Type CPF-8, CF-8). . . . .	8-8
Table 8-5.	LAST-A-FOAM FR-3700 Series Foams – Testing Program . . . . .	8-10
Table 8-6.	LAST-A-FOAM FR-3700 Series Foam Dynamic Crush Strength Limits, Parallel to Rise – All Models . . . . .	8-12
Table 8-7.	LAST-A-FOAM FR-3700 Series Foam Dynamic Crush Strength Limits, Perpendicular to Rise – All Models . . . . .	8-13
Table 8-8.	Fabrication Examination Program Summary. . . . .	8-14

## 9. Quality Assurance Program

There are no tables in Chapter 9.