



- NOTES:
1. FOR TECH SPEC SETTING VALVES, REFER TO TECH. SPECS.
  2. ALL INSTRUMENTATION SHOWN ON THIS DIAGRAM SHOULD BE PREFIXED BY E51 UNLESS NOTED OTHERWISE.
  3. ALL VALVES AND ORIFICES SHOWN ON THIS DIAGRAM SHOULD BE PREFIXED BY E5150 UNLESS NOTED OTHERWISE.

4M721-5876  
LATEST REVISION

NUCLEAR SAFETY RELATED

THIS IS A MICROSTATION PRODUCED DRAWING. CHANGES OR REVISIONS MUST BE BROUGHT TO THE ATTENTION OF THE PLANT ENGINEERING DESIGN GROUP TO ENSURE THAT CONFIGURATION CONTROL IS MAINTAINED.

THIS DRAWING WAS REFORMATTED BY MICROSTATION AT REVISION "C". ALL PREVIOUS APPROVAL SIGNATURES ARE ON FILE ON MICROFILM IN DOCUMENT CONTROL.

D DCD'S INCORPORATED: EDP 36178.B011, REV. 0			
OTHER REVISIONS:			
PREPARED BY WJ ADLER	DATE 3/28/11	CHECKED BY <i>DAVID W. ADLER</i>	DATE 5-18-11
APPROVED BY <i>John Hayes</i>	DATE 5-26-2011	EDP POSTING ENTRIES REQUIRE THE ADDITION OF THE ARMS STATUS CODE: EITHER "APC" OR "ASB"	

A PORTION OF THIS DRAWING IS AFFECTED BY THE FOLLOWING:		PREPARED BY	DATE
TC	CHANGE DOCUMENT	CHECKED BY	DATE
		APPROVED BY	DATE
		OTHER APPROVALS	DATE

INC.CODE U	Detroit Edison Fermi 2	
TITLE REACTOR CORE ISOLATION COOLING SIMPLIFIED DRAWING VALVE POSITIONS DURING NORMAL OPERATION		
APERTURE CARD TITLE UFSAR FIG. 5.5-8		
PLANT IDENTIFICATION SYSTEM NUMBER E5100		ARMS RECIPIENT #
DOCUMENT TYPE CODE DDDMC	NUC OPS FILE NO. 1801	DATE ISSUED TO IS 5-27-11
DRAWING NUMBER 4M721-5876	REV. D	