



The EQSIM Computational Framework for Fault-to-Structure Earthquake Simulations


DOE/NRC NPH Workshop 2020

David McCallen
Lawrence Berkeley National Laboratory
& University of Nevada, Reno




The success of HPC - a continuous march “up and to the right”

Mainframe → Vector → Massively Parallel




The DOE Exascale Computing Project (ECP) is preparing to exploit a billion-billion FLOPS

Three components...



Earthquake SIMulation (EQSIM) framework - fault-to-structure regional simulations



Key issues that will be explored through simulations...

- How do earthquake ground motions actually vary across a region and how does this impact risk to infrastructure?
- How do complex (realistic) incident ground motion waveforms actually interact with a particular facility?

Our project team spans engineering, seismology, math/computer science

Structural/Geotechnical Mechanics

David McCallen



Mamun Miah



Maryam
Tabbakhha



Applied Math / Numerical Methods

Anders Petersson



Bjorn Sjogreen



Computer Science

Houjun Tang



Ramesh
Pankajakshan



Seismology / Geophysics

Arben Pitarka




Arthur Rodgers Ana Aguiar Moya




This is a complex, multi-scale scientific and engineering problem


Fault – to – structure simulations



We couple an explicit finite difference code with implicit structure/soil codes



Our Exascale challenge - regional simulations at “engineering” frequencies



Necessary capabilities to do this...

Run much larger models much faster

- Very large models at higher frequency
- Many realizations to account for uncertainties (e.g. fault rupture)


Represent fine-scale geology

- Waveform data inversion to improve geologic models
- Stochastic geology


Specifying our Exascale goals

San Francisco Bay Area (SFBA) regional model

Regional-scale model (SFBA)





Application ground motion simulation performance goals




$$\text{FOM} = \frac{(\text{Freq})^4}{\text{Wall Clock Time} \times 7.6} \left[\frac{500}{\text{Vsmin}} \right]^4$$



Computer science - efficient distribution of work at ~200 billion grid points is essential



We have already achieved high performance on advanced platforms (FOM = 189)




San Francisco Bay Area simulations to 10Hz on the Summit computer




Frequency Resolved	10 Hz
$V_{s_{min}}$	500 m/s
Number of Grid Points	63 Billion
Smallest Cell Size	6.25 m
Platform	SUMMIT (ORNL)
Number of Nodes	1024
Wall Clock Time	6 hours, 58 minutes,


Coupling geophysics and engineering models




Strong coupling via DRM






Step 2 – Soil island / structure simulation



Coupling geophysics and engineering models



The coupling of geophysics and engineering models has been comprehensively tested



Suiwen Wu









Eric Eckert



Junfei Huang








Near-field building response

Twenty story steel moment frame (OpenSees)




2 Km from fault






Scrutinizing the simulation model results





Ground Displacements (FP)






Ground Displacements (FN)




Scrutinizing the simulation model results




Min/Max
PID
▽ 0.28%
△ 3.20%



All these capabilities must be wrapped into an effective end-to-end workflow



Next – getting ready for exascale platforms and exploring just how far we can go



Computational domain for M=7 Hayward fault event (63B grid points)

Computational domain for M=7.5 San Andreas fault event (220B grid points)

First Exascale Platforms

Aurora



Frontier

