

UNITED STATES NUCLEAR REGULATORY COMMISSION

WASHINGTON, D.C. 20555-0001

June 17, 2021

Mr. David P. Rhoades Senior Vice President Exelon Generation Company, LLC President and Chief Nuclear Officer Exelon Nuclear 4300 Winfield Road Warrenville, IL 60555

SUBJECT: JAMES A. FITZPATRICK NUCLEAR POWER PLANT – CORRECTION TO

AMENDMENT NO 342 ISSUED JUNE 14, 2021, RE: ONE TIME EXTENSION TO TECHNICAL SPECIFICATIONS 3.5.1, 3.6.1.9, AND 3.6.4.1 COMPLETION

TIMES TO SUPPORT RESIDUAL HEAT REMOVAL PUMP MOTOR

REPLACEMENT (EMERGENCY CIRCUMSTANCES) (EPID L-2021-LLA-0110)

Dear Mr. Rhoades:

By letter dated June 14, 2021, the U.S. Nuclear Regulatory Commission (NRC) issued Amendment No. 342 to Renewed Facility Operating License No. DPR-59 for the James A. FitzPatrick Nuclear Power Plant. The amendment was in response to your application dated June 12, 2021, as supplemented by two letters dated June 13, 2021, and a letter dated June 14, 2021, which superseded all previous letters. The amendment modifies TS 3.5.1, ECCS [Emergency Core Cooling System] – Operating Condition A, TS 3.6.4.1, Secondary Containment, Condition A, and TS 3.6.1.9 RHR [Residual Heat Removal] Containment Spray System, as well as certain Surveillance Requirements (SR) to support emergent repair of the "A" residual heat removal pump motor.

Subsequent to issuance of the amendment, the licensee informed the NRC that in its creation of the clean technical specification pages, administrative errors were introduced. All the errors were in different sections than those changed by the license amendment. On page 3.5.1-3, condition "H.1" was erroneously changed to "B.1." On page 3.5.1-4, in SR 3.5.1.3, the "≤" and "≥" were erroneously changed to "<" and ">", respectively. On page 3.3.6.1-5, in SR 3.3.6.1.8 an "O" was erroneously removed from "INSTRUMENTATION." On pages 3.5.3-2 and 3.6.1.3-8, "continued" was erroneously removed from the bottom of the table. On page 3.8.5-2, the dashed lines for the note associated with SR 3.8.5.1 were erroneously changed to solid lines. The attached TS pages correct these unintended changes. These corrections do not change any of the conclusions in the safety evaluation associated with the issuance of the amendment.

D. Rhoades - 2 -

If you have any questions, please contact me at 301-415-2048 or Justin.Poole@nrc.gov.

Sincerely,

/RA/

Justin C. Poole, Project Manager Plant Licensing Branch I Division of Operating Reactor Licensing Office of Nuclear Reactor Regulation

Docket No. 50-333

Enclosure: Corrected TS pages

cc: Listserv

ENCLOSURE

JAMES A. FITZPATRICK NUCLEAR POWER PLANT CORRECTED TS PAGES FOR AMENDMENT NO. 342

SURVEILLANCE REQUIREMENTS (continued)

	SURVEILLANCE	FREQUENCY
SR 3.3.6.1.4	Calibrate the trip units.	In accordance with the Surveillance Frequency Control Program*
SR 3.3.6.1.5	Perform CHANNEL CALIBRATION.	In accordance with the Surveillance Frequency Control Program*
SR 3.3.6.1.6	Calibrate the radiation detectors.	In accordance with the Surveillance Frequency Control Program
SR 3.3.6.1.7	Perform LOGIC SYSTEM FUNCTIONAL TEST.	In accordance with the Surveillance Frequency Control Program
SR 3.3.6.1.8	"n" equals 2 channels for the purpose of determining the STAGGERED TEST BASIS Frequency.	
	Verify the ISOLATION INSTRUMENTATION RESPONSE TIME is within limits.	In accordance with the Surveillance Frequency Control Program

^{*} This Surveillance for ISP-150B is not required to be performed for functions 4.a, 4.b, 4.d, 4.e and 4.f of table 3.3.6.1-1 until following the return of the "A" RHR pump to OPERABLE. This past due Surveillance will be completed as stated in Section 3.5 of letter JAFP-21-0053, dated June 14, 2021.

JAFNPP 3.3.6.1-5 Amendment 342

3.5 EMERGENCY CORE COOLING SYSTEMS (ECCS), REACTOR PRESSURE VESSEL (RPV)
WATER INVENTORY CONTROL, AND REACTOR CORE ISOLATION COOLING (RCIC)
SYSTEM

3.5.1 ECCS-Operating

LCO 3.5.1

 Depressurization System (ADS) function of six safety/relief valves shall be OPERABLE.
NOTE
Low pressure coolant injection (LPCI) subsystems may be considered
OPERABLE during alignment and operation for decay heat removal with
reactor steam dome pressure less than the Residual Heat Removal
(RHR) cut in permissive pressure in MODE 3, if capable of being
manually realigned and not otherwise inoperable.

Each ECCS injection/spray subsystem and the Automatic

APPLICABILITY: MODE 1,

MODES 2 and 3, except high pressure coolant injection (HPCI) and ADS valves are not required to be OPERABLE with reactor steam dome

pressure ≤ 150 psig.

ACTIONS

-----NOTE-----

LCO 3.0.4.b is not applicable to HPCI.

	CONDITION		REQUIRED ACTION	COMPLETION TIME
A.	One low pressure ECCS injection/spray subsystem inoperable. OR One low pressure coolant injection (LPCI) pump in both LPCI subsystems inoperable.	A.1	Restore low pressure ECCS injection/spray subsystem(s) to OPERABLE status.	7 days*
В.	Required Action and associated Completion Time of Condition A not	B.1 AND	Be in MODE 3.	12 hours
	met.		Be in Mode 4.	36 hours

^{*} The Completion Time to return the "A" RHR pump to OPERALE is extended to 34 days, contingent on implementation of Compensatory Actions stated in Section 3.4 of letter JAFP-21-0053, dated June 14, 2021, as a one-time only change ending upon restoration the "A" RHR pump to OPERABLE, or on July 11, 2021 at 20:00 hours.

ACTIONS (continued)

	CONDITION		REQUIRED ACTION	COMPLETION TIME
G.	Required Action and associated Completion Time of Condition C, D, E, or F not met. OR Two or more required ADS valves inoperable.	G.1 AND G.2	Be in Mode 3. Reduce reactor steam dome pressure to ≤ 150 psig.	12 hours 36 hours
Н.	Two or more low pressure ECCS injection/spray subsystems inoperable for reasons other than Condition A. OR HPCI System and one or more required ADS valves inoperable.	H.1	Enter LCO 3.0.3.	Immediately

SURVEILLANCE REQUIREMENTS

	SURVEILLANCE	FREQUENCY
SR 3.5.1.1	Verify, for each ECCS injection/spray subsystem, the piping is filled with water from the pump discharge valve to the injection valve.	In accordance with the Surveillance Frequency Control Program*

^{*} This Surveillance for ST-4B is not required to be performed until following the return of the "A" RHR pump to OPERABLE. This past due Surveillance will be completed as stated in Section 3.5 of letter JAFP-21-0053, dated June 14, 2021.

SURVEILLANCE REQUIREMENTS (continued)

	SURVEILLANCE	FREQUENCY
SR 3.5.1.2	Verify each ECCS injection/spray subsystem manual, power operated, and automatic valve in the flow path, that is not locked, sealed, or otherwise secured in position, is in the correct position.	In accordance with the Surveillance Frequency Control Program*
SR 3.5.1.3	Verify ADS pneumatic supply header pressure is ≥ 95 psig.	In accordance with the Surveillance Frequency Control Program
SR 3.5.1.4	Verify the RHR System cross tie valves are closed and power is removed from the electrical valve operator.	In accordance with the Surveillance Frequency Control Program
SR 3.5.1.5	Cycle open and closed each LPCI motor operated valve independent power supply battery charger AC input breaker and verify each LPCI inverter output voltage is ≥ 576 V and ≤ 624 V while supplying the respective bus.	In accordance with the Surveillance Frequency Control Program

^{*} This Surveillance for ST-4B is not required to be performed until following the return of the "A" RHR pump to OPERABLE. This past due Surveillance will be completed as stated in Section 3.5 of letter JAFP-21-0053, dated June 14, 2021.

SURVEILLANCE REQUIREMENTS

	SURVEILLANCE	FREQUENCY
SR 3.5.3.1	Verify the RCIC System piping is filled with water from the pump discharge valve to the injection valve.	In accordance with the Surveillance Frequency Control Program*
SR 3.5.3.2	Verify each RCIC System manual, power operated, and automatic valve in the flow path, that is not locked, sealed, or otherwise secured in position, is in the correct position.	In accordance with the Surveillance Frequency Control Program*
SR 3.5.3.3	Not required to be performed until 12 hours after reactor steam pressure and flow are adequate to perform the test.	
	Verify, with reactor pressure \leq 1040 psig and \geq 970 psig, the RCIC pump can develop a flow rate \geq 400 gpm against a system head corresponding to reactor pressure.	In accordance with the Surveillance Frequency Control Program*
SR 3.5.3.4	Not required to be performed until 12 hours after reactor steam pressure and flow are adequate to perform the test.	
	Verify, with reactor pressure ≤ 165 psig, the RCIC pump can develop a flow rate ≥ 400 gpm against a system head corresponding to reactor pressure.	In accordance with the Surveillance Frequency Control Program*

^{*} This Surveillance for ST-24J is not required to be performed until following the return of the "A" RHR pump to OPERABLE. This past due Surveillance will be completed as stated in Section 3.5 letter JAFP-21-0053, dated June 14, 2021.

SURVEILLANCE REQUIREMENTS (continued)

	SURVEILLANCE	FREQUENCY
SR 3.6.1.3.3	 Valves and blind flanges in high radiation areas may be verified by use of administrative means. Not required to be met for PCIVs that are open under administrative controls. 	
	Verify each primary containment manual isolation valve and blind flange that is located inside primary containment and not locked, sealed or otherwise secured and is required to be closed during accident conditions is closed.	Prior to entering MODE 2 or 3 from MODE 4 if primary containment was de-inerted while in MODE 4, if not performed within the previous 92 days
SR 3.6.1.3.4	Verify continuity of the traversing incore probe (TIP) shear isolation valve explosive charge.	In accordance with the Surveillance Frequency Control Program
SR 3.6.1.3.5	Verify the isolation time of each power operated, automatic PCIV, except for MSIVs, is within limits.	In accordance with the Inservice Testing Program*
SR 3.6.1.3.6	Verify the isolation time of each MSIV is ≥ 3 seconds and ≤ 5 seconds.	In accordance with the Inservice Testing Program

^{*} This Surveillance for ST-24J is not required to be performed until following the return of the "A" RHR pump to OPERABLE. This past due Surveillance will be completed as stated in Section 3.5 of letter JAFP-21-0053, dated June 14, 2021.

ACTIONS

CONDITIONS	REQUIRED ACTION	COMPLETION TIME
A. (continued)	A.2.3 Initiate action to restore required DC electrical power subsystem to OPERABLE status.	Immediately

SURVEILLANCE REQUIREMENTS

	SURVEILLANCE	FREQUENCY
SR 3.8.5.1	The following SRs are not required to be performed: SR 3.8.4.2, SR 3.8.4.3, and SR 3.8.4.4. For DC electrical power subsystem required to be OPERABLE the following SRs are applicable: SR 3.8.4.1, SR 3.8.4.2, SR 3.8.4.3, and SR 3.8.4.4.	In accordance with applicable SRs*

^{*} This Surveillance for MST-071.12 is not required to be performed following the return of the "A" RHR pump to OPERABLE. This past due Surveillance will be completed as stated in Section 3.5 of letter JAFP-21-0053, dated June 14, 2021.

D. Rhoades - 3 -

SUBJECT: JAMES A. FITZPATRICK NUCLEAR POWER PLANT – CORRECTION TO

AMENDMENT NO 342 ISSUED JUNE 14, 2021, RE: ONE TIME EXTENSION TO TECHNICAL SPECIFICATIONS 3.5.1, 3.6.1.9, AND 3.6.4.1 COMPLETION

TIMES TO SUPPORT RESIDUAL HEAT REMOVAL PUMP MOTOR

REPLACEMENT (EMERGENCY CIRCUMSTANCES) (EPID L-2021-LLA-0110)

DATED JUNE 17, 2021

DISTRIBUTION:

Public RidsNrrLAKZeleznock Resource
PM File Copy RidsACRS_MailCTR Resource
RidsNrrDssStsb Resource RidsNrrDorlLpl1 Resource
RidsRgn1MailCenter Resource
RidsNrrPMFitzPatrick Resource

ADAMS Accession No. ML21166A366

OFFICE	NRR/DORL/LPL1/PM	NRR/DORL/LPL1/LAiT	NRR/DORL/LPL3/LA
NAME	JPoole	KZeleznock	JBurkhardt (KGoldstein for)
DATE	06/17/2021	06/17/2021	06/17/2021
OFFICE	NRR/DORL/LPL1/BC	NRR/DORL/LPL1/PM	
NAME	JDanna	JPoole	
DATE	06/17/2021	06/17/2021	

OFFICIAL RECORD COPY