



- NOTES:
- FOR NOTES AND LEGENDS SEE DWG. D-302-001.
 - ORIFICE AND SUPPORT AREA C-8 TO BE CLASSIFIED NISR CL. 3
 - 3.8"-150" BLIND FLANGE WITH 1/2" DIAMETER HOLE PER ECR-50585.
 - 4.8"-150" BLIND FLANGE WITH 1/4" DIAMETER HOLE PER ECR-50585.
 5. LOOP SEA ADDED PER ECR-50585.
 6. 8" 150" BLIND FLANGE WITH 1/4" DIAMETER HOLE PER NC-16-04716.
 7. 8" 150" BLIND FLANGE WITH 1/32" DIAMETER HOLE PER NC-16-04716.

ABBREVIATION KEY:
FED - FLOOR AND EQUIPMENT DRAIN PIPE

DRAWING LEGIBILITY CLASS 1

NUCLEAR SAFETY RELATED

FSAR Figure 9.3-10
SOUTH CAROLINA ELECTRIC & GAS COMPANY
VIRCIL C. SUMNER NUCLEAR STATION
BUILDING SERVICE FLOOR & EQUIPMENT DRAIN
STATION DRAINAGE FLOOR DIAGRAM

NO.	DATE	BY	REVISION	CHK. BY	APP. BY
1			REVISED PER ECR-70028		
2			REVISED PER ECR-7205		
3			REVISED PER NC-16-04716		
4			REVISED PER ECR-50585		
5			REVISED PER NC-16-04716		

