

SUMMARY TABLE OF CONTENTS**Chapter 1****1.0 INTRODUCTION AND GENERAL DESCRIPTION OF PLANT**

- 1.1 Introduction
 - 1.1.1 Type of License
 - 1.1.2 Identification of Applicant
 - 1.1.3 Number of Plant Units
 - 1.1.4 Description of Location
 - 1.1.5 Type of Nuclear Steam Supply
 - 1.1.6 Type of Containment
 - 1.1.7 Core Thermal Power Levels
 - 1.1.8 Scheduled Fuel Load and Operation Data
 - 1.1.9 FSAR Organization

- 1.2 General Plant Description
 - 1.2.1 Principal Design Criteria
 - 1.2.2 Plant Description

- 1.3 Comparison Tables
 - 1.3.1 Comparison With Similar Facility Designs
 - 1.3.2 Comparison of Final and Preliminary Information

- 1.4 Identification of Agents and Contractors
 - 1.4.1 Pennsylvania Power & Light Company (Applicant)
 - 1.4.2 Architect Engineer
 - 1.4.3 Nuclear Steam Supply System
 - 1.4.4 Turbine-Generator Vendor
 - 1.4.5 Other Consultants

- 1.5 Requirements for Further Technical Information
 - 1.5.1 Development of BWR Technology
 - 1.5.2 Programs Conducted During Operations Phase

- 1.6 Material Incorporated by Reference
 - 1.6.1 General Electric Topical Reports
 - 1.6.2 Bechtel Topical Reports
 - 1.6.3 Other Topical Reports

- 1.7 Electrical, Instrumentation, and Control Drawings

- 1.8 Symbols and Terms Used in Engineering and Text
 - 1.8.1 Text Definitions and Abbreviations
 - 1.8.2 Drawing Index and Symbols
 - 1.8.3 Piping Identification
 - 1.8.4 Valve Identification
 - 1.8.5 Instrument Identification
 - 1.8.6 Electrical Component Identification

SUMMARY TABLE OF CONTENTS**Chapter 1 Tables**

| | |
|-------|---|
| 1.3-1 | Comparison of Nuclear Steam Supply System Design Characteristics |
| 1.3-2 | Comparison of Power Conversion System Design Characteristics |
| 1.3-3 | Comparison of Engineered Safety Features Design Characteristics |
| 1.3-4 | Comparison of Containment Design Characteristics |
| 1.3-5 | Radioactive Waste Management Systems Design Characteristics |
| 1.3-6 | Comparison of Structural Design Characteristics |
| 1.3-7 | Comparison of Electrical Power Systems Design Characteristics |
| 1.3-8 | Significant Design Changes from PSAR to FSAR |
| 1.4-1 | Commercial Nuclear Reactors Completed, Under Construction, or in Design By General Electric |
| 1.6-1 | General Electric Topical Reports |
| 1.6-2 | Bechtel Topical Reports |
| 1.6-4 | Other Topical Reports |
| 1.7-1 | Electrical Drawings |
| 1.8-1 | SSES-Project Glossary Terms |
| 1.8-2 | Acronyms |
| 1.8-3 | Technical Abbreviations |
| 1.8-5 | Drawing Abbreviations |
| 1.8-6 | Piping and Valve Class Identification |

SUMMARY TABLE OF CONTENTS**Chapter 1 Figures**

| | |
|--------|---|
| 1.2-1 | Figure replaced by Drawing M-220, Sh. 1 |
| 1.2-2 | Figure replaced by Drawing M-221, Sh. 1 |
| 1.2-3 | Figure replaced by Drawing M-222, Sh. 1 |
| 1.2-4 | Figure replaced by Drawing M-223, Sh. 1 |
| 1.2-5 | Figure replaced by Drawing M-224, Sh. 1 |
| 1.2-6 | Figure replaced by Drawing M-225, Sh. 1 |
| 1.2-7 | Figure replaced by Drawing M-226, Sh. 1 |
| 1.2-8 | Figure replaced by Drawing M-227, Sh. 1 |
| 1.2-9 | Figure replaced by Drawing M-230, Sh. 1 |
| 1.2-10 | Figure replaced by Drawing M-231, Sh. 1 |
| 1.2-11 | Figure replaced by Drawing M-232, Sh. 1 |
| 1.2-12 | Figure replaced by Drawing M-233, Sh. 1 |
| 1.2-13 | Figure replaced by Drawing M-234, Sh. 1 |
| 1.2-14 | Figure replaced by Drawing M-235, Sh. 1 |
| 1.2-15 | Figure replaced by Drawing M-236, Sh. 1 |
| 1.2-16 | Figure replaced by Drawing M-237, Sh. 1 |
| 1.2-17 | Figure replaced by Drawing M-240, Sh. 1 |
| 1.2-18 | Figure replaced by Drawing M-241, Sh. 1 |
| 1.2-19 | Figure replaced by Drawing M-242, Sh. 1 |
| 1.2-20 | Figure replaced by Drawing M-243, Sh. 1 |
| 1.2-21 | Figure replaced by Drawing M-244, Sh. 1 |
| 1.2-22 | Figure replaced by Drawing M-245, Sh. 1 |
| 1.2-23 | Figure replaced by Drawing M-246, Sh. 1 |
| 1.2-24 | Figure replaced by Drawing M-247, Sh. 1 |
| 1.2-25 | Figure replaced by Drawing M-248, Sh. 1 |
| 1.2-26 | Figure replaced by Drawing M-249, Sh. 1 |
| 1.2-27 | Figure replaced by Drawing M-250, Sh. 1 |
| 1.2-28 | Figure replaced by Drawing M-251, Sh. 1 |
| 1.2-29 | Figure replaced by Drawing M-252, Sh. 1 |
| 1.2-30 | Figure replaced by Drawing M-253, Sh. 1 |
| 1.2-31 | Figure replaced by Drawing M-254, Sh. 1 |
| 1.2-32 | Figure replaced by Drawing M-255, Sh. 1 |
| 1.2-33 | Figure replaced by Drawing M-256, Sh. 1 |
| 1.2-34 | Figure replaced by Drawing M-257, Sh. 1 |
| 1.2-35 | Figure replaced by Drawing M-258, Sh. 1 |
| 1.2-36 | Figure replaced by Drawing M-259, Sh. 1 |
| 1.2-37 | Figure replaced by Drawing M-260, Sh. 1 |
| 1.2-38 | Figure replaced by Drawing M-261, Sh. 1 |
| 1.2-39 | Figure replaced by Drawing M-270, Sh. 1 |
| 1.2-40 | Figure replaced by Drawing M-271, Sh. 1 |
| 1.2-41 | Figure replaced by Drawing M-272, Sh. 1 |
| 1.2-42 | Figure replaced by Drawing M-273, Sh. 1 |
| 1.2-43 | Figure replaced by Drawing M-274, Sh. 1 |
| 1.2-44 | Figure replaced by Drawing M-276, Sh. 1 |
| 1.2-45 | Figure replaced by Drawing M-280, Sh. 1 |
| 1.2-46 | Figure replaced by Drawing M-281, Sh. 1 |
| 1.2-47 | Figure replaced by Drawing M-282, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 1 Figures**

| | |
|----------|--|
| 1.2-48 | Figure replaced by Drawing M-284, Sh. 1 |
| 1.2-49 | Unit 1 - Heat Balance at Rated Power with 100 x 106 LBm/hr Core Flow |
| 1.2-49-1 | Unit 1 - Heat Balance at Rated Power with 108 x 106 LBm/hr Increased Core Flow |
| 1.2-49-2 | Unit 2 - Heat Balance at Rated Power with 100 x 106 LBm/hr Core Flow |
| 1.2-49-3 | Unit 2 - Heat Balance at Rated Power with 108 x 106 LBm/hr Increased Core Flow |
| 1.2-50 | Figure replaced by Drawing M-5200, Sh. 1 |
| 1.2-51 | Figure replaced by Drawing M-5200, Sh. 2 |
| 1.8-1 | Piping and Instrument Symbols |
| 1.8-2a | Figure replaced by Drawing M-100, Sh. 1 |
| 1.8-2b | Figure replaced by Drawing M-100, Sh. 2 |
| 1.8-2c | Figure replaced by Drawing M-100, Sh. 3 |
| 1.8-2d | Figure replaced by Drawing M-100, Sh. 4 |
| 1.8-3 | Logic Symbols |
| 1.8-4 | Instrument Symbol |

SUMMARY TABLE OF CONTENTS**Chapter 2****2.0 SITE CHARACTERISTICS**

- 2.1 Geography and Demography
 - 2.1.1 Site Location and Description
 - 2.1.2 Exclusion Area Authority and Control
 - 2.1.3 Population Distribution
 - 2.1.4 References

- 2.2 Nearby Industrial, Transportation, and Military Facilities
 - 2.2.1 Locations and Routes
 - 2.2.2 Descriptions
 - 2.2.3 Evaluation of Potential Accidents
 - 2.2.4 References

- 2.3 Meteorology
 - 2.3.1 Regional Climatology
 - 2.3.2 Local Meteorology
 - 2.3.3 On-Site Meteorological Measurements Program
 - 2.3.4 Short-Term (Accident) Diffusion Estimates
 - 2.3.5 Long Term (Routine) Diffusion Estimates
 - 2.3.6 References

- 2.4 Hydrologic Engineering
 - 2.4.1 Hydrologic Description
 - 2.4.2 Floods
 - 2.4.3 Probable Maximum Flood (PMF) on Streams and Rivers
 - 2.4.4 Potential Dam Failures Seismically Induced
 - 2.4.5 Probable Maximum Surge and Seiche Flooding
 - 2.4.6 Probable Maximum Tsunami Flooding
 - 2.4.7 Ice Effects
 - 2.4.8 Cooling Water Canals and Reservoirs
 - 2.4.9 Channel Diversions
 - 2.4.10 Flooding Protection Requirements
 - 2.4.11 Low Water Considerations
 - 2.4.12 Dispersion Dilution and Travel Time of Accidental Releases of Liquid Effluents in Surface Waters
 - 2.4.13 Groundwater
 - 2.4.14 Technical Specification and Emergency Operation Requirements
 - 2.4.15 References

- 2.5 Geology, Seismology and Geotechnical Engineering
 - 2.5.1 Basic Geologic and Seismic Information
 - 2.5.2 Vibratory Ground Motion
 - 2.5.3 Surface Faulting
 - 2.5.4 Stability of Subsurface Materials and Foundations
 - 2.5.5 Stability of Slopes
 - 2.5.6 References

SUMMARY TABLE OF CONTENTS

Chapter 2

- 2.5A U.S. Department of the Interior Report on Investigation of an Earth Disturbance at Wilkes-Barre
- 2.5B City of Wilkes-Barre Report on an Earth Disturbance
- 2.5C Boring Logs
 - 2.5C.1 Summary of Field Density Test Results
 - 2.5C.2 Listings of Boring Logs

SUMMARY TABLE OF CONTENTS**Chapter 2 Tables**

| | |
|--------|---|
| 2.1-33 | Past Population Changes of Counties Within 20 Miles of the Site |
| 2.1-34 | Population by Residence for Counties Within 20 Miles of the Site |
| 2.1-35 | Population Distribution 2010 0-10 Miles Distance (Miles) |
| 2.1-36 | Population Distribution 2010 0-50 Miles Distance (Miles) |
| 2.1-37 | Population Distribution 2020 0-10 Miles Distance (Miles) |
| 2.1-38 | Population Distribution 2020 0-50 Miles Distance (Miles) |
| 2.1-39 | Population Distribution 2000 0-10 Miles Distance (Miles) |
| 2.1-40 | Communities Within 10 Miles of the Site, 2000 |
| 2.1-41 | Population Distribution 2000 0-50 Miles Distance (Miles) |
| 2.1-42 | Seasonal Population of Counties in Study Area, 2000 |
| 2.1-43 | Industries Within 5 Miles of the Site |
| 2.1-44 | Population Projections for Berwick, Pennsylvania |
| 2.1-45 | Cumulative Populations for 1990 and 2000 |
| 2.1-46 | Cumulative Populations for 1990, 2000, 2010 and 2020 |
| 2.2-1 | Pipelines Within 5 Miles of the Site |
| 2.3-1 | Hurricanes Within 75 and 150 Nautical Miles of the Susquehanna Site Period of Record 1871 to 1969 |
| 2.3-2 | Thunderstorm Days for Avoca, Pennsylvania Wilkes-Barre Scranton Airport, Period of Record 1956 to 1974, Values are expressed in Days |
| 2.3-3 | Total Number of Days in 5 Years Mixing Heights < 1500 m Wind Speeds < 4.0 sec-1 and No Significant Precipitation For Episodes Lasting at least 2 Days |
| 2.3-5 | Mean Monthly Values: Susquehanna Site (1973-1976) |
| 2.3-6 | Long Term Average Wind Speed and Prevailing Direction at Wilkes-Barre Scranton Airport, Period of Record: 1956-1974 |
| 2.3-7 | Average Wind Speed and Prevailing Direction at the Susquehanna Site, Period of Record (1973-1976) |
| 2.3-8 | Wind Direction Persistence - Pasquill A (1973-1976) |
| 2.3-9 | Wind Direction Persistence - Pasquill B (1973-1976) |
| 2.3-10 | Wind Direction Persistence - Pasquill C (1973-1976) |
| 2.3-11 | Wind Direction Persistence - Pasquill D (1973-1976) |
| 2.3-12 | Wind Direction Persistence - Pasquill E (1973-1976) |
| 2.3-13 | Wind Direction Persistence - Pasquill F (1973-1976) |
| 2.3-14 | Wind Direction Persistence - Pasquill G (1973-1976) |
| 2.3-15 | Wind Direction Persistence - Pasquill All (1973-1976) |
| 2.3-16 | Wind Direction Persistence - Pasquill E, F, & G (1973-1976) |
| 2.3-17 | Long Term Temperature (°F) At Wilkes-Barre -Scranton Airport |
| 2.3-18 | Mean Monthly Temperature, Dew Point Temperature and Relative Humidity Wilkes-Barre Scranton Airport Period of Record: 1956-1974 |
| 2.3-19 | Temperature and Moisture Data for the Susquehanna Site, Period of Record: 1973-1976 |
| 2.3-20 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: January 1973-1976 |
| 2.3-21 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: February 1973-1976 |

SUMMARY TABLE OF CONTENTS**Chapter 2 Tables**

| | |
|--------|--|
| 2.3-22 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: March 1973-1976 |
| 2.3-23 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: April 1973-1976 |
| 2.3-24 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: May 1973-1976 |
| 2.3-25 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: June 1973-1976 |
| 2.3-26 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: July 1973-1976 |
| 2.3-27 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: August 1973-1976 |
| 2.3-28 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: September 1973-1976 |
| 2.3-29 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: October 1973-1976 |
| 2.3-30 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: November 1973-1976 |
| 2.3-31 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: December 1973-1976 |
| 2.3-32 | Statistics and Diurnal Variation of Meteorological Parameters Data Period: January 1973-December 1976 |
| 2.3-33 | Long Term Monthly Precipitation Data (Liquid Equivalent, In Inches) for Wilkes-Barre Scranton Airport at Avoca, PA |
| 2.3-34 | Expected Rainfall by Duration and Recurrence Interval for Vicinity of Susquehanna Site (Ref. 2.3-20) (Inches) |
| 2.3-35 | Probable Maximum Precipitation for Varying Rainfall Durations and Areas (Ref. 2.3-21) (Inches) |
| 2.3-36 | Precipitation Data for the Susquehanna Site (Inches of Water) (1973-1976) |
| 2.3-37 | Frequency Distribution of Precipitation Data Period: January 1973-1976 |
| 2.3-38 | Frequency Distribution of Precipitation Data Period: February 1973-1976 |
| 2.3-39 | Frequency Distribution of Precipitation Data Period: March 1973-1976 |
| 2.3-40 | Frequency Distribution of Precipitation Data Period: April 1973-1976 |
| 2.3-41 | Frequency Distribution of Precipitation Data Period: May 1973-1976 |
| 2.3-42 | Frequency Distribution of Precipitation Data Period: June 1973-1976 |
| 2.3-43 | Frequency Distribution of Precipitation Data Period: July 1973-1976 |
| 2.3-44 | Frequency Distribution of Precipitation Data Period: August 1973-1976 |
| 2.3-45 | Frequency Distribution of Precipitation Data Period: September 1973-1976 |
| 2.3-46 | Frequency Distribution of Precipitation Data Period: October 1973-1976 |
| 2.3-47 | Frequency Distribution of Precipitation Data Period: November 1973-1976 |
| 2.3-48 | Frequency Distribution of Precipitation Data Period: December 1973-1976 |
| 2.3-49 | Frequency Distribution of Precipitation Data Period: January 1973-December 1976 |
| 2.3-50 | Precipitation Wind Rose January 1973-1976 |
| 2.3-51 | Precipitation Wind Rose February 1973-1976 |
| 2.3-52 | Precipitation Wind Rose March 1973-1976 |
| 2.3-53 | Precipitation Wind Rose April 1973-1976 |
| 2.3-54 | Precipitation Wind Rose May 1973-1976 |

SUMMARY TABLE OF CONTENTS**Chapter 2 Tables**

| | |
|--------|---|
| 2.3-55 | Precipitation Wind Rose June 1973-1976 |
| 2.3-56 | Precipitation Wind Rose July 1973-1976 |
| 2.3-57 | Precipitation Wind Rose August 1973-1976 |
| 2.3-58 | Precipitation Wind Rose September 1973-1976 |
| 2.3-59 | Precipitation Wind Rose October 1973-1976 |
| 2.3-60 | Precipitation Wind Rose November 1973-1976 |
| 2.3-61 | Precipitation Wind Rose December 1973-1976 |
| 2.3-62 | Precipitation Wind Rose January 1973-December 1976 |
| 2.3-63 | Heavy Fog (Visibility 1/4 Mile or Less) at Avoca, PA. |
| 2.3-64 | Joint Frequency (%) of Wind Direction, Wind Speed and Stability, Stability Class A |
| 2.3-65 | Joint Frequency (%) of Wind Direction, Wind Speed and Stability, Stability Class B |
| 2.3-66 | Joint Frequency (%) of Wind Direction, Wind Speed and Stability, Stability Class C |
| 2.3-67 | Joint Frequency (%) of Wind Direction, Wind Speed and Stability, Stability Class D |
| 2.3-68 | Joint Frequency (%) of Wind Direction, Wind Speed and Stability, Stability Class E |
| 2.3-69 | Joint Frequency (%) of Wind Direction, Wind Speed and Stability, Stability Class F |
| 2.3-70 | Joint Frequency (%) of Wind Direction, Wind Speed and Stability, Stability Class G |
| 2.3-71 | Joint Frequency (%) of Wind Direction, Wind Speed and Stability, All Stability Classes |
| 2.3-72 | Mixing Heights (meters) |
| 2.3-73 | Heights of Meteorological Sensors |
| 2.3-74 | Data Recovery Rates |
| 2.3-75 | Joint Wind Frequency Distribution by Stability Class, Lower Wind January 1, 1999 through December 31, 2003 Stability Class: Pasquill A |
| 2.3-76 | Joint Wind Frequency Distribution by Stability Class, Lower Wind January 1, 1999 through December 31, 2003 Stability Class: Pasquill B |
| 2.3-77 | Joint Wind Frequency Distribution by Stability Class, Lower Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill C |
| 2.3-78 | Joint Wind Frequency Distribution by Stability Class, Lower Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill D |
| 2.3-79 | Joint Wind Frequency Distribution By Stability Class, Lower Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill E |
| 2.3-80 | Joint Wind Frequency Distribution By Stability Class, Lower Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill F |
| 2.3-81 | Joint Wind Frequency Distribution by Stability Class, Lower Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill G |
| 2.3-82 | Joint Wind Frequency Distribution by Stability Class Lower Wind January 1, 1999 through December 31, 2003, All Classes |
| 2.3-84 | Joint Wind Frequency Distribution by Stability Class, Upper Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill A |
| 2.3-85 | Joint Wind Frequency Distribution by Stability Class, Upper Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill B |
| 2.3-86 | Joint Wind Frequency Distribution by Stability Class, Upper Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill C |
| 2.3-87 | Joint Wind Frequency Distribution by Stability Class, Upper Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill D |
| 2.3-88 | Joint Wind Frequency Distribution by Stability Class, Upper Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill E |

SUMMARY TABLE OF CONTENTS**Chapter 2 Tables**

| | |
|---------|---|
| 2.3-89 | Joint Wind Frequency Distribution by Stability Class, Upper Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill F |
| 2.3-90 | Joint Wind Frequency Distribution by Stability Class, Upper Wind January 1, 1999 through December 31, 2003, Stability Class: Pasquill G |
| 2.3-91 | Joint Wind Frequency Distribution by Stability Class, Upper Wind January 1, 1999 through December 31, 2003, All Classes |
| 2.3-92 | Summary of Short-Term X/Q (SEC/M3) Results at 549M EAB |
| 2.3-93 | 1999 Probability Values for 1 Hour at SSES EAB |
| 2.3-94 | 2000 Probability Values for 1 Hour at SSES EAB |
| 2.3-95 | 2001 Probability Values for 1 Hour at SSES EAB |
| 2.3-96 | 2002 Probability Values for 1 Hour at SSES EAB |
| 2.3-97 | 2003 Probability Values for 1 Hour at SSES EAB |
| 2.3-98 | 1999-2003 Probability Values for 1 Hour at SSES EAB |
| 2.3-99 | 1999 Probability Values for 1 Hour at SSES LPZ |
| 2.3-100 | 2000 Probability Values for 1 Hour at SSES LPZ |
| 2.3-101 | 2001 Probability Values for 1 Hour at SSES LPZ |
| 2.3-102 | 2002 Probability Values for 1 Hour at SSES LPZ |
| 2.3-103 | 2003 Probability Values for 1 Hour at SSES LPZ |
| 2.3-104 | 1999-2003 Probability Values for 1 Hour at SSSS LPZ |
| 2.3-105 | Summary of Long-Term X/G (SEC/M3) Results at 4827M LPZ |
| 2.3-106 | Distances and Terrain/Recirculation Correction Factors for SSES 2003 Land Use Census Locations |
| 2.3-107 | 1999 Average Relative Concentration (sec/m^3) and Disposition (m^{-2}) Estimates at the Site Boundary |
| 2.3-108 | 2000 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Site Boundary |
| 2.3-109 | 2001 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Site Boundary |
| 2.3-110 | 2002 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Site Boundary |
| 2.3-111 | 2003 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Site Boundary |
| 2.3-112 | 1999-2003 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Site Boundary |
| 2.3-113 | 1999 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Exclusion Area Boundary |
| 2.3-114 | 2000 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Exclusion Area Boundary |
| 2.3-115 | 2001 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Exclusion Area Boundary |
| 2.3-116 | 2002 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Exclusion Area Boundary |
| 2.3-117 | 2003 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Exclusion Area Boundary |
| 2.3-118 | 1999-2003 Average Relative Concentration (sec/m^3) and Deposition (m^{-2}) Estimates at the Exclusion Area Boundary. |

SUMMARY TABLE OF CONTENTS**Chapter 2 Tables**

| | |
|---------|---|
| 2.3-119 | 1999 Atmospheric Dispersion Estimates for Nearest Residence and Vegetable Garden |
| 2.3-120 | 2000 Atmospheric Dispersion Estimates for Nearest Residence and Vegetable Garden |
| 2.3-121 | 2001 Atmospheric Dispersion Estimates for Nearest Residence and Vegetable Garden |
| 2.3-122 | 2002 Atmospheric Dispersion Estimates for Nearest Residence and Vegetable Garden |
| 2.3-123 | 2003 Atmospheric Dispersion Estimates for Nearest Residence and Vegetable Garden |
| 2.3-124 | 1999-2003 Atmospheric Dispersion Estimates for Nearest Residence and Vegetable Garden |
| 2.3-125 | 1999 Atmospheric Dispersion Estimates for Nearest Meat Animal, Dairy Locations and Special Receptors |
| 2.3-126 | 2000 Atmospheric Dispersion Estimates for Nearest Meat Animal, Dairy Locations and Special Receptors |
| 2.3-127 | 2001 Atmospheric Dispersion Estimates for Nearest Meat Animal, Dairy Locations and Special Receptors |
| 2.3-128 | 2002 Atmospheric Dispersion Estimates for Nearest Meat Animal, Dairy Locations and Special Receptors |
| 2.3-129 | 2003 Atmospheric Dispersion Estimates for Nearest Meat Animal, Dairy Locations and Special Receptors |
| 2.3-130 | 1999-2003 Atmospheric Dispersion Estimates for Nearest Meat Animal, Dairy Locations and Special Receptors |
| 2.3-131 | 1999 Atmospheric Dispersion Estimates at Selected Locations |
| 2.3-132 | 2000 Atmospheric Dispersion Estimates at Selected Locations |
| 2.3-133 | 2001 Atmospheric Dispersion Estimates at Selected Locations |
| 2.3-134 | 2002 Atmospheric Dispersion Estimates at Selected Locations |
| 2.3-135 | 2003 Atmospheric Dispersion Estimates at Selected Locations |
| 2.3-136 | 1999-2003 Atmospheric Dispersion Estimates at Selected Locations |
| 2.3-137 | SSES Relative Concentrations No Decay, Undepleted X/Q (sec/m^3) X/Q Accumulation for Ground Average for the Period of 01/01/99 through 12/31/03 |
| 2.3-138 | SSES Relative Concentrations 2.26-Day Decay, Undepleted X/Q (sec/m^3) for Ground Decayed Sector Average for the Period of 01/01/99 through 12/31/03 |
| 2.3-139 | SSES Relative Concentrations 8-Day Decay, Depleted X/Q (sec/m^3) for Ground Decayed Sector Average for the Period of 01/01/99 through 12/31/03 |
| 2.3-140 | SSES Relative Deposition D/Q (m^{-2}) for the Period of 01/01/99 through 12/31/03 |
| 2.4-1 | Existing and Proposed Dams Located in the Susquehanna River Basin (Chemung River Basin) |
| 2.4-2 | Minor Upstream Dams and Reservoirs |
| 2.4-3 | Water Users |
| 2.4-4 | Historic Floods in the Vicinity of the Susquehanna Steam Electric Station. |
| 2.4-5 | All-Season 24-Hour Probable Maximum Precipitation |
| 2.4-6 | Probable Maximum Precipitation for Durations Less Than 30 Min. |
| 2.4-7 | Peak Runoff Rates from and Maximum Ponding Depths on Roofs of Safety Related Structures for Local All-Season PMP |

SUMMARY TABLE OF CONTENTS**Chapter 2 Tables**

| | |
|--------|---|
| 2.4-8 | Adopted 4-Hour Unit Hydrographs and Characteristics. |
| 2.4-9 | Susquehanna River Basin Routing Coefficients |
| 2.4-10 | Manning "N" Values Computed from 1936 Flood |
| 2.4-11 | Susquehanna River Freeze Over at Harrisburg (1870-1955) |
| 2.4-12 | Ice Jam Flooding |
| 2.4-13 | Summary of Flood Routing Studies - Spray Pond |
| 2.4-14 | Results of Wind Wave Computation |
| 2.4-15 | Maximum Loadings Resulting from Wind-Wave Activities |
| 2.4-16 | Maximum Hydrodynamic Loading Resulting from Earthquake |
| 2.4-18 | ESW Cooling Duty on Simultaneous Loss of All Auxiliary Power to Both Units |
| 2.4-21 | Regional Hydrogeologic Section (within 20-mile radius of Susquehanna SES) |
| 2.4-22 | Water Well Data Within Two Miles of the Station |
| 2.4-23 | Spring Data Within Two Miles of the Station |
| 2.4-24 | Data for Major Water Wells, Other Than Public Wells, located Between 2 and 10 Miles From the Station |
| 2.4-25 | Data for Public Supply Wells Located Between 2 and 20 Miles from the Station |
| 2.4-26 | Estimated Groundwater Withdrawal in 1976 Within Two Miles of the Station |
| 2.4-27 | Projections of Future Groundwater Withdrawal Within 2 and 20 Miles of the Station |
| 2.4-28 | Major Groundwater Withdrawal, and Population Served by Water Supply Companies Within 20-Mile Area |
| 2.4-29 | Estimation of Total Groundwater Withdrawal in 1975 Within 20 Mile Radius of the Station |
| 2.4-30 | Details of the Construction of Observation Wells at the Susquehanna SES |
| 2.4-31 | Groundwater Level Data Taken at Susquehanna SES 1972 through 1975 |
| 2.4-32 | Groundwater Level Data Taken at Susquehanna SES in 1976 and 1977 |
| 2.4-33 | Summary of Permeability Tests of Overburden and Upper Bedrock at the Susquehanna SES Performed During Previous Investigations |
| 2.4-34 | Summary of Permeability Tests of Overburden and Upper Bedrock at the Susquehanna SES Performed for This Investigation |
| 2.4-35 | Radionuclide Content of the Tank Postulated to Rupture – Reactor Water Cleanup (RWCU) Phase Separator Tanks-Susquehanna SES |
| 2.4-36 | Groundwater Parameter Values Used for SLUG3D Simulations Accident Analysis for Susquehanna SES |
| 2.4-37 | Range of Parameter Values used in Calibrated Numerical Model of Buried Valley Aquifer Northern Side of Susquehanna SES |
| 2.4-38 | Estimated Peak Concentration of Radionuclides in Groundwater Resulting from Postulated Rupture of RWCU Phase Separator Tank – Results of Simulations with SLUG3D Model – Susquehanna SES |
| 2.4-39 | Estimated Peak Concentration of Radionuclides in Groundwater in Buried Valley Aquifer Resulting from postulated Rupture of RWCU Phase Separator Tank – Results of Simulations with SLUG3D Model – Susquehanna SES |
| 2.5-1 | Modified Mercalli Intensity (Damage) Scale (Abridged) |
| 2.5-2 | Earthquake list |
| 2.5-3 | Unconfined Compressive Strengths of Foundation Rock (Mahantango Formation) |
| 2.5-4 | Laboratory Measurements of P-Wave Seismic Velocities on Rock Cores taken from Reactor and Turbine Building Areas |

SUMMARY TABLE OF CONTENTS**Chapter 2 Tables**

| | |
|--------|--|
| 2.5-5 | Representative Engineering Properties of Unweathered Foundation Rock for Principal Plant Structures |
| 2.5-6 | P-Wave and S-Wave Velocities and Computed Dynamic Moduli, Spray Pond Area |
| 2.5-7 | Cross-Hole Seismic Velocities, Reactor Area |
| 2.5-8 | Results of Settlement Measurements Taken on ESSW Pumphouse Basemat |
| 2.5-9 | Spray Pond Water Level Elevations |
| 2.5-10 | Permeabilities Measured in Spray Pond |
| 2.5-11 | Permeabilities Measured Near the Railroad Bridge |
| 2.5-12 | Circulation Losses in Drill Holes in Spray Pond |
| 2.5-13 | Soil Test Results Summary |
| 2.5-14 | Spray Pond Summary of Cyclic Consolidated-Undrained Triaxial (CR) Tests |
| 2.5-15 | Design Parameters for Spray Pond Liner |
| 2.5-16 | Spray Pond, Summary of Liquefaction Analysis |
| 2.5-17 | Effect of Varying Standard Relationship of Effective Strain with Damping and Moduli for Profile 2, GWT-665 |
| 2.5-18 | Spray Pond Factor of Safety as Obtained Using Different Earthquakes |
| 2.5-19 | Probable Settlement During Earthquake |

SUMMARY TABLE OF CONTENTS**Chapter 2 Figures**

| | |
|---------|---|
| 2.1-21 | Site Vicinity Map |
| 2.1-22 | Site Area Map |
| 2.1-23 | Population Distribution 0-10 Miles, 2010 |
| 2.1-24 | Population Distribution 0-50 Miles, 2010 |
| 2.1-25 | Population Distribution 0–10 Miles, 2020 |
| 2.1-26 | Population Distribution 0–50 Miles, 2020 |
| 2.1-27 | Seasonal Population 0-10 Miles, 2000 |
| 2.1-28 | Seasonal Population 0-50 Miles, 2000 |
| 2.2-1 | Major Transportation Routes and Pipelines |
| 2.2-2 | Airport and Airline Route Map |
| 2.2-3 | Pipeline Break at Elevation 700', Steady State Break Flow |
| 2.2-4 | Pipeline Break at Elevation 600', Steady State Break Flow |
| 2.3-1 | Tornado Occurrence and Intensity in Susquehanna Region |
| 2.3-2 | TP25 Rainfall Intensity – Duration Frequency Curves USDC WB, 1955 |
| 2.3-3 | Topography Within 5 Miles |
| 2.3-4-1 | Maximum Terrain Elevation Versus Distance By Sector |
| 2.3-4-2 | Maximum Terrain Elevation Versus Distance By Sector |
| 2.3-4-3 | Maximum Terrain Elevation Versus Distance By Sector |
| 2.3-4-4 | Maximum Terrain Elevation Versus Distance By Sector |
| 2.3-4-5 | Maximum Terrain Elevation Versus Distance By Sector |
| 2.3-4-6 | Maximum Terrain Elevation Versus Distance By Sector |
| 2.3-4-7 | Maximum Terrain Elevation Versus Distance By Sector |
| 2.3-4-8 | Maximum Terrain Elevation Versus Distance By Sector |
| 2.3-5 | Schematic of Instrumentation |
| 2.3-6 | One Hour Direction Independent X/Q at the EAB (Weighted Average of 1999, 2000, 2001, 2002 and 2003 Calculations) |
| 2.3-7 | One Hour Direction Dependent X/Q Values at the EAB (Weighted Average of 1999, 2000, 2001, 2002 and 2003 Calculations) |
| 2.3-8 | One Hour Direction Dependent X/Q Values at the LPZ (Weighted Average of 1999, 2000, 2001, 2002 and 2003 Calculations) |
| 2.3-9 | One Hour Direction Independent X/Q at the LPZ (Weighted Average of 1999, 2000, 2001, 2002 and 2003 Calculations) |
| 2.3-10 | Interpolated X/Q Values at the LPZ (Weighted Average of 1999, 2000, 2001, 2002 and 2003 Calculations) |
| 2.4-3 | Plant Complete Showing Storm Drain Pipe Layout |
| 2.4-4 | Susquehanna River Basin |
| 2.4-5 | Stage Discharge Curve at Low Flows |
| 2.4-6 | Stage Discharge Curve, Discharge Range 1000-37,000 CFS |
| 2.4-7 | Water Users on the Susquehanna River |
| 2.4-8 | Stage Discharge Curves at Plant Site |
| 2.4-9 | Flood Profiles on the Susquehanna River at the Site |
| 2.4-10 | General Site Drainage Plan |
| 2.4-11 | Site Drainage Locations A&B |
| 2.4-12 | Site Drainage Locations C&D |

SUMMARY TABLE OF CONTENTS**Chapter 2 Figures**

| | |
|--------|---|
| 2.4-13 | Site Drainage Locations E&F |
| 2.4-14 | Probable Maximum Precipitation Storm Pattern and Outline of Sub-Basins, Susquehanna River above Wilkes-Barre, Pennsylvania |
| 2.4-15 | Probable Maximum Precipitation on Susquehanna River Basin and Probable Maximum Flood Hydrograph at Wilkes-Barre, Pennsylvania |
| 2.4-16 | Map of the Susquehanna River, River Miles 150-170 |
| 2.4-17 | Stage Discharge Curve at Section 2-Berwick Bridge |
| 2.4-18 | River and Water Surface Profiles of Susquehanna River in Vicinity of Site |
| 2.4-19 | Cross Sections at the Eight River Sections Near the Site |
| 2.4-20 | Cross Section of River at the Plant Site |
| 2.4-21 | Wind Fetch, Susquehanna River PMF |
| 2.4-22 | Tioga Dam and Hammond Dam Reservoir Areas and Sections |
| 2.4-23 | Surface Drainage Patterns around the Spray Pond |
| 2.4-24 | Spray Pond Inflow and Outflow Hydrograph |
| 2.4-25 | Spray Pond Outlet Rating Curves |
| 2.4-26 | Spray Pond Elevation Area Storage Capacity Curves |
| 2.4-27 | Spray Pond Emergency Spillway Water Surface Profile |
| 2.4-28 | Spray Pond Design Spectrum for SSE |
| 2.4-29 | Spray Pond Design Spectrum for OBE |
| 2.4-30 | Duration Curves of Daily Discharge |
| 2.4-31 | Time of Travel, Susquehanna River Shickshinny to Danville |
| 2.4-32 | Map of Susquehanna SES Showing Groundwater Contours in September 1977 |
| 2.4-33 | Hydrogeologic Cross Section from West to East Along Groundwater Flow Path at the Susquehanna SES |
| 2.4-34 | Bedrock Geologic Map of Area Within 20 Miles of Susquehanna SES |
| 2.4-35 | Major Pleistocene Sand and Gravel Deposits Within 20 Miles of Susquehanna SES |
| 2.4-36 | Geologic Map of Area Within Two Miles of the Station |
| 2.4-37 | Water Wells Within Two Miles of the Station |
| 2.4-38 | Springs Used for Water Supply Within Two Miles of the Station |
| 2.4-39 | Major Water Wells Two to Ten Miles from the Station, Excepting Public Supply Wells |
| 2.4-40 | Public Supply Wells Two to Twenty Miles from the Station |
| 2.4-41 | Map of Susquehanna SES Showing Isopach Contours of Overburden Thickness |
| 2.4-42 | Map of Susquehanna SES Showing Top-of-Bedrock Contours |
| 2.4-43 | Map of Susquehanna SES Showing Groundwater Contours in April 1977 |
| 2.4-44 | Log of Boring and Observation Well Construction Details-1200, 1200A |
| 2.4-45 | Log of Boring and Observation Well Construction Details-1201 |
| 2.4-46 | Log of Boring and Observation Well Construction Details-1204 |
| 2.4-47 | Log of Boring and Observation Well Construction Details-1208 |
| 2.4-48 | Log of Boring and Observation Well Construction Details-1209A |
| 2.4-49 | Log of Boring and Observation Well Construction Details-1210 |
| 2.4-50 | Map of Susquehanna SES Showing Groundwater Contours in June 1971 |
| 2.4-51 | Drawdown Curves from Pumping Tests of Observation Wells 1204 and 1210 |
| 2.4-52 | River Intake Structure |
| 2.4-53 | River Discharge Diffuser |
| 2.4-54 | Figure replaced by Drawing A-12. Sh. 1 |
| 2.4-55 | Figure replaced by Drawing FF62005, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 2 Figures**

| | |
|---------|---|
| 2.5-1 | Site Location |
| 2.5-2 | Regional Physiographic Map |
| 2.5-3 | Regional Geologic Map |
| 2.5-4 | Location of Appalachian Basin |
| 2.5-5 | Regional Isopach Maps |
| 2.5-6 | Stratigraphic Columns |
| 2.5-7 | Regional Tectonic Map |
| 2.5-8a | Earthquake Epicenters and Tectonic Province Boundaries in the Site Region |
| 2.5-8b | Earthquake Epicenters Within 200 Miles of the Site |
| 2.5-9 | Bouguer Gravity Anomaly Map |
| 2.5-10 | Geologic Map of the Bloomsburg-Berwick Area |
| 2.5-11 | Regional Landsat Lineaments |
| 2.5-12 | Site Geologic Map |
| 2.5-13 | Photograph of Geologic Feature Found in Turbine Building Excavation |
| 2.5-14 | Site Vicinity Geologic Column |
| 2.5-15 | Geologic Map of Spray Pond Area |
| 2.5-17 | Contours on Top of Bedrock Surface |
| 2.5-17a | Extent of Rock and Soil Foundations |
| 2.5-18 | Geologic Map of Foundation Excavation |
| 2.5-19 | Geologic Section Through Foundation Excavations |
| 2.5-20a | Photograph of Geologic Features Exposed in Excavations |
| 2.5-20b | Photograph of Geologic Features Exposed in Excavations |
| 2.5-20c | Photograph of Geologic Features Exposed in Excavations |
| 2.5-20d | Photograph of Geologic Features Exposed in Excavations |
| 2.5-20e | Photograph of Geologic Features Exposed in Excavations |
| 2.5-20f | Photograph of Geologic Features Exposed in Excavations |
| 2.5-20g | Photograph of Geologic Features Exposed in Excavations |
| 2.5-21a | Site Geologic Cross Sections |
| 2.5-21b | Site Geologic Cross Sections |
| 2.5-22 | Plot Plan |
| 2.5-22a | Plot Plan Details |
| 2.5-23a | Log of Borings |
| 2.5-23b | Log of Borings |
| 2.5-23c | Log of Borings |
| 2.5-23d | Log of Borings |
| 2.5-23e | Log of Borings |
| 2.5-23f | Log of Borings |
| 2.5-23g | Log of Borings |
| 2.5-23h | Log of Borings |
| 2.5-23i | Log of Borings |
| 2.5-23j | Log of Borings |
| 2.5-23k | Log of Borings |
| 2.5-23l | Log of Borings |
| 2.5-23m | Log of Borings |
| 2.5-23n | Log of Borings |
| 2.5-23o | Log of Borings |
| 2.5-23p | Log of Borings |

SUMMARY TABLE OF CONTENTS**Chapter 2 Figures**

| | |
|---------|--|
| 2.5-23q | Log of Borings |
| 2.5-23r | Log of Borings |
| 2.5-23s | Log of Borings |
| 2.5-23t | Log of Borings |
| 2.5-24 | Final Plant Grades |
| 2.5-25 | Tectonic Map of Anthracite Region |
| 2.5-26 | Geologic Section of Anthracite Region |
| 2.5-27 | Design Response Spectra-Safe Shutdown Earthquake |
| 2.5-28 | Design Response Spectra-Operating Basis Earthquake |
| 2.5-29 | Geophysical Surveys |
| 2.5-30 | Spray Pond-Generalized Cross-Sections |
| 2.5-30a | Diesel Generator 'E' Fuel Tank – Generalized Cross-Sections |
| 2.5-31 | Spray Pond, Range of Grain Size Curves |
| 2.5-32 | Relative Density Related to N Value at ESSW Pumphouse Site |
| 2.5-33 | "N" Value Versus Elevation at ESSW Pumphouse Site |
| 2.5-34 | Spray Pond, Consolidated Drained Triaxial Test - Mohr Circle Diagram |
| 2.5-35 | Spray Pond, Summary of Cyclic Shear Test (CR) Results |
| 2.5-36 | Spray Pond, Shear Wave Velocity Design Curves |
| 2.5-37 | Location and Limits of Excavation Fill and Backfill for Class 1 Structures |
| 2.5-38 | Location of Spray Pond with Contours on Top of Rock and Water Table |
| 2.5-39 | Lateral Soil Pressure Diagrams |
| 2.5-40 | Spray Pond, Measured and Projected Water Levels |
| 2.5-41 | Details of Settlement Pins Cast in ESSW Pumphouse Basemat |
| 2.5-42 | Spray Pond, Earthwork Plan |
| 2.5-43 | Figure replaced by Drawing C-63, Sh. 1 |
| 2.5-44 | Spray Pond, Boring and Test Pits Location Plan |
| 2.5-45 | Spray Pond, Generalized Cross Sections with Laboratory Test Locations |
| 2.5-46 | Spray Pond, Relative Density Related to "N" Value |
| 2.5-47 | Spray Pond, Relationship Between Seepage Loss and Maximum Groundwater Elevation |
| 2.5-48 | Spray Pond, Soil Profiles Used in Liquefaction Analysis |
| 2.5-49 | Spray Pond, Factor of Safety Variation with Groundwater Table and Depth |
| 2.5-50 | Spray Pond, Minimum Factor of Safety Against Liquefaction At Selected Locations |
| 2.5-50A | Variation Factor of Safety (F.S) vs Change of Damping Ratio |
| 2.5-51 | Spray Pond, Comparison of Factors of Safety for Liquefaction for the Design Earthquake and Some Real Earthquakes |
| 2.5-52 | Spray Pond, Comparison of Average Cycle Stress As Induced by Design Earthquake and Some Real Earthquakes |
| 2.5-53 | Spray Pond, Average Shear Variation with Depth |
| 2.5-54 | Spray Pond, Summary of Pore Pressure Buildup |
| 2.5-55 | Site Water Table Map (Preconstruction) |
| 2.5-56 | Profile of Slope North of Spray Pond |
| 2.5-57 | Spray Pond Relationship Between Liner Thickness, Liner Permeability and Seepage Loss |
| 2.5-58 | Damping Ratio Versus Shear Strain of Sand in Liquefaction Analysis |
| 2.5-59 | Sample Locations of Soil Density Tests |
| 2.5-60 | Statistical Analysis of Field Density Test Results |

SUMMARY TABLE OF CONTENTS

Chapter 2 Figures

| | |
|--------|---|
| 2.5-61 | Statistical Analysis of Sand-Cement-Flyash Bedding and Backfill |
| 2.5-62 | ESSW Pumphouse Floor Plan El. 685'-6" |

SUMMARY TABLE OF CONTENTS**Chapter 3****3.0 DESIGN OF STRUCTURES, COMPONENTS, EQUIPMENT SYSTEMS**

- 3.1 Conformance with NRC General Design Criteria
 - 3.1.1 Summary Description
 - 3.1.2 Criterion Conformance

- 3.2 Classification of Structures, Components and Systems
 - 3.2.1 Seismic Classification
 - 3.2.2 System Quality Group Classification
 - 3.2.3 System Safety Classifications
 - 3.2.4 Quality Assurance
 - 3.2.5 Correlation of Safety Classes with Industry Codes

- 3.3 Wind and Tornado Loadings
 - 3.3.1 Wind Loadings
 - 3.3.2 Tornado Loadings
 - 3.3.3 References

- 3.4 Water Level (Flood) Design

- 3.5 Missile Protection
 - 3.5.1 Missile Selection and Description
 - 3.5.2 Systems to be Protected
 - 3.5.3 Barrier Design Procedures
 - 3.5.4 References

- 3.6 Protection against Dynamic Effects Associated with the Postulated Rupture of Piping
 - 3.6.1 Postulated Piping Failures in Fluid Systems
 - 3.6.2 Determination of Pipe Failure Locations and Dynamic Effects Associated with the Postulated Piping Failure
 - 3.6.3 Definitions
 - 3.6.4 References

- 3.6A Pipe Break Outside Containment Summary of Analysis and Results

- 3.7A Seismic Design
 - 3.7a.1 Seismic Input
 - 3.7a.2 Seismic System Analysis
 - 3.7a.3 Seismic Subsystem Analysis
 - 3.7a.4 Seismic Instrumentation
 - 3.7a.5 References

- 3.7B Seismic Design
 - 3.7b.1 Seismic Input
 - 3.7b.2 Seismic System Analysis
 - 3.7b.3 Seismic Subsystem Analysis

SUMMARY TABLE OF CONTENTS**Chapter 3**

- 3.7b.4 Seismic Instrumentation
- 3.7b.5 References

- 3.8 Design of Category I Structures
 - 3.8.1 Concrete Containment
 - 3.8.2 ASME Class MC Steel Components of the Containment
 - 3.8.3 Containment Internal Structures
 - 3.8.4 Other Seismic Category I Structures
 - 3.8.5 Foundations

- 3.8A Computer Programs
 - 3.8A.1 D/SAP
 - 3.8A.2 ASHSD
 - 3.8A.3 CECAP
 - 3.8A.4 CE 668
 - 3.8A.5 EASE
 - 3.8A.6 EO119
 - 3.8A.7 EO781
 - 3.8A.8 FINEL
 - 3.8A.9 ME620
 - 3.8A.10 SUPERB
 - 3.8A.11 References

- 3.8B Concrete, Concrete Materials, Quality Control, and Special Construction Techniques
 - 3.8B.1 Concrete and Concrete Materials - Qualifications
 - 3.8B.2 Concrete and Concrete Materials - Batching, Placing, Curing and Protection
 - 3.8B.3 Concrete and Concrete Materials - Construction Testing
 - 3.8B.4 Concrete Reinforcement Materials - Qualifications
 - 3.8B.5 Concrete Reinforcement Materials - Fabrication
 - 3.8B.6 Concrete Reinforcement Materials - Construction Testing
 - 3.8B.7 Formwork and Construction Joints

- 3.8C Concrete Unit Masonry, Masonry Materials and Quality Control
 - 3.8C.1 Concrete Unit Masonry and Masonry Materials - Qualifications
 - 3.8C.2 Concrete Unit Masonry and Masonry Materials - Construction and Erection
 - 3.8C.3 Concrete Unit Masonry and Masonry Materials - Construction Testing

- 3.9 Mechanical Systems and Components
 - 3.9.1 Special Topics for Mechanical Components
 - 3.9.2 Dynamic Testing and Analysis
 - 3.9.3 ASME Code Class 1, 2, and 3 Components, Component Supports, and Core Support Structures
 - 3.9.4 Control Rod Drive System
 - 3.9.5 Reactor Pressure Vessel Internals
 - 3.9.6 In-service Testing of Pumps and Valves
 - 3.9.7 References

SUMMARY TABLE OF CONTENTS**Chapter 3**

- 3.9A Computer Programs
 - 3.9A.1 ME101
 - 3.9A.2 ME632
 - 3.9A.3 ME912
 - 3.9A.4 ME913
 - 3.9A.5 References

- 3.10 Seismic Qualifications of Category I Instrumentation and Electrical Equipment
 - 3.10A Seismic Qualification of Seismic Category I NSSS Instrumentation and Electrical Equipment
 - 3.10a.1 Seismic Qualification Criteria
 - 3.10a.2 Methods and Procedures for Qualifying Electrical Equipment and Instrumentation (Excluding Motors and Valve Mounted Equipment)
 - 3.10a.3 Methods and Procedure of Analysis or Testing of Supports of Electrical Equipment and Instrumentation
 - 3.10a.4 Operating License Review
 - 3.10a.5 Dynamic Analysis By Response Spectrum Method

 - 3.10B Seismic Qualification of Non-NSSS Supplied Seismic Category I Instrumentation
 - 3.10b.1 Seismic Qualification Criteria
 - 3.10b.2 Seismic Category I Equipment Qualification
 - 3.10b.3 Methods and Procedures of Analysis or Testing of Supports of Instrumentation
 - 3.10b.4 Operating License Review

 - 3.10C Seismic Qualification of Non-NSSS Seismic Category I Electrical Equipment
 - 3.10c.1 Seismic Qualification Criteria
 - 3.10c.2 Methods and Procedures for Qualifying Electrical Equipment
 - 3.10c.3 Methods and Procedures of Analysis or Testing of Supports of Electrical Equipment
 - 3.10c.4 Operating License Review

- 3.11 Environmental Design of Mechanical and Electrical Equipment
 - 3.11.1 Equipment Identification and Environmental Conditions
 - 3.11.2 Qualification Test and Analysis
 - 3.11.3 Qualification Test Results
 - 3.11.4 Loss of Ventilation
 - 3.11.5 Estimated Chemical, Physical, and Radiation Environment
 - 3.11.6 References

- 3.12 Separation Criteria for Safety-Related Mechanical and Electrical Equipment
 - 3.12.1 Introduction
 - 3.12.2 Mechanical Systems
 - 3.12.3 Electrical Systems and Equipment Separation Criteria

SUMMARY TABLE OF CONTENTS

Chapter 3

- 3.13 Compliance with NRC Regulatory Guides
- 3.13.1 Division 1, Regulatory Guides - Power Reactors

- 3.14 License Renewal Programs, TLAA and Commitments
- 3.14.1 Introduction
- 3.14.2 Aging Management Program (AMP)
- 3.14.3 Evaluation of Time-Limited Aging Analysis (TLAA)
- 3.14.4 License Renewal Regulatory Commitments List
- 3.14.5 Newly Identified Items (10 CFR 54.37 (b))

SUMMARY TABLE OF CONTENTS**Chapter 3 Tables**

| | |
|--------|--|
| 3.2-1 | SSES Design Criteria Summary |
| 3.2-2 | Summary of Codes and Standards for Components of Water-Cooled Nuclear Power Units Supplied by AE (ordered prior to July 1, 1971 with the exception of those components located inside the RCPB, and the reactor pressure vessel) |
| 3.2-3 | Summary of Codes and Standards for Components of Water-Cooled Nuclear Power Units Supplied by AE (ordered after July 1, 1971) |
| 3.2-4 | Code Group Designations - Industry Codes and Standards for Mechanical Components Supplied by the NSSS Vendor |
| 3.2-5 | Summary of Safety Class Design Requirements (Minimum) |
| 3.3-1 | Wind Loads on Structures |
| 3.3-2 | Tornado Wind Protected Systems and Tornado Resistant Enclosures |
| 3.5-4 | Tornado-Generated Missile Parameters for All Tornado-Resistant Structures Except the Diesel Generator 'E' Building |
| 3.5-4a | Tornado-Generated Missile Parameters for Diesel Generator 'E' Building |
| 3.5-5 | Berwick Airport Movement Summary |
| 3.5-6 | Plant Target Areas |
| 3.5-7 | Calculated Stress for Bonnet-Seal Type Valves |
| 3.5-10 | Turbine System Reliability Criteria |
| 3.6-1 | High Energy Fluid System Piping |
| 3.6-1a | Moderate Energy Fluid System Piping (Located in Safety-Related Structures) |
| 3.6-2 | Safety Components in Close Proximity to High Energy Fluid System Piping – (Requiring Jet Impingement Protection) Primary Containment) |
| 3.6-3 | Safety Components in Close Proximity to High Energy Fluid System Piping – (Requiring Jet Impingement Protection) Reactor Building |
| 3.6-4 | Restraint Data |
| 3.6-5 | Comparison of PDA and NSC Code |
| 3.6-6a | Summary of Stress in High Energy ASME Class 1 Piping - Main Steam Line Inside Containment - Unit 1-Line "A" |
| 3.6-6b | Summary of Stress in High Energy ASME Class 1 Piping - Main Steam Line Inside Containment - Unit 1-Line "B" |
| 3.6-6c | Summary of Stress in High Energy ASME Class 1 Piping - Main Steam Line Inside Containment - Unit 1-Line "C" |
| 3.6-6d | Summary of Stress in High Energy ASME Class 1 Piping - Main Steam Line Inside Containment - Unit 1-Line "D" |
| 3.6-6e | Summary of Stress in High Energy ASME Class 1 Piping - Main Steam Line Inside Containment - Unit 2-Line "A" |
| 3.6-6f | Summary of Stress in High Energy ASME Class 1 Piping - Main Steam Line Inside Containment - Unit 2-Line "B" |
| 3.6-6g | Summary of Stress in High Energy ASME Class 1 Piping - Main Steam Line Inside Containment - Unit 2-Line "C" |
| 3.6-6h | Summary of Stress in High Energy ASME Class 1 Piping - Main Steam Line Inside Containment - Unit 2-Line "D" |
| 3.6-7 | Summary of Stress in High Energy ASME Class 1 Piping - Feedwater Line Inside Containment-Unit 1 |

SUMMARY TABLE OF CONTENTS**Chapter 3 Tables**

| | |
|-----------|--|
| 3.6-7a | Summary of Stress in High Energy ASME Class 1 Piping - Feedwater Line Inside Containment-Unit 2 |
| 3.6-8 | Summary of Stress in High Energy ASME Class 1 Piping - HPCI Steam Supply Line Inside Containment - Unit 1 |
| 3.6-8a | Summary of Stress in High Energy ASME Class 1 Piping - HPCI Steam Supply Line Inside Containment - Unit 2 |
| 3.6-9 | Summary of Stress in High Energy ASME Class 1 Piping - RCIC Steam Supply Line Inside Containment - Unit 1 |
| 3.6-9a | Summary of Stress in High Energy ASME Class 1 Piping - RCIC Steam Supply Line Inside Containment - Unit 2 |
| 3.6-10 | Summary of Stress in High Energy ASME Class 1 Piping - Core Spray Line Inside Containment-Unit 1 |
| 3.6-10a | Summary of Stress in High Energy ASME Class 1 Piping - Core Spray Line Inside Containment-Unit 2 |
| 3.6-11 | Summary of Stress in High Energy ASME Class 1 Piping - RHR Supply Line Inside Containment - Unit 1 |
| 3.6-11a | Summary of Stress in High Energy ASME Class 1 Piping - RHR Supply Line Inside Containment - Unit 2 |
| 3.6-12a | Summary of Stress in High Energy ASME Class 1 Piping - RHR Return Line Inside Containment Unit 1 Loop "A" |
| 3.6-12a.1 | Summary of Stress in High Energy ASME Class 1 Piping - Reactor Water Clean Up Line Inside Containment - Unit 1 |
| 3.6-12a.2 | Summary of Stress in High Energy ASME Class 1 Piping - Reactor Water Clean Up Line Inside Containment - Unit 1 |
| 3.6-12a.3 | Summary of Stress in High Energy ASME Class 1 Piping - Reactor Water Clean Up Line Inside Containment - Unit 1 |
| 3.6-12a.4 | Summary of Stress in High Energy ASME Class 1 Piping - Reactor Water Clean Up Line Inside Containment - Unit 2 |
| 3.6-12a.5 | Summary of Stress in High Energy ASME Class 1 Piping - Reactor Water Clean Up Line Inside Containment - Unit 2 |
| 3.6-12a.6 | Summary of Stress in High Energy ASME Class 1 Piping - RHR Return Line Inside Containment - Unit 2-Loop "A" |
| 3.6-12a.7 | Summary of Stress in High Energy ASME Class 1 Piping - Reactor Water Clean Up Line Inside Containment-Unit 2 |
| 3.6-12b | Summary of Stress in High Energy ASME Class 1 Piping - RHR Return Line Inside Containment Unit 1 Loop "B" |
| 3.6-12b.1 | Summary of Stress in High Energy ASME Class 1 Piping - Head Vent Line Inside Containment-Unit 1 |
| 3.6-12b.2 | Summary of Stress in High Energy ASME Class 1 Piping - Head Vent Line Inside Containment-Unit 1 |
| 3.6-12b.3 | Summary of Stress in High Energy ASME Class 1 Piping - RHR Return Line Inside Containment-Unit 2 - Loop "B" |
| 3.6-12b.4 | Summary of Stress in High Energy ASME Class 1 Piping - Head Vent Line Inside Containment-Unit 2 |
| 3.6-12c | Summary of Stress in High Energy ASME Class 1 Piping - Head Spray Line Inside Containment-Unit 1 |

SUMMARY TABLE OF CONTENTS**Chapter 3 Tables**

| | |
|-----------|--|
| 3.6-12c.1 | Summary of Stress in High Energy ASME Class 1 Piping - Head Spray Line Inside Containment-Unit 2 |
| 3.6-12d.1 | Summary of Stress in High Energy ASME Class 1 Piping - Standby Liquid Control Line Inside Containment-Unit 1 |
| 3.6-12d.3 | Summary of Stress in High Energy ASME Class 1 Piping - Standby Liquid Control Line Inside Containment-Unit 2 |
| 3.6-12e.1 | Summary of Stress in High Energy ASME Class 1 Piping - MSIV Drain Lines Inside Containment - Unit 1 |
| 3.6-12e.2 | Summary of Stress in High Energy ASME Class 1 Piping - MSIV Drain Lines Inside Containment - Unit 1 |
| 3.6-12e.3 | Summary of Stress in High Energy ASME Class 1 Piping - MSIV Drain Lines Inside Containment - Unit 2 |
| 3.6-13 | High Energy Fluid Systems With and Without Sufficient Capacity to Develop a Jet Stream |
| 3.6-14 | Summary of Stress in High Energy ASME Class 1 Piping - Recirculation Piping System - Loop "A" - Unit 1 |
| 3.6-15 | Summary of Stress in High Energy ASME Class 1 Piping - Recirculation Piping System - Loop "A" -Unit 2 |
| 3.6A-1 | Comparison of Flow Rates Computed from the Time Dependent Momentum Equation |
| 3.6A-2 | Case A - Steam Tunnel Compartment Volumes |
| 3.6A-3 | Steam Tunnel Flow Areas Coefficients and L/A |
| 3.6A-4 | For Case A & Case B |
| 3.6A-5 | Case B - Steam Tunnel Compartment Volumes |
| 3.6A-6 | Steam Tunnel Flow Areas Coefficients and L/A |
| 3.7a-1 | Critical Damping Ratios for Different Materials |
| 3.7a-3 | Number of Dynamic Response Cycles Expected During a Seismic Event |
| 3.7b-1 | Amplification Factors for Ground Spectra |
| 3.7b-2 | Amplification Factors for Diesel Generator 'E' Building's Ground Spectra |
| 3.7b-3 | Damping Values for Non-NSSS Materials (Percent of Critical Damping) |
| 3.7b-4 | Damping Values for Diesel Generator 'E' Facility |
| 3.7b-5 | Structure Foundation Interaction Coefficients |
| 3.7b-6 | Properties of Foundation Media for Containment and ESSW Pumphouse |
| 3.7b-7 | Natural Frequencies of Containment Below 33 CPS |
| 3.7b-8 | Natural Frequencies of the Reactor and Control Building Below 33 CPS |
| 3.7b-9 | ESSW Pumphouse: Frequencies With and Without Eccentricities |
| 3.7b-10 | Diesel Generator A-D Building Frequencies With and Without Eccentricities |
| 3.7b-11 | Comparisons of Torsional Moments Between Original Design and the Values Computed from the Results of 3-D Stick Model |
| 3.8-1 | List of Applicable Codes, Standards, Recommendations, and Specifications |
| 3.8-2 | Load Combinations for Primary Containment, Drywell Floor |
| 3.8-2a | Load Combinations for Reactor Pedestal |
| 3.8-3 | Load Combinations and Allowable Stresses For ASME Class MC Components |

SUMMARY TABLE OF CONTENTS**Chapter 3 Tables**

| | |
|----------|--|
| 3.8-3a | Comparison of FSAR and SRP Load Combinations and Allowable Stresses for ASME Class MC Components |
| 3.8-4 | Load Combination for the Reactor Shield Wall |
| 3.8-5 | Load Combinations for the Suppression Chamber Columns |
| 3.8-6 | Load Combinations for the Drywell Platforms |
| 3.8-7 | Load Combination for the Seismic Truss |
| 3.8-8 | Load Combinations Applicable to Reactor Building |
| 3.8-9 | Load Combinations Applicable to Seismic Category I Structures Other Than Containment, Reactor Building and Diesel Generator 'E' Building |
| 3.8-9a | Load Combinations Applicable to Diesel Generator 'E' Building |
| 3.8-10 | Load Combinations Applicable to Turbine & Radwaste Building |
| 3.8-11 | Concrete Design Compressive Strengths |
| 3.8-12 | Allowable Stress Increase Factor for Masonry Structures |
| 3.8A-1 | Tabulation of Membrane Stress Resultants From the ASHSD Program |
| 3.8A-2 | CECAP and Hand Calculation Comparison - Thermal Gradient |
| 3.8A-3 | Comparison of CECAP and Hand Calculation Results - Real Moment |
| 3.8A-4 | CECAP and Hand Calculation Comparison - Real Moment and Real Compressive Load |
| 3.8A-5 | Comparison of Results for the Rectangular Plate with a Concentrated Load at the Center |
| 3.8A-6 | Comparison of Results for the Rectangular Plate with Various Edge Conditions |
| 3.8A-7 | Comparison of Stresses for Welding Neck Flange |
| 3.8A-8 | Comparison of Stresses for Slip-On Flange |
| 3.8A-9 | Comparison of Final Results for Hoop Force, N, and Meridional Moment, M |
| 3.8A-10 | Material Properties of the Concrete and Reinforcing Steel Used for FINEL Verification |
| 3.8A-11 | Loading History Used for the FINEL Verification |
| 3.8A-12 | Comparison of Stress Results |
| 3.8A-13 | Comparison of Stress Results |
| 3.8A-14 | Comparison of Results |
| 3.8B-1 | Minimum Testing Frequencies for Concrete Materials and Concrete (Except for the Diesel Generator 'E' Building) |
| 3.8B-2 | Testing Requirements for Concrete Materials Used in the Diesel Generator 'E' Building |
| 3.8B-3 | Testing Requirements for Concrete Used in the Diesel Generator 'E' Building |
| 3.9-1 | Transients and the Number of Associated Cycles Considered in the Design and Fatigue Analysis of the RPV Assembly and Internal Transients |
| 3.9-2 | Introduction/ Index/ Load Combination and Acceptance Criteria for ASME Code Class 1, 2, and 3 NSSS Piping and Equipment |
| 3.9-2a | Reactor Pressure Vessel and Shroud Support Assembly |
| 3.9-2b | Reactor Internals and Associated Equipment |
| 3.9-2(c) | Reactor Water Cleanup Heat Exchangers |
| 3.9-2d | ASME Code Class I Main Steam Piping and Pipe Mounted Equipment - Highest Stress Summary - Unit 1 |

SUMMARY TABLE OF CONTENTS**Chapter 3 Tables**

| | |
|-----------|--|
| 3.9-2d.1 | ASME Code Class I Main Steam Piping and Pipe Mounted Equipment - Highest Stress Summary - Unit 2 |
| 3.9-2e | ASME Code Class I Recirculation Piping and Pipe Mounted Equipment - Highest Stress Summary - Unit 1 |
| 3.9-2e.1 | ASME Code Class I Recirculation Piping and Pipe Mounted Equipment - Highest Stress Summary - Unit 2 |
| 3.9-2g | Safety/Relief Valves (Main Steam) |
| 3.9-2(h) | Main Steam Isolation Valve |
| 3.9-2i | Recirculation Pump |
| 3.9-2(j) | Reactor Recirculation System Gate Valves, Discharge Structural & Mechanical Loading Criteria |
| 3.9-2L | Standby Liquid Control Pump |
| 3.9-2m | Standby Liquid Control Tank |
| 3.9-2n | (i) RHR Pumps (ii) Core Spray Pumps |
| 3.9-2o | RHR Heat Exchanger |
| 3.9-2(p) | RWCU Pump |
| 3.9-2q | RCIC Turbine |
| 3.9-2(r) | RCIC Pump |
| 3.9-2s | Reactor Refueling and Servicing Equipment |
| 3.9-2t | High Pressure Coolant Injection Pump |
| 3.9-2u | Control Rod Drive (Index Tube) |
| 3.9-2v | Control Rod Drive Housing |
| 3.9-2w | Jet Pumps |
| 3.9-2aa | Control Rod Guide Tube Flange |
| 3.9-2ab | Incore Housing |
| 3.9-2(ac) | Reactor Vessel Support Equipment CRD Housing Support |
| 3.9-2(ae) | HPCI Turbine Design Calculations |
| 3.9-2(af) | High Density Spent Fuel Racks |
| 3.9-3 | NSSS Seismic Category I Active Pumps and Valves |
| 3.9-4 | Applicable Thermal Transients |
| 3.9-5 | List of Computer Programs Used in BOP Mechanical Systems and Components |
| 3.9-6 | Design Loading Combinations For ASME Code Class 1, 2, and 3 Components |
| 3.9-7 | Design Criteria for ASME Code Class I Valves |
| 3.9-8 | Design Criteria for ASME Code Class 2 and 3 Vessels Designed to NC-3300 and ND-3300 |
| 3.9-9 | Design Criteria for ASME Code Class 2 Vessels Designed to Alternate Rules of NC-3200 |
| 3.9-10 | Design Criteria for ASME Code Class 2 and 3 Piping |
| 3.9-11 | Design Criteria for ASME Code Class 2 and 3 Pumps |
| 3.9-12 | Design Criteria for ASME Code Class 2 and 3 Valves |
| 3.9-14 | Design Loading Combinations for Supports for ASME Code Class 1, 2 and 3 Components |
| 3.9-15 | Valve Qualification Test Range |
| 3.9-16 | Listing of Dynamically Qualified Equipment |
| 3.9-17 | Diesel Generator 'A-D' Seismic Test or Analysis Submittal Chart |
| 3.9-18 | Summary Comparison - Project Specification -10, "General Project Requirements for A Seismic Design and Analysis of Class 1 Equipment and Equipment Supports" |

SUMMARY TABLE OF CONTENTS**Chapter 3 Tables**

| | |
|----------|---|
| 3.9-20 | BOP Piping System Power Ascension Testing |
| 3.9A-1 | Comparison Between Sample Problem and Computer Program ME 913 Results |
| 3.9A-2 | Comparison of ME912 with ME643 and Analytical Results |
| 3.10a-1 | Essential Electrical Components and Instruments |
| 3.10a-2 | Seismic Qualification Test Summary Class IE Control Panels and Local Panels and Racks |
| 3.10a-3 | Summary of Sample Seismic Static Analysis For Three Typical Cabinets |
| 3.10a-4 | Seismic Design Verification Data Sheet |
| 3.10c-1 | Secondary Unit Substations and Power Transformers |
| 3.10c-2 | Motor Control Centers |
| 3.10c-3 | Battery Monitors and Fuse Boxes |
| 3.10c-4 | DC Distribution Panels |
| 3.10c-5 | Battery Racks |
| 3.10c-6 | Electrical Cable Penetration |
| 3.10c-7 | Cable Trays "Safeguard" |
| 3.10c-8 | Battery Charger Racks and Cabinets |
| 3.10c-9 | Large Induction Motors 4000V |
| 3.10c-10 | Panels and Termination Cabinets |
| 3.10c-11 | Battery Chargers |
| 3.10c-12 | 4.16 KV Switchgear |
| 3.10c-13 | DC Control and Load Centers |
| 3.10c-14 | Instrument AC Transformers |
| 3.10c-15 | Automatic Transfer Switches |
| 3.10c-16 | Load Isolation Motor-Generator Sets |
| 3.10c-17 | Non-NSSS and Non-ACR Relays Required to be Energized |
| 3.10c-18 | Inverters and 120V AC Instrument Panels |
| 3.11-1 | Normal and Maximum Plant Environmental Conditions |
| 3.11-7 | Water Quality |
| 3.12-1 | ESF Division Separation |
| 3.12-2 | Channel Separation |
| 3.12-3 | Main Control Room and Relay Panel Annunciator and Computer Interface Device |
| 3.13-1 | Comparison with Regulatory Guide 1.48 |
| 3.14-1 | License Renewal Commitments |
| 3.14-2 | Newly Identified Structures, Systems, and Components (SSC) |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|----------|---|
| 3.2-1 | Code Classification of Piping Valves |
| 3.2-2 | Minimum Instrument Line Classifications |
| 3.5-6 | Figure replaced by Drawing A-17, Sh. 1 |
| 3.5-7 | Figure replaced by Drawing A-21, Sh. 1 |
| 3.5-8 | Figure replaced by Drawing A-5, Sh. 1 |
| 3.5-9 | Typical 900# Bonnet Seal Type Valve |
| 3.5-10 | Retaining Ring Design for 900# Bonnet-Seal Type Valve |
| 3.6-1A | Main Steam Line A |
| 3.6-1B | Main Steam Line B |
| 3.6-1C | Main Steam Line C |
| 3.6-1D | Main Steam Line D |
| 3.6-2 | Feedwater System |
| 3.6-3 | HPCI Steam Supply |
| 3.6-4 | RCIC Steam Supply |
| 3.6-5 | Core Spray |
| 3.6-6 | RHR Supply |
| 3.6-7 | RHR Return Loop A |
| 3.6-8 | RHR Return Loop B |
| 3.6-8A.1 | Reactor Water Cleanup |
| 3.6-8A.2 | Reactor Water Cleanup |
| 3.6-8A.3 | Reactor Water Cleanup |
| 3.6-8A.4 | Reactor Water Cleanup |
| 3.6-8A.5 | Reactor Water Cleanup |
| 3.6-8B | Reactor Vessel Head Vent |
| 3.6-8C | Head Spray |
| 3.6-8D | Standby Liquid Control |
| 3.6-8E | MSIV Drains |
| 3.6-10 | Typical Pipe Whip Restraints |
| 3.6-11 | Pipe Whip Restraint Arrangement to Protect Feedwater Outside Containment Isolation Valves |
| 3.6-11a | Main Feedwater Line PIPERUP Mathematical Model |
| 3.6-12 | Forcing Functions Model Associated with Pipe Whip Dynamic Analysis |
| 3.6-12a | Forcing Functions Model Associated with Pipe Whip Dynamite Analysis |
| 3.6-13 | Typical Pipe Whip Restraint Configuration |
| 3.6-14 | Recirculation System Postulated Break Locations and Restraint Locations (LOOP A and B Same, Unless Otherwise Specified) |
| 3.6-15 | Typical Restraint Force-Deflection Curve |
| 3.6-16 | Break Locations and Restraints Analyzed, PDA Verification Program |
| 3.6-17-1 | Pipe Break Protection for High Energy Piping in the Reactor Building |
| 3.6-17-2 | Pipe Break Protection for High Energy Piping in the Reactor Building |
| 3.6-17-3 | Pipe Break Protection for High Energy Piping in the Reactor Building |
| 3.6A-1 | Case A MSLB in Reactor Building |
| 3.6A-2 | Panel and Platform Locations |
| 3.6A-3 | Case A Volume Flows |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|---------|--|
| 3.6A-4 | Case A Pressure Transient |
| 3.6A-5 | Case B MSLB in Turbine Building |
| 3.6A-6 | Case B Volume Flows |
| 3.6A-7 | Case B Pressure Transient |
| 3.6A-8 | Model for Double-Ended Guillotine MSLB |
| 3.7a-1 | Reactor Pressure Vessel and Internal Seismic Model |
| 3.7a-2 | Density of Stress Reversals |
| 3.7b-2 | Diesel Generator 'E' Building Design Response Spectra Safe Shutdown Earthquake Horizontal Component |
| 3.7b-3 | Design Response Spectra Safe Shutdown Earthquake Horizontal Component |
| 3.7b-4 | Diesel Generator 'E' Buildings Design Response Spectra Safe Shutdown Earthquake Horizontal Component |
| 3.7b-5 | Synthetic Time History Normalized to 1G |
| 3.7b-6 | Diesel Generator 'E' Building Horizontal Synthetic Time History Normalized to 0.1G |
| 3.7b-7 | Diesel Generator 'E' Building Vertical Synthetic Time History Normalized to 0.1G |
| 3.7b-8 | Comparison of Time History Response Spectra and Design Response Spectra 2% and 5% Damping (0.2-30 CPS) |
| 3.7b-9 | Comparison of Time History Response Spectra and Design Response Spectra 3% and 7% Damping (0.2-30 CPS) |
| 3.7b-10 | Comparison of Time History Response Spectra and Design Response Spectra 2% and 5% Damping (0.2-1.0 CPS) |
| 3.7b-11 | Diesel Generator 'E' Building Comparison of Horizontal Time History Response Spectrum and Horizontal Design Response Spectrum 2% Damping |
| 3.7b-12 | Diesel Generator 'E' Building Comparison of Horizontal Time History Response Spectrum and Horizontal Design Response Spectrum 5% Damping |
| 3.7b-13 | Diesel Generator 'E' Building Comparison of Horizontal Time History Response Spectrum and Horizontal Design Response Spectrum 7% Damping |
| 3.7b-14 | Diesel Generator 'E' Building Comparison of Vertical Time History Response Spectrum and Vertical Design Response Spectrum 2% Damping |
| 3.7b-15 | Diesel Generator 'E' Building Comparison of Vertical Time History Response Spectrum and Vertical Design Response Spectrum 5% Damping |
| 3.7b-16 | Diesel Generator 'E' Building Comparison of Vertical Time History Response Spectrum and Vertical Design Response Spectrum 7% Damping |
| 3.7b-17 | Horizontal Seismic Model of Containment With Flexible Base |
| 3.7b-18 | Vertical Seismic Model of Containment With Flexible Base |
| 3.7b-19 | E-W Seismic Model of Reactor and Control Building |
| 3.7b-20 | N-S Seismic Model of Reactor and Control Building |
| 3.7b-21 | Vertical Seismic Model of Reactor and Control Building |
| 3.7b-22 | Plan View of Reactor and Control Building |
| 3.7b-23 | Correlation of Vertical Seismic Model Masspoints of the Physical Structure |
| 3.7b-24 | Containment Horizontal Mode Shapes Mode 1 |
| 3.7b-25 | Containment Horizontal Mode Shapes Mode 2 |
| 3.7b-26 | Containment Horizontal Mode Shapes Mode 4 |
| 3.7b-27 | Containment Vertical Mode Shapes Mode 1 |
| 3.7b-28 | Containment Vertical Mode Shapes Mode 2 |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|---------|--|
| 3.7b-29 | Containment Vertical Mode Shapes Mode 3 |
| 3.7b-30 | Reactor and Control Building E-W Mode Shapes - Mode 1 (Cranes at Points 32 and 33) |
| 3.7b-31 | Reactor and Control Building E-W Mode Shapes - Mode 2 |
| 3.7b-32 | Reactor and Control Building E-W Mode Shapes - Mode 3 (Cranes at Points 32 and 33) |
| 3.7b-33 | Reactor and Control Building E-W Mode Shapes - Mode 4 |
| 3.7b-34 | Reactor and Control Building E-W Mode Shapes, Mode 5 |
| 3.7b-35 | Reactor and Control Building N-S Mode Shapes - Mode 1 |
| 3.7b-36 | Reactor and Control Building N-S Mode Shapes - Mode 3 |
| 3.7b-37 | Reactor and Control Building Vertical Mode Shapes Mode 1 |
| 3.7b-38 | Reactor and Control Building Vertical Mode Shapes Mode 2 |
| 3.7b-39 | Reactor and Control Building Vertical Mode Shapes Mode 3 |
| 3.7b-40 | Containment Horizontal Displacements OBE |
| 3.7b-41 | Containment Horizontal Displacements SSE |
| 3.7b-42 | Containment Vertical Displacements OBE |
| 3.7b-43 | Containment Vertical Displacements SSE |
| 3.7b-44 | Containment Horizontal Accelerations OBE |
| 3.7b-45 | Containment Horizontal Accelerations SSE |
| 3.7b-46 | Containment Vertical Accelerations OBE |
| 3.7b-47 | Containment Vertical Accelerations SSE |
| 3.7b-48 | Reactor and Control Building E-W Displacements OBE |
| 3.7b-49 | Reactor and Control Building E-W Displacements SSE |
| 3.7b-50 | Reactor and Control Building N-S Displacements OBE |
| 3.7b-51 | Reactor and Control Building N-S Displacements SSE |
| 3.7b-52 | Reactor and Control Building Vertical Displacements OBE |
| 3.7b-53 | Reactor and Control Building Vertical Displacements SSE |
| 3.7b-54 | Reactor and Control Building E-W Accelerations OBE |
| 3.7b-55 | Reactor and Control Building E-W Accelerations SSE |
| 3.7b-56 | Reactor and Control Building N-S Accelerations OBE |
| 3.7b-57 | Reactor and Control Building N-S Accelerations SSE |
| 3.7b-58 | Reactor and Control Building Vertical Acceleration OBE |
| 3.7b-59 | Reactor and Control Building Vertical Accelerations SSE |
| 3.7b-60 | Response Spectrum at RPV Pedestal Horizontal OBE |
| 3.7b-61 | Response Spectrum at RPV Pedestal Horizontal SSE |
| 3.7b-62 | Response Spectrum at RPV Pedestal Vertical OBE |
| 3.7b-63 | Response Spectrum at RPV Pedestal Vertical SSE |
| 3.7b-64 | Response Spectrum at Refueling Area E-W OBE |
| 3.7b-65 | Response Spectrum at Refueling Area E-W SSE |
| 3.7b-66 | Response Spectrum at Refueling Area N-S OBE |
| 3.7b-67 | Response Spectrum at Refueling Area N-S SSE |
| 3.7b-68 | Response Spectrum at Refueling Area Vertical OBE |
| 3.7b-69 | Response Spectrum at Refueling Area Vertical SSE |
| 3.7b-70 | Response Spectrum at Top of Pedestal (Diesels A-D) E-W OBE |
| 3.7b-71 | Response Spectrum at Top of Pedestal (Diesel E) E-W OBE |
| 3.7b-72 | Response Spectrum at Top of Pedestal (Diesels A-D) E-W SSE |
| 3.7b-73 | Response Spectrum at Top of Pedestal (Diesel E) E-W SSE |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|----------|---|
| 3.7b-74 | Response Spectrum at Top of Pedestal (Diesels A-D) N-S OBE |
| 3.7b-75 | Response Spectrum at Top of Pedestal (Diesel E) N-S OBE |
| 3.7b-76 | Response Spectrum at Top of Pedestal (Diesels A-D) N-S SSE |
| 3.7b-77 | Response Spectrum at Top of Pedestal (Diesel E) N-S SSE |
| 3.7b-78 | Response Spectrum at Top of Pedestal (Diesels A-D) Vertical OBE |
| 3.7b-79 | Response Spectrum at Top of Pedestal for Diesel E Vertical OBE |
| 3.7b-80 | Response Spectrum at Top of Pedestal (Diesels A-D) Vertical-SSE |
| 3.7b-81 | Response Spectrum at Top of Pedestal for Diesel 'E' Vertical SSE |
| 3.7b-82 | Response Spectrum at Operating Floor of ESSW Pumphouse E-W OBE |
| 3.7b-83 | Response Spectrum at Operating Floor of ESSW Pumphouse E-W SSE |
| 3.7b-84 | Response Spectrum at Operating Floor of ESSW Pumphouse N-S OBE |
| 3.7b-85 | Response Spectrum at Operating Floor of ESSW Pumphouse N-S SSE |
| 3.7b-86 | Response Spectrum at Operating Floor of ESSW Pumphouse Vertical OBE |
| 3.7b-87 | Response Spectrum at Operating Floor of ESSW Pumphouse Vertical SSE |
| 3.7b-88 | Comparison of Design and R.G. 1.60 Response Spectra Horizontal OBE |
| 3.7b-89 | Comparison of Design and R.G. 1.60 Response Spectra Horizontal SSE |
| 3.7b-90 | Comparison of Design and R.G. 1.60 Response Spectra Vertical OBE |
| 3.7b-91 | Comparison of Design and R.G. 1.60 Response Spectra Vertical SSE |
| 3.7b-92 | Damping V/S ZPA for Raceway System |
| 3.7b-93 | ESSW Pump House 3-D Stick Model |
| 3.7b-94 | Diesel Generator 'A-D' Building 3-D Stick Model |
| 3.7b-95 | Diesel Generator 'E' Building Seismic Models |
| 3.8-1 | Figure replaced by Drawing C-331, Sh. 1 |
| 3.8-2 | Figure replaced by Drawing C-371, Sh. 1 |
| 3.8-3 | Figure replaced by Drawing C-1932, Sh. 3 |
| 3.8-4 | Figure replaced by Drawing C-1932, Sh. 4 |
| 3.8-5 | Figure replaced by Drawing C-1932, Sh. 5 |
| 3.8-9 | Primary Containment – Drywell Head Connection |
| 3.8-10 | Figure replaced by Drawing C-284, Sh. 1 |
| 3.8-11-1 | Figure replaced by Drawing C-332, Sh. 1 |
| 3.8-11-2 | Figure replaced by Drawing C-333, Sh. 1 |
| 3.8-12 | Figure replaced by Drawing C-281, Sh. 1 |
| 3.8-13 | Figure replaced by Drawing C-281, Sh. 1 |
| 3.8-14 | Figure replaced by Drawing C-370, Sh. 1 |
| 3.8-15-1 | Figure replaced by Drawing C-334, Sh. 1 |
| 3.8-15-2 | Figure replaced by Drawing C-335, Sh. 1 |
| 3.8-15-3 | Figure replaced by Drawing C-336, Sh. 1 |
| 3.8-15-4 | Figure replaced by Drawing C-337, Sh. 1 |
| 3.8-15-5 | Figure replaced by Drawing C-338, Sh. 1 |
| 3.8-16-1 | Figure replaced by Drawing C-351, Sh. 1 |
| 3.8-16-2 | Figure replaced by Drawing C-352, Sh. 1 |
| 3.8-16-3 | Figure replaced by Drawing C-353, Sh. 1 |
| 3.8-16-4 | Figure replaced by Drawing C-354, Sh. 1 |
| 3.8-16-5 | Figure replaced by Drawing C-355, Sh. 1 |
| 3.8-16-6 | Figure replaced by Drawing C-356, Sh. 1 |
| 3.8-16-7 | Figure replaced by Drawing C-357, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|-----------|--|
| 3.8-16-8 | Figure replaced by Drawing C-358, Sh. 1 |
| 3.8-16-9 | Figure replaced by Drawing C-359, Sh. 1 |
| 3.8-16-10 | Figure replaced by Drawing C-360, Sh. 1 |
| 3.8-16-11 | Figure replaced by Drawing C-393, Sh. 1 |
| 3.8-16-12 | Figure replaced by Drawing C-394, Sh. 1 |
| 3.8-16-13 | Figure replaced by Drawing C-395, Sh. 1 |
| 3.8-16-14 | Figure replaced by Drawing C-396, Sh. 1 |
| 3.8-16-15 | Figure replaced by Drawing C-397, Sh. 1 |
| 3.8-16-16 | Figure replaced by Drawing C-398, Sh. 1 |
| 3.8-16-17 | Figure replaced by Drawing C-399, Sh. 1 |
| 3.8-16-18 | Figure replaced by Drawing C-400, Sh. 1 |
| 3.8-17 | Figure replaced by Drawing C-282, Sh. 1 |
| 3.8-18 | Figure replaced by Drawing C-285, Sh. 1 |
| 3.8-19-1 | Figure replaced by Drawing C-288, Sh. 1 |
| 3.8-19-2 | Figure replaced by Drawing C-287, Sh. 1 |
| 3.8-19-3 | Figure replaced by Drawing C-283, Sh. 1 |
| 3.8-20-1 | Suppression Chamber Electrical Penetration Details |
| 3.8-20-2 | Drywell Electrical Penetration Details |
| 3.8-21 | Figure replaced by Drawing C-286, Sh. 1 |
| 3.8-22 | Figure replaced by Drawing C-291, Sh. 1 |
| 3.8-23 | Figure replaced by Drawing C-278, Sh. 1 |
| 3.8-24 | Containment Wall Temperature Gradients |
| 3.8-25 | Containment Wall Analytical Model for Axisymmetric Loads |
| 3.8-26 | Drywell Wall Analytical Model for Non-Axisymmetric Missile and Postulated Pipe Rupture Loads |
| 3.8-27 | Base Foundation Slab Analytical Model |
| 3.8-28 | Equipment Hatch Analytical Model |
| 3.8-29 | Structural Acceptance Test - Pressurization Sequence |
| 3.8-30 | Structural Acceptance Test - Locations of Deflection Measuring Devices for the Containment |
| 3.8-31 | Structural Acceptance Test - Locations of Deflection Measuring Devices for the Equipment Hatch |
| 3.8-32 | Figure replaced by Drawing C-384, Sh. 1 |
| 3.8-33 | Figure replaced by Drawing C-387, Sh. 1 |
| 3.8-34 | Structural Acceptance Test - Containment Analytical Model |
| 3.8-35 | Structural Acceptance Test - Equipment Hatch Analytical Model |
| 3.8-36 | Structural Acceptance Test - Comparison of Measured and Predicted Deflections for the Containment |
| 3.8-37 | Structural Acceptance Test - Comparison of Measured and Predicted Deflection for the Equipment Hatch |
| 3.8-38 | Structural Acceptance Test - Inside Meridional Strain at Mid-height of Suppression Chamber Wall |
| 3.8-39 | Structural Acceptance Test - Inside Hoop Strain at Mid-height of Suppression Chamber Wall |
| 3.8-40 | Structural Acceptance Test - Outside Meridional Strain at Mid-height of Suppression Chamber Wall |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|----------|---|
| 3.8-41 | Structural Acceptance Test - Outside Hoop Strain at Mid-height of Suppression Chamber Wall |
| 3.8-42 | Structural Acceptance Test - Outside Helical Strain at Mid-height of Suppression Chamber Wall |
| 3.8-43 | Structural Acceptance Test - External Concrete Surface Cracks at Mid-height of Drywell Wall |
| 3.8-44 | Drywell Head |
| 3.8-45 | Analytical Model of Drywell Head Assembly |
| 3.8-46-1 | Figure replaced by Drawing C-348, Sh. 1 |
| 3.8-46-2 | Figure replaced by Drawing C-349, Sh. 1 |
| 3.8-46-3 | Figure replaced by Drawing C-350, Sh. 1 |
| 3.8-47 | Figure replaced by Drawing C-293, Sh. 1 |
| 3.8-48 | Figure replaced by Drawing C-340, Sh. 1 |
| 3.8-49 | Figure replaced by Drawing C-341, Sh. 1 |
| 3.8-50 | Figure replaced by Drawing C-376, Sh. 1 |
| 3.8-51-1 | Figure replaced by Drawing C-344, Sh. 1 |
| 3.8-51-2 | Figure replaced by Drawing C-377, Sh. 1 |
| 3.8-52 | Figure replaced by Drawing C-362, Sh. 1 |
| 3.8-53 | Figure replaced by Drawing C-363, Sh. 1 |
| 3.8-54 | Figure replaced by Drawing C-354, Sh. 1 |
| 3.8-55 | Figure replaced by Drawing C-365, Sh. 1 |
| 3.8-56 | Figure replaced by Drawing C-367, Sh. 1 |
| 3.8-57 | Figure replaced by Drawing C-380, Sh. 1 |
| 3.8-58 | Temperature Gradients for Drywell Floor and Reactor Pedestal |
| 3.8-59 | Reactor Shield Wall Temperature Gradients |
| 3.8-60 | Drywell Floor Analytical Model |
| 3.8-61 | Analytical Model for Reactor Pedestal Above Drywell Floor |
| 3.8-62 | Reactor Shield Wall-EASE Program Analytical Model |
| 3.8-63 | Reactor Shield Wall-Analytical Model for "FINEL" and "ASHSD" Program |
| 3.8-64 | Suppression Chamber Columns - ASHSD Program Analytical Model |
| 3.8-65 | Suppression Chamber Columns - Seismic Model |
| 3.8-66 | Suppression Chamber Columns - "CE 668" Program Analytical Model |
| 3.8-67 | Seismic Truss Analytical Model |
| 3.8-68 | Structural Acceptance Test - Comparison of Measured and Predicted Deflections for the Drywell Floor |
| 3.8-69 | Figure replaced by Drawing A-11, Sh. 1 |
| 3.8-70 | Figure replaced by Drawing A-12, Sh. 1 |
| 3.8-71 | Figure replaced by Drawing A-13, Sh. 1 |
| 3.8-72 | Figure replaced by Drawing M-203, Sh. 1 |
| 3.8-73 | Figure replaced by Drawing M-204, Sh. 1 |
| 3.8-74 | Figure replaced by Drawing A-16, Sh. 1 |
| 3.8-75 | Figure replaced by Drawing A-17, Sh. 1 |
| 3.8-77 | Reactor, Control and Turbine Building Sections Looking North |
| 3.8-78 | Reactor Building Looking West |
| 3.8-79 | Figure replaced by Drawing M-227, Sh. 1 |
| 3.8-80 | Figure replaced by Drawing M-237, Sh. 1 |
| 3.8-81 | Figure replaced by Drawing M-260, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|----------|---|
| 3.8-82 | Figure replaced by Drawing M-261, Sh. 1 |
| 3.8-83 | Figure replaced by Drawing M-5200, Sh. 1 |
| 3.8-84 | Figure replaced by Drawing M-5200, Sh. 2 |
| 3.8-85 | Figure replaced by Drawing M-284, Sh. 1 |
| 3.8-86 | Figure replaced by Drawing C-64, Sh. 1 |
| 3.8-87 | Figure replaced by Drawing C-65, Sh. 1 |
| 3.8-88 | Figure replaced by Drawing C-66, Sh. 1 |
| 3.8-89 | Figure replaced by Drawing C-67, Sh. 1 |
| 3.8-90 | Figure replaced by Drawing M-270, Sh. 1 |
| 3.8-91 | Figure replaced by Drawing M-271, Sh. 1 |
| 3.8-92 | Figure replaced by Drawing M-272, Sh. 1 |
| 3.8-93 | Figure replaced by Drawing M-273, Sh. 1 |
| 3.8-94 | Figure replaced by Drawing M-274, Sh. 1 |
| 3.8-95 | Figure replaced by Drawing C-795, Sh. 1 |
| 3.8A-1 | Thin Shell Cylinder |
| 3.8A-2 | Layered Cylinder |
| 3.8A-3 | General Layout of Cylinder |
| 3.8A-4 | Finite Element Model |
| 3.8A-5 | Axial Moment |
| 3.8A-6 | Cylinder with Hinged Ends |
| 3.8A-7 | Finite Element Model |
| 3.8A-8-1 | Comparison of Results for Cylindrical Shell Subjected to an Asymmetric Bending |
| 3.8A-8-2 | Comparison (Continued) of Results for Cylindrical Shell Subjected to Asymmetric Bending |
| 3.8A-9 | Reinforced Concrete Beam |
| 3.8A-10 | Reinforced Concrete Beam and CECAP Concrete Element Model |
| 3.8A-11 | Beam Cross-Section and Initial Stress Distribution |
| 3.8A-12 | Final Thermal Stress Distribution |
| 3.8A-13 | Reinforced Concrete Beam and CECAP Concrete Element Model |
| 3.8A-14 | Reinforced Concrete Beam and CECAP Concrete Element Model |
| 3.8A-15 | Reinforced Concrete Beam and CECAP Model |
| 3.8A-16 | Beam Cross-Section and Stress Block |
| 3.8A-17 | Plate Geometry, Loading, and Finite Element Mesh for Rectangular Plate with a Concentrated Load at the Center |
| 3.8A-18 | Plate Geometry, Loading, and Finite Element Mesh for Rectangular Plate with Various Edge Conditions |
| 3.8A-19 | Welding Neck Flange Detail |
| 3.8A-20 | Slip-On Flange Detail |
| 3.8A-21 | Geometry of Torispherical and Ellipsoidal Heads (Fit to Correspond to Geometry of Ellipsoidal Head in Reference 3.8A-9) |
| 3.8A-22 | Measured Thickness Variation in Experimental Head No. 1 (From Reference 3.8A-10, Page 18) |
| 3.8A-23 | Thickness Variation in Cylinder No. 1 (From Reference 3.8A-11 Fig. 4) |
| 3.8A-24 | Analytical Model with Boundary Conditions |
| 3.8A-25 | Plot of Hoop Force and Longitudinal Movement from E0781 Output |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|-----------|---|
| 3.8A-26 | Plot of Stress in the Θ (Hoop) Direction on the Inside Surface ($\Theta = 0^\circ$) (Ref. 3.8A-12 Page G-14) |
| 3.8A-27 | Plot of Stress in the Θ (Hoop) Direction on the Outside Surface ($\Theta = 0^\circ$) (Ref. 3.8A-12 Page G-11) |
| 3.8A-28 | Plot of Stress in the ϕ (Longitudinal) Direction on the Inside Surface ($\Theta = 0^\circ$) (Ref. 3.8A-12 Page G-20) |
| 3.8A-29 | Plot of Stress in the ϕ (Longitudinal) Direction on the Outside Surface ($\phi = 0^\circ$) (Ref. 3.8A-12 Page G-17) |
| 3.8A-30 | Plot of Membrane Stress ($\phi = 0^\circ$) (Ref. 3.8A-12 Page G-23) |
| 3.8A-31 | Dimensions of Cylindrical Water Tank |
| 3.8A-32 | Experimental Beam Dimensions |
| 3.8A-33 | Reference 3.8A-14 Mesh |
| 3.8A-34 | Finel Finite Element Mesh |
| 3.8A-35-1 | Regions of Cracking |
| 3.8A-35-2 | Regions of Cracking (Cont.) |
| 3.8A-36 | Load-Displacement Curves from Finel Verification Using a Simply Supported Beam |
| 3.8A-37 | Finite Element Model |
| 3.8A-38 | Finite Element Model |
| 3.8A-39 | Temperature Distribution |
| 3.8A-40 | Schematic of Test Problem |
| 3.8A-41 | Finite Element Layout |
| 3.8A-42 | Comparison of Results |
| 3.8A-43 | Steel Sphere |
| 3.8A-44 | Finite Element Model |
| 3.9-1 | Transient Pressure Differentials following a Steam Line Break at 105% Rated Steam Flow, 100% Recirculation |
| 3.9-2 | Typical Relief Valve Transient |
| 3.9-3 | Reactor Vessel Cutaway |
| 3.9-4 | Reactor Internals Flow Paths |
| 3.9-5 | Fuel Support Pieces |
| 3.9-6 | Jet Pump |
| 3.9-7 | Pressure Nodes Used for Depressurization Analysis |
| 3.9A-1 | Transient Temperature Response |
| 3.10a-1 | Typical Vertical Board |
| 3.10a-2 | Instrument Rack |
| 3.10a-3 | Typical Local Rack |
| 3.10a-4 | NEMA Type-12 Enclosure |
| 3.10a-5-1 | Cabinet Installation for Seismic and Hydrodynamic Loads- Sample Calculation (Cabinet H12-P608) |
| 3.10a-5-2 | Cabinet Installation for Seismic and Hydrodynamic Loads- Sample Calculation (Cabinet H12-P608) |
| 3.10a-5-3 | Cabinet Installation for Seismic and Hydrodynamic Loads- Sample Calculation (Cabinet H12-P608) |
| 3.10a-6 | Corner Post |
| 3.10a-7 | Plan View of Panel |

SUMMARY TABLE OF CONTENTS**Chapter 3 Figures**

| | |
|---------|---|
| 3.10a-8 | Barrier With Two End Plates |
| 3.10a-9 | Panel Deflections |
| 3.11-1 | Figure replaced by Drawing C-1815, Sh. 1 |
| 3.11-2 | Figure replaced by Drawing C-1815, Sh. 2 |
| 3.11-3 | Figure replaced by Drawing C-1815, Sh. 3 |
| 3.11-4 | Figure replaced by Drawing C-1815, Sh. 4 |
| 3.11-5 | Figure replaced by Drawing C-1815, Sh. 5 |
| 3.11-6 | Figure replaced by Drawing C-1815, Sh. 6 |
| 3.11-7 | Figure replaced by Drawing C-1815, Sh. 7 |
| 3.11-8 | Figure replaced by Drawing C-1815, Sh. 8 |
| 3.11-9 | Figure replaced by Drawing C-1815, Sh. 9 |
| 3.11-10 | Figure replaced by Drawing C-1815, Sh. 10 |
| 3.11-11 | Figure replaced by Drawing C-1815, Sh. 11 |
| 3.11-12 | Figure replaced by Drawing C-1815, Sh. 12 |
| 3.13-1 | One line diagram illustrating relationship of loads, penetration assemblies, and protective devices for curves presented as Figures 3.13-2A, 3.13-2B & 3.13-3 |
| 3.13-2 | Figure replaced by Figure 3.13-2A and Figure 3.13-2B |
| 3.13-2A | Time-Current Characteristic Curves For Overcurrent Protection Of #10 Copper, Containment Penetrations |
| 3.13-2B | Time-Current Characteristic Curves For Overcurrent Protection Of #10 Copper, Containment Penetrations |
| 3.13-3 | Relationship Of Loads, Penetration Assemblies & Protective Devices for Curves Presented in Figures 3.13-2, 3.13-3, & 3.18-8 |
| 3.13-4 | 120 Volt AC Control Circuits |
| 3.13-5 | 125 Volt DC Control Circuits |
| 3.13-6 | 208/120 Lighting Circuits |
| 3.13-7 | React Recir Pump - Max Short Circuit Capability |

SUMMARY TABLE OF CONTENTS**Chapter 4****4.0 REACTOR**

- 4.1 Summary Description
 - 4.1.1 Reactor Vessel
 - 4.1.2 Reactor Internal Components
 - 4.1.3 Reactivity Control Systems
 - 4.1.4 Analysis Techniques
 - 4.1.5 References

- 4.2 Fuel System Design
 - 4.2.1 Design Bases
 - 4.2.2 General Design Description
 - 4.2.3 Design Evaluations
 - 4.2.4 Testing and Inspection
 - 4.2.5 Operating and Developmental Experience
 - 4.2.6 References

- 4.3 Nuclear Design
 - 4.3.1 Design Bases
 - 4.3.2 Description
 - 4.3.3 Analytical Methods
 - 4.3.4 Changes
 - 4.3.5 References

- 4.4 Thermal and Hydraulic Design
 - 4.4.1 Design Basis
 - 4.4.2 Description of Thermal-Hydraulic Design of the Reactor Core
 - 4.4.3 Description of the Thermal and Hydraulic Design of the Reactor Coolant System
 - 4.4.4 Evaluation
 - 4.4.5 Testing and Verification
 - 4.4.6 Instrumentation Requirements

- 4.5 Reactor Materials
 - 4.5.1 Control Rod System Structural Materials
 - 4.5.2 Reactor Internal Materials
 - 4.5.3 Control Rod Drive Housing Supports

- 4.6 Functional Design of Reactivity Control Systems
 - 4.6.1 Information for CRDS
 - 4.6.2 Evaluations of the CRDS
 - 4.6.3 Testing and Verification of the CRDs
 - 4.6.4 Information for Combined Performance of Reactivity Systems
 - 4.6.5 Evaluation of Combined Performance
 - 4.6.6 References

SUMMARY TABLE OF CONTENTS**Chapter 4 - Tables**

| | |
|--------|--|
| 4.2-14 | Fuel Design Characteristics (Nominal) |
| 4.3-1 | Reactor Core Characteristics |
| 4.3-4 | Typical Core Reactivity Coefficients |
| 4.3-5 | Fast Neutron Fluences >1 MEV 54 EFPY Fluence |
| 4.4-1 | Typical Thermal and Hydraulic Design Characteristics of the Reactor Core |
| 4.4-2 | Typical Void Distribution |
| 4.4-2a | Axial Power Distribution Used to Generate Typical Void and Quality Distributions |
| 4.4-3 | Typical Flow Quality Distribution |
| 4.4-4 | Typical Core Flow Distribution |
| 4.4-6 | Uncertainties Considered in MCPR Safety Limit |
| 4.4-7 | Bypass Flow Paths |
| 4.4-8 | Plant Configuration Data |
| 4.4-9 | Lengths of Safety Injection Line |

NOTE: Additional tables are presented in NEDE 20944/20944-P.

SUMMARY TABLE OF CONTENTS**Chapter 4 - Figures**

| | |
|-----------|---|
| 4.1-2 | Steam Dryer Panel |
| 4.1-3 | Steam Dryer |
| 4.2-15 | Core Cell (ATRIUM™-10 Fuel with Duralife 60C Control Rod) |
| 4.2-15A | Core Cell (ATRIUM-10 Fuel with MARATHON Control Rod) |
| 4.2-15B | Core Cell (ATRIUM-10 Fuel with Ultra-HD Control Rod) |
| 4.2-15C | Core Cell (ATRIUM-10 Fuel with Westinghouse CR 99 Control Rod) |
| 4.2-16A | Typical Core Cell (ATRIUM-11 Fuel with GE Hitachi Control Rod) |
| 4.2-16B | Typical Core Cell (ATRIUM-11 Fuel with Westinghouse Control Rod) |
| 4.2-17 | Fuel Bundle FANP ATRIUM-10 |
| 4.2-17-1 | Representative ATRIUM-11 Fuel Bundle (Not to Scale) |
| 4.2-18 | 80 MIL Fuel Channel |
| 4.2-18-1 | 80 MIL Fuel Channel |
| 4.2-18-2 | 100 MIL Fuel Channel |
| 4.2-18-3 | Advanced Fuel Channel |
| 4.2-18-4 | ATRIUM-11 Advanced Fuel Channel |
| 4.2-19 | Correct Fuel Assembly Orientation |
| 4.2-20 | Control Rod Assembly Original Equipment |
| 4.2-21 | Control Rod Assembly Duralife 160-C (D-160C) |
| 4.2-22 | Control Rod Assembly Marathon |
| 4.2-23 | Control Rod Assembly Westinghouse CR 99 |
| 4.3-1 | Core Loading Map Typical of Unit 1 |
| 4.3-2 | Core Loading Map Typical of Unit 2 |
| 4.3-3 | Uranium Depletion as a Function of Exposure, 40% Voids (Typical) |
| 4.3-4 | Plutonium Buildup as a Function of Exposure, 40% Voids (Typical) |
| 4.3-5 | Fission Fraction as a Function of Exposure, 40% Voids (Typical) |
| 4.3-6 | Delayed Neutron Fraction as a Function of Exposure, 40% Voids (Typical) |
| 4.3-7 | Neutron Lifetime as a Functions of Exposure, 40% Voids (Typical) |
| 4.3-8-46 | ATRIUM™ -10 Fuel Axial Enrichment (Nominal) Typical Assemblies |
| 4.3-8-47 | ATRIUM-11 Fuel Axial Enrichment (Nominal) Typical Assemblies |
| 4.3-9-123 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice A |
| 4.3-9-124 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice B |
| 4.3-9-125 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice C |
| 4.3-9-126 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice D |
| 4.3-9-127 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice E |
| 4.3-9-128 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice F |
| 4.3-9-129 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice G |
| 4.3-9-130 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice H |
| 4.3-9-131 | ATRIUM™-10 Fuel Radial Enrichment (Nominal) Typical Lattice I |
| 4.3-9-132 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice A |
| 4.3-9-133 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice B |
| 4.3-9-134 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice C |
| 4.3-9-135 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice D |
| 4.3-9-136 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice E |
| 4.3-9-137 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice F |
| 4.3-9-138 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice G |

SUMMARY TABLE OF CONTENTS**Chapter 4 - Figures**

| | |
|-----------|--|
| 4.3-9-139 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice H |
| 4.3-9-140 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice I |
| 4.3-9-141 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice J |
| 4.3-9-142 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice K |
| 4.3-9-143 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice L |
| 4.3-9-144 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice M |
| 4.3-9-145 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice N |
| 4.3-9-146 | ATRIUM-11 Fuel Radial Enrichment (Nominal) Typical Lattice O |
| 4.3-11-1 | FANP ATRIUM 10 Fuel Dominant Lattice Hot-Uncontrolled K-Infinity vs Exposure (Typical) |
| 4.3-11-2 | FANP ATRIUM 10 Fuel Dominant Lattice Local Peaking, Unrodded, 40% Voids 0 MWD/MTU (Typical) |
| 4.3-11-3 | FANP ATRIUM 10 Fuel Dominant Lattice Local Peaking, Unrodded, 40% Voids 15000 MWD/MTU (Typical) |
| 4.3-11-4 | FANP ATRIUM 10 Fuel Dominant Lattice Local Peaking, Unrodded, 40% Voids 40000 MWD/MTU (Typical) |
| 4.3-11-5 | FANP ATRIUM 10 Fuel Dominant Lattice Local Peaking, Unrodded, 0% Voids 0 MWD/MTU (Typical) |
| 4.3-11-6 | FANP ATRIUM 10 Fuel Dominant Lattice Local Peaking, Unrodded, 80% Voids 0 MWD/MTU (Typical) |
| 4.3-11-7 | FANP ATRIUM 10 Fuel Dominant Lattice Maximum Hot-Uncontrolled Local Peaking Factor vs Exposure (Typical) |
| 4.3-11-8 | ATRIUM 11 Fuel Dominant Lattice Hot-Uncontrolled K-Infinity vs Exposure (Typical) |
| 4.3-11-9 | ATRIUM 11 Fuel Dominant Lattice Local Peaking, Unrodded, 40% Voids 0 MWD/MTU (Typical) |
| 4.3-11-10 | ATRIUM 11 Fuel Dominant Lattice Local Peaking, Unrodded, 40% Voids 15000 MWD/MTU (Typical) |
| 4.3-11-11 | ATRIUM 11 Fuel Dominant Lattice Local Peaking, Unrodded, 40% Voids 40000 MWD/MTU (Typical) |
| 4.3-11-12 | ATRIUM 11 Fuel Dominant Lattice Local Peaking, Unrodded, 0% Voids 0 MWD/MTU (Typical) |
| 4.3-11-13 | ATRIUM 11 Fuel Dominant Lattice Local Peaking, Unrodded, 80% Voids 0 MWD/MTU (Typical) |
| 4.3-11-14 | ATRIUM 11 Fuel Dominant Lattice Maximum Hot-Uncontrolled Local Peaking Factor vs. Exposure (Typical) |
| 4.3-12 | Hot Excess Reactivity vs Exposure (Typical) |
| 4.3-13 | Shutdown Margin vs Exposure (Typical) |
| 4.3-14 | Vessel Fluence (R,0) Model for Azimuthal Flux Distribution |
| 4.4-1 | Schematic of Reactor Assembly Showing the Bypass Flow Paths |
| 4.4-2 | Damping Coefficient Versus Decay Ratio (Second Order Systems) |
| 4.4-3 | Hydrodynamic and Core Stability Model for Initial Core |
| 4.4-5 | Power-Flow Operating Map |
| 4.4-7a | 10 Cent Rod Reactivity Step at 51.5% Rated Power (Natural Circulation) |
| 4.4-7b | 10 psi Pressure Regulator Setpoint Step at 51.5% Rated Power (Natural Circulation) |

SUMMARY TABLE OF CONTENTS**Chapter 4 - Figures**

| | |
|--------|---|
| 4.4-7c | 6-9 Inch Level Setpoint Step at 51.5% Rated Power (Natural Circulation) |
| 4.4-8a | 10 Cent Rod Reactivity Step at 105% Rated Power and 100% Rated Flow |
| 4.4-8b | 10 psi Pressure Regulator Setpoint Step at 105% Rated Power and 100% Rated Flow |
| 4.4-8c | 6-inch Level Setpoint Step at 105% Rated Power and 100% Rated Flow |
| 4.4-8d | 10% Load Demand Step at 105% Rated Power and 100% Rated Flow |
| 4.4-9a | 10 Cent Rod Reactivity Step at 68% Rated Power and 51.5% Rated Flow |
| 4.4-9b | 10 psi Pressure Regulator Step at 68% Rated Power and 51.5% Rated Flow |
| 4.4-9c | 6-inch Water Level Setpoint Step at 60% Rated Power and 51.5% Rated Flow |
| 4.4-9d | 10% Load Demand Step at 68% Rated Power and 51.5% Rated Flow |
| 4.6-1 | Control Rod to Control Rod Drive Coupling |
| 4.6-2 | Control Rod Drive Unit |
| 4.6-3 | Control Rod Drive Schematic |
| 4.6-4 | Control Rod Drive (Cutaway) |
| 4.6-5a | Figured replaced by Drawing M-146, Sh. 1 |
| 4.6-5b | Figured replaced by Drawing M-147, Sh. 1 |
| 4.6-6 | Figured replaced by Drawing M1-C12-8, Sh. 1 |
| 4.6-7 | Control Rod Drive Hydraulic Control Unit |
| 4.6-8 | Control Rod Drive Housing Support |

NOTE: Additional Figures are presented in NEDE 20944/20944-P.

SUMMARY TABLE OF CONTENTS**Chapter 5****5.0 REACTOR COOLANT SYSTEM AND CONNECTED SYSTEMS**

- 5.1 Summary Description
 - 5.1.1 Schematic Flow Diagram
 - 5.1.2 Piping and Instrumentation Diagram
 - 5.1.3 Plan and Elevation Drawings

- 5.2 Integrity of Reactor Coolant Pressure Boundary
 - 5.2.1 Compliance with Codes and Code Cases
 - 5.2.2 Overpressure Protection
 - 5.2.3 Reactor Coolant Pressure Boundary Materials
 - 5.2.4 In-Service Inspection and Testing of Reactor Coolant Pressure Boundary
 - 5.2.5 Detection of Leakage Through Reactor Coolant Pressure Boundary
 - 5.2.6 References

- 5.3 Reactor Vessel
 - 5.3.1 Reactor Vessel Materials
 - 5.3.2 Pressure-Temperature Limits
 - 5.3.3 Reactor Vessel Integrity
 - 5.3.4 References

- 5.4 Component and Subsystem Design
 - 5.4.1 Reactor Recirculation Pumps
 - 5.4.2 Steam Generators (PWR)
 - 5.4.3 Reactor Coolant Piping
 - 5.4.4 Main Steamline Flow Restrictors
 - 5.4.5 Main Steamline Isolation System
 - 5.4.6 Reactor Core Isolation Cooling System
 - 5.4.7 Residual Heat Removal System
 - 5.4.8 Reactor Water Cleanup System
 - 5.4.9 Main Steam Lines and Feedwater Piping
 - 5.4.10 Pressurizer
 - 5.4.11 Pressurizer Relief Discharge System
 - 5.4.12 Valves
 - 5.4.13 Safety and Relief Valves
 - 5.4.14 Component Supports
 - 5.4.15 High Pressure Coolant Injection (HPCI) System
 - 5.4.16 Core Spray (CS) System
 - 5.4.17 Standby Liquid Control (SLC) System
 - 5.4.18 References

SUMMARY TABLE OF CONTENTS**Chapter 5 - Tables**

| | |
|--------|---|
| 5.1-1 | Design and Performance Characteristics of the Reactor Coolant System and Its Components |
| 5.2-1 | Reactor Coolant Pressure Boundary Components Code Case Interpretations |
| 5.2-2 | Nuclear System Safety/Relief Set Points Units 1 and 2 |
| 5.2-3 | Design Temperature, Pressure and Maximum Test Pressure for RCPB Components |
| 5.2-4 | Reactor Coolant Pressure Boundary Materials |
| 5.2-5 | BWR Water Chemistry |
| 5.2-6 | Systems Which May Initiate During Overpressure Event |
| 5.2-7 | Water Sample Locations |
| 5.2-8 | Summary of Isolation/Alarm of System Monitored and Leak Detection Methods Used |
| 5.2-9 | Sequence of Events for MSIV Isolation Closure Unit 1 Typical and Unit 2 Typical |
| 5.2-10 | RCPB Components in Compliance with 10CFR50.55(a) (2) (ii) |
| 5.2-11 | Identified Leakages into the Drywell Equipment Drain Tank |
| 5.2-12 | Unidentified Leakages into the Drywell Floor Drain Sump |
| 5.2-13 | Estimated Monitor Responses |
| 5.2-14 | RCPB Leak Detection Monitors Inside Primary Containment Drywell |
| 5.3-1a | Appendix G Matrix For Susquehanna Unit 1 |
| 5.3-1b | Appendix H Matrix For Susquehanna SES Unit 1 |
| 5.3-2a | Appendix G Matrix For Susquehanna SES Unit 2 |
| 5.3-2b | Appendix H Matrix For Susquehanna SES Unit 2 |
| 5.3-3 | Reactor Vessel Material Surveillance Program - Withdrawal Schedule |
| 5.4-2 | Reactor Water Cleanup System Equipment Design Data |
| 5.4-3 | RHR Relief Valve Data |
| 5.4-4 | RCPB Component Description |

SUMMARY TABLE OF CONTENTS**Chapter 5 - Figures**

| | |
|----------|---|
| 5.1-2 | Coolant Volumes of the Boiling Water Reactor |
| 5.1-3A-1 | Figure replaced by Drawing M-141, Sh. 1 |
| 5.1-3A-2 | Figure replaced by Drawing M-141, Sh. 2 |
| 5.1-3B | Figure replaced by Drawing M-142, Sh. 1 |
| 5.1-4-1 | Reactor Coolant System Plan |
| 5.1-4-2 | Reactor Coolant System Elevation |
| 5.1-4-3 | Reactor Coolant System Elevation |
| 5.2-2 | Simulated Safety/Relief Valve Spring Mode Characteristic Used for Capacity Sizing Analysis |
| 5.2-2A | Simulated Safety/Relief Valve Spring Mode Characteristic |
| 5.2-6 | Safety Valve Lift Versus Time Characteristic |
| 5.2-7 | Schematic of Safety Valve with Auxiliary Actuating Device |
| 5.2-8 | Typical BWR Feedwater Cycle |
| 5.2-9 | Conductance vs. pH as a Function of Chloride Concentration of Aqueous Solution at 25°C |
| 5.2-10 | Calculated Leak Rate Versus Crack Length as a Function of Applied Hoop Stress |
| 5.2-11 | Axial Through-Wall Crack Length Data Correlation |
| 5.2-12 | Region for Spring Safety Mode Nominal Setpoint |
| 5.2-13 | Overpressure Protection Analysis (MSIV Closure with High Flux Scram Trip) Typical of Unit 1 |
| 5.2-14 | Overpressure Protection Analysis (MSIV Closure with High Flux Scram Trip) Typical of Unit 2 |
| 5.3-1 | Reactor Vessel |
| 5.3-3 | Bracket for Holing Surveillance Capsule |
| 5.3-4c | Unit 1 Predicted Adjusted Reference Temperature vs. Effective Full Power Years of Operation |
| 5.3-4d | Unit 2 Predicted Adjusted Reference Temperature vs. Effective Full Power Years of Operation |
| 5.4-1 | Recirculation System Elevation and Isometric |
| 5.4-2b-1 | Figure replaced by Drawing M-143, Sh. 1 |
| 5.4-2b-2 | Figure replaced by Drawing M-143, Sh. 2 |
| 5.4-2c | Figure replaced by Drawing M1-B31-13, Sh. 3 |
| 5.4-3 | Recirculation Pump Head, NPSH, Flow and Efficiency Curves |
| 5.4-4a | RHR Suction Strainer Details |
| 5.4-4b | RHR Suction Strainer Details |
| 5.4-5 | Operating Principle of Jet Pump |
| 5.4-6 | Core Flooding Capability of Recirculation System |
| 5.4-7 | Main Steam Line Flow Restrictor Location |
| 5.4-9a | Figure replaced by Drawing M-149, Sh. 1 |
| 5.4-9b | Figure replaced by Drawing M-150, Sh. 1 |
| 5.4-10 | Figure replaced by Drawing M1-E51-81, Sh. 1 |
| 5.4-13-1 | Figure replaced by Drawing M-151, Sh. 1 |
| 5.4-13-2 | Figure replaced by Drawing M-151, Sh. 2 |
| 5.4-13-3 | Figure replaced by Drawing M-151, Sh. 3 |

SUMMARY TABLE OF CONTENTS

Chapter 5 - Figures

| | |
|----------|---|
| 5.4-13-4 | Figure replaced by Drawing M-151, Sh. 4 |
| 5.4-14-1 | Figure replaced by Drawing M1-E11-3, Sh. 1 |
| 5.4-14-2 | Figure replaced by Drawing M1-E11-3, Sh. 2 |
| 5.4-15A | Figure replaced by Drawing M1-G33-16, Sh. 1 |
| 5.4-15B | Figure replaced by Drawing M1-G33-18, Sh. 1 |
| 5.4-16-1 | Figure replaced by Drawing M1-144, Sh. 1 |
| 5.4-16-2 | Figure replaced by Drawing M1-144, Sh. 2 |
| 5.4-16-3 | Figure replaced by Drawing M1-144, Sh. 3 |
| 5.4-18 | Figure replaced by Drawing M-145, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 6****6.0 ENGINEERED SAFETY FEATURES**

- 6.1 Engineered Safety Feature Materials
 - 6.1.1 Metallic Materials
 - 6.1.2 Organic Materials
 - 6.1.3 Post-Accident Chemistry

- 6.2 Containment Systems
 - 6.2.1 Primary Containment Functional Design
 - 6.2.2 Containment Heat Removal System
 - 6.2.3 Secondary Containment Functional Design
 - 6.2.4 Containment Isolation System
 - 6.2.5 Combustible Gas Control in Containment
 - 6.2.6 Primary Reactor Containment Leakage Rate Testing
 - 6.2.7 References

- 6.3 Emergency Core Cooling Systems
 - 6.3.1 Design Bases and Summary Description
 - 6.3.2 System Design
 - 6.3.3 ECCS Performance Evaluation
 - 6.3.4 Tests and Inspections
 - 6.3.5 Instrumentation Requirements
 - 6.3.6 NPSHA Margin and Vortex Formation After a Passive Failure in a Water Tight ECCS Pump Room
 - 6.3.7 References

- 6.4 Habitability Systems
 - 6.4.1 Design Bases
 - 6.4.2 System Design
 - 6.4.3 System Operational Procedures
 - 6.4.4 Design Evaluations
 - 6.4.5 Testing and Inspection
 - 6.4.6 Instrumentation Requirements

- 6.5 Fission Product Removal and Control Systems
 - 6.5.1 Engineered Safety Feature (ESF) Filter Systems
 - 6.5.2 Containment Spray Systems
 - 6.5.3 Fission Product Control System
 - 6.5.4 Ice Condenser as a Fission Product Cleanup System
 - 6.5.5 References

- 6.6 Inservice Inspection of Class 2 and 3 Components
 - 6.6.1 Components Subject to Examination
 - 6.6.2 Accessibility
 - 6.6.3 Examination Techniques and Procedures
 - 6.6.4 Inspection Intervals
 - 6.6.5 Examination Categories and Requirements

SUMMARY TABLE OF CONTENTS**Chapter 6**

| | |
|--------|--|
| 6.6.6 | Evaluation of Examination Results |
| 6.6.7 | System Pressure Tests |
| 6.6-8 | Augmented Inservice Inspection to Protect Against Postulated Piping Failures |
| 6.6-9 | Containment Inspections |
| 6.7 | Main Steam Isolation Valve Leakage Isolated Condenser Treatment Method |
| 6.7.1 | Design Bases |
| 6.7.2 | System Description |
| 6.7.3 | System Evaluation |
| 6.7.4 | Instrumentation Requirements |
| 6.7.5 | Inspection and Testing |
| 6A | Subcompartment Differential Pressure Considerations |
| 6B | Compartment Differential Pressure Analysis Description |
| 6B.1 | FLUD Calculational Procedure |
| 6B.1.1 | Equation of State |
| 6B.1.2 | Compartment Thermodynamic State |
| 6B.1.3 | Compartment Initial Conditions |
| 6B.1.4 | Air and Vapor Component Flow Rates |
| 6B.2 | Energy Transfer Mechanisms |
| 6B.2.1 | Blowdown Energy |
| 6B.2.2 | Enthalpy Flow |
| 6B.2.3 | Compartment Heat Loads |
| 6B.2.4 | Unit Coolers |
| 6B.2.5 | Energy Balance |
| 6B.2.6 | Blowout Panel Activation |
| 6B.2.7 | Energy and Mass Conversion |
| 6B.2.8 | Eulerian Integration |
| 6B.3 | Thermodynamic Properties of Steam, Water, and Air |
| 6B.4 | References |

SUMMARY TABLE OF CONTENTS**Chapter 6 Tables**

| | |
|----------|--|
| 6.1-1a | NSSS Supplied Engineered Safety Features Component Materials |
| 6.1-1b | Engineered Safety Features Materials |
| 6.1-2 | Containment Components-Coating Schedule |
| 6.1-3 | Inventory of Qualified and Unqualified Containment Coatings |
| 6.2-1 | Containment Design Parameters |
| 6.2-2 | Engineered Safety Systems Inputs and Assumptions for Containment Response Analyses |
| 6.2-3a | Initial Plant Conditions for DBA-LOCA Containment Response |
| 6.2-4a | Input and Assumptions for the Short-Term DBA-LOCA Analysis |
| 6.2-5a | Input and Assumptions for the Long-Term DBA-LOCA Analysis |
| 6.2-6a | Containment Performance for DBA-LOCA |
| 6.2-9 | RPV Break Flow Data For Recirculation Line Break (102% P / 100% F) |
| 6.2-10 | RPV Break Flow Data For Main Steam Line Break (102% P / 100% F) |
| 6.2-11 | Core Decay Heat Following LOCA for Containment Analysis |
| 6.2-12 | Containment Penetration Data |
| 6.2-12a | Data on Instrument Lines Penetrating Containment |
| 6.2-13 | Parameters Used for the Evaluation of Combustible Gases in the Containment After a LOCA (HISTORICAL) |
| 6.2-14 | Primary Containment Atmosphere Monitoring System (Hydrogen/Oxygen Analyzer) System Level, Failure Mode and Effect Analysis |
| 6.2-15 | Evaluation of Potential Secondary Containment Bypass Leakage Pathways |
| 6.2-17 | Information for the SSES Secondary Containment |
| 6.2-19 | Type A Test Data |
| 6.2-21 | System Venting and Draining for Primary Containment Integrated Leakage Rate Test |
| 6.2-22 | Leakage Rate Test List |
| 6.2-23 | Initial and Boundary Conditions for Inadvertent Spray Actuation Study |
| 6.2-24 | Initial and Boundary Conditions For Drywell- Wetwell Bypass Leakage Study |
| 6.2-25 | Blowdown Data and Bypass Leakage |
| 6.2-26 | Long-term Blowdown Data for a Recirculation Line Break (Case D) |
| 6.3-1B-2 | Event Times for the Highest PCT Case from the TLO Recirculation Line Break Spectrum Analysis |
| 6.3-2B | Significant Input Parameters to the Loss-of-Coolant Accident Analysis |
| 6.3-3B-2 | Results for Limiting Two Loop Operation Recirculation Line Break 1.0 Deg Pump Suction SF-LPCI Top-Peaked Axial 102% Power (4031 MWt) 80 Mlbs/HR Flow |
| 6.3-3C | Recirculation Line Break Results Highest PCT Cases |
| 6.3-5 | Single Failures And Available Systems For Susquehanna |
| 6.3-8 | HPCI System Design Parameters |
| 6.3-9 | Manual Valves in the ECCS |
| 6.3-10 | Safety-Related Valves in the Drywell Subject to Spray Impingement |
| 6.4-1 | Control Structure Isolation Damper Leakage Characteristics and Closure Times |
| 6.5-1 | Engineered Safety Feature Filter System Design Parameters |
| 6.5-2 | Engineered Safety Feature Filter Systems Compliance with Recommendations of Regulatory Guide 1.52 |

SUMMARY TABLE OF CONTENTS**Chapter 6 Tables**

| | |
|---------|--|
| 6.5-3 | Standby Gas Treatment System Failure Mode and Effect Analysis |
| 6.5-4 | Recirculation System Failure Mode and Effect Analysis |
| 6.5-5 | List of Materials Used in the Standby Gas Treatment System |
| 6.5-6 | List of Materials Used in the Emergency Outside Air Supply System |
| 6.5-7 | Zone Volumes and Their Estimated Recirculation Airflow Rates |
| 6A-1(a) | Reactor Primary System Blowdown Flow Rates and Fluid Enthalpy-Recirculation Outlet Line Break |
| 6A-1(b) | Recirc. Outlet Line Break Blowdown Mass Flux Time History |
| 6A-1(c) | Reactor Primary System Blowdown Flow Rates and Fluid Enthalpy – Feedwater Line Break |
| 6A-1(d) | Feedwater Line Break Blowdown Mass Flux Time History |
| 6A-2 | Head Spray Line Break |
| 6A-3 | Susquehanna-Compartment Volumes Used in Reactor Vessel Shield Annulus Subcompartment Analysis |
| 6A-4 | Susquehanna-Flow Area and Coefficients Used in Reactor Vessel Shield Annulus Subcompartment Analysis |
| 6A-5 | Geometry Node Locations |
| 6A-6 | RPV Geometry Node Areas for Recirculation Outlet Line Break |
| 6A-7 | RPV Geometry Node Areas for Feedwater Line Break |
| 6A-8 | Reactor Primary System Blowdown Flow Rates And Fluid Enthalpy - Recirculation Outlet Line Break |

SUMMARY TABLE OF CONTENTS**Chapter 6 Figures**

| | |
|---------|---|
| 6.2-1 | Diagram of the Recirculation Line Break Location |
| 6.2-2 | Pressure Response for Recirculation Line Break |
| 6.2-3 | Temperature Response for Recirculation Line Break |
| 6.2-4 | Floor Differential Pressure For Recirculation Line Breaks |
| 6.2-5 | Vent Flow for Recirculation Line Break |
| 6.2-6 | Containment Pressure Response Long-Term |
| 6.2-7 | Drywell Temperature Response - Long-Term |
| 6.2-8 | Suppression Pool Temperature Response - Long-Term |
| 6.2-9 | RHR Heat Removal Rate |
| 6.2-11 | Pressure Response for Main Steamline Break |
| 6.2-12 | Temperature Response for Main Steamline Break |
| 6.2-16 | Schematic of ECCS Loop |
| 6.2-17 | Allowable Leakage Capacity |
| 6.2-18 | Vessel Blowdown Rate for Recirculation Line Break |
| 6.2-20 | Vessel Blowdown Rate for Main Steamline Break |
| 6.2-24 | Secondary Containment Boundary Outline – Unit 1 EL. 645'-0" |
| 6.2-25 | Secondary Containment Boundary Outline – Unit 1 EL. 670'-0" |
| 6.2-26 | Secondary Containment Boundary Outline – Unit 1 EL. 683'-0" |
| 6.2-27 | Secondary Containment Boundary Outline – Unit 1 EL. 719'-0" |
| 6.2-28 | Secondary Containment Boundary Outline – Unit 1 EL. 749'-1" |
| 6.2-29 | Secondary Containment Boundary Outline – Unit 1 EL. 779'-1" |
| 6.2-30 | Secondary Containment Boundary Outline – Unit 1 EL. 818'-1" |
| 6.2-31 | Secondary Containment Boundary Outline – Unit 1 Section A-A |
| 6.2-32 | Secondary Containment Boundary Outline – Unit 1 Section B-B |
| 6.2-33 | Secondary Containment Boundary Outline – Unit 1 EL. 799'-1" |
| 6.2-34 | Secondary Containment Boundary Outline – Unit 2 EL. 645'-0" |
| 6.2-35 | Secondary Containment Boundary Outline – Unit 2 EL. 670'-0" |
| 6.2-36 | Secondary Containment Boundary Outline – Unit 2 EL. 683'-0" |
| 6.2-37 | Secondary Containment Boundary Outline – Unit 2 EL. 719'-0" |
| 6.2-38 | Secondary Containment Boundary Outline – Unit 2 EL. 749'-1" |
| 6.2-39 | Secondary Containment Boundary Outline – Unit 2 EL. 779'-1" |
| 6.2-40 | Secondary Containment Boundary Outline – Unit 2 EL. 818'-1" |
| 6.2-41 | Secondary Containment Boundary Outline – Unit 2 Section A-A |
| 6.2-42 | Secondary Containment Boundary Outline – Unit 2 Section B-B |
| 6.2-43 | Secondary Containment Boundary Outline – Unit 2 EL. 799'-1" |
| 6.2-44 | Containment Penetration Details |
| 6.2-44A | Containment Penetration Details |
| 6.2-44B | Containment Penetration Details |
| 6.2-44C | Containment Penetration Details |
| 6.2-44D | Containment Penetration Details |
| 6.2-44E | Containment Penetration Details |
| 6.2-44F | Containment Penetration Details |
| 6.2-44g | Containment Penetration Details |
| 6.2-44H | Containment Penetration Details |
| 6.2-44i | Containment Penetration Details |
| 6.2-44J | Containment Penetration Details |
| 6.2-44K | Containment Penetration Details |

SUMMARY TABLE OF CONTENTS**Chapter 6 Figures**

| | |
|-----------|---|
| 6.2-44L | Containment Penetration Details |
| 6.2-44M | Containment Penetration Details |
| 6.2-46 | Energy Absorption Rate By the Coolant vs. Time After LOCA |
| 6.2-47 | Integrated Energy Absorbed By Coolant vs. Time After LOCA |
| 6.2-52 | Reactor Building Ventilation Recirculation and Standby Gas Treatment Systems Zone I and Zone III Isolation |
| 6.2-53 | Reactor Building Ventilation Recirculation and Standby Gas Treatment Systems Normal Plant Operation |
| 6.2-54 | Reactor Building Ventilation Recirculation and Standby Gas Treatment Systems Zone III Isolation |
| 6.2-55A | Figure replaced by Drawing M-157, Sh. 1 |
| 6.2-55B | Figure replaced by Drawing M-157, Sh. 2 |
| 6.2-55C | Figure replaced by Drawing M-157, Sh. 3 |
| 6.2-56 | Drywell to Wetwell Downcomers |
| 6.2-57-1 | Vacuum Breaker – DISC/ARM Assembly Unit 1 |
| 6.2-57-2 | Vacuum Breaker - DISC/ARM Assembly Unit 2 |
| 6.2-57a-1 | Containment Personnel Lock Door Penetrations |
| 6.2-57a-2 | Containment Personnel Lock Door Penetrations |
| 6.2-57a-3 | Containment Personnel Lock Penetrations |
| 6.2-58-1 | Containment Personnel Lock Door Seals |
| 6.2-58-2 | Containment Personnel Lock Door Seals |
| 6.2-59 | Personnel Lock Inner Door Tie Downs |
| 6.2-60 | Secondary Containment Pressure Transient Post-LOCA |
| 6.2-61 | Model for Inadvertent Spray Actuation |
| 6.2-62 | Thermal Heat Removal Efficiency of Containment Atmosphere Spray |
| 6.2-63 | Drywell Pressure Response For Inadvertent Spray Actuation |
| 6.2-64 | Drywell Temperature Response For Inadvertent Spray Actuation |
| 6.2-65 | Differential Pressure Experienced Across the Diaphragm Slab During Inadvertent Actuation of the Drywell Spray |
| 6.2-66B | RWCW Line Penetration |
| 6.2-66C | Suppression Pool Purification Line Penetration |
| 6.2-66F | Reactor Building Closed Cooling Water Line Penetration |
| 6.2-66G | Reactor Building Control Rod Drive Seismic Island |
| 6.2-66H | RBCCW Supply/Return lines at the Reactor Building to Turbine Building Interface |
| 6.2-67 | Figure replaced by Drawing M-159, Sh. 1 |
| 6.2-70 | Long-Term Energy Release Rate for a Recirculation Line Break |
| 6.2-72 | TIP Guide Tube Isolation Control |
| 6.3-1A | Figure replaced by Drawing M-155, Sh. 1 |
| 6.3-1B | Figure replaced by Drawing M-156, Sh. 1 |
| 6.3-2 | Figure replaced by Drawing M1-E41-4, Sh. 1 |
| 6.3-3A | High Pressure Coolant Injection Pump Speed Characteristics |
| 6.3-4 | Figure replaced by Drawing M-152, Sh. 1 |
| 6.3-5 | Figure replaced by Drawing M1-E21-15, Sh. 1 |
| 6.3-77 | Pump Characteristic Curves For HPCI Pumps |
| 6.3-79C | Low Pressure Core Spray Flow vs. Head Used in LOCA Analysis |
| 6.3-80C | RHR (LPCI) Flow vs. Head Characteristics Use in LOCA Analysis |

SUMMARY TABLE OF CONTENTS**Chapter 6 Figures**

| | |
|---------|---|
| 6.3-118 | Characteristic Curves for Core Spray Pump |
| 6.3-119 | Characteristic Curves for LPCI Pump |
| 6.3-120 | Speed Characteristic Curves for HPCI Pumps - Unit 1 |
| 6.3-121 | Speed Characteristic Curves for HPCI Pumps - Unit 2 |
| 6.3-201 | Limiting TLO Recirculation Line Break Upper Plenum Pressure (Lower) |
| 6.3-202 | Limiting TLO Recirculation Line Break Total Break Flow Rate |
| 6.3-203 | Limiting TLO Recirculation Line Break Core Inlet Flow Rate |
| 6.3-204 | Limiting TLO Recirculation Line Break Core Inlet Flow Rate |
| 6.3-205 | Limiting TLO Recirculation Line Break Broken Loop Jet Pump Drive Flow Rate |
| 6.3-206 | Limiting TLO Recirculation Line Break Ads Flow Rate |
| 6.3-207 | Limiting TLO Recirculation Line Break HPCI Flow Rate |
| 6.3-208 | Limiting TLO Recirculation Line Break LPCS Flow Rate |
| 6.3-209 | Limiting TLO Recirculation Line Break Intact Loop LPCI Flow Rate |
| 6.3-210 | Limiting TLO Recirculation Line Break Broken Loop LPCI Flow Rate |
| 6.3-211 | Limiting TLO Recirculation Line Break Upper Downcomer Mixture Level |
| 6.3-212 | Limiting TLO Recirculation Line Break Lower Downcomer Mixture Level |
| 6.3-213 | Limiting TLO Recirculation Line Break Lower Downcomer Liquid Mass |
| 6.3-214 | Limiting TLO Recirculation Line Break Upper Plenum Liquid Mass |
| 6.3-215 | Limiting TLO Recirculation Line Break Lower Plenum Liquid Mass |
| 6.3-216 | Limiting TLO Recirculation Line Break Hot Channel Inlet Flow Rate |
| 6.3-217 | Limiting TLO Recirculation Line Break Hot Channel Outlet Flow Rate |
| 6.3-218 | Limiting TLO Recirculation Line Break Hot Channel Coolant Temperature At The Limiting Node |
| 6.3-219 | Limiting TLO Recirculation Line Break Hot Channel Quality At The Limiting Node |
| 6.3-220 | Limiting TLO Recirculation Line Break Hot Channel Heat Transfer Coeff. at The Limiting Node |
| 6.3-221 | Limiting TLO Recirculation Line Break Cladding Temperatures |
| 6.4-1A | Control Structure Elevation |
| 6.4-1B | Control Structure Envelope Plan - El. 697'-0" and 714'-0" |
| 6.4-1C | Control Structure Envelope Control Room Floor Plan EL. 729'-0" Technical Support Center EL. 741'-1" |
| 6.4-1D | Control Structure Envelope Plan EL. 753'-0" & 771'-0" |
| 6.4-1E | Control Structure Envelope Plan EL. 783'-0" |
| 6.4-2 | Control Room Location Intake and Exhaust Location |
| 6A-1(a) | Reactor Shield Annulus Arrangement |
| 6A-1(b) | RPV Shield Wall and Pedestal |
| 6A-2 | RPV Shield Annulus Subcompartment Model Schematic |
| 6A-3a | Pressure Transient in Shield Annulus Following a Recirculation Line Break at the Nozzle Safe End |
| 6A-3b | Pressure Transient in Shield Annulus Following a Recirculation Line Break at the Nozzle Safe End |
| 6A-3c | Pressure Transient in Shield Annulus Following a Recirculation Line Break at the Nozzle Safe End |
| 6A-3d | Pressure Transient in Shield Annulus Following a Recirculation Line Break at the Nozzle Safe End |

SUMMARY TABLE OF CONTENTS**Chapter 6 Figures**

| | |
|-------|--|
| 6A-3e | Pressure Transient in Shield Annulus Following a Recirculation Line Break at the Nozzle Safe End |
| 6A-3f | Pressure Transient in Shield Annulus Following a Recirculation Line Break at the Nozzle Safe End |
| 6A-3g | Pressure Transient in Shield Annulus Following a Feedwater Line Break at the Nozzle Safe End |
| 6A-3h | Pressure Transient in Shield Annulus Following a Feedwater Line Break at the Nozzle Safe End |
| 6A-3i | Pressure Transient in Shield Annulus Following a Feedwater Line Break at the Nozzle Safe End |
| 6A-3j | Pressure Transient in Shield Annulus Following a Feedwater Line Break at the Nozzle Safe End |
| 6A-3k | Pressure Transient in Shield Annulus Following a Feedwater Line Break at the Nozzle Safe End |
| 6A-3l | Pressure Transient in Shield Annulus Following a Feedwater Line Break at the Nozzle Safe End |
| 6A-4 | Drywell Head Arrangement |
| 6A-5 | Head Spray Line Break Geometry |
| 6A-6 | Pressure Response in the Drywell Head For a Head Spray Line Break |
| 6A-7 | Force Transient on Reactor Pressure Vessel Following A Recirculation Line Break at the Nozzle Safe End |
| 6A-8 | Force Transient on Reactor Shield Wall Following A Recirculation Line Break at the Nozzle Safe End |
| 6A-9 | Resultant Force Transient on RPV Following a Feedwater Line Break at the Nozzle |
| 6A-10 | Resultant Force Transient on RPV Following a Feedwater Line Break at the Nozzle |
| 6B-1 | Basic FLUD Calculation Flowchart |

SUMMARY TABLE OF CONTENTS**Chapter 7****7.0 INSTRUMENTATION AND CONTROLS**

- 7.1 Introduction
 - 7.1.1 Identification of Safety-Related Systems
 - 7.1.2 Identification of Safety Criteria

- 7.2 Reactor Trip System-(Reactor Protection System)Instrumentation and Controls
 - 7.2.1 Description
 - 7.2.2 Analysis
 - 7.2.3 Alternate Rod Injection System
 - 7.2.4 ARI Analysis

- 7.3 Engineered Safety Feature Systems
 - 7.3.1 Description
 - 7.3.2 Analysis
 - 7.3.2a Analysis of ESFAS Supplied with the NSSS
 - 7.3.2b Analysis for Non-NSSS Systems

- 7.4 Systems Required for Safe Shutdown
 - 7.4.1 Description
 - 7.4.2 Analysis
 - 7.4.3 References

- 7.5 Safety Related Display Instrumentation (SRDI)
 - 7.5.1a Description
 - 7.5.1b Description of Non-NSSS Safety-Related Displays
 - 7.5.2a Analysis of NSSS Safety-Related Displays
 - 7.5.2b Analysis of Non-NSSS Safety-Related Display Instrumentation

- 7.6 All Other Instrumentation Systems Required for Safety
 - 7.6.1a Description
 - 7.6.1b Description
 - 7.6.2a Analysis for NSSS - Systems
 - 7.6.2b Analysis for Non-NSSS Systems
 - 7.6.3 References

- 7.7 Control Systems Not Required for Safety
 - 7.7.1 Description
 - 7.7.2 Analysis
 - 7.7.3 References

SUMMARY TABLE OF CONTENTS**Chapter 7 Tables**

| | |
|--------|--|
| 7.1-1 | Responsibility |
| 7.1-2 | Similarity to Licensed Reactors |
| 7.1-3 | Codes and Standards Applicability Matrix |
| 7.1-4 | Reactor Protection System Codes and Standards |
| 7.1-5 | Primary Containment and Reactor Vessel Isolation Control System Codes and Standards |
| 7.1-6 | High Pressure ECCS (HPCI, ADS A, ADS B Network) Codes and Standards |
| 7.1-7 | Low Pressure ECCS (CS, RHR Network) Codes and Standards |
| 7.1-8 | Process Radiation Monitoring Codes and Standards |
| 7.1-9 | Leak Detection System Codes and Standards |
| 7.1-10 | Reactor Protection System Sensor Suffix Letters and Division Allocation |
| 7.1-11 | Four Division Grouping for Neutron Monitoring System |
| 7.1-12 | Emergency Core Cooling System and RCIC Sensor Suffix Letters and Division Allocation |
| 7.2-1 | Reactor Protection System Instrumentation Specifications |
| 7.2-2 | Channels Required for Functional Performance of RPS |
| 7.2-3 | ATWS Recirculation Pump Trip and Alternate Rod Injection Instrumentation Specifications |
| 7.2-4 | Channels Required for Functional Performance of ARI |
| 7.3-1 | High Pressure Coolant Injection System-Instrument Specifications and Channels |
| 7.3-2 | Automatic Depressurization System-Instrument Specifications and Channels |
| 7.3-3 | Core Spray System-Instrument Specifications and Channels |
| 7.3-4 | Low Pressure Coolant Injection-Instrument Specification and Channels |
| 7.3-5 | Primary Containment and Reactor Vessel Isolation Control System Instrumentation Specifications |
| 7.3-13 | ESFAS Actuated Equipment Standby Gas Treatment System |
| 7.3-14 | ESFAS Actuated Equipment Recirculation System, Reactor Building Isolation Dampers, and Reactor Building Non-Safety Related Equipment |
| 7.3-15 | ESFAS Actuated Equipment Control Structure Emergency Outside Air Supply System |
| 7.3-16 | ESFAS Actuated Equipment Battery Rooms Exhaust System |
| 7.3-17 | General Notes for Tables 7.3-13 Through 7.3-16 |
| 7.3-18 | Standby Gas Treatment System (SGTS) Failure Mode and Effects Analysis |
| 7.3-19 | Reactor Building Recirculation System Failure Mode and Effects Analysis |
| 7.3-20 | Failure Mode and Effects Analysis Primary Containment Isolation Control System Fan Non-NSS Systems |
| 7.3-21 | Emergency Outside Air Supply System (EOASS) Failure Mode and Effects Analysis |
| 7.3-22 | Computer Room Cooling System (CRCS) Failure Mode and Effects Analysis |
| 7.3-23 | Control Structure H&V System (CSHVS) Failure Mode and Effects Analysis |
| 7.3-24 | Control Structure Chilled Water System (CSCWS) Failure Mode and Effects Analysis |
| 7.3-25 | Battery Rooms Exhaust System Failure Mode and Effects Analysis |
| 7.3-26 | Control Room Floor Cooling System (CRFCS) Failure Mode and Effects Analysis |
| 7.3-28 | Reactor Protection System Response Times |
| 7.3-29 | Isolation System Instrumentation Response Time |
| 7.3-30 | Emergency Core Cooling System Response Times |

SUMMARY TABLE OF CONTENTS**Chapter 7 Tables**

| | |
|--------|---|
| 7.4-2 | RHRS Shutdown Cooling Bypasses and Interlocks |
| 7.4-3 | Remote Shutdown Panel Instrumentation |
| 7.4-4 | Alternate Control Structure HVAC Control Panel |
| 7.5-1 | Safety Related Display Instrumentation |
| 7.5-2 | Safety Related Display Instrumentation-Habitability (Emergency Outside Air System/Control Structure HVAC) |
| 7.5-3 | Safety Related Display Instrumentation-Containment and Suppression Pool Instrumentation |
| 7.5-4 | Safety Related Display Instrumentation-Standby Gas Treatment System, RX Building Recirculation and Isolation System |
| 7.5-5 | Safety Related Display Instrumentation-Emergency Service Water System |
| 7.5-6 | Safety Related Display Instrumentation-RHR Service Water System and Spray Pond |
| 7.5-7 | Safety Related Display Instrumentation-Containment Instrument Gas System |
| 7.5-7a | Safety Related Display Instrumentation Standby Liquid Control System |
| 7.5-8 | Bypass Indication System for Non-NSSS Systems |
| 7.6-3 | IRM Trips |
| 7.6-4 | LPRM System Trips |
| 7.6-5 | APRM System Trips |
| 7.6-7 | OPRM System Trip |
| 7.6-9 | Suppression Pool Temperature Sensor Locations |
| 7.6-10 | End-of-Cycle Recirculation Pump Trip System Response Time |
| 7.7-1 | CRD Hydraulic System Process Indicators |
| 7.7-2 | Refueling Interlock Effectiveness |
| 7.7-3 | RBM System Trips |
| 7.7-4 | IRM Trips |

SUMMARY TABLE OF CONTENTS**Chapter 7 Figures**

| | |
|----------|---|
| 7.2-1-1 | Figure replaced by Drawing M1-C72-2, Sh. 1 |
| 7.2-1-2 | Figure replaced by Drawing M1-C72-2, Sh. 2 |
| 7.2-1-3 | Figure replaced by Drawing M1-C72-2, Sh. 3 |
| 7.2-1-4 | Figure replaced by Drawing M1-C72-2, Sh. 4 |
| 7.2-2 | Reactor Protection System Scram Functions |
| 7.2-3 | Arrangement of Channels and Logics |
| 7.2-4 | Actuators and Actuator Logics |
| 7.2-5 | Logic in One Trip System |
| 7.2-6 | Relationship Between Neutron Monitoring System and Reactor Protection System |
| 7.2-7 | Configuration for Turbine Stop Valve Closure Reactor Trip |
| 7.2-8 | Configuration for Main Steamline Isolation Reactor Trip |
| 7.2-9 | Block Diagram - RPS Protective Circuit – Electrical Protection Assembly (EPA) |
| 7.2-10 | ARI Trip System Logic |
| 7.3-2 | Isolation Control System for Main Steamline Isolation Valves |
| 7.3-3 | Isolation Control System Using Motor-Operated Valves |
| 7.3-4 | Main Steamline Isolation Valve Schematic |
| 7.3-5-1 | Initiation Logic – ADS, CS, RHR |
| 7.3-5-2 | ADS Initiation Logic |
| 7.3-5-3 | Unit 2 ADS Initiation Logic |
| 7.3-6 | Initiation Logic – HPCI, RCIC |
| 7.3-7-1 | Figure replaced by Drawing M1-E41-65, Sh. 1 |
| 7.3-7-2 | Figure replaced by Drawing M1-E41-65, Sh. 2 |
| 7.3-7-3 | Figure replaced by Drawing M1-E41-65, Sh. 3 |
| 7.3-7-4 | Figure replaced by Drawing M1-E41-65, Sh. 4 |
| 7.3-7-5 | Figure replaced by Drawing M1-E41-65, Sh. 5 |
| 7.3-8-1 | Figure replaced by Drawing M1-B21-92, Sh. 1 |
| 7.3-8-2 | Figure replaced by Drawing M1-B21-92, Sh. 2 |
| 7.3-8-3 | Figure replaced by Drawing M1-B21-92, Sh. 3 |
| 7.3-8-4 | Figure replaced by Drawing M1-B21-92, Sh. 4 |
| 7.3-8-5 | Figure replaced by Drawing M1-B21-92, Sh. 5 |
| 7.3-8-6 | Figure replaced by Drawing M1-B21-92, Sh. 6 |
| 7.3-9-1 | Figure replaced by Drawing M1-E21-3, Sh. 1 |
| 7.3-9-2 | Figure replaced by Drawing M1-E21-3, Sh. 2 |
| 7.3-9-3 | Figure replaced by Drawing M1-E21-3, Sh. 3 |
| 7.3-10-1 | Figure replaced by Drawing M1-E11-51, Sh. 1 |
| 7.3-10-2 | Figure replaced by Drawing M1-E11-51, Sh. 2 |
| 7.3-10-3 | Figure replaced by Drawing M1-E11-51, Sh. 3 |
| 7.3-10-4 | Figure replaced by Drawing M1-E11-51, Sh. 4 |
| 7.3-10-5 | Figure replaced by Drawing M1-E11-51, Sh. 5 |
| 7.3-11-1 | Figure replaced by Drawing M1-D12-1, Sh. 1 |
| 7.3-11-2 | Figure replaced by Drawing M1-D12-1, Sh. 2 |
| 7.3-11-3 | Figure replaced by Drawing M1-D12-1, Sh. 3 |
| 7.3-11-4 | Figure replaced by Drawing M1-D12-1, Sh. 4 |
| 7.3-11-5 | Figure replaced by Drawing M1-D12-1, Sh. 5 |
| 7.4-1 | Figure replaced by Drawing M-149, Sh. 1 & M-150, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 7 Figures**

| | |
|----------|--|
| 7.4-2-1 | Figure replaced by Drawing M1-E51-80, Sh. 1 |
| 7.4-2-2 | Figure replaced by Drawing M1-E51-80, Sh. 2 |
| 7.4-2-3 | Figure replaced by Drawing M1-E51-80, Sh. 3 |
| 7.4-2-4 | Figure replaced by Drawing M1-E51-80, Sh. 4 |
| 7.4-3 | Figure replaced by Drawing M-148, Sh. 1 |
| 7.4-4 | Figure replaced by Drawing M1-C41-31, Sh. 1 |
| 7.5-3 | Neutron Flux at Primary Shield |
| 7.6-1 | Recirculation Pump Leak Detection Block Diagram |
| 7.6-2 | RHR Area Temperature Monitoring System Block Diagram |
| 7.6-3 | Vessel Penetrations for Nuclear Instrumentation |
| 7.6-4-1 | Figure replaced by Drawing M1-C51-35, Sh. 1 |
| 7.6-4-2 | Figure replaced by Drawing M1-C51-35, Sh. 2 |
| 7.6-5 | SRM/IRM Neutron Monitoring Unit |
| 7.6-6 | Detector Drive System Schematic |
| 7.6-7-1 | Figure replaced by Drawing M1-C51-2, Sh. 1 |
| 7.6-7-2 | Figure replaced by Drawing M1-C51-2, Sh. 2 |
| 7.6-7-3 | Figure replaced by Drawing M1-C51-2, Sh. 3 |
| 7.6-7-4 | Figure replaced by Drawing M1-C51-2, Sh. 4 |
| 7.6-7-5 | Figure replaced by Drawing M1-C51-2, Sh. 5 |
| 7.6-7-6 | Figure replaced by Drawing M1-C51-2, Sh. 6 |
| 7.6-7-7 | Figure replaced by Drawing M1-C51-2, Sh. 7 |
| 7.6-8 | Functional Block Diagram of SRM Channel |
| 7.6-9 | Functional Block Diagram of IRM Channel |
| 7.6-10 | Power Range Monitor Detector Assembly Location |
| 7.6-11-1 | Refer to Figure 5.4-2A |
| 7.6-11-2 | Figure replaced by Drawing M1-B31-13, Sh. 2 |
| 7.6-11-3 | Figure replaced by Drawing M1-B31-13, Sh. 3 |
| 7.6-12 | APRM Circuit Arrangement for Reactor Protection System Input |
| 7.6-13 | Ranges of Neutron Monitoring System |
| 7.7-1 | Water Level Range Definition |
| 7.7-2-1 | Control Rod Drive Hydraulic System - FCD |
| 7.7-2-2 | Control Rod Drive Hydraulic System - FCD |
| 7.7-2-3 | Control Rod Drive Hydraulic System - FCD |
| 7.7-2-4 | Control Rod Drive Hydraulic System - FCD |
| 7.7-2-5 | Control Rod Drive Hydraulic System - FCD |
| 7.7-2-6 | Control Rod Drive Hydraulic System - FCD |
| 7.7-2-7 | Control Rod Drive Hydraulic System - FCD |
| 7.7-3-1 | Figure replaced by Drawing M1-C12-90, Sh. 4 |
| 7.7-3-2 | Figure replaced by Drawing M1-C12-110, Sh. 8 |
| 7.7-4 | Reactor Manual Control System Operation |
| 7.7-5 | Reactor Manual Control Self-Test Provisions |
| 7.7-6 | Eleven-Wire Position Probe |
| 7.7-7-1 | Figure replaced by Drawing M1-B31-189, Sh. 1 |
| 7.7-7-2 | Figure replaced by Drawing M1-B31-189, Sh. 2 |

SUMMARY TABLE OF CONTENTS**Chapter 7 Figures**

| | |
|---------|---|
| 7.7-7-3 | Figure replaced by Drawing M1-B31-189, Sh. 3 |
| 7.7-7-4 | Figure replaced by Drawing M1-B31-189, Sh. 4 |
| 7.7-7-5 | Figure replaced by Drawing M1-B31-189, Sh. 5 |
| 7.7-7-6 | ATWS Recirculation Pump Trip Logic |
| 7.7-8 | Recirculation Flow Control Illustration |
| 7.7-9 | Figure replaced by Drawing M1-C32-3, Sh. 1 |
| 7.7-10 | Detector Drive System Schematic |
| 7.7-11 | Figure replaced by Drawing M1-G33-143, Sh. 1 |
| 7.7-13 | Figure replaced by Drawing A-105, Sh. 1 |
| 7.7-13a | Control room Panel Safety Related Display Instr. Plant Operator Interface |
| 7.7-14 | Traversing In-Core Probe Assembly |
| 7.7-15 | Main Turbine Control System Block Diagram |
| 7.7-16 | Assignment of LPRM Input to RBM System |
| 7.7-19 | Unit 2, Typical RBM Channel Responses, Old Versus New LPRM Assignment (No Failed LPRMS) |

SUMMARY TABLE OF CONTENTS

Chapter 8

8.0 ELECTRIC POWER

- 8.1 Introduction
 - 8.1.1 General
 - 8.1.2 Utility Power Grid and Offsite Power Systems
 - 8.1.3 Onsite Power Systems
 - 8.1.4 Safety Related Loads
 - 8.1.5 Design Bases
 - 8.1.6 Regulatory Guides and IEEE Standards

- 8.2 Offsite Power System
 - 8.2.1 Description
 - 8.2.2 Analysis

- 8.2A Reliability Principles and Standards for Planning Bulk Electric Supply System of MAAC Group

- 8.3 Onsite Power Systems
 - 8.3.1 AC Power Systems
 - 8.3.2 DC Power Systems
 - 8.3.3 Fire Protection for Cable Systems

SUMMARY TABLE OF CONTENTS**Chapter 8 Tables**

| | |
|--------|---|
| 8.1-1 | Motor Operated Valves With Thermal Overload Continuously Bypassed During Plant Operation |
| 8.1-2 | Affiliated and Non-Class 1E Circuits That Connect to Class 1E Power Supplies |
| 8.1-3 | Non-Class 1E Annunciator and Computer Interface Devices |
| 8.1-4 | Divisional or Affiliated Loads Supplied From Class 1E Channel C or D 4.16 kV Buss |
| 8.1-5 | Containment Radiation Monitors Supplied from Class 1E System |
| 8.2-1 | Susquehanna Unit #1 & #2 Stability Case List (Summer Light Load Conditions) |
| 8.3-1 | Assignment of ESF and Selected Non-ESF Loads to Diesel Generators and ESS Buses |
| 8.3-1a | Diesel Generator Loading (Note 1), Diesel Generators A, B, C and D In Service, Unit - Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-1b | Supplement to Table 8.3-1 |
| 8.3-1c | Diesel Generator E Loading, Diesel Generator E In Service for A or B or C or D, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-2 | Diesel Generator Loading, Diesel A Unavailable, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-2a | Diesel Generator E Loading, Diesel A Unavailable, Diesel Generator E Substituted for Diesel B or C or D, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-3 | Diesel Generator Loading, Diesel B Unavailable, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-3a | Diesel Generator Loading E, Diesel B Unavailable, Diesel Generator E Substituted for Diesel A or C or D, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-4 | Diesel Generator Loading, Diesel C Unavailable, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-4a | Diesel Generator E Loading, Diesel C Unavailable, Diesel Generator E Substituted for Diesel A or B or D, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-5 | Diesel Generator Loading, Diesel D Unavailable, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-5a | Diesel Generator E Loading, Diesel D Unavailable, Diesel Generator E Substituted for Diesel A or B or C, Unit 1-Design Basis Accident; Unit 2-Forced Shutdown |
| 8.3-6A | 125 Volt DC Load Cycle 1D610 |
| 8.3-6B | 125 Volt DC Load Cycle 1D620 |
| 8.3-6C | 125 Volt DC Load Cycle 1D630 |
| 8.3-6D | 125 Volt DC Load Cycle 1D640 |
| 8.3-6E | 125 Volt DC Load Cycle 2D610 |
| 8.3-6F | 125 Volt DC Load Cycle 2D620 |
| 8.3-6G | 125 Volt DC Load Cycle 2D630 |
| 8.3-6H | 125 Volt DC Load Cycle 2D640 |
| 8.3-6I | 125 Volt DC Load Cycle Channel H 0D597 |
| 8.3-6J | 125V DC Battery Duty Load Profiles |
| 8.3-7A | Unit 1 250V DC Load Cycle Div. I (1D650) |
| 8.3-7B | Unit 1 250V DC Load Cycle Div. II (1D660) |
| 8.3-7C | Unit 2 250V DC Load Cycle Div. I (2D650) |
| 8.3-7D | Unit 2 250V DC Load Cycle Div. II (2D660) |
| 8.3-7E | 250V DC Battery Duty Load Profiles |

SUMMARY TABLE OF CONTENTS**Chapter 8 Tables**

| | |
|--------|--|
| 8.3-7F | Unit 1 250V DC Load Cycl Div I (1D650) SBO Profile |
| 8.3-7G | Unit 1 250V DC Load Cycl Div II (1D660) SBO Profile |
| 8.3-7H | Unit 2 250V DC Load Cycl Div I (2D650) SBO Profile |
| 8.3-7I | Unit 2 250V DC Load Cycl Div II (2D660) SBO Profile |
| 8.3-8 | ±24 Volt DC Load Cycle |
| 8.3-9 | AC Power Failure Mode Effects Analysis |
| 8.3-10 | Routing Table |
| 8.3-16 | Diesel Generator Auto Start Circuit Failure Effects Analysis (1) |
| 8.3-17 | 125V DC Control Power Source for Non-Class 1E 13.8 kV and 4.16 kV Switchgear |
| 8.3-18 | 125V DC Control Power Source For Non-Class 1E 480V L.C. |
| 8.3-19 | 125V DC Control Power Source For Class 1E 4.16 kV Switchgear |
| 8.3-20 | 125V DC Control Power Source For Class 1E 480V LC |
| 8.3-21 | Failure Mode and Effect Analysis-125V DC System (4 Channels) |
| 8.3-22 | Failure Mode and Effect Analysis-250V DC System (2 Divisions) |
| 8.3-23 | Failure Mode and Effect Analysis-24V DC System (2 Divisions) |
| 8.3-24 | Common Mode-Common Cause Failure Analysis-Auto Transfer Switch Separation Methods and Requirements Within Junction Boxes and Field Installed Pull Boxes |
| 8.3-25 | Separation Methods and Requirements Within Junction Boxes and Field Installed Pull Boxes |

SUMMARY TABLE OF CONTENTS**Chapter 8 Figures**

| | |
|----------|--|
| 8.2-1 | Figure replaced by Drawing D159760, Sh. 1 |
| 8.2-2 | Figure replaced by Drawing D159760, Sh. 2 |
| 8.2-3 | Figure replaced by Drawing D159760, Sh. 3 |
| 8.2-4 | Figure replaced by Drawing D159760, Sh. 4 |
| 8.3-1-1 | Figure replaced by Drawing E-1, Sh. 1 |
| 8.3-1-2 | Figure replaced by Drawing E-1, Sh. 1A |
| 8.3-1-2a | Figure replaced by Drawing E-1, Sh. 2 |
| 8.3-2 | Figure replaced by Drawing E-4, Sh. 2 |
| 8.3-2A | Preferred Power Supplies to Diesel Generator E Class 1E Power System |
| 8.3-3 | Figure replaced by Drawing E-5, Sh. 1 |
| 8.3-4 | Figure replaced by Drawing E-5, Sh. 2 |
| 8.3-4A | Figure replaced by Drawing E-5, Sh. 5 |
| 8.3-5 | Figure replaced by Drawing E-11, Sh. 1 |
| 8.3-5A | Figure replaced by Drawing E-11, Sh. 11 |
| 8.3-6 | Figure replaced by Drawing E-13, Sh. 1 |
| 8.3-7 | Figure replaced by Drawing E-8, Sh. 4 |
| 8.3-8 | Figure replaced by Drawing E-8, Sh. 8 |
| 8.3-9 | 480 Volt Swing Buses |
| 8.3-10 | Figure replaced by Drawing M-260, Sh. 1 |
| 8.3-10A | Figure replaced by Drawing M-261, Sh. 1 |
| 8.3-10B | Figure replaced by Drawing M-5200, Sh. 1 |
| 8.3-11 | Figure replaced by Drawing E-31, Sh. 8 |
| 8.3-12 | Figure replaced by Drawing E-31, Sh. 9 |
| 8.3-13 | Single Line Diagram for 480 Volt Swing Bus System |
| 8.3-14 | Swing Bus Auto Trans for Switch Control Schematic |
| 8.3-15 | Figure replaced by Drawing E-31, Sh. 5 |

SUMMARY TABLE OF CONTENTS**Chapter 9****9.0 AUXILIARY SYSTEMS**

- 9.1 Fuel Storage and Handling
 - 9.1.1 New Fuel Storage
 - 9.1.2 Spent Fuel Storage
 - 9.1.3 Spent Fuel Pool Cooling and Cleanup System
 - 9.1.4 Fuel Handling System and Reactor Servicing Equipment
 - 9.1.5 Reactor Building Cranes
 - 9.1.6 References

- 9.2 Water Systems
 - 9.2.1 Service Water System
 - 9.2.2 Reactor Building Closed Cooling Water System
 - 9.2.3 Turbine Building Closed Cooling Water System
 - 9.2.4 Gaseous Radwaste Recombiner Closed Cooling Water System
 - 9.2.5 Emergency Service Water System
 - 9.2.6 RHR Service Water System
 - 9.2.7 Ultimate Heat Sink
 - 9.2.8 Raw Water Treatment System
 - 9.2.9 Makeup Demineralizer System
 - 9.2.10 Condensate Storage and Transfer System
 - 9.2.11 Potable Water and Sanitary Water Systems
 - 9.2.12 Chilled Water Systems
 - 9.2.13 References

- 9.3 Process Auxiliaries
 - 9.3.1 Compressed Air Systems
 - 9.3.2 Process Sampling System
 - 9.3.3 Equipment and Floor Drainage System
 - 9.3.4 Chemical and Volume Control System
 - 9.3.5 Standby Liquid Control System

- 9.4 Air Conditioning, Heating, Cooling and Ventilation Systems
 - 9.4.1 Control Room and Control Structure HVAC Systems
 - 9.4.2 Reactor Building Ventilation System
 - 9.4.3 Radwaste Building Ventilation System
 - 9.4.4 Turbine Building Ventilation System
 - 9.4.5 Primary Containment Atmosphere Recirculation and Cooling System
 - 9.4.6 Refueling and Spent Fuel Area Ventilation System
 - 9.4.7 Diesel Generator Buildings Ventilation System
 - 9.4.8 Engineered Safeguard Service Water Pumphouse Ventilation System
 - 9.4.9 Circulating Water Pumphouse and Water Treatment Building HVAC

- 9.5 Other Auxiliary Systems
 - 9.5.1 Fire Protection System
 - 9.5.2 Communication Systems
 - 9.5.3 Lighting System

SUMMARY TABLE OF CONTENTS

Chapter 9

| | |
|--------|--|
| 9.5.4 | Diesel Generator Fuel Oil Storage and Transfer System |
| 9.5.5 | Diesel Generator Cooling Water System |
| 9.5.6 | Diesel Generator Starting System |
| 9.5.7 | Diesel Generator Lubrication System |
| 9.5.8 | Diesel Generator Combustion Air Intake and Exhaust System |
| 9.5-9 | Hydrogen Water Chemistry (HWC) System |
| 9.5-10 | Passive Zinc Injection System |
| 9.5-11 | References |
| 9A | Analysis for Non-Seismic Spent Fuel Pool Cooling Systems |
| 9B | Compliance with NRC Branch Technical Position ASB 9-1 Susquehanna Steam Electric Station Unit 1 Reactor Building Crane |

SUMMARY TABLE OF CONTENTS**Chapter 9 Tables**

| | |
|---------|---|
| 9.1-1 | Spent Fuel Pool Cooling and Cleanup System Component Description |
| 9.1-2 | Fuel Servicing Equipment Classification |
| 9.1-2a | Original Design Basis - Decay Heat Output Under Normal Fuel Storage Conditions |
| 9.1-2b | Original Design Basis - Decay Heat Output Under Normal Fuel Storage Conditions |
| 9.1-2c | Original Design Basis - Decay Heat Output Under Full Core Unload Conditions |
| 9.1-2d | Original Design Basis - Decay Heat Output Under Full Core Unload Conditions |
| 9.1-2e | Updated Design Basis - Decay Heat Output Under Normal Fuel Storage Conditions |
| 9.1-2f | Updated Design Basis - Decay Heat Output Under Full Core Unload Conditions |
| 9.1-3 | Reactor Vessel Servicing Equipment Classification |
| 9.1-4 | Under-Reactor Vessel Servicing Equipment and Tools Classification |
| 9.1-5 | Tools and Services Equipment |
| 9.1-6a | Unit 1 Reactor Building Crane Failure Modes and Effect Analysis |
| 9.1-6b | Unit 2 Reactor Building Crane Failure Modes and Effect Analysis |
| 9.1-7a | Load Combinations & Factored Allowable Stress Limits |
| 9.1-7b | Load Definitions |
| 9.2-1 | List of Coolers Supplied Cooling Water by the Service Water System |
| 9.2-3 | Definition of ESW Flows for Units 1 & 2 |
| 9.2-4 | ESW Cooling Duty Following DBA for Minimum Heat Transfer Case (Loss of Auxiliary Power Followed by a Single Unit LOCA) |
| 9.2-5 | ESW Cooling Duty Following DBA for Maximum Water Loss Case (Loss of All Auxiliary Power Followed by a Single Unit LOCA) |
| 9.2-6 | Ultimate Heat Sink Components |
| 9.2-7 | Spray Pond Design Data |
| 9.2-8 | Susquehanna Pond Water Allowances |
| 9.2-9 | Minimum Heat Transfer Meteorology - Site Data First of the Two Worst Consecutive Days - August 2, 1975 |
| 9.2-10 | Maximum Water Loss Meteorology Avoca Airport Data - Hourly Average Data For Worst 30 Days - March 6, 1951 Through April 4, 1951 |
| 9.2-12 | Summary of Peak Temperature Values and Final Pond Water Inventory |
| 9.2-13 | Condensate and Refueling Water Storage Flow Paths |
| 9.2-14 | Control Structure Chilled Water System Design Data |
| 9.2-15 | Control Structure Chilled Water Systems Failure Mode and Effect Analysis |
| 9.2-16 | Turbine Building Chilled Water System Design Data |
| 9.2-17 | Reactor Building Chilled Water System Design Data |
| 9.2-18 | Radwaste Building Chilled Water System Design Data |
| 9.2-19 | Decay Heat Generation Branch Technical Position ASB 9-2 for One Core |
| 9.2-20 | Emergency Service Water System Heat Loads (Both Units) ($\times 10^6$ BTU/HR) |
| 9.2-21 | RHR and RHR Service Water System Flow Rates (GPM) Minimum Heat Transfer Case |
| 9.2-21a | RHR and RHR Service Water System Flow Rates (GPM) Maximum Heat Transfer Case |
| 9.2-22 | Emergency Service Water System Flow Rates (GPM) |
| 9.2-23 | Initial Conditions |
| 9.2-27 | Size Comparison of Spray Ponds Investigated |
| 9.2-28 | Performance Comparison of CANADYS Station and Model Results |
| 9.2-29 | Performance Comparison of RANCHO SECO Test Results and Model Results |

SUMMARY TABLE OF CONTENTS**Chapter 9 Tables**

| | |
|---------|---|
| 9.3-1 | Instrument Air System Design Parameters (Typical for Units 1 & 2) |
| 9.3-2 | Instrument Air System Pneumatically Operated Valves Which Have a Safety Function |
| 9.3-3 | Instrument Air Compressors Failure Mode and Effect Analysis |
| 9.3-4 | Service Air System Design Parameters (Typical for Units 1 & 2) |
| 9.3-5 | Low Pressure Air System Design Parameters (Common to Units 1 & 2) |
| 9.3-6 | River Intake Structure Compressed Air System Design Parameters (Common for Units 1 & 2) |
| 9.3-7 | List of Instrument Gas Operated Devices |
| 9.3-8 | Containment Instrument Gas System Design Parameters (Typical for Units 1 & 2) |
| 9.3-9 | Containment Instrument Gas System Failure Mode and Effect Analysis |
| 9.3-10 | Equipment and Floor Drainage System Component Description |
| 9.3-11 | Standby Liquid Control System Operating Pressure/Temperature Conditions |
| 9.4-1 | Ventilation Systems Tests and Inspections |
| 9.4-2 | Control Structure HVAC Systems Design Parameters |
| 9.4-3 | Reactor Building HVAC Systems Design Parameters |
| 9.4-4 | Reactor Building - Safety Related and RCIC Air Cooling System Design Parameters |
| 9.4-5 | Reactor Building HVAC Systems Failure Mode and Effect Analysis |
| 9.4-6 | Radwaste Building HVAC Systems Design Parameters |
| 9.4-7 | Turbine Building HVAC Systems Design Parameters |
| 9.4-8 | Unit 1 and 2 Primary Containment Unit Coolers and Ventilation Fans' Design Parameters |
| 9.4-9 | Drywell Unit Coolers' and Recirculation Fans' Operating Modes |
| 9.4-10 | Primary Containment Atmosphere Recirculation and Cooling System Failure Mode and Effect Analysis |
| 9.4-11 | Diesel Generator A, B, C and D Building HVAC Systems Design Parameters |
| 9.4-11A | Diesel Generator 'E' Building HVAC System Design Parameters |
| 9.4-11B | Diesel Generator 'E' Building Ventilation System Design Temperature Parameters |
| 9.4-12 | Diesel Generator Building H&V Failure Mode and Effect Analysis |
| 9.4-13 | ESSW Pumphouse HVAC Systems Design Parameters |
| 9.4-14 | Engineered Safeguard Service Water Pumphouse H&V Systems Failure Mode and Effect Analysis |
| 9.4-15 | Circulating Water Pumphouse HVAC Systems Design Parameters |
| 9.4-16 | Control Room and Control Structure HVAC Systems Control Room Floor Cooling Systems Failure Mode and Effect Analysis |
| 9.4-17 | Control Room and Control Structure HVAC Systems Computer Room Floor Cooling Systems Failure Mode and Effect Analysis |
| 9.4-18 | Control Room and Control Structure HVAC Systems Control Structure H&V Systems Failure Mode and Effect Analysis |
| 9.4-19 | Control Room and Control Structure HVAC Systems Emergency Outside Air Supply Systems Failure Mode and Effect Analysis |
| 9.4-20 | Control Room and Control Structure HVAC Systems SGTS Equipment Room H&V Systems Failure Mode and Effect Analysis |
| 9.4-21 | Control Room and Control Structure HVAC Systems Battery Room Exhaust Systems Failure Mode and Effect Analysis |

SUMMARY TABLE OF CONTENTS

Chapter 9 Tables

| | |
|-------|---|
| 9.5-3 | Emergency Lighting System in Susquehanna SES |
| 9.5-4 | Communication Systems |
| 9A-1 | Results of Boiling Spent Fuel Pool Analysis |
| 9B-1 | Comparison of Unit 1 Reactor Building Crane Design with BTP ASB 9-1 |

SUMMARY TABLE OF CONTENTS**Chapter 9 Figures**

| | |
|----------|---|
| 9.1-1 | New Fuel Storage |
| 9.1-2 | New Fuel Vault Cover Details |
| 9.1-3 | Spent Fuel Rack Isometric |
| 9.1-4 | Spent Fuel Rack Arrangement |
| 9.1-5 | Spent Fuel Rack Detail |
| 9.1-6 | Reference Case Fuel Storage Poison Can |
| 9.1-7-1 | Figure replaced by Drawing M-153, Sh. 1 |
| 9.1-7-2 | Figure replaced by Drawing M-153, Sh. 2 |
| 9.1-8 | Figure replaced by Drawing M-154, Sh. 1 |
| 9.1-9 | Fuel Preparation Machine |
| 9.1-10 | New Fuel Inspection Stand |
| 9.1-11 | Channel Bolt Wrench |
| 9.1-12 | Channel Handling Tool |
| 9.1-13 | Fuel Pool Sipper |
| 9.1-14 | Fuel Inspection Fixture |
| 9.1-15 | Channel Gauging Fixture |
| 9.1-16 | General Purpose Grapple |
| 9.1-18 | Figure replaced by Drawing C-1807, Sh. 1 |
| 9.1-19 | Figure replaced by Drawing C-1807, Sh. 2 |
| 9.1-20 | Simplified Section of New Fuel Handling Facilities (Section X-X, Figure 9.1-18) |
| 9.1-21 | Simplified Section of Refueling Facilities (Section Y-Y, Figure 9.1-18) |
| 9.1-22 | Simplified Section of Fuel Shipping Facilities (Section Z-Z, Figure 9.1-19) |
| 9.1-23 | Unit 2 Refueling Mast and Grapple Outline |
| 9.1-23-1 | Unit 1 Refueling Mast and Grapple Outline |
| 9.1-24 | Fuel Transfer Stand |
| 9.1-25 | Air Operated General Purpose Grapple BWR 6 |
| 9.1-26 | New Fuel Channel Up Ender |
| 9.1-27 | New Fuel Up Ending Stand |
| 9.1-28 | New Fuel Inspection Equipment General Arrangement |
| 9.2-1A-1 | Figure replaced by Drawing M-109, Sh. 1 |
| 9.2.1A-2 | Figure replaced by Drawing M-109, Sh. 2 |
| 9.2.1A-3 | Figure replaced by Drawing M-109, Sh. 3 |
| 9.2-1B | Figure replaced by Drawing M-110, Sh. 1 |
| 9.2-1C | Figure replaced by Drawing M-2110, Sh. 1 |
| 9.2-2 | Figure replaced by Drawing M-113, Sh. 1 |
| 9.2-3 | Figure replaced by Drawing M-114, Sh. 1 |
| 9.2-4 | Figure replaced by Drawing M-131, Sh. 1 |
| 9.2-5a | Figure replaced by Drawing M-111, Sh. 1 |
| 9.2-5b | Figure replaced by Drawing M-111, Sh. 2 |
| 9.2-5c | Figure replaced by Drawing M-111, Sh. 3 |
| 9.2-5d | Figure replaced by Drawing M-111, Sh. 4 |
| 9.2-6 | Figure replaced by Drawing M-112, Sh. 1 |
| 9.2-7-1 | Figure replaced by Drawing M-117, Sh. 1 |
| 9.2-7-2 | Figure replaced by Drawing M-117, Sh. 2 |
| 9.2-7-3 | Figure replaced by Drawing M-117, Sh. 3 |
| 9.2-7-4 | Figure replaced by Drawing M-117, Sh. 4 |

SUMMARY TABLE OF CONTENTS**Chapter 9 Figures**

| | |
|----------|---|
| 9.2-7-5 | Figure replaced by Drawing M-117, Sh. 5 |
| 9.2-8-1 | Figure replaced by Drawing M-118, Sh. 1 |
| 9.2-8-2 | Figure replaced by Drawing M-118, Sh. 2 |
| 9.2-8-3 | Figure replaced by Drawing M-118, Sh. 3 |
| 9.2-9 | Figure replaced by Drawing M-108, Sh. 1 |
| 9.2-10 | Sewage Treatment Plant Flowsheet |
| 9.2-11-1 | Figure replaced by Drawing M-186, Sh. 1 |
| 9.2-11-2 | Figure replaced by Drawing M-186, Sh. 3 |
| 9.2-12 | Figure replaced by Drawing M-188, Sh. 1 |
| 9.2-13a | Figure replaced by Drawing M-187, Sh. 1 |
| 9.2-13b | Figure replaced by Drawing M-187, Sh. 2 |
| 9.2-14-1 | Figure replaced by Drawing M-189, Sh. 1 |
| 9.2-14-2 | Figure replaced by Drawing M-189, Sh. 2 |
| 9.2-14-3 | Figure replaced by Drawing M-189, Sh. 3 |
| 9.2-14-4 | Figure replaced by Drawing M-189, Sh. 4 |
| 9.2-15 | Drift Loss vs. Wind Speed |
| 9.2-16 | Drift Loss vs. Perimeter Distance |
| 9.2-17 | Spray Pond Incremental Mass and Energy Flow Schematic |
| 9.2-18 | Spray Pond Droplet Trajectory Parameters |
| 9.2-21 | Spray Pond Temperature Transient Minimum Heat Transfer Case |
| 9.2-22 | Spray Pond Water Inventory Maximum Water Loss Case |
| 9.2-23 | Spray Pond Spray Nozzle |
| 9.2-24-1 | Spray Pond Plan |
| 9.2-24-2 | ESSW Spray Pond Network A1 & B1 Plan, Section & Details |
| 9.2-24-3 | ESSW Spray Pond Network A2 & B2 Plan, Section & Details |
| 9.3-1 | Figure replaced by Drawing M-125, Sh. 1 |
| 9.3-2 | Figure replaced by Drawing M-125, Sh. 2 |
| 9.3-2A | Figure replaced by Drawing M-125, Sh. 6 |
| 9.3-3 | Figure replaced by Drawing M-125, Sh. 30 |
| 9.3-3-4 | Figure replaced by Drawing M-2125, Sh. 16 |
| 9.3-4 | Figure replaced by Drawing M-125, Sh. 5 |
| 9.3-5-1 | Figure replaced by Drawing M-126, Sh. 1 |
| 9.3-5-2 | Figure replaced by Drawing M-126, Sh. 2 |
| 9.3-6-1 | Figure replaced by Drawing M-123, Sh. 1 |
| 9.3-6-2 | Figure replaced by Drawing M-123, Sh. 2 |
| 9.3-6-3 | Figure replaced by Drawing M-123, Sh. 3 |
| 9.3-6-4 | Figure replaced by Drawing M-123, Sh. 4 |
| 9.3-6-5 | Figure replaced by Drawing M-123, Sh. 5 |
| 9.3-6-6 | Figure replaced by Drawing M-123, Sh. 6 |
| 9.3-6-7 | Figure replaced by Drawing M-123, Sh. 7 |
| 9.3-6-8 | Figure replaced by Drawing M-123, Sh. 8 |
| 9.3-6-9 | Figure replaced by Drawing M-123, Sh. 9 |
| 9.3-6-9A | Figure replaced by Drawing M-123, Sh. 12 |
| 9.3-6-10 | Figure replaced by Drawing M-123, Sh. 10 |
| 9.3-6-11 | Figure replaced by Drawing M-123, Sh. 11 |
| 9.3-6-12 | Figure replaced by Drawing M-123, Sh. 13 |

SUMMARY TABLE OF CONTENTS**Chapter 9 Figures**

| | |
|-----------|---|
| 9.3-10-1 | Figure replaced by Drawing M-161, Sh. 1 |
| 9.3-10-2 | Figure replaced by Drawing M-161, Sh. 2 |
| 9.3-10-3 | Figure replaced by Drawing M-161, Sh. 3 |
| 9.3-12 | Figure replaced by Drawing M-160, Sh. 1 |
| 9.3-12A | Figure replaced by Drawing M-160, Sh. 2 |
| 9.3-14 | Sodium Pentaborate Volume-Concentration Requirements |
| 9.3-15 | Saturation Temperature of Sodium Pentaborate Solution |
| | |
| 9.4-1-1 | Figure replaced by Drawing M-178, Sh. 1 |
| 9.4-1-2 | Figure replaced by Drawing M-178, Sh. 2 |
| 9.4-2-1 | Figure replaced by Drawing VC-178, Sh. 1 |
| 9.4-2-2 | Figure replaced by Drawing VC-178, Sh. 2 |
| 9.4-2-3 | Figure replaced by Drawing VC-178, Sh. 3 |
| 9.4-2-4 | Figure replaced by Drawing VC-178, Sh. 4 |
| 9.4-4a | Figure replaced by Drawing M-176, Sh. 1 |
| 9.4-4b | Figure replaced by Drawing M-2176, Sh. 1 |
| 9.4-5a | Figure replaced by Drawing M-175, Sh. 1 |
| 9.4-5b | Figure replaced by Drawing M-175, Sh. 2 |
| 9.4-5c | Figure replaced by Drawing M-2175, Sh. 1 |
| 9.4-6a | Figure replaced by Drawing VC-176, Sh. 1 |
| 9.4-6b | Figure replaced by Drawing VC-2176, Sh. 1 |
| 9.4-7 | Figure replaced by Drawing VC-175, Sh. 1 |
| 9.4-8 | Figure replaced by Drawing VC-175, Sh. 2 |
| 9.4-9 | Figure replaced by Drawing VC-175, Sh. 3 |
| 9.4-10 | Figure replaced by Drawing M-179, Sh. 1 |
| 9.4-11 | Figure replaced by Drawing M-179, Sh. 2 |
| 9.4-12 | Figure replaced by Drawing VC-179, Sh. 1 |
| 9.4-13a | Figure replaced by Drawing M-174, Sh. 1 |
| 9.4-13b | Figure replaced by Drawing M-174, Sh. 2 |
| 9.4-14 | Figure replaced by Drawing VC-174, Sh. 1 |
| 9.4-15 | Figure replaced by Drawing M-177, Sh. 1 |
| 9.4-16a-1 | Figure replaced by Drawing VC-177, Sh. 1 |
| 9.4-16a-2 | Figure replaced by Drawing VC-177, Sh. 2 |
| 9.4-17 | Exhaust Registers Refueling Floor |
| 9.4-18 | Figure replaced by Drawing VC-182, Sh. 1 |
| 9.4-18A | Figure replaced by Drawing V-182, Sh. 8 |
| 9.4-18B | Figure replaced by Drawing V-182, Sh. 8A |
| 9.4-19 | Figure replaced by Drawing M-182, Sh. 1 |
| 9.4-19A | Figure replaced by Drawing M-182, Sh. 2 |
| 9.4-20 | Figure replaced by Drawing M-173, Sh. 1 |
| 9.4-21 | Figure replaced by Drawing VC-173, Sh. 1 |
| 9.4-22-1 | Figure replaced by Drawing V-26-2, Sh. 1 |
| 9.4-22-2 | Figure replaced by Drawing V-26-3, Sh. 1 |
| 9.4-22-3 | Figure replaced by Drawing V-26-4, Sh. 1 |
| 9.4-22-4 | Figure replaced by Drawing V-26-5, Sh. 1 |
| 9.4-22-5 | Figure replaced by Drawing V-26-6, Sh. 1 |
| 9.4-22-6 | Figure replaced by Drawing V-26-10, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 9 Figures**

| | |
|-----------|--|
| 9.4-22-7 | Figure replaced by Drawing V-26-11, Sh. 1 |
| 9.4-22-8 | Figure replaced by Drawing V-26-12, Sh. 1 |
| 9.4-22-9 | Figure replaced by Drawing V-26-13, Sh. 1 |
| 9.4-22-10 | Figure replaced by Drawing V-26-14, Sh. 1 |
| 9.4-22-11 | Figure replaced by Drawing V-26-15, Sh. 1 |
| 9.4-22-12 | Figure replaced by Drawing V-34-2, Sh. 1 |
| 9.4-22-13 | Figure replaced by Drawing V-34-3, Sh. 1 |
| 9.5-13 | Figure replaced by Drawing E-408, Sh. 1 |
| 9.5-14 | Figure replaced by Drawing E-408, Sh. 2 |
| 9.5-15 | Figure replaced by Drawing E-409, Sh. 1 |
| 9.5-16 | Figure replaced by Drawing E-409, Sh. 2 |
| 9.5-16A | Figure replaced by Drawing E-409, Sh. 3 |
| 9.5-16B | Figure replaced by Drawing E-409, Sh. 4 |
| 9.5-16C | Figure replaced by Drawing E-409, Sh. 5 |
| 9.5-16D | Figure replaced by Drawing E-409, Sh. 6 |
| 9.5-16E | Figure replaced by Drawing E-409, Sh. 7 |
| 9.5-17 | Figure replaced by Drawing E-411, Sh. 1 |
| 9.5-18 | Figure replaced by Drawing E-411, Sh. 2 |
| 9.5-19 | Figure replaced by Drawing M-120, Sh. 1 |
| 9.5-19A | Figure replaced by Drawing M-120, Sh. 2 |
| 9.5-19B | Figure replaced by Drawing M-120, Sh. 3 |
| 9.5-20 | Figure replaced by Drawing M-134, Sh. 1 |
| 9.5-20A | Figure replaced by Drawing M-134, Sh. 5 |
| 9.5-20B | Figure replaced by Drawing M-134, Sh. 6 |
| 9.5-20C | Figure replaced by Drawing M-134, Sh. 7 |
| 9.5-21 | Figure replaced by Drawing M30-69, Sh. 1 |
| 9.5-22 | Figure replaced by Drawing M30-71, Sh. 1 |
| 9.5-22A | Figure replaced by Drawing FF61604, Sh. 7 |
| 9.5-23 | Figure replaced by Drawing M-738, Sh. 1 |
| 9.5-24 | Figure replaced by Drawing FF61604, Sh. 3 |
| 9.5-26 | Diesel Generator Building Area 44 Plan on El. 677'-0" Intake & Exhaust |
| 9.5-26A | Diesel Generator E Building Intake & Exhaust Piping |
| 9.5-26B | Diesel Generator E Building Area 81 Plan of El. 656'-6" |
| 9.5-27 | Diesel Generator Building |
| 9.5-28 | Figure replaced by Drawing C-1006, Sh. 1 |
| 9.5-29 | Figure replaced by Drawing C-1007, Sh. 1 |
| 9.5-29-1 | Figure replaced by Drawing C-1007, Sh. 2 |
| 9.5-30 | Figure replaced by Drawing C-1032, Sh. 1 |
| 9.5-30A | Figure replaced by Drawing C-5028, Sh. 1 |
| 9.5-31 | Figure replaced by Drawing EC-1, Sh. 1 |
| 9.5-32 | Figure replaced by Drawing EC-2, Sh. 1 |
| 9.5-33 | Figure replaced by Drawing EC-3, Sh. 1 |
| 9.5-34 | Figure replaced by Drawing EC-4, Sh. 1 |
| 9.5-35 | Figure replaced by Drawing EC-5, Sh. 1 |
| 9.5-36 | Figure replaced by Drawing EC-6, Sh. 1 |
| 9.5-37 | Figure replaced by Drawing EC-7, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 9 Figures**

| | |
|----------|--|
| 9.5-38 | Figure replaced by Drawing EC-8, Sh. 1 |
| 9.5-39 | Figure replaced by Drawing C-46, Sh. 1 |
| 9.5-40 | Figure replaced by Drawing C-901, Sh. 1 |
| 9.5-40A | Figure replaced by Drawing C-5012, Sh. 1 |
| 9.5-41 | Figure replaced by Drawing C-904, Sh. 1 |
| 9.5-41A | Figure replaced by Drawing C-5013, Sh. 1 |
| 9.5-42 | Figure replaced by Drawing C-905, Sh. 1 |
| 9.5-42A | Figure replaced by Drawing C-5014, Sh. 1 |
| 9.5-42B | Figure replaced by Drawing C-5015, Sh. 1 |
| 9.5-43-1 | Figure replaced by Drawing C-1029, Sh. 1 |
| 9.5-43-2 | Figure replaced by Drawing C-1029, Sh. 2 |
| 9.5-47 | Figure replaced by Drawing E-412, Sh. 1 |

SUMMARY TABLE OF CONTENTS**Chapter 10****10.0 STEAM AND POWER CONVERSION SYSTEM**

- 10.1 Summary Description
- 10.2 Turbine-Generator
 - 10.2.1 Design Bases
 - 10.2.2 Description
 - 10.2.3 Turbine Disk Integrity
 - 10.2.4 Evaluation
 - 10.2.5 References
- 10.3 Main Steam Supply System
 - 10.3.1 Design Bases
 - 10.3.2 Description
 - 10.3.3 Evaluation
 - 10.3.4 Inspection and Testing Requirements
 - 10.3.5 Water Chemistry (PWR)
 - 10.3.6 Steam and Feedwater System Materials
- 10.4 Other Features of the Steam and Power Conversion System
 - 10.4.1 Main Condenser
 - 10.4.2 Main Condenser Evacuation System
 - 10.4.3 Steam Seal System
 - 10.4.4 Turbine Bypass System
 - 10.4.5 Circulating Water System
 - 10.4.6 Condensate Cleanup System
 - 10.4.7 Condensate and Feedwater
 - 10.4.8 Steam Generator Blowdown System (PWR)
 - 10.4.9 Auxiliary Feedwater System (PWR)
 - 10.4.10 Extraction Steam and Feedwater Heater Drain and Vent System
 - 10.4.11 Auxiliary Steam System

SUMMARY TABLE OF CONTENTS

Chapter 10 Tables

| | |
|---------|---|
| 10.1-1 | Unit 1 - Summary of Typical Design and Performance Characteristics of Power Conversion System |
| 10.1-1a | Unit 2 - Summary of Typical Design and Performance Characteristics of Power Conversion System |
| 10.2-1 | Turbine Overspeed Protection |
| 10.4-1 | Condenser Design Parameters |
| 10.4-3 | Circulating Water Quality Design Parameters Used for the Condensate Cleanup |
| 10.4-6 | Design Conditions for Feedwater Heaters |

SUMMARY TABLE OF CONTENTS**Chapter 10 Figures**

| | |
|-----------|---|
| 10.1-1a | Guaranteed Flow Unit 1 |
| 10.1-1b | Guaranteed Flow Unit 2 |
| 10.1-2a | Valves Wide Open (VWO) Unit 1 |
| 10.1-2b | Valves Wide Open (VWO) Unit 2 |
| 10.2-1 | Turbine Stop Valve Closure Characteristic |
| 10.2-2 | Turbine Control Valve Fast Closure Characteristic |
| 10.2-3 | Mechanical Overspeed Trip |
| 10.2-4 | Figure replaced by Drawing M2H-54, Sh. 1 |
| 10.2-5 | Figure replaced by Drawing M2J-101, Sh. 5 |
| 10.2-6 | Rate Sensitive Power/Load Unbalance Circuit |
| 10.2-11 | Figure replaced by Drawing M-133, Sh. 1 |
| 10.4-1-1 | Figure replaced by Drawing M-101, Sh. 1 |
| 10.4-1-1a | Figure replaced by Drawing M-2101, Sh. 1 |
| 10.4-1-2 | Figure replaced by Drawing M-101, Sh. 2 |
| 10.4-1-2a | Figure replaced by Drawing M-2101, Sh. 2 |
| 10.4-1-3 | Figure replaced by Drawing M-101, Sh. 3 |
| 10.4-1-3a | Figure replaced by Drawing M-2101, Sh. 3 |
| 10.4-2-1 | Figure replaced by Drawing M-116, Sh. 1 |
| 10.4-2-2 | Figure replaced by Drawing M-116, Sh. 2 |
| 10.4-2-3 | Figure replaced by Drawing M-116, Sh. 3 |
| 10.4-4-1 | Figure replaced by Drawing M-105, Sh. 1 |
| 10.4-4-2 | Figure replaced by Drawing M-105, Sh. 2 |
| 10.4-4-3 | Figure replaced by Drawing M-105, Sh. 3 |
| 10.4-4-4 | Figure replaced by Drawing M-105, Sh. 4 |
| 10.4-5-1 | Figure replaced by Drawing M-106, Sh. 1 |
| 10.4-5-2 | Figure replaced by Drawing M-106, Sh. 2 |
| 10.4-5-2A | Figure replaced by Drawing M-2106, Sh. 2 |
| 10.4-5-3 | Figure replaced by Drawing M-106, Sh. 3 |
| 10.4-5-3A | Figure replaced by Drawing M-2106, Sh. 3 |
| 10.4-5-4 | Figure replaced by Drawing M-106, Sh. 4 |
| 10.4-5-4A | Figure replaced by Drawing M-2106, Sh. 4 |
| 10.4-5-5 | Figure replaced by Drawing M-106, Sh. 5 |
| 10.4-6-1 | Figure replaced by Drawing M-102, Sh. 1 |
| 10.4-6-1a | Figure replaced by Drawing M-2102, Sh. 1 |
| 10.4-6-2 | Figure replaced by Drawing M-102, Sh. 2 |
| 10.4-6-2a | Figure replaced by Drawing M-2102, Sh. 2 |
| 10.4-6-3 | Figure replaced by Drawing M-102, Sh. 3 |
| 10.4-6-3a | Figure replaced by Drawing M-2102, Sh. 3 |
| 10.4-7 | Figure replaced by Drawing M-103, Sh. 1 |
| 10.4-8 | Figure replaced by Drawing M-104, Sh. 1 |
| 10.4-9-1 | Figure replaced by Drawing M-107, Sh. 1 |
| 10.4-9-2 | Figure replaced by Drawing M-107, Sh. 2 |
| 10.4-9-3 | Figure replaced by Drawing M-107, Sh. 3 |
| 10.4-9-4 | Figure replaced by Drawing M-107, Sh. 4 |

SUMMARY TABLE OF CONTENTS**Chapter 11****11.0 RADIATION WASTE MANAGEMENT**

- 11.1 Source Terms
 - 11.1.1 Fission Products
 - 11.1.2 Activation Products
 - 11.1.3 Tritium
 - 11.1.4 Core Inventory, Fuel Experience and Depressurization Spiking
 - 11.1.5 Process Leakage Sources
 - 11.1.6 Other Releases
 - 11.1.7 References

- 11.2 Liquid Waste Management Systems
 - 11.2.1 Design Bases
 - 11.2.2 System Descriptions
 - 11.2.3 Radioactive Releases
 - 11.2.4 Estimated Doses

- 11.3 Gaseous Waste Management Systems
 - 11.3.1 Design Bases
 - 11.3.2 System Descriptions
 - 11.3.3 Radioactive Releases
 - 11.3.4 Estimated Doses
 - 11.3.5 References

- 11.4 Solid Waste Management System
 - 11.4.1 Design Bases
 - 11.4.2 System Description
 - 11.4.3 References

- 11.5 Process and Effluent Radiological Monitoring And Sampling Systems
 - 11.5.1 Design Bases
 - 11.5.2 Process and Effluent Radiological Monitoring System Description
 - 11.5.3 Effluent Monitoring and Sampling
 - 11.5.4 Process Monitoring and Sampling

- 11.6 Low Level Radwaste Holding Facility (LLRWHF)
 - 11.6.1 Design Basis
 - 11.6.2 Low Level Radwaste Holding Facility Description
 - 11.6.3 LLRWHF Waste Description and Capacity
 - 11.6.4 LLRWHF Source Term
 - 11.6.5 Containers
 - 11.6.6 Container Shielding for Transport and Storage
 - 11.6.7 Crane Loading and Unloading System
 - 11.6.8 Health and Safety Requirements
 - 11.6.9 Floor Drain System
 - 11.6.10 LLRWHF HVAC System
 - 11.6.11 Effluent Monitoring

SUMMARY TABLE OF CONTENTS**Chapter 11**

- 11.6.12 Electrical Systems
- 11.6.13 Control Panels
- 11.6.14 Radiation Zoning
- 11.6.15 Radiation Monitoring System
- 11.6.16 Shielding
- 11.6.17 Security
- 11.6.18 Fire Protection System Operating Description
- 11.6.19 Exposure to Operating Personnel
- 11.6.20 Environmental Consequences of Operation of the Low-Level Radioactive Waste Holding Facility
- 11.6.21 Liner Inspections
- 11.6.22 Safety Analysis
- 11.6-23 References

- 11.7 Independent Spent Fuel Storage Installation (ISFSI)
 - 11.7.1 Design Basis
 - 11.7.2 NUHOMS® Horizontal Modular Dry Storage System Description (NUHOMS® System)
 - 11.7.3 ISFSI Source Terms
 - 11.7.4 Dry Shielded Canister (DSC)
 - 11.7.5 Horizontal Storage Module (HSM)
 - 11.7.6 Transport Equipment
 - 11.7.7 NUHOMS® System Operation
 - 11.7.8 Radiological Assessment
 - 11.7.9 Site Specific Evaluations
 - 11.7.10 Heavy Loads
 - 11.7.11 Auxiliary Systems
 - 11.7.12 Dry Fuel Storage Aging Management Program (AMP)

SUMMARY TABLE OF CONTENTS**Chapter 11 Tables**

| | |
|---------|---|
| 11.1-1 | Noble Radiogas Source Terms |
| 11.1-2 | Halogen Radioisotopes in Reactor Water and Steam |
| 11.1-3 | Other Fission Product Radioisotopes in Reactor Water |
| 11.1-4 | Coolant Activation Products in Reactor Water and Steam |
| 11.1-5 | Noncoolant Activation Products in Reactor Water |
| 11.1-6 | Depressurization Spiking Activity 95th Percentile Cumulative Probability |
| 11.2-1 | Expected Daily Inputs and Activities to the Liquid Waste Management System From Two Units |
| 11.2-2 | Expected Batched Inputs to the Liquid Radwaste System From the Solid Radwaste System For Normal Operation of Two Units |
| 11.2-3 | Liquid Waste Management System Component Description |
| 11.2-4 | Liquid Radwaste System Flows (Refer to Fig. 11.2-8) |
| 11.2-5 | Expected Radionuclide Activity Inventories of Liquid Radwaste System Components (Curies Per Component) |
| 11.2-6 | Design Basis Radionuclide Activity Inventories of Liquid Radwaste System Components (Curies Per Component) |
| 11.2-8 | Assumptions and Parameters Used For Evaluation of Radioactive Releases |
| 11.2-9 | Expected Radionuclide Activity Concentrations In Reactor Coolant and Main Steam Used For Evaluation of Radioactive Releases |
| 11.2-10 | Radwaste System Flow Rates and Stream Activities Used for Evaluation of Radioactive Releases |
| 11.2-11 | Expected Holdup Times For Collection, Processing, and Discharge Used for Evaluation of Radioactive Releases |
| 11.2-12 | Decontamination Factors Used For Evaluation of Radioactive Releases |
| 11.2-13 | Expected Yearly Activity Released From Liquid Radwaste Management Systems Used For Evaluation of Compliance With Appendix I of 10CFR50 (Ci/yr/site) |
| 11.2-14 | Calculated Expected Effluent Activity Concentrations for Evaluation of Radioactive Releases to the Susquehanna River |
| 11.2-15 | Input Data for Aquatic Dose Calculations |
| 11.2-16 | Tanks Outside Primary Containment Which Contain Potentially Radioactive Liquids |
| 11.3-1 | Annual Gaseous Releases Per Unit |
| 11.3-2 | Assumptions and Parameters Used For Evaluation of Gaseous Releases |
| 11.3-4 | Filter Trains Used to Control Gaseous Effluents |
| 11.3-5 | Off Gas System Major Equipment Description |
| 11.3-6 | Off Gas System Equipment Malfunction Analysis |
| 11.3-7 | Input Data For Atmospheric Dose Calculations |
| 11.3-8 | Off Gas System Flows (Refer to Fig. 11.3-1) (PPH 1 SCFM) |
| 11.3-10 | Comparison of Individual Doses from Expected Gaseous Effluent Releases with 10CFR50, Appendix I Design Objectives |
| 11.3-11 | Comparison of Expected Radionuclide Concentrations in the Environment from Routine Atmospheric Releases to 10CFR20 Limits |
| 11.4-1 | Inputs to the Solid Radwaste Collection System For Both Units |
| 11.4-2 | Dry Solid Waste Amount From Gas, Laundry Drain Filters, and Maintenance Activities |
| 11.4-3 | Solid Waste Management System Component Description |

SUMMARY TABLE OF CONTENTS**Chapter 11 Tables**

| | |
|---------|---|
| 11.4-4 | Solid Waste Management System Flows (Refer to Fig. 11.4-3) |
| 11.4-5 | Expected Inventories of Radioactive Materials in Components of the Solid Radwaste System |
| 11.4-6 | Design Inventories of Radioactive Materials in Components of the Solid Waste Management System (Curies) |
| 11.4-9 | Expected Inventories Of Radioactive Materials In Waste Shipping Casks |
| 11.4-10 | Design Inventories Of Radioactive Materials In Waste Shipping Casks |
| 11.5-1 | Process and Effluent Radiation Monitoring Systems |
| 11.5-2 | Radiological Analysis Summary of Routine Effluent Sampling |
| 11.5-3 | Composition and Concentration of Nuclides in Routine Effluent Samples |
| 11.6-1 | Design Basis Sources and Assumptions Used to Calculate the Off-Site Radiological Consequences Due to a Container Drop from a Transport Vehicle (Reference 11.6-7) |
| 11.6-2 | Design Basis Sources and Assumptions Used to Calculate the Off-Site Radiological Consequences Due to Dropping a Heavy Component Onto the Solidified Waste Storage Vault (Reference 11.6-11) |
| 11.6-3 | Design Basis Sources and Assumptions Used to Calculate the Off-Site Radiological Consequences Due to an Unspecified Incendiary Event Involving 100% of DAW (Reference 11.6-4) |
| 11.6-4 | Design Basis Sources and Assumptions Used to Calculate the Off-Site Radiological Consequences Due to Loss of Off-Site Power to the LLRWHF (Reference 11.6-5) |
| 11.6-5 | Design Basis Sources and Assumptions Used to Calculate the Off-Site Radiological Consequences Due to Mobile Shielded Storage Module Without Lid (Reference 11.6-6) |

SUMMARY TABLE OF CONTENTS**Chapter 11 Figures**

| | |
|-----------|--|
| 11.1-1 | Noble Radiogas Decay Constant Exponent Frequency Histogram |
| 11.1-2 | Radiohalogen Decay Constant Exponent Frequency Histogram |
| 11.1-3 | Nobel Radiogas Versus I-131 Leakage |
| 11.2-1 | Figure replaced by Drawing M-270, Sh. 1 |
| 11.2-2 | Figure replaced by Drawing M-271, Sh. 1 |
| 11.2-3 | Figure replaced by Drawing M-272, Sh. 1 |
| 11.2-4 | Figure replaced by Drawing M-273, Sh. 1 |
| 11.2-5 | Figure replaced by Drawing M-274, Sh. 1 |
| 11.2-6 | Figure replaced by Drawing M-220, Sh. 1 |
| 11.2-7 | Figure replaced by Drawing M-230, Sh. 1 |
| 11.2-8 | Liquid Radwaste Management System Flow Diagram |
| 11.2-9-1 | This Figure has been replaced by Dwg. M-162, Sh. 1 |
| 11.2-9-2 | This Figure has been replaced by Dwg. M-162, Sh. 2 |
| 11.2-9-3 | This Figure has been replaced by Dwg. M-162, Sh. 3 |
| 11.2-11-1 | Figure replaced by Drawing M-163, Sh. 1 |
| 11.2-11-2 | Figure replaced by Drawing M-163, Sh. 2 |
| 11.2-11-3 | Figure replaced by Drawing M-163, Sh. 3 |
| 11.2-12 | Figure replaced by Drawing M-164, Sh. 1 |
| 11.2-13 | Liquid Waste Management Scheme |
| 11.2-14 | Typical Mobile Processing System Flow Diagram |
| 11.3-1 | Offgas System Process Flow Diagram |
| 11.3-2A-1 | Figure replaced by Drawing M-169, Sh. 1 |
| 11.3-2A-2 | Figure replaced by Drawing M-169, Sh. 2 |
| 11.3-2A-3 | Figure replaced by Drawing M-169, Sh. 3 |
| 11.3-2A-4 | Figure replaced by Drawing M-169, Sh. 4 |
| 11.3-2C-1 | Figure replaced by Drawing M-2169, Sh. 1 |
| 11.3-2C-2 | Figure replaced by Drawing M-2169, Sh. 2 |
| 11.3-2D-1 | Figure replaced by Drawing M-2171, Sh. 1 |
| 11.3-2D-2 | Figure replaced by Drawing M-2171, Sh. 2 |
| 11.3-3-1 | Figure replaced by Drawing M-171, Sh. 1 |
| 11.3-3-2 | Figure replaced by Drawing M-171, Sh. 2 |
| 11.3-4 | Release Points Locations and Details |
| 11.4-1-1 | Figure replaced by Drawing M-166, Sh. 1 |
| 11.4-1-2 | Figure replaced by Drawing M-166, Sh. 2 |
| 11.4-2-1 | Figure replaced by Drawing M-167, Sh. 1 |
| 11.4-2-2 | Figure replaced by Drawing M-167, Sh. 2 |
| 11.4-3 | Solid Waste Management System Flow Diagram |
| 11.6-1 | Figure replaced by Drawing B1P-005, Sh. 1 |
| 11.6-2 | Figure replaced by Drawing B1N-100, Sh. 1 |
| 11.6-3 | Shield Bell Assembly |

SUMMARY TABLE OF CONTENTS**Chapter 12****12.0 RADIATION PROTECTION**

- 12.1 Ensuring that Occupational Radiation Exposures Are As Low As Reasonably Achievable (ALARA)
 - 12.1.1 Policy Considerations
 - 12.1.2 Design Considerations
 - 12.1.3 Operational Considerations
 - 12.1.4 References

- 12.2 Radiation Sources
 - 12.2.1 Contained Sources
 - 12.2.2 Airborne Radioactive Material Sources

- 12.3 Radiation Protection Design Features
 - 12.3.1 Facility Design Features
 - 12.3.2 Shielding
 - 12.3.3 Ventilation
 - 12.3.4 Area Radiation and Airborne Radioactivity Monitoring Instrumentation
 - 12.3.5 References

- 12.4 Dose Assessment
 - 12.4.1 Direct Radiation Dose Estimates for Exposures Within the Plant
 - 12.4.2 Airborne Radioactivity Dose Estimates for Exposures Within the Plant
 - 12.4.3 Exposures at Locations Outside Plant Structures
 - 12.4.4 References

- 12.5 Health Physics Program
 - 12.5.1 Organization
 - 12.5.2 Facilities, Equipment, & Instrumentation
 - 12.5.3 Procedures

SUMMARY TABLE OF CONTENTS**Chapter 12 Tables**

| | |
|----------|--|
| 12.2-1 | Basic Reactor Data |
| 12.2-2 | Core Region Description Used in Calculations to Determine Radial Flux Distribution at Reactor Core Midplane |
| 12.2-3 | Material Composition to Determine Radial Flux Distributions at Reactor Core Midplane |
| 12.2-4 | Calculated Gamma Ray and Neutron Fluxes at Outside Surface of RPV |
| 12.2-5 | Calculated Gamma Ray and Neutron Fluxes at Outside Surface of Primary Shield |
| 12.2-6 | Reactor Water Cleanup System N-16 Shielding Source Terms |
| 12.2-7 | Reactor Water Cleanup Filter Demineralizer Shielding Source Terms |
| 12.2-8 | Reactor Water Cleanup Backwash Receiving Tank Shielding Source Terms |
| 12.2-9A1 | Activity (Curies) per Full Core of ATRIUM-11 Fuel |
| 12.2-9A2 | Activity (Curies) per Single Assembly of ATRIUM-11 Fuel |
| 12.2-10 | Residual Heat Removal System Shielding Source Terms |
| 12.2-11 | Steam N-16 Shielding Source Terms for Turbine and Reactor Building Equipment |
| 12.2-12 | Fuel Pool System Shielding Source Terms |
| 12.2-13 | Fuel Pool Filter Demineralizer Shielding Source Terms |
| 12.2-14 | Fuel Pool Water Cleanup Backwash Receiving Tank Shielding Source Terms |
| 12.2-15 | Condensate Shielding Source Terms |
| 12.2-16 | Condensate Demineralizer Shielding Source Terms |
| 12.2-17 | Off-gas Line from SJAE to Recombiner Shielding Source Terms |
| 12.2-18 | Off-gas Primary Recombiner Shielding Source Terms |
| 12.2-19 | Off-gas Line from Recombiner to Charcoal System Shielding Source Terms |
| 12.2-21 | Off-gas Ambient Charcoal Freon Chiller Shielding Source Terms |
| 12.2-22 | Off-gas Charcoal Guard Bed Shielding Source Terms |
| 12.2-23 | Off-gas Charcoal Beds Shielding Source Terms |
| 12.2-24 | Off-gas Post-HEPA Filter Shielding Source Terms |
| 12.2-29 | Condensate Storage Tank Source Terms |
| 12.2-30 | Estimated Airborne Radioactive Releases Prior to Treatment (Curies/Year) |
| 12.2-31 | Estimated Distribution of Airborne Radioactive Releases |
| 12.2-32 | Turbine Building Airborne Source Descriptions |
| 12.2-33 | Reactor Building Airborne Source Descriptions |
| 12.2-34 | Radwaste Building Airborne Source Descriptions |
| 12.2-35 | Estimated Airborne Concentrations in the Turbine Building and Fraction of DACs |
| 12.2-36 | Estimated Airborne Concentrations in the Reactor Building and Fraction of DACs |
| 12.2-37 | Estimated Airborne Concentrations in the Radwaste Building and Fraction of DACs |
| 12.2-38 | Turbine Building Shielding Design Radiation Source Description |
| 12.2-39 | Reactor Building Shielding Design Radiation Source Description |
| 12.2-40 | Radwaste Building Shielding Design Radiation Source Terms |
| 12.2-41 | Material Composition of the TIP System Components As Used in Activation Calculations |
| 12.2-42 | Traversing Incore Probe Detector Decay Gamma Activities in MEV/Sec of 0.001 g of U-235 |
| 12.2-43 | Traversing Incore Probe Detector Decay Gamma Activities of Materials in the Detector (Excluding U-235) in Microcuries in the Irradiated Detector |
| 12.2-44 | Decay Gamma Activities of Materials in the Cable in Microcuries per Inch of Irradiated Cable. |
| 12.2-46 | Condensate Filter Vessel Shielding Source Terms |

SUMMARY TABLE OF CONTENTS**Chapter 12 Tables**

| | |
|---------|--|
| 12.2-47 | Condensate Filter Vessel Backwash Shielding Source Terms |
| 12.2-48 | Condensate Filter Vessel Backwash Receiving Tank Shielding Source Terms |
| 12.3-1 | Plant Radiation Zone Description |
| 12.3-2 | List of Computer Codes Used in Shielding Design Calculations |
| 12.3-7 | Area Radiation Monitoring System |
| 12.4-1 | Summary of Historical Data Used in Compilation of Exposures Received at Operating Boiling Water Reactors |
| 12.4-2 | Occupational Exposures By Job Function for Operating Boiling Water Reactors |
| 12.4-3 | Exposure Estimates for the Turbine Building and Control Structure |
| 12.4-4 | Exposure Estimates for the Reactor Building |
| 12.4-5 | Exposure Estimates for the Radwaste Building |
| 12.4-6 | Estimated Exposure for Operators in Residence in Control Rooms |
| 12.4-7 | Summary of Routine Operations Exposure Estimate |
| 12.4-8 | Estimate of Expected Maintenance Man-hours for Various Types of Equipment |
| 12.4-9 | Summary of In-Plant Direct Radiation Exposure Estimates |
| 12.4-10 | Estimated Turbine Building Inhalation Exposures Due to Airborne Radioactivity |
| 12.4-11 | Estimated Reactor Building Inhalation Exposures Due to Airborne Radioactivity |
| 12.4-12 | Estimated Radwaste Building Inhalation Exposures Due to Airborne Radioactivity |

SUMMARY TABLE OF CONTENTS**Chapter 12 Figures**

| | |
|-----------|---|
| 12.3-1 | Typical Shielding Arrangement for Liquid Radwaste Filters and Valve Gallery |
| 12.3-2 | Typical Shielding Arrangement for Radwaste Demineralizer |
| 12.3-3 | Typical Shielding Arrangement for Charcoal and Particulate Filter |
| 12.3-4 | Typical Shielding Arrangement for Off-gas Recombiners |
| 12.3-5 | Typical Shielding Arrangement for Radwaste Tanks and Pumps |
| 12.3-6 | Typical Shielding Arrangement for Radwaste Evaporator |
| 12.3-8 | Figure replaced by Drawing A-511, Sh. 1 |
| 12.3-9 | Figure replaced by Drawing A-512, Sh. 1 |
| 12.3-10 | Figure replaced by Drawing A-513, Sh. 1 |
| 12.3-11 | Figure replaced by Drawing A-514, Sh. 1 |
| 12.3-12 | Figure replaced by Drawing A-515, Sh. 1 |
| 12.3-13 | Figure replaced by Drawing A-516, Sh. 1 |
| 12.3-14 | Figure replaced by Drawing A-517, Sh. 1 |
| 12.3-15 | Figure replaced by Drawing A-518, Sh. 1 |
| 12.3-16 | Figure replaced by Drawing A-519, Sh. 1 |
| 12.3-17 | Figure replaced by Drawing A-520, Sh. 1 |
| 12.3-18 | Figure replaced by Drawing A-521, Sh. 1 |
| 12.3-19 | Figure replaced by Drawing A-522, Sh. 1 |
| 12.3-20 | Figure replaced by Drawing A-523, Sh. 1 |
| 12.3-21 | Figure replaced by Drawing A-524, Sh. 1 |
| 12.3-22 | Figure replaced by Drawing A-525, Sh. 1 |
| 12.3-23 | Figure replaced by Drawing A-526, Sh. 1 |
| 12.3-24 | Figure replaced by Drawing A-527, Sh. 1 |
| 12.3-25 | Figure replaced by Drawing A-528, Sh. 1 |
| 12.3-26 | Figure replaced by Drawing A-529, Sh. 1 |
| 12.3-27 | Figure replaced by Drawing A-530, Sh. 1 |
| 12.3-28 | Figure replaced by Drawing BIN-100 |
| 12.3-29 | Scaled Isometric of Control Building with Relationship to Containment |
| 12.3-30-1 | Figure replaced by Drawing M-137, Sh. 1 |
| 12.3-30-2 | Figure replaced by Drawing M-137, Sh. 2 |
| 12.4-1 | Estimated Turbine Shine Dose Rates |
| 12.5-1 | Health Physics Organization |

SUMMARY TABLE OF CONTENTS

Chapter 13

13.0 CONDUCT OF OPERATIONS

- 13.1 Organizational Structure
 - 13.1.1 Management and Technical Support Organization
 - 13.1.2 Operating Organization
 - 13.1.3 Qualification Requirements for Nuclear Plant (On-Site) Personnel

- 13.2 Training Program
 - 13.2.1 Plant Personnel Training Program
 - 13.2.2 Requalification and Replacement Training

- 13.3 Emergency Plan

- 13.4 Review and Audit
 - 13.4.1 Plant Operations Review Committee
 - 13.4.2 Nuclear Safety Review Board
 - 13.4.3 Audit Program
 - 13.4.4 Process Control Program (PCP)
 - 13.4.5 Technical Review and Control

- 13.5 Plant Procedures
 - 13.5.1 Administrative Procedures
 - 13.5.2 Operating and Maintenance Procedures

- 13.6 Industrial Security

SUMMARY TABLE OF CONTENTS

Chapter 13 Tables

- 13.1-1 Resumes of Key General Office Personnel
- 13.1-2 Resumes of Key Plant Personnel

SUMMARY TABLE OF CONTENTS

Chapter 13 Figures

- 13.1-1 Talen Energy Corporation Management Organization Applicable to Susquehanna SES
- 13.1-2 Susquehanna Nuclear, LLC, Off-Site Organization
- 13.1-3 Susquehanna Nuclear, LLC, On-Site Organization

- 13.5-2 Main Control Room

SUMMARY TABLE OF CONTENTS

Chapter 14

14.0 **INITIAL TEST PROGRAM**

- 14.1 Specific Information to be Included in Preliminary Safety Analysis Reports
- 14.2 Specific Information to be Included in Final Safety Analysis Report
 - 14.2.1 Summary Of Test Program and Objectives
 - 14.2.2 Organization and Staffing
 - 14.2.3 Test Procedures
 - 14.2.4 Conduct of Test Program
 - 14.2.5 Review, Evaluation, and Approval of Test Results
 - 14.2.6 Test Records
 - 14.2.7 Conformance of Test Programs With Regulatory Guides
 - 14.2.8 Utilization of Reactor Operating and Testing Experience In the Development of The Test Program
 - 14.2.9 Trial Use of Plant Operating and Emergency Procedures
 - 14.2.10 Initial Fuel Loading and Initial Criticality
 - 14.2.11 Test Program Schedule
 - 14.2.12 Individual Test Descriptions
- 14.3 Power Uprate Test Program
 - 14.3.1 Summary of Power Uprate Test Program and Objectives
 - 14.3.2 Organization and Staffing
 - 14.3.3 Test Procedures

SUMMARY TABLE OF CONTENTS

Chapter 14 Tables

| | |
|--------|--|
| 14.2-1 | Preoperational Test Procedures |
| 14.2-2 | Acceptance Test Procedures |
| 14.2-3 | Startup Test Procedures |
| 14.2-4 | Major Test Phase and Test Plateau Schedule - Test Condition Sequence |
| 14.2-5 | Control Rod Drive System Startup Tests |
| 14.2-6 | Unit 2 Preoperational Test Procedures |
| 14.2-7 | Unit 2 Acceptance Test |
| 14.3-1 | Power Uprate Test Procedures |
| 14.3-2 | Test Plateau and Test Condition Definition |

SUMMARY TABLE OF CONTENTS**Chapter 14 Figures**

| | |
|----------|---|
| 14.2-1 | Integrated Startup Group Organization |
| 14.2-2A | Preoperational Test Procedure Standard Format |
| 14.2-2B | Startup Test Procedure Standard Format - Unit 1 |
| 14.2-2C | Startup Test Procedure Standard Format - Unit 2 |
| 14.2-3 | Initial Test Program Schedule |
| 14.2-4a | Unit 1 Preoperational Test Sequence |
| 14.2-4b | Unit 2 Preoperational Test Sequence |
| 14.2-5-1 | Individual Startup Test Sequence - Unit 1 |
| 14.2-5-2 | Individual Startup Test Sequence - Unit 1 |
| 14.2-5-3 | Individual Startup Test Sequence - Unit 2 |
| 14.2-5-4 | Individual Startup Test Sequence - Unit 2 |
| 14.2-6-1 | Power Flow Map and Startup Test Conditions |
| 14.2-6-2 | Power Flow Map and Power Test Conditions |
| 14.2-7 | RCIC Acceptance Criteria Curves For Capacity and Actuation Time |

SUMMARY TABLE OF CONTENTS**Chapter 15****15.0 ACCIDENT ANALYSIS**

- 15.0.1 Analytical Objective
- 15.0.2 Analytical Categories
- 15.0.3 Event Evaluation
- 15.0.4 Nuclear Safety Operational Analysis (NSQA) Relationship
- 15.0.5 References

- 15.1 Decrease in Reactor Coolant Temperature
 - 15.1.1 Loss of Feedwater Heating
 - 15.1.2 Feedwater Controller Failure-Maximum Demand
 - 15.1.3 Pressure Regulator Failure - Open
 - 15.1.4 Inadvertent Safety/Relief Valve Opening
 - 15.1.5 Spectrum of Steam System Piping Failures Inside and Outside of Containment In A PWR
 - 15.1.6 Inadvertent RHR Shutdown Cooling Operation
 - 15.1.7 References

- 15.2 Increase in Reactor Pressure
 - 15.2.1 Pressure Regulator Failure - Closed
 - 15.2.2 Generator Load Rejection
 - 15.2.3 Turbine Trip
 - 15.2.4 MSIV Closures
 - 15.2.5 Loss of Condenser Vacuum
 - 15.2.6 Loss of AC Power
 - 15.2.7 Loss of Feedwater Flow
 - 15.2.8 Feedwater Line Break
 - 15.2.9 Failure of RHR Shutdown Cooling
 - 15.2.10 References

- 15.3 Decrease in Reactor Coolant System Flow Rate
 - 15.3.1 Recirculation Pump Trip
 - 15.3.2 Recirculation Flow Control Failure - Decreasing Flow
 - 15.3.3 Recirculation Pump Seizure
 - 15.3.4 Recirculation Pump Shaft Break
 - 15.3.5 References

- 15.4 Reactivity and Power Distribution Anomalies
 - 15.4.1 Rod Withdrawal Error - Low Power
 - 15.4.2 Rod Withdrawal Error-at Power
 - 15.4.3 Control Rod Maloperation (System Malfunction or Operator Error)
 - 15.4.4 Abnormal Startup of Idle Recirculation Pump
 - 15.4.5 Recirculation Flow Control Failure with Increasing Flow
 - 15.4.6 Chemical and Volume Control System Malfunctions
 - 15.4.7 Misplaced Bundle Accident
 - 15.4.8 Spectrum of Rod Ejection Assemblies

SUMMARY TABLE OF CONTENTS**Chapter 15**

| | |
|---------|---|
| 15.4.9 | Control Rod Drop Accident (CRDA) |
| 15.4.10 | References |
| 15.5 | Increase in Reactor Coolant Inventory |
| 15.5.1 | Inadvertent HPCI Startup |
| 15.5.2 | Chemical Volume Control System Malfunction (or Operator Error) |
| 15.5.3 | BWR Transients Which Increase Reactor Coolant Inventory |
| 15.5.4 | References |
| 15.6 | Decrease in Reactor Coolant Inventory |
| 15.6.1 | Inadvertent Safety Relief Valve Opening |
| 15.6.2 | Instrument Line Break |
| 15.6.3 | Steam Generator Tube Failure |
| 15.6.4 | Steam System Piping Break Outside Containment |
| 15.6.5 | Loss-Of-Coolant Accidents (Resulting From Spectrum of Postulated Piping Breaks Within The Reactor Coolant Pressure Boundary) - Inside Containment |
| 15.6.6 | Feedwater Line Break-Outside Containment |
| 15.6.7 | References |
| 15.7 | Radioactive Release from Subsystems and Components |
| 15.7.1 | Gaseous Radwaste System Leak or Failure |
| 15.7.2 | Liquid Radwaste System Failure |
| 15.7.3 | Postulated Radioactive Releases Due To Liquid Radwaste Tank Failure |
| 15.7.4 | Fuel and Equipment Handling Accidents |
| 15.7.5 | Spent Fuel Cask Drop Accident |
| 15.7.6 | References |
| 15.8 | Anticipated Transients Without Scram (ATWS) |
| 15.8.1 | Causes, Frequency Classification, Initiating Events, Acceptance Criteria, Mathematical Models, Input Parameters, and Initial Conditions |
| 15.8.2 | Inadvertent Control Rod Withdrawal |
| 15.8.3 | Loss of Feedwater (LOFW) |
| 15.8.4 | Loss of Offsite Power (LOOP) |
| 15.8.5 | Loss of Electrical Load |
| 15.8.6 | Loss of Condenser Vacuum |
| 15.8.7 | Turbine Trip |
| 15.8.8 | Closure of Main Steam Line Isolation Valves |
| 15.8.9 | Pressure Regulator Failure–Open |
| 15.8.10 | Feedwater Controller Failure–Open (FWCFO) |
| 15.8.11 | Inadvertent Opening of a S/R Valve |
| 15.8.12 | References |
| 15.9 | Station Blackout (SBO) |
| 15.9.0 | Coping Assessment for the Susquehanna Steam Electric Station During a Station Blackout |
| 15.9.1 | References |

SUMMARY TABLE OF CONTENTS**Chapter 15**

| | |
|---------|--|
| 15A | Nuclear Safety Operational Analysis (NOSA) (A System Level/Qualitative Type Plant FMEA) |
| 15A.1 | OBJECTIVES |
| 15A.1.1 | General Objectives |
| 15A.1.2 | Specific Objectives |
| 15A.2 | APPROACH TO OPERATIONAL NUCLEAR SAFETY |
| 15A.2.1 | General Philosophy |
| 15A.2.2 | Specific Philosophy |
| 15A.2.3 | Comprehensiveness of the Analysis |
| 15A.2.4 | Systematic Approach of the Analysis |
| 15A.2.5 | Relationship of Nuclear Safety Operational Analysis to Safety Analyses of Chapter 15 |
| 15A.2.6 | Relationship Between NSOA and Operational Requirements, Technical Specifications, Design Basis, and SACF Aspects |
| 15A.2.7 | Unacceptable Results Criteria |
| 15A.2.8 | General Nuclear Safety Operational Criteria |
| 15A.3 | METHOD OF ANALYSIS |
| 15A.3.1 | General Approach |
| 15A.3.2 | BWR Operating States |
| 15A.3.3 | Selection of Events for Analysis |
| 15A.3.4 | Applicability of Events to Operating States |
| 15A.3.5 | Rules for Event Analysis |
| 15A.3.6 | Steps in an Operational Analysis |
| 15A.4 | DISPLAY OF OPERATIONAL ANALYSIS RESULTS |
| 15A.4.1 | General |
| 15A.4.2 | Protection Sequence and Safety System Auxiliary Diagrams |
| 15A.5 | BASES FOR SELECTING SURVEILLANCE TEST FREQUENCIES |
| 15A.5.1 | Normal Surveillance Test Frequencies |
| 15A.5.2 | Allowable Repair Times |
| 15A.5.3 | Repair Time Rule |
| 15A.6 | OPERATIONAL ANALYSES |
| 15A.6.1 | Safety System Auxiliaries |
| 15A.6.2 | Planned (Normal) Operations |
| 15A.6.3 | Anticipated (Expected) Operational Transients |
| 15A.6.4 | Abnormal (Unexpected) Operational Transients |
| 15A.6.5 | Design Basis (Postulated) Accidents |
| 15A.6.6 | Special (Plant Capability) Events |
| 15A.7 | REMAINDER OF NSQA |
| 15A.8 | CONCLUSIONS |
| 15A.9 | LIST OF REFERENCES |
| 15B | Accident Dose Model Descriptions |
| 15B.1 | OFFSITE DOSE MODEL |
| 15B.1.1 | Total Body Gamma Dose |
| 15B.1.2 | Thyroid Inhalation Dose |
| 15B.1.3 | Beta Skin Dose |

SUMMARY TABLE OF CONTENTS

Chapter 15

| | |
|---------|--|
| 15B.2 | CONTROL ROOM DOSE MODEL |
| 15B.3 | REFERENCES |
| 15C | Susquehanna Steam Electric Station Unit 1 Final Safety Analysis Report- Cycle Specific Data |
| 15C.1 | Appendix C Contents |
| 15C.1.1 | Content Discussion |
| 15C.1.2 | References |
| 15D | Susquehanna Steam Electric Station Unit 2 Final Safety Analysis Report- Cycle Specific Data |
| 15D.1 | Appendix D Contents |
| 15D.1.1 | Content Discussion |
| 15D.1.2 | References |
| 15E | Susquehanna Steam Electric Station Units 1 and 2 Non-Limiting Events |

SUMMARY TABLE OF CONTENTS**Chapter 15 Tables**

| | |
|---------|--|
| 15.1-1 | Sequence of Events for Inadvertent Safety Relief Valve Opening |
| 15.1-2 | Safety Relief Valve Opening Event Activity Above Suppression Pool (Curies) |
| 15.1-3 | Safety Relief Valve Opening Event Activity Release to Environs (Curies) |
| 15.1-4 | Safety Relief Valve Opening Event Radiological Doses (REM-TEDE) |
| 15.1-5 | Inadvertent Safety/Relief Valve Openings |
| 15.4-2 | Control Rod Drop Accident – Design Basis Analysis–Airborne Activity in Condense (2000 Failed Rods) |
| 15.4-3 | Control Rod Drop Accident – Design Basis Analysis-Airborne Activity in Condenser (35 Failed Rods) |
| 15.4-4 | Control Rod Drop Accident – Design Basis Analysis- Activity Released to Environs (2000 Failed Rods) |
| 15.4-5 | Control Rod Drop Accident – Design Basis Analysis- Activity Released to Environs (35 Failed Rods) |
| 15.4-6 | Control Rod Drop Accident – Activity Airborne in Condenser (Realistic Analysis) (2000 Rods) |
| 15.4-7 | Control Rod Drop Accident – Activity Airborne in Condenser (Realistic Analysis) (35 Rods) |
| 15.4-8 | Control Rod Drop Accident – Activity Released to Environs (Realistic Analysis) (2000 Rods) |
| 15.4-9 | Control Rod Drop Accident – Activity Released to Environs (Realistic Analysis) (35 Rods) |
| 15.4-10 | Control Rod Accident Radiological Effects Design Basis Case and Realistic Case |
| 15.4-11 | Control Rod Drop Accident – Parameters to be Tabulated for Postulated Accident Analysis |
| 15.6-1 | Sequence of Events for Instrument Line Break |
| 15.6-2 | Mass Releases-Instrument Line Break |
| 15.6-3 | Instrument Line Break Activity Released to the Environment (Curies) |
| 15.6-4 | Instrument Line Break Inside Secondary Containment Radiological Consequences |
| 15.6-5 | Instrument Line Break Accident - Parameters for Postulated Accident Analysis |
| 15.6-6 | Sequence of Events for Steam Line Break Outside Containment |
| 15.6-7 | Steam Line Break Accident Activity Released to the Environment (Curies) (Design Basis Analysis) |
| 15.6-8 | Steam Line Break Accident Activity Released to the Environment (Curies) (Realistic Analysis) |
| 15.6-9 | Steam Line Break Outside Containment Radiological Doses (rem) |
| 15.6-10 | Steam Line Break Accident - Parameters to be Tabulated for Postulated Accident Analyses |
| 15.6-11 | Loss of Coolant Accident - Activity Airborne in Primary Containment (Curies) (Design Basis Analysis) |
| 15.6-13 | Loss of Coolant Accident - Activity Airborne in Reactor Building (Curies) (Design Basis Analysis) |
| 15.6-14 | Loss of Coolant Accident - Activity Released to Environment (Curies) (Design Basis Analysis) |

SUMMARY TABLE OF CONTENTS**Chapter 15 Tables**

| | |
|---------|---|
| 15.6-15 | Loss of Coolant Accident - Activity Airborne in Primary Containment (Curies) (Realistic Analysis) |
| 15.6-16 | Loss of Coolant Accident - Activity Airborne in Reactor Building (Curies) (Realistic Analysis) |
| 15.6-17 | Loss of Coolant Accident - Activity Released to Environment (Curies) (Realistic Analysis) |
| 15.6-18 | Loss-of-Coolant Accident - Summary of Offsite Doses |
| 15.6-21 | Loss-of-Coolant Accident - Summary of Control Room Operator Doses (Design Basis Analysis) |
| 15.6-22 | Loss-of-Coolant Accident - Parameters for Postulated Accident Analysis |
| 15.6-23 | Sequence of Events for Feedwater Line Break Outside Containment |
| 15.6-24 | Feedwater Line Break Accident - Parameters for Postulated Accident Analyses |
| 15.6-25 | Feedwater Line Break Activity Released to Environment (Curies) |
| 15.6-26 | Feedwater Line Break Outside Containment Radiological Doses (rem) |
| 15.7-1 | Sequence of Events for Main Condenser Offgas Treatment System Failure |
| 15.7-2 | Activity Inventory Stored in Offgas Treatment System Activity Released to the Environs (curies) (Design Basis Analysis) |
| 15.7-3 | Activity Inventory Stored in Offgas Treatment System Activity Released to the Environs (curies) (Realistic Analysis) |
| 15.7-4 | Main Condenser Offgas Treatment System Failure Radiological Effects |
| 15.7-5 | Offgas Treatment System Failure Parameters for Postulated Accident Analysis |
| 15.7-6 | Failure of Air Ejector Lines Activity Released to the Environment (curies/sec) |
| 15.7-7 | Failure of Steam Jet Air Ejector Lines Radiological Consequences |
| 15.7-8 | Failure of Air Ejector Lines Parameters for Postulated Accident Analysis |
| 15.7-9 | RWCU Phase Separator Tank Failure – Initial Activity |
| 15.7-9A | RWCU Phase Separator Tank Failure Activity Release to Environment |
| 15.7-10 | RWCU Phase Separator Tank Failure Radiological Effects |
| 15.7-11 | RWCU Phase Separator Tank Failure |
| 15.7-12 | Refueling Accidents Activity Airborne in Reactor Building (Curies) (Design Basis Analysis) |
| 15.7-13 | Refueling Accidents Activity Released to Environment (Curies) (Design Basis Analysis) |
| 15.7-14 | Refueling Accidents - Activity Airborne in Reactor Building (Realistic Analysis) |
| 15.7-15 | Refueling Accidents - Activity Released to Environs (Realistic Analysis) |
| 15.7-16 | Refueling Accidents - Radiological Effects |
| 15.7-17 | Refueling Accidents - Parameters to be Tabulated for Postulated Accident Analyses |
| 15.7-18 | Sequence of Events for SJAE Failure |
| 15.8-1 | Input Parameters for ATWS Analysis |
| 15.8-3 | Input Operating Conditions for ATWS Analysis |
| 15.8-5 | Sequence of Events for MSIV Closure ATWS |
| 15.8-7 | Results for MSIV Closure ATWS Event |
| 15.8-9 | Sequence of Events for Prego ATWS |
| 15.8-11 | Results for Prego ATWS Event |

SUMMARY TABLE OF CONTENTS**Chapter 15 Tables**

| | |
|-----------|---|
| 15.9-1 | Unit 1 Station Blackout Instrumentation List |
| 15.9-2 | Unit 2 Station Blackout Instrumentation List |
| 15A.2-1 | Planned (Normal) Operation Cross-Correlation References |
| 15A.2-2 | Anticipated (Expected) Operational Transients Cross-Correlation References |
| 15A.2-3 | Abnormal (Unexpected) Operational Transients Cross-Correlation References |
| 15A.2-4 | Design Basis (Postulated) Accidents Cross-Correlation References |
| 15A.2-5 | Special (Plant Capability) Events Cross-Correlation References |
| 15A.2-6 | Plant Event Category: Planned (Normal) Operation Unacceptable Results Criteria |
| 15A.2-7 | Plant Event Category: Anticipated (Expected) Operational Transients Unacceptable Results Criteria |
| 15A.2-8 | Plant Event Category: Abnormal (Unexpected) Operational Transients Unacceptable Results Criteria |
| 15A.2-9 | Plant Event Category: Design Basis (Postulated) Accidents Unacceptable Result Criteria |
| 15A.2-10 | Plant Event Category: Special (Plant Capability) Events Unacceptable Results Considerations |
| 15A.3-1 | BWR Operating States |
| 15A.6-1 | Plant Events Applicable in Each BWR Operating State Planned (Normal) Operation |
| 15A.6-2 | Plant Events Applicable in Each BWR Operating State Anticipated (Expected) Operational Transients |
| 15A.6-3 | Plant Events Applicable in Each BWR Operating State Abnormal (Unexpected) Operational Transients |
| 15A.6-4 | Plant Events Applicable in Each BWR Operating State Design Basis (Postulated) Accidents |
| 15A.6-5 | Plant Events Applicable in Each BWR Operating State Special (Plant Capability) Events |
| 15.B-1 | Control Room Atmospheric Dispersion Factors For Design Basis Accidents - X/Q |
| 15B-2 | Physical Data for Isotopes |
| 15B-3 | Breathing Rates |
| 15C.0-1 | Results Summary of Transient Events Unit 1 (Typical) |
| 15C.0-2 | Input Parameters and Initial Conditions for Transients Unit 1 |
| 15C.0-3 | MCPR Fuel Cladding Integrity Safety Limit (All Fuel) Unit 1 |
| 15C.0-4 | Unit 1 Minimum MCPR Requirement For Single Loop Operation & 2 Loop Operation |
| 15C.0-5 | Average Scram Insertion Times Unit 1 |
| 15C.1.1-1 | Sequence of Events for Loss of Feedwater Heating Unit 1 |
| 15C.1.2-1 | Sequence of Events for Feedwater Controller Failure, Maximum Demand Unit 1 (Typical) |
| 15C.1.3-1 | Sequence of Events for Pressure Regulator Failure – Open Unit 1 |
| 15C.2.2-1 | Sequence of Events for Generator Load Rejection Without Bypass and Turbine Trip Without Bypass Unit 1 (Typical) |
| 15C.3.3-1 | Pump Seizure Accident from Two Loop Operation Sequence of Events Unit 1 |

SUMMARY TABLE OF CONTENTS**Chapter 15 Tables**

| | |
|-----------|--|
| 15C.3.3-2 | Pump Seizure Accident from Single Loop Operation Sequence of Events Unit 1 |
| 15C.4.2-1 | Sequence of Events – RWE Drift in Power Range Unit 1 |
| 15C.4.5-1 | Sequence of Events for Recirculation Flow Controller Failure Unit 1 |
| 15C.4.7-1 | Unit 1 Sequence of Events for Misloaded Bundle Accident |
| 15C.4.9-1 | Sequence of Events for Control Rod Drop Accident Unit 1 |
| 15C.4.9-2 | Control Rod Drop Accident Unit 1 (Typical) |
| 15D.0-1 | Results Summary of Transient Events Unit 2 (Typical) |
| 15D.0-2 | Input Parameters and Initial Conditions for Transients Unit 2 |
| 15D.0-3 | MCPR Fuel Cladding Integrity Safety Limit (All Fuel) Unit 2 |
| 15D.0-4 | Unit 2 Minimum MCPR Requirement for Single Loop Operation & Minimum MCPR Requirement for 2 Loop Operation |
| 15D.0-5 | Average Scram Insertion Times Unit 2 |
| 15D.1.1-1 | Sequence of Events for Loss of Feedwater Heating Unit 2 |
| 15D.1.2-1 | Sequence of Events for Feedwater Controller Failure, Maximum Demand Unit 2 (Typical) |
| 15D.1.3-1 | Sequence of Events for Pressure Regulator Failure – Open Unit 2 |
| 15D.2.2-1 | Sequence of Events for Generator Load Rejection Without Bypass and Turbine Trip Without Bypass Unit 2 (Typical) |
| 15D.3.3-1 | Pump Seizure Accident from Two Loop Operation Sequence of Events Unit 2 |
| 15D.3.3-2 | Pump Seizure Accident from Single Loop Operation Sequence of Events Unit 2 |
| 15D.4.2-1 | Sequence of Events – RWE Drift in Power Range Unit 2 |
| 15D.4.5-1 | Sequence of Events for Recirculation Flow Controller Failure Unit 2 |
| 15D.4.7-1 | Sequence of Events for Misloaded Bundle Accident Unit 2 |
| 15D.4.9-1 | Sequence of Events for Control Rod Drop Accident Unit 2 |
| 15D.4.9-2 | Control Rod Drop Accident Unit 2 (Typical) |
| 15E.0-1 | Results Summary of Transient Events Units 1 and 2 Non-Limiting Events (Values are for the Initial Cores Only) |
| 15E.0-2 | Input Parameters and Initial Conditions for Transients Units 1 and 2 Initial Cycles |
| 15E.1.1-1 | Operator Actions When Reactor Scram is Incurred |
| 15E.1.4-1 | Sequence of Events for Inadvertent Safety Relief Valve Opening |
| 15E.1.4-2 | Safety Relief Valve Opening Event Activity Above Suppression Pool (curies) |
| 15E.1.4-3 | Safety Relief Valve Opening Event Activity Released to the Environs (curies) |
| 15E.1.4-4 | Safety Relief Valve Opening Event Offsite Radiological Doses (rems) |
| 15E.1.6-1 | Sequence of Events for Inadvertent RHR Shutdown Cooling Operation |
| 15E.2.2-1 | Sequence of Events for Figure 15E2.2-1 Generator Load Rejection, Bypass On |
| 15E.2.3-1 | Sequence of Events for Turbine Trip With Bypass Operable Figure 15E.2.3-1 |
| 15E.2.4-1 | Sequence of Events for MSIV Closure, Figure 15E.2.4-1 |
| 15E.2.5-1 | Typical Rates of Decay for Condenser Vacuum |
| 15E.2.5-2 | Loss of Condenser Vacuum Sequence of Events for Figure 15E.2.5-1 |
| 15E.2.5-3 | Trips Signals Associated With Loss of Condenser Vacuum |
| 15E.2.6-1 | Loss of Auxiliary Power Sequence of Events for Figure 15E.2.6-1 |
| 15E.2.6-2 | Loss of All Grid Connections Sequence of Events for Figure 15E.2.6-2 |
| 15E.2.7-1 | Loss of Feedwater Flow Sequence of Events for Figure 15E.2.7-1 |
| 15E.2.9-1 | Sequence of Events for Failure of RHR Shutdown Cooling |
| 15E.2.9-2 | Input Parameters for Evaluation of Failure of RHR Shutdown Cooling |

SUMMARY TABLE OF CONTENTS

Chapter 15 Tables

| | |
|-----------|--|
| 15E.3.1-1 | Sequence of Events for Trip of One Recirculation Pump |
| 15E.3.1-2 | Sequence of Events for Trip of Two Recirculation Pumps |
| 15E.4.4-1 | Sequence of Events Abnormal Startup of Idle Recirculation Pump for Figure 15E.4.4-1 |
| 15E.5.1-1 | Sequence of Events for Inadvertent Startup of HPCI |

SUMMARY TABLE OF CONTENTS**Chapter 15 Figures**

| | |
|-----------|--|
| 15.4-1 | Leakage Path for Control Rod Drop Accident |
| 15.6-1 | Leakage Path for Instrument Line Break |
| 15.6-2 | Steam Flow Schematic for Steam Break Outside Containment |
| 15.6-3 | Leakage Flow for LOCA |
| 15.6-4 | Leakage Path for Feedwater Line Break Outside Containment |
| 15.7-1 | Leakage Path for Refueling Accidents |
| 15A.2-1 | Possible Inconsistencies in the Selection of Nuclear Safety Operational Requirements |
| 15A.2-2 | Methods Used to Derive NSO Requirements System and Sub-System Level Qualitative FMEA and Design Basis Confirmation Audits and Tech. Specs. |
| 15A.4-1 | Format for Protection Sequence Diagrams |
| 15A.4-2 | Format for Safety System Auxiliary Diagrams |
| 15A.4-3 | Format for Commonality of Auxiliary Diagrams |
| 15A.6-1 | Safety System Auxiliaries |
| 15A.6-2 | Safety System Auxiliaries |
| 15A.6-3 | Safety Action Sequences for Planned Operations in State A |
| 15A.6-4 | Safety Action Sequences for Planned Operations in State B |
| 15A.6-5 | Safety Action Sequences for Planned Operations in State C |
| 15A.6-6 | Safety Action Sequences for Planned Operations in State D |
| 15A.6-7 | Protection Sequence for Manual or Inadvertent Scram |
| 15A.6-8 | Protection Sequence for Loss of Plant Instrument Air System |
| 15A.6-9 | Protection Sequence for Inadvertent Start-Up of HPCI's Pump |
| 15A.6-10 | Protection Sequences for Inadvertent Start-Up of Idle Recirculation Loop Pump |
| 15A.6-11 | Protection Sequence for Recirculation Loop Flow Control Failure - Maximum Demand |
| 15A.6-12 | Protection Sequence for Recirculation Loop Flow Control Failure – Decreasing Recirculation Loop Pump Trip - One or Both |
| 15A.6-13 | Protection Sequences for Isolation of All Main Steamlines |
| 15A.6-14a | Protection Sequences for Isolation of the One Main Steamline |
| 15A.6-14b | Protection Sequences for Isolation of the One Main Steamline |
| 15A.6-15 | Protection Sequences for Inadvertent Opening of a Safety/Relief Valve |
| 15A.6-16 | Protection Sequence for Control Rod Withdrawal Error - Startup and Refueling Operation |
| 15A.6-17 | Protection Sequence for Control Rod Withdrawal Error - Power Operation |
| 15A.6-18 | Protection Sequences for RHR'S - Loss of Shutdown Cooling Failure |
| 15A.6-19 | RHR'S - Shutdown Cooling Failure - Increased Cooling |
| 15A.6-20 | Protection Sequences for Loss of Feedwater Flow |
| 15A.6-21 | Protection Sequence for Loss of a Feedwater Heater |
| 15A.6-22 | Protection Sequences for Feedwater Controller Failure - Maximum Demand |
| 15A.6-23 | Protection Sequences for Pressure Regulator Failure - Open |
| 15A.6-24 | Protection Sequence for Pressure Regulator Failure - Closed |
| 15A.6-25 | Protection Sequences for Main Turbine Trip with Bypass |
| 15A.6-26 | Protection Sequences for Loss of Main Condenser Vacuum |
| 15A.6-27 | Protection Sequences for Main Generator Trip with Bypass |
| 15A.6-28 | Protection Sequence for Loss of Normal AC Power - Aux Transformer Failure |

SUMMARY TABLE OF CONTENTS**Chapter 15 Figures**

| | |
|-------------|---|
| 15A.6-29 | Protection Sequences for Loss of Normal AC Power - Grid Connection Loss |
| 15A.6-30 | Protection Sequences Main Generator Trip - Without Bypass |
| 15A.6-31 | Protection Sequences Main Turbine Trip – With Bypass Failure |
| 15A.6-32 | Protection Sequence for Inadvertent Loading and Operations of Fuel Assembly in Improper Position |
| 15A.6-38 | Protection Sequences for Recirculation Loop Pump Seizure |
| 15A.6-39 | Protection Sequence for Recirculation Loop Pump Shaft Break |
| 15A.6-40 | Protection Sequences for Control Rod Drop Accident |
| 15A.6-41 | Protection Sequences for Fuel Handling Accident |
| 15A.6-42 | Protection Sequences for Loss-of-Coolant Piping Breaks in RCPB - Inside Containment |
| 15A.6-43 | Protection Sequences for Liquid, Steam, Large, Small Piping Breaks Outside Containment |
| 15A.6-46 | Protection Sequences for Gaseous Radwaste System Leak or Failure |
| 15A.6-47 | Protection Sequence for Off-Gas Treatment System Failure |
| 15A.6-48 | Protection Sequence for Liquid Radwaste System Leak or Failure |
| 15A.6-49 | Protection Sequence for Liquid Radwaste System Storage Tank Failure |
| 15A.6-50 | Protection Sequence for Spent Fuel Cask Drop |
| 15A.6-51 | Protection Sequence for Reactor Shutdown - From Anticipated Transient Without Scram |
| 15A.6-52 | Protection Sequences for Reactor Shutdown - From Outside Main Control Room |
| 15A.6-53 | Protection Sequence for Reactor Shutdown - Without Control Rods |
| 15A.6-54-1 | Commonality of Auxiliary Systems - DC Power Systems (125/250 Volts) |
| 15A.6-54-2 | Event Identification For Figure 15A.6-54, Page 1 of 2 |
| 15A.6-54-3 | Event Identification For Figure 15A.6-54, Page 2 of 2 |
| 15A.6-55-1 | Commonality of Auxiliary Systems – AC Power Systems (120/480/4160 Volts) |
| 15A.6-55-2 | Event Identification For Figure 15A.6-55, Page 1 of 2 |
| 15A.6-55-3 | Event Identification For Figure 15A.6-55, Page 2 of 2 |
| 15A.6-56-1 | Commonality of Auxiliary Systems - Equipment Area Coding System |
| 15A.6-56-2 | Event Identification For Figure 15A.6-56 |
| 15A.6-57-1 | Commonality of Auxiliary Systems - Plant Service Water System |
| 15A.6-57-2 | Event Identification For Figure 15A.6-57 |
| 15A.6-58 | Commonality of Auxiliary Systems - RHR Service Water System |
| 15A.6-59-1 | Commonality of Auxiliary Systems - Suppression Pool Storage |
| 15A.6-59-2 | Event Identification For Figure 15A.6-59 |
| 15C.1.2-1-1 | Susquehanna Feedwater Controller Failure, Maximum Demand, with High Water Level Trip Unit 1 (Typical) |
| 15C.1.2-1-2 | Susquehanna Feedwater Controller Failure, Maximum Demand, with High Water Level Trip Unit 1 (Typical) |
| 15C.1.2-1-3 | Susquehanna Feedwater Controller Failure, Maximum Demand, with High Water Level Trip Unit 1 (Typical) |
| 15C.1.2-1-4 | Susquehanna Feedwater Controller Failure, Maximum Demand, with High Water Level Trip Unit 1 (Typical) |
| 15C.1.2-1-5 | Susquehanna Feedwater Controller Failure, Maximum Demand, with High Water Level Trip Unit 1 (Typical) |

SUMMARY TABLE OF CONTENTS**Chapter 15 Figures**

| | |
|-------------|---|
| 15C.1.3-1-1 | Pressure Regulator Failure – Steam Flow at 130% of Steam Flow at 3441 MWt |
| 15C.1.3-1-2 | Pressure Regulator Failure – Steam Flow 130% of Rated |
| 15C.1.3-1-3 | Pressure Regulator Failure – Steam Flow 130% of Rated |
| 15C.1.3-1-4 | Pressure Regulator Failure – Steam Flow 130% of Rated |
| 15C.1.3-1-5 | Pressure Regulator Failure – Steam Flow 130% of Rated |
| 15C.2.2-1-1 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 1 (Typical) |
| 15C.2.2-1-2 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 1 (Typical) |
| 15C.2.2-1-3 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 1 (Typical) |
| 15C.2.2-1-4 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 1 (Typical) |
| 15C.2.2-1-5 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 1 (Typical) |
| 15C.3.3-1 | Pump Seizure Accident Two Loop Operation 4031 MWth/108Mlbm/HR Core Response |
| 15C.3.3-2 | Pump Seizure Accident Two Loop Operation 4031 MWth/108Mlbm/HR Typical CPR Response |
| 15C.3.3-3 | Pump Seizure Accident Single Loop Operation 2652 MWth/52Mlbm/HR Core Response |
| 15C.3.3-4 | Pump Seizure Accident Single Loop Operation 2652 MWth/52Mlbm/HR Typical CPR Response |
| 15D.1.2-1-1 | Susquehanna Feedwater Controller Failure, Maximum Demand, With High Water Level Trip Unit 2 (Typical) |
| 15D.1.2-1-2 | Susquehanna Feedwater Controller Failure, Maximum Demand, With High Water Level Trip Unit 2 (Typical) |
| 15D.1.2-1-4 | Susquehanna Feedwater Controller Failure, Maximum Demand, With High Water Level Trip Unit 2 (Typical) |
| 15D.1.2-1-5 | Susquehanna Feedwater Controller Failure, Maximum Demand, With High Water Level Trip Unit 2 (Typical) |
| 15D.1.3-1 | Pressure Regulator Failed Open – Typical of Unit 2 |
| 15D.2.2-1-1 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 2 (Typical) |
| 15D.2.2-1-2 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 2 (Typical) |
| 15D.2.2-1-4 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 2 (Typical) |
| 15D.2.2-1-5 | Susquehanna Generator Load Reject Without Bypass and Turbine Trip Without Bypass Unit 2 (Typical) |
| 15D.3.3-5 | Pump Seizure Accident Two Loop Operation Typical of Unit 2 |
| 15D.3.3-6 | Pump Seizure Accident Single Loop Operation Typical of Unit 2 |
| 15E.0-1 | Typical Power/Flow Map |
| 15E.0-2 | Scram Position and Reactivity Characteristics |
| 15E.2.2-1 | Susquehanna Generator Load Rejection, With Bypass On |

SUMMARY TABLE OF CONTENTS**Chapter 15 Figures**

| | |
|-------------|---|
| 15E.2.3-1 | Turbine Trip, Trip Scram, Bypass and RPT On |
| 15E.2.4-1 | Three-Second Closure of All MSIV's With Position Switch Scram Trip |
| 15E.2.5-1 | Loss of Condenser Vacuum at 2 Inches Per Second |
| 15E.2.6-1 | Loss of Auxiliary Power Transformer |
| 15E.2.6-2 | Loss of All Grid Connections |
| 15E.2.7-1 | Loss of All Feedwater Flow |
| 15E.2.7-2 | Loss of Feedwater Core Power, Heat Flux and Core Flow |
| 15E.2.7-3 | Loss of Feedwater, Feedwater Flow Steam Flow and RCIC Flow |
| 15E.2.9-1-1 | ADS/RHR Cooling Loops |
| 15E.2.9-1-2 | Notes for Figure 15E.2.9-1-1 |
| 15E.2.9-1-3 | Notes for Figure 15E.2.9-1-1 |
| 15E.2.9-2 | Summary of Paths Available to Achieve Cold Shutdown |
| 15E.2.9-3 | Vessel Temperature and Pressure Versus Time (Activity C1 or C2) |
| 15E.2.9-4 | Suppression Pool Temperature Versus Time (90° Service Water Temperature) Capacity C1 or C2 |
| 15E.2.9-5 | Activity C1 Alternate Shutdown Cooling Path Utilizing RHR Loop B |
| 15E.2.9-6 | Activity C2 Alternate Shutdown Cooling Path Utilizing RHR Loop A |
| 15E.3.1-1 | Trip of One Recirculation Pump Motor |
| 15E.3.1-2 | Trip of Both Recirculation Pump Motors |
| 15E.4.4-1 | Startup of Idle Recirculation Loop Pump |
| 15E.5.1-1 | Inadvertent Startup of HPCI |

SUMMARY TABLE OF CONTENTS

Chapter 16

16.0 TECHNICAL SPECIFICATIONS

- 16.1 Preliminary Technical Specifications
- 16.2 Proposed Final Technical Specifications
- 16.3 Technical Requirements Manuals

SUMMARY TABLE OF CONTENTS

Chapter 17

17.0 **QUALITY ASSURANCE**

- 17.1 Quality Assurance During Design and Construction
- 17.2 Quality Assurance During the Operations Phase
 - 17.2.0 Introduction
 - 17.2.1 Organization
 - 17.2.2 Quality Assurance Program
 - 17.2.3 Design Control
 - 17.2.4 Procurement Document Control
 - 17.2.5 Instructions, Procedures, and Drawings
 - 17.2.6 Document Control
 - 17.2.7 Control of Purchased Material, Equipment, and Services
 - 17.2.8 Identification and Control of Materials, Parts, and Components
 - 17.2.9 Control of Special Processes
 - 17.2.10 Inspection
 - 17.2.11 Test Control
 - 17.2.12 Control of Measuring and Test Equipment
 - 17.2.13 Handling, Storage, and Shipping
 - 17.2.14 Inspection, Test, and Operating Status
 - 17.2.15 Nonconforming Materials, Parts, or Components
 - 17.2.16 Corrective Action
 - 17.2.17 Quality Assurance Records
 - 17.2-18 Audits

SUMMARY TABLE OF CONTENTS

Chapter 17 Tables

| | |
|--------|---|
| 17.2-1 | Quality Assurance Program Description Compliance Matrix |
| 17.2-2 | Operational Policy Statement Cross Reference Matrix with 10CFR50 Appendix B Criteria |

SUMMARY TABLE OF CONTENTS

Chapter 17 Figures

| | |
|--------|---|
| 17.2-1 | Hierarchy of Operational Quality Assurance Documents |
| 17.2-2 | Talen Energy Corporation Management Organization Applicable to Susquehanna SES |
| 17.2-3 | Susquehanna Nuclear, LLC Management Organization |
| 17.2-4 | Nuclear Oversight Organization |

SUMMARY TABLE OF CONTENTS**Chapter 18****18.0 RESPONSES TO TMI RELATED REQUIREMENTS**

- 18.0 Organization
- 18.1 Response to Requirements in NUREG 0737
 - 18.1.1 Shift Technical Advisor (I.A.1.1)
 - 18.1.2 Shift Supervisor Responsibilities (I.A.1.2)
 - 18.1.3 Shift Manning (I.A.1.3)
 - 18.1.4 Immediate Upgrading Of Reactor Operator and Senior Reactor Operator Training and Qualifications (I.A.2.1)
 - 18.1.5 Administration of Training Programs (I.A.2.3)
 - 18.1-6 Revise Scope And Criteria for Licensing Examinations (I.A.3.1)
 - 18.1.7 Evaluation Of Organization and Management (I.B.1.2)
 - 18.1.8 Short-Term Accident and Procedure Review (I.C.1)
 - 18.1-9 Shift Relief and Turnover Procedures (I.C.2)
 - 18.1.10 Shift Supervisor Responsibility (I.C.3)
 - 18.1.11 Control Room Access (I.C.4)
 - 18.1.12 Feedback Of Operating Experience (I.C.5)
 - 18.1.13 Verify Correct Performance of Operating Activities (I.C.6)
 - 18.1.14 NSSS Vendor Review of Procedures (I.C.7)
 - 18.1.15 Pilot Monitoring of Selected Emergency Procedures for Near Term Operating Licenses (I.C.8)
 - 18.1.16 Control Room Design Review (I.D.1)
 - 18.1.17 Plant Safety Parameter Display System (I.D.2)
 - 18.1.18 Training During Low-Power Testing (I.G.1)
 - 18.1.19 Reactor Coolant System Vents (II.B.1)
 - 18.1.20 Plant Shielding (II.B.2)
 - 18.1.21 Post-Accident Sampling (II.B.3)
 - 18.1.22 Training For Mitigating Core Damage (II.B.4)
 - 18.1.23 Relief and Safety Valve Test Requirements (II.D.1)
 - 18.1.24 Safety/Relief Valve Position Indication (II.D.3)
 - 18.1.25 Auxiliary Feedwater System Evaluation (II.E.1.1)
 - 18.1.26 Auxiliary Feedwater System Initiation And Flow (II.E.1.2)
 - 18.1.27 Emergency Power for Pressurizer Heaters (II.E.3.1)
 - 18.1.28 Dedicated Hydrogen Penetrations (II.E.4.1)
 - 18.1.29 Containment Isolation Dependability (II.E.4.2)
 - 18.1.30 Accident-Monitoring Instrumentation (II.F.1)
 - 18.1.31 Instrument for Detection of Inadequate Core Cooling (II.F.2)
 - 18.1.32 Emergency Power for Pressurizer Equipment (II.G.1)
 - 18.1.33 Review ESF Valves (II.K.1.5)
 - 18.1.34 Operability Status (II.K.1.10)
 - 18.1.35 Trip Pressurizer Low-Level Coincident Signal Bistables (II.K.1.17)
 - 18.1.36 Operator Training for Prompt Manual Reactor Trip (II.K.1.20)
 - 18.1.37 Automatic Safety Grade Anticipatory Reactor Trip (II.K.1.21)
 - 18.1.38 Auxiliary Heat Removal System Procedures (II.K.1.22)
 - 18.1.39 Reactor Vessel Level Procedures (II.K.1.23)
 - 18.1.40 Commission Orders On Babcock and Wilcox Plants (II.K.2)

SUMMARY TABLE OF CONTENTS**Chapter 18**

- 18.1.41 Automatic Power-Operated Relief Valve Isolation System (II.K.3.1)
- 18.1.42 Report On Power-Operated Relief Valve Failures (II.K.3.2)
- 18.1.43 Reporting Safety/Relief Valve Failures and Challenges (II.K.3.3)
- 18.1.44 Automatic Trip of Reactor Coolant Pumps During A LOCA (II.K.3.5)
- 18.1.45 Evaluation of Power-Operated Relief Valve Opening Probability (II.K.3.7)
- 18.1.46 Proportional Integral Derivative Controller Modification (II.K.3.9)
- 18.1.47 Proposed Anticipatory Trip Modification (II.K.3.10)
- 18.1.48 Power-Operated Relief Valve Failure Rate (II.K.3.11)
- 18.1.49 Anticipatory Reactor Trip on Turbine Trip (II.K.3.12)
- 18.1.50 Separation Of High Pressure Coolant Injection and Reactor Core Isolation Cooling System Initiation Levels (II.K.3.13)
- 18.1.51 Modify Break-Detection Logic to Prevent Spurious Isolation of High Pressure Coolant Injection and Reactor Core Isolation Cooling (II.K.3.15)
- 18.1.52 Reduction of Challenges and Failures of Relief Valves (II.K.3.16)
- 18.1.53 Report On Outages Of Emergency Core Cooling Systems (II.K.3.17)
- 18.1.54 Modification of Automatic Depressurization System Logic (II.K.3.18)
- 18.1.55 Restart of Core Spray And Low Pressure Coolant Injection Systems (II.K.3.21)
- 18.1.56 Automatic Switchover of Reactor Core Isolation Cooling System Suction (II.K.3.22)
- 18.1.57 Confirm Adequacy of Space Cooling For High Pressure Coolant Injection and Reactor Core Isolation Cooling Systems (II.K.3.24)
- 18.1.58 Effect of Loss of Alternating-Current Power on Recirculation Pump Seals (II.K.3.25)
- 18.1.59 Provide A Common Reference Level for Vessel Level Instrumentation (II.K.3.27)
- 18.1.60 Verify Qualification of Accumulators on Automatic Depressurization System Valves (II.K.3.28)
- 18.1.61 Revised Small-Break Loss of Coolant Accident Methods (II.K.3.30)
- 18.1.62 Plant-Specific Calculations To Show Compliance with 10CFR Part 50.46 (II.K.3.31)
- 18.1.63 Evaluation of Anticipated Transients with Single Failure To Verify No Fuel Cladding Failure (II.K.3.44)
- 18.1.64 Evaluation of Depressurization With Other Than The Automatic Depressurization System (II.K.3.45)
- 18.1.65 Michelsen Concerns (II.K.3.46)
- 18.1.66 Emergency Preparedness - Short Term (III.A.1.1)
- 18.1.67 Upgrade Emergency Support Facilities (III.A.1.2)
- 18.1.68 Emergency Preparedness - Long Term (III.A.2)
- 18.1.69 Integrity Of Systems Outside Containment Likely To Contain Radioactive Material (III.D.1.1)
- 18.1.70 Inplant Iodine Radiation Monitoring (III.D.3.3)
- 18.1.71 Control Room Habitability Requirements (III.D.3.4)
- 18.1.72 References

- 18.2 Response to Requirements in NUREG 0694
- 18.2.1 Shift Technical Advisor (I.A.1.1)

SUMMARY TABLE OF CONTENTS**Chapter 18**

- 18.2.2 Shift Supervisor Administrative Duties (I.A.1.2)
- 18.2.3 Shift Manning (I.A.1.3)
- 18.2.4 Immediate Upgrading Of Operator And Senior Operator Training And Qualification (I.A.2.1)
- 18.2.5 Revise Scope And Criteria For Licensing Examinations (I.A.3.1)
- 18.2.6 Evaluation Of Organization And Management Improvements Of Near-Term Operating License Applicants (I.B.1.2)
- 18.2.7 Short-Term Accident Analysis And Procedure Revision (I.C.1)
- 18.2.8 Shift Relief And Turnover Procedures (I.C.2)
- 18.2.9 Shift Supervisor Responsibilities (I.C.3)
- 18.2.10 Control Room Access (I.C.4)
- 18.2.11 Procedures For Feedback Of Operating Experience To Plant Staff (I.C.5)
- 18.2.12 NSSS Vendor Review Of Procedures (I.C.7)
- 18.2.13 Pilot Monitoring Of Selected Emergency Procedures Near-Term Operating License Applicants (I.C.8)
- 18.2.14 Control Room Design (I.D.1)
- 18.2.15 Training During Low Power Testing (I.G.1)
- 18.2.16 Reactor Coolant System Vents (II.B.1)
- 18.2.17 Plant Shielding (II.B.2)
- 18.2.18 Post-Accident Sampling (II.B.3)
- 18.2.19 Training For Mitigating Core Damage (II.B.4)
- 18.2.20 Relief And Safety Valve Test Requirements (II.D.1)
- 18.2.21 Relief And Safety Valve Position Indication (II.D.3)
- 18.2.22 Containment Isolation Dependability (II.E.4.2)
- 18.2.23 Additional Accident Monitoring Instrumentation (II.F.1)
- 18.2.24 Inadequate Core Cooling Instruments (II.F.2)
- 18.2.25 Assurance Of Proper ESF Functioning (II.K.1.5)
- 18.2.26 Safety Related System Operability Status (II.K.1.10)
- 18.2.27 Trip Pressurizer Low-Level Coincident Signal Bistables (II.K.1.17)
- 18.2.28 Operator Training For Prompt Manual Reactor Trip (II.K.1.20)
- 18.2.29 Automatic Safety Grade Anticipatory Trip (II.K.1.21)
- 18.2.30 Auxiliary Heat Removal Systems Operating Procedures (II.K.1.22)
- 18.2.31 Reactor Level Instrumentation (II.K.1.23)
- 18.2.32 Commission Orders On Babcock And Wilcox Plants (II.K.2)
- 18.2.33 Reporting Requirements For Safety/Relief Valve Failures Or Challenges (II.K.3.3)
- 18.2.34 Proportional Integral Derivative Controller (II.K.3.9)
- 18.2.35 Anticipatory Reactor Trip Modification (II.K.3.10)
- 18.2.36 Power Operated Relief Valve Failure Rate (II.K.3.11)
- 18.2.37 Anticipatory Reactor Trip on Turbine Trip (II.K.3.12)
- 18.2.38 Emergency Preparedness-Short Term (II.A.1.1)
- 18.2.39 Upgrade Emergency Support Facilities (III.A.1.2)
- 18.2.40 Primary Coolant Sources Outside Containment (III.D.1.1)
- 18.2.41 Inplant Radiation Monitoring (III.D.3.3)
- 18.2.42 Control Room Habitability (III.D.3.4)

SUMMARY TABLE OF CONTENTS**Chapter 18 Tables**

| | |
|---------|---|
| 18.1-1 | Interim Required Shift Staffing |
| 18.1-2 | Initial Core Isotopic Inventory |
| 18.1-3 | Post Accident Radiation Zone Classification |
| 18.1-4 | Vital Areas |
| 18.1-5 | Principal Dose Rate Contributors in Plant Area |
| 18.1-8 | Training Criteria for Mitigating Core Damage |
| 18.1-9 | Mitigating Core Damage Course Outline |
| 18.1-10 | Containment Isolation Actuation Provision |
| 18.1-11 | Essential/Non-Essential Penetration Classification Basis |
| 18.1-12 | Actuation/Isolation Signal Codes and Corresponding Actuating Switches |
| 18.1-13 | Meteorological Information |
| 18.1-17 | Information Required for Control Room Habitability Evaluation |
| 18.1-18 | Possible ICC Detection Devices |
| 18.2-1 | Testing Program Outline |

SUMMARY TABLE OF CONTENTS**Chapter 18 Figures**

| | |
|---------|---|
| 18.1-1 | Radiation Levels for the Site Plan |
| 18.1-2 | Radiation Levels for the Site Plan Elevations 646'-0," 645'0," and 656'-0" |
| 18.1-3 | Radiation Levels for Elevations 670'-0" and 676'-0" |
| 18.1-4 | Radiation Levels for Elevations 683'-0," 699'-0," 714'-0," and 716'-3" |
| 18.1-5 | Radiation Levels for Elevations 719'-1," 729'-0," and 741'-1" |
| 18.1-6 | Radiation Levels for Elevations 749'-1," 754'-0," 762'-0," 771'-0," and 783'-0" |
| 18.1-7 | Radiation Levels for Elevations 779'-1," 799'-1," and 806'-0" |
| 18.1-8 | Radiation Levels for Elevations 818'-1" and 872'-4 1/2" |
| 18.1-12 | Typical HPCI RCIC Steamline Break Detection Logic |
| 18.1-13 | Typical Reactor Water Level Display |
| 18.1-14 | Downcomer Water Level History |
| 18.1-15 | Water Level as an Indicator of Core Overheating |
| 18.1-16 | Cladding Temperature Sensitivity to Core Recovery Time |

SUMMARY TABLE OF CONTENTS**Chapter – Responses to NRC Questions**

NOTE 1: 040, 281, and 441 questions concerning fire protection may be found in the FPRR

NOTE 2: Any 040 questions which contain "X10" in the question numbers were initiated by the Oak Ridge National Laboratories

| <u>Branch No.</u> | <u>Branch Title</u> |
|-------------------|--|
| 005 | Auxiliary System |
| 010 | Auxiliary Systems |
| 021 | Containment Systems |
| 032 | Instrumentation and Control Systems |
| 040 | Power Systems |
| 110 | Mechanical Engineering |
| 112 | Mechanical Engineering |
| 121 | Materials Engineering Branch-Materials Integrity Section |
| 123 | Structural and Geosciences Branch |
| 130 | Structural Engineering |
| 211 | Reactor Systems |
| 221 | Analysis Branch-Reactor Analysis Section |
| 222 | Analysis Branch-System Analysis Section |
| 230 | Core Performance Branch |
| 231 | Core Performance Branch-Reactor Fuels Section |
| 232 | Core Performance Branch-Reactor Physics Section |
| 260 | Quality Assurance Branch |
| 281 | Chemical Engineering Branch |
| 312 | Accident Analysis |
| 313 | Accident Analysis Branch-Emergency Planning |
| 321 | Effluent Treatment Systems |
| 331 | Radiological Assessment |
| 361 | Geosciences Branch-Seismology Geology Section |
| 362 | Geosciences Branch-Foundation Engineering Section |
| 371 | Hydrology-Meteorology Branch-Hydrology Section |
| 372 | Hydrology-Meteorology Branch-Meteorology Section |
| 400 | Project Management |
| 410 | Licensee Qualification Branch |
| 421 | Quality Assurance-Operations |
| 422 | Licensee Qualification Branch |
| 423 | Quality Assurance Branch-Initial Test Program |
| 440 | Operator Licensing |
| 441 | Operator Licensing Branch-Training |
| 442 | Operator Licensing Branch-Procedures |
| 500 | Security |