

Facility: Braidwood Crew 1			Date of Exam: 5/29/18			Operating Test No.: 17-1 NRC												
A P P L I C A N T	E V E N T T Y P E	Scenarios													T O T A L	M I N I M U M (*)		
		1			2			3			4							
		CREW POSITION			CREW POSITION			CREW POSITION			CREW POSITION							
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	R		I	U	
RO <input checked="" type="checkbox"/>	RX		1											1	1	1	0	
SRO-I <input type="checkbox"/>	NOR					1			1					2	1	1	1	
SRO-U <input type="checkbox"/>	I/C		2			2			2					6	4	4	2	
	MAJ		2			2			1					5	2	2	1	
	TS														0	2	2	
RO <input type="checkbox"/>	RX					1			1					2	1	1	0	
SRO-I <input checked="" type="checkbox"/>	NOR			1					1					2	1	1	1	
SRO-U <input type="checkbox"/>	I/C			2		2			4					8	4	4	2	
	MAJ			2		2			1					5	2	2	1	
	TS								3					3	0	2	2	
RO <input type="checkbox"/>	RX	1			1				1					3	1	1	0	
SRO-I <input checked="" type="checkbox"/>	NOR	1												1	1	1	1	
SRO-U <input type="checkbox"/>	I/C	4			4				2					10	4	4	2	
	MAJ	2			2				1					5	2	2	1	
	TS	3			2									5	0	2	2	
RO <input type="checkbox"/>	RX														1	1	0	
SRO-I <input type="checkbox"/>	NOR														1	1	1	
SRO-U <input type="checkbox"/>	I/C														4	4	2	
	MAJ														2	2	1	
	TS														0	2	2	

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the at-the-controls (ATC) and balance-of-plant (BOP) positions. Instant SROs (SRO-I) must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an SRO-I *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional I/C malfunctions on a one-for-one basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.
- For new reactor facility licensees that use the ATC operator primarily for monitoring plant parameters, the chief examiner may place SRO-I applicants in either the ATC or BOP position to best evaluate the SRO-I in manipulating plant controls.

Facility: Braidwood Crew 2&3			Date of Exam: 5/29/18			Operating Test No.: 17-1 NRC												
A P P L I C A N T	E V E N T T Y P E	Scenarios													T O T A L	M I N I M U M (*)		
		1			2			3			4							
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N							
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P					
RO <input checked="" type="checkbox"/>	RX		1											1	1	1	0	
SRO-I <input type="checkbox"/>	NOR					1			1					2	1	1	1	
SRO-U <input type="checkbox"/>	I/C		2			2			2					6	4	4	2	
	MAJ		2			2			1					5	2	2	1	
	TS														0	2	2	
RO <input checked="" type="checkbox"/>	RX					1								1	1	1	0	
SRO-I <input type="checkbox"/>	NOR			1										1	1	1	1	
SRO-U <input type="checkbox"/>	I/C			2		2								4	4	4	2	
	MAJ			2		2								4	2	2	1	
	TS														0	2	2	
RO <input type="checkbox"/>	RX	1			1				1					3	1	1	0	
SRO-I <input checked="" type="checkbox"/>	NOR	1												1	1	1	1	
SRO-U <input type="checkbox"/>	I/C	4			4				2					10	4	4	2	
	MAJ	2			2				1					4	2	2	1	
	TS	3			2									5	0	2	2	
RO <input type="checkbox"/>	RX														1	1	0	
SRO-I <input type="checkbox"/>	NOR														1	1	1	
SRO-U <input type="checkbox"/>	I/C														4	4	2	
	MAJ														2	2	1	
	TS														0	2	2	

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the at-the-controls (ATC) and balance-of-plant (BOP) positions. Instant SROs (SRO-I) must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an SRO-I *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional I/C malfunctions on a one-for-one basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.
- For new reactor facility licensees that use the ATC operator primarily for monitoring plant parameters, the chief examiner may place SRO-I applicants in either the ATC or BOP position to best evaluate the SRO-I in manipulating plant controls.