NRC FORM 374

PAGE 1 OF 5 PAGES Amendment No. 26

U.S. NUCLEAR REGULATORY COMMISSION

MATERIALS LICENSE

Pursuant to the Atomic Energy Act of 1954, as amended, the Energy Reorganization Act of 1974 (Public Law 93-438), and Title 10, Code of Federal Regulations, Chapter I, Parts 30, 31, 32, 33, 34, 35, 36, 37, 39, 40, 70 and 71, and in reliance on statements and representations heretofore made by the licensee, a license is hereby issued authorizing the licensee to receive, acquire, possess, and transfer byproduct, source, and special nuclear material designated below; to use such material for the purpose(s) and at the place(s) designated below; to deliver or transfer such material to persons authorized to receive it in accordance with the regulations of the applicable Part(s). This license shall be deemed to contain the conditions specified in Section 183 of the Atomic Energy Act of 1954, as amended, and is subject to all applicable rules, regulations, and orders of the Nuclear Regulatory Commission now or hereafter in effect and to any conditions specified below.

Licensee 1. Anderson Engineering, Inc.			In accordance with letter dated November 10, 2023,		4. Expiration Date: December 31, 20375. Docket No.: 030-17919			
2.	3213 S. West Byp. Springfield, MO 65807		ES A		ded in	: 24-20063-01 is its entirety to read as	Refe	erence No.:
6.	Byproduct, source, and/or special nuclear material	7.	Chemical and/or physical fo	irm	78.	Maximum amount that licens may possess at any one time under this license		Authorized use
A.	Cesium-137	A.	Sealed Sources (AEA Technology/QSA, Inc., M CDC.W556; Isotope Pro Laboratories, Model HEC	duct	А.	9 millicuries per source and 108 millicuries total	А.	For use in Troxler Electronic Laboratories Model 3400 Series portable gauges for measuring physical properties of materials.
В.	Americium-241/ Beryllium	B.	Sealed Sources (AEA Technology/QSA, Inc., M AMN.V997; Isotope Proc Laboratories, Model Am1	luct	ЦВ.	44 millicuries per source and 528 millicuries total	В.	For use in Troxler Electronic Laboratories Model 3400 Series portable gauges for measuring physical properties of materials.
C.	Cesium-137	C.	Sealed Sources (CPN, M CPN-131)	lodel	C.	10 millicuries per source and 90 millicuries total	C.	For use in CPN International Division of InstroTek, Inc. Model MC Series PORTAPROBE portable gauges for measuring physical properties of materials.

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMM	MISSION PAGE 2 OF 5 PAGES
MATERIALS LICENSE SUPPLEMENTARY SHEET	License No.: 24-20063-01 Amendment No. 26	Docket or Reference No.: 030-17919
6. Byproduct, source, 7. Chemical and and/or special nuclear material D. Americium-241/ D. Sealed Sour CPN-131)	ces (CPN, Model CPN, M	 mount that licensee s at any one time ense es per source illicuries total D. For use in CPN International Division of InstroTek, Inc. Model MC Series PORTAPROBE portable gauges for measuring physical properties of materials.

NRC FORM 374A	U.S. NUCLEAR REGULATORY CO	PAGE 3 OF 5 PAGES	
MATERIALS LICENSE	License No.: 24-20063-01 Docket or Reference No.: 030-17919		
SUPPLEMENTARY SHEET	Amendment No. 26		

CONDITIONS

10. Licensed material shall be used or stored at the licensee's facilities located at

A. 915 E. 3rd St., Joplin, Missouri, 66801

B. 3213 S. West Byp., Springfield, Missouri, 65807

Licensed material may be used at temporary job sites of the licensee anywhere in the United States where the U.S. Nuclear Regulatory Commission maintains jurisdiction for regulating the use of licensed material, including areas of exclusive Federal jurisdiction within Agreement States. If the jurisdiction status of a Federal facility within an Agreement State is unknown, the licensee should contact the Federal agency controlling the job site in question to determine whether the proposed job site is an area of exclusive Federal jurisdiction. Authorization for use of radioactive materials at job sites in Agreement States not under exclusive Federal jurisdiction should be obtained from the appropriate state regulatory agency.

- 11. Licensed material shall only be used by, or under the supervision and in the physical presence of, individuals who have received the training described in the letter dated December 5, 2022. The licensee shall maintain records of individuals designated as users for 3 years following the last use of licensed material by the individual.
- 12. The Radiation Safety Officer (RSO) for this license is Tyler Lukachick.
- 13. A. Sealed sources and detector cells shall be tested for leakage and/or contamination at intervals not to exceed the intervals specified in the certificate of registration issued by the U.S. Nuclear Regulatory Commission under 10 CFR 32.210 or by an Agreement State. In the absence of a registration certificate, sealed sources shall be tested for leakage and/or contamination at intervals not to exceed 6 months, or at such other intervals as specified.
 - B. In the absence of a certificate from a transferor indicating that a leak test has been made within the intervals specified in the certificate of registration issued by the U.S. Nuclear Regulatory Commission under 10 CFR 32.210 or by an Agreement State, prior to the transfer, a sealed source received from another person shall not be put into use until tested and the test results received.

NRC FORM 374A	U.S. NUCLEAR REGULATORY	PAGE 4 OF 5 PAGES	
MATERIALS LICENSE	License No.: 24-20063-01	Docket or Reference No.: 030-17919	
SUPPLEMENTARY SHEET	Amendment No. 26		
C Scaled sources need not be teste	d if they are in stars and are not be	ing used However, when they are re-	amound from storage for

- C. Sealed sources need not be tested if they are in storage and are not being used. However, when they are removed from storage for use or transferred to another person, and have not been tested within the required leak test interval, they shall be tested before use or transfer. No sealed source shall be stored for a period of more than 10 years without being tested for leakage and/or contamination.
- D. The leak test shall be capable of detecting the presence of 185 becquerels (0.005 microcuries) of radioactive material on the test sample. If the test reveals the presence of 185 becquerels (0.005 microcuries) or more of removable contamination, a report shall be filed with the U.S. Nuclear Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall be removed immediately from service and decontaminated, repaired, or disposed of in accordance with Commission regulations.
- E. Analysis of leak test samples and/or contamination shall be performed by persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is authorized to collect leak test samples but not perform the analysis.
- F. Records of leak test results shall be kept in units of becquerels (microcuries) and shall be maintained for 3 years.
- 14. Sealed sources or source rods containing licensed material shall not be opened or sources removed from source holders or detached from source rods by the licensee, except as specifically authorized.
- 15. The licensee shall conduct a physical inventory every 6 months, or at other intervals approved by the U.S. Nuclear Regulatory Commission, to account for all sealed sources and/or devices received and possessed under the license. Records of inventories shall be maintained for 3 years from the date of each inventory, and shall include the radionuclides, quantities, manufacturer's name and model numbers, and the date of the inventory.
- 16. Except for maintaining labeling as required by 10 CFR Part 20, or Part 71, the licensee shall obtain authorization from the U.S. Nuclear Regulatory Commission before making any changes in the sealed source, device, or source-device combination that would alter the description or specifications as indicated in the respective certificate of registration issued either by the U.S. Nuclear Regulatory Commission pursuant to 10 CFR 32.210 or by an Agreement State.

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMM	ISSION	PAGE 5 OF 5 PAGES
	License No.: 24-20063-01	Docket or Reference No.:	
MATERIALS LICENSE		030-17919	
SUPPLEMENTARY SHEET	Amendment No. 26		

17. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gauge or its container must be locked when in transport or storage, or when not under the EAR REGI direct surveillance of an authorized user.

18. Any cleaning, maintenance, or repair of the gauge(s) that requires detaching the source or source rod from the gauge shall be performed only by the manufacturer or by other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services.

19. Except as specifically provided otherwise in this license, the licensee shall conduct its program in accordance with the statements, representations, and procedures contained in the documents, including any enclosures, listed below. This license condition applies only to those statements, representations, and procedures that are required to be submitted in accordance with the regulations. The U.S. Nuclear Regulatory Commission's regulations shall govern unless the statements, representations, and procedures in the licensee's application and correspondence impose on the licensee requirements that are more restrictive than or in addition to the regulations.

A. Letter dated December 5, 2022 (ML22350A100)

NOISS NOISS B. Letter dated November 10, 2023 (ML23317A208)

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

Date: January 8, 2024

By:

Jason M. Kelly, MPH, CPH Health Physicist Region III