

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

| 1 a. CERTIFICATE NUMBER | b. REVISION NUMBER | c. DOCKET NUMBER | d. PACKAGE IDENTIFICATION NUMBER | PAGE | PAGE |
|-------------------------|--------------------|------------------|----------------------------------|------|------|
| 9291 | 12 | 71-9291 | USA/9291/B(U)F-96 | 1 OF | 3 |

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- | | |
|--|--|
| a. ISSUED TO (<i>Name and Address</i>) TN Americas LLC 7160 Riverwood Drive, Suite 200 Columbia, MD 21046 | b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION TN Americas LLC, application dated June 2024 |
|--|--|

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

- (a) Packaging
- (1) Model No.: Liqui-Rad (LR) Transport Unit Package
 - (2) Description

The LR Package is designed to transport Type B quantities of fissile uranyl nitrate solutions. The package uses thermal and impact limiting systems to protect the containment vessel and prevent the contents from being released. The primary structural components of the LR packaging consist of a stainless-steel containment vessel, a carbon steel outer vessel and a carbon steel framing system. The containment vessel is built in accordance with ASME Pressure Vessel Code (Section VIII, Division 1) but does not require an ASME stamp. Double O-ring seals on the containment vessel's primary and secondary lids provide a leak tight seal which is leak testable. A closed-cell phenolic foam or polyurethane foam surrounds the top and bottom head area of the containment vessel and ceramic fiber blanket and board insulation are used in the sidewalls and outer lid for thermal insulation and impact absorption. The maximum volume of the contents is limited to 230 gallons which maintains a minimum ullage of 33 gallons.

The LR is a cylindrical package set in a rectangular angle frame. The dimensions of the package are approximately 56 inches long (l) x 56 inches wide (w) x 73 inches high (h). The maximum weight of the package is 5,692 pounds. The outer vessel is constructed of 10-gauge carbon steel. The containment vessel is constructed of ¼ - inch stainless steel with ¼ - inch thick flanged and dished heads. The containment vessel is rated at 50 psig pressure. Closed-cell phenolic or polyurethane foam and ceramic fiber insulation are sandwiched between the containment vessel and the package's outer shell.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

| | | | | | |
|--------------------------|--------------------|------------------|----------------------------------|------|------|
| 1. a. CERTIFICATE NUMBER | b. REVISION NUMBER | c. DOCKET NUMBER | d. PACKAGE IDENTIFICATION NUMBER | PAGE | PAGE |
| 9291 | 12 | 71-9291 | USA/9291/B(U)F-96 | 2 OF | 3 |

5.(a)(2) Description (Continued)

The package is designed to be leak-tight [maximum allowable leak rate of 1×10^{-7} ref-cubic centimeters per second (cm^3/s)]. The containment vessel is closed using a double O-ring and is secured by sixteen 5/8 - inch stainless steel studs. The outer lid is closed with twelve 5/8 - inch stainless steel studs and the Manual Vent Enclosure (MVE) lid is secured with four 5/8 - inch stainless steel bolts and nuts. The package is also equipped with plastic plugs to vent any gases that may be generated by the insulation during a fire event. All valves and fittings are provided within sealed enclosures to contain any leakage during valve failure.

(3) Drawings

The packaging is constructed and assembled in accordance with Drawing No. LR-SAR, "Liqui-Rad Transport Unit" (4 sheets) Rev. 11.

5.(b) Contents

(1) Type and form of material

Low enriched Uranyl Nitrate solutions with the specifications shown in Table 1 below. The uranium concentration must be less than or equal to 125 grams of Uranium per liter (gU/l) with an enrichment less than or equal to 5.0 wt.% ^{235}U . Non-fissile chemical impurities may be present up to the chemical impurity specification in Table 1. Additionally, fissile isotopes are also limited to the quantities in Table 1.

(2) Maximum quantity of material per package

230 gallons of Uranyl Nitrate solution with limits as shown in Table 1.

Table 1

| ITEM | SPECIFICATION |
|-----------------------|--|
| Solution Density | $\leq 1.17 \text{ g/cm}^3$ |
| Chemical Impurities | $\leq 1,500 \text{ } \mu\text{g/gU}$ |
| Nitric Acid Normality | 0.1 - 0.7 |
| Uranium Concentration | $\leq 125 \text{ gU/l}$ |
| ^{232}U | $\leq 2.0 \times 10^{-3} \text{ } \mu\text{g/gU}$ |
| ^{234}U | $\leq 2.0 \times 10^3 \text{ } \mu\text{g/gU}$ |
| ^{235}U | $\leq 0.05 \text{ g/gU}$ (12 pounds maximum quantity of ^{235}U per LR) |
| ^{236}U | $\leq 2.5 \times 10^4 \text{ } \mu\text{g/gU}$ |
| ^{238}U | remainder of uranium |

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

| | | | | | |
|--------------------------|--------------------|------------------|----------------------------------|------|------|
| 1. a. CERTIFICATE NUMBER | b. REVISION NUMBER | c. DOCKET NUMBER | d. PACKAGE IDENTIFICATION NUMBER | PAGE | PAGE |
| 9291 | 12 | 71-9291 | USA/9291/B(U)F-96 | 3 OF | 3 |

5.(b)(2) Maximum quantity of material per package (Continued)

| ITEM | SPECIFICATION |
|----------------------|-------------------------------|
| Pu/Np Alpha Activity | ≤ 93 Becquerel/gU |
| Gamma Emitters | 0.515×10^{-1} Curies |

(c) Criticality Safety Index 0.0

6. In addition to the requirements of Subpart G of 10 CFR Part 71:

- (a) The package must be prepared for shipment and operated in accordance with the Operating Procedures in Chapter 7 of the application.
- (b) Each packaging must be acceptance tested and maintained in accordance with the Acceptance Tests and Maintenance Program in Chapter 8 of the application.

7. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.

8. Packagings must be marked with Package Identification Number USA/9291/B(U)F-96.

9. Transport by air of fissile material is not authorized.

10. Expiration date: July 31, 2029.

REFERENCES

TN Americas, LLC, consolidated application dated June 2024.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

**YOIRA DIAZ-
SANABRIA**

Digitally signed by YOIRA DIAZ-
SANABRIA

Date: 2024.07.01 13:50:07 -04'00'

Yoira Diaz-Sanabria, Chief
Storage and Transportation Licensing Branch
Division of Fuel Management
Office of Nuclear Material Safety
and Safeguards

Date: July 1, 2024