

## Test Pad Construction for Site with Extensive Backfill



**NRC Regulatory Information Conference**  
March 12, 2008

**Tom McCallum**  
Vogtle Deployment Project Engineer  
Southern Nuclear Operating Company

1

---

---

---


---

---

---

---

---



- Deep soil site (1050' to rock)
- Upper 90 feet - liquefaction potential and limestone dissolution features
- Nuclear Island will sit on 50' of engineered fill

**Vogtle Site Conditions**

2

---

---

---

---

---

---

---

---



**Planned Excavation for Vogtle AP1000**

3

---

---

---

---

---

---

---

---

## Purpose of Test Pad



1. Refine backfill placement techniques
2. Measure backfill properties under field conditions

$V_s$  = Shear Wave Velocity

SASW = Spectral Analysis of Surface Waves

RCTS = Resonant Column Torsional Shear

4

---

---

---

---

---

---

---

---

## RCTS vs Test Pad



	RCTS	Test Pad
<b>Gradation</b>	Small sample (<1 cu ft)	Large volume (1500 cu yds)
<b>Compaction (Void Ratio)</b>	Compacted using lab equipment	Compacted using field procedures
<b>Confining Pressure</b>	Test apparatus	Overburden
<b>Results</b>	Discrete points	Averaged

5

---

---

---


---

---

---

---

---



Test Pad Layout

6

---

---

---


---

---

---

---

---




---

---

---


---

---

---

---

---




---

---

---

---

---

---

---

---




---

---

---

---

---

---

---

---



**Compaction in Progress**

10

---

---

---

---

---

---

---

---



**Moisture Conditioning**

11

---

---

---

---

---

---

---

---



**Surveying after Five Feet of Backfill**

12

---

---

---

---

---

---

---

---



**Density Testing Using Sand Cone Method**

13

---

---

---

---

---

---

---

---



**Hand-Compaction after Sand Cone Test**

14

---

---

---

---

---

---

---

---



**SASW Using Hammer as Source**

15

---

---

---

---

---

---

---

---



**SASW Using Bulldozer as the Source**

16

---

---

---

---

---

---

---

---



**Compaction of Final Layer**

17

---

---

---

---

---

---

---

---



**Cross-Hole Testing**

18

---

---

---


---

---

---

---

---




---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---


---

---

---

---

---




---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---


---

---

---

---

---




---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---


---

---

---

---

## Results of Fill Material RCTS Testing



February 28, 2008

22

---

---

---

---

---

---


---

---

---

---

## Comparison – Field and Lab $V_s$ Profiles



February 28, 2008

23

---

---

---

---

---

---

---

---

---

---

## Summary



- Conclusions:
  - Backfill placement will provide homogeneous fill with predictable properties
  - Backfill  $V_s$  will reach 1000 fps at depth of less than 20 feet
  - SASW, cross-hole data were consistent with RCTS predictions of  $V_s$
- Test pad provided confidence that required density and stiffness could be achieved
- Test pad provided insights into variability in backfill properties placed under field conditions

24

---

---

---

---

---

---

---

---

---

---